



**THE DATASHEET OF**  
**FT-01**



Path: [Home](#) > [Enclosure Index](#) > [MOREnclosures](#) > **RITEC** - Instrument ABS Plastic Enclosures












click to enlarge  
(Assembled View)




















click to enlarge  
(Open View)

## Key Features:

- Designed to house P.C. boards - for instrument use.
- Molded in light grey - general purpose ABS plastic with a light texture (front & rear panels are smooth). Material carries a UL flammability rating of UL94 HB.
- Two part - clam shell construction. Bottom half includes molded in standoffs for easy P.C. board installation. Larger enclosures also include P.C. board standoffs on the top half (see [photo tables](#) for details). Four short M3 screws included
- Front & rear panels are interchangeable and easily removable for modifications.
- Tongue and groove construction provides protection against dust & water. Designed to meet IP43.
- Includes two (or four) - assembly screws (depending on size).
- All units except the **RM2015S** and **RM2055S** are secured with M3 Philips machine screws, threaded into integral brass bushings. Perfect for applications when repetitive assembly and disassembly are required. The **RM2015S** and **RM2055S** use self tapping Philips screws.
- Options include replacement IR translucent or aluminum panels.

Part Number	Color	PDF Reader File	AutoCAD .dwg Files (zipped)	3D Solid Model .igs & .stp files (zipped)	Units	Length	Width	Enclosure Depth (Assembled)
<b>RM2015S</b>	Grey	 227K	 167K	 312K	Inches	5.12	3.94	1.18
					mm	130	100	30
<b>RM2015M</b>	Grey	 246K	 167K	 301K	Inches	5.12	3.94	1.97
					mm	130	100	50
<b>RM2015L</b>	Grey	 231K	 163K	 258K	Inches	5.12	3.94	2.76
					mm	130	100	70
					Inches	7.48	5.51	1.18

<b>RM2055S</b>	Grey	 237K	 169K	 302K	mm	190	140	30
<b>RM2055M</b>	Grey	 340K	 167K	 283K	Inches	7.48	5.51	1.97
					mm	190	140	50
<b>RM2055L</b>	Grey	 222K	 163K	 238K	Inches	7.48	5.51	2.76
					mm	190	140	70
<b>RM2095S</b>	Grey	 256K	 163K	 296K	Inches	9.84	7.09	1.97
					mm	250	180	50
<b>RM2095M</b>	Grey	 352K	 167K	 313K	Inches	9.84	7.09	2.95
					mm	250	180	75
<b>RM2095L</b>	Grey	 260K	 167K	 344K	Inches	9.84	7.09	3.94
					mm	250	180	100

 [Link here to photo tables](#) of each part number.



(click to enlarge)  
**Assembled View  
(Top)**



(click to enlarge)  
**Assembled View  
(Bottom)**



(click to enlarge)  
**Open View**

## Accessories

***Folding Feet Kit:***



(click to enlarge)



(click to enlarge)

- Kit consists of two (2) enclosure brackets, two (2) mounting screws & two (2) hinged feet
- Mounts to the bottom half - towards the front of the enclosure
- Allows angled view of enclosure front panel
- Part Number: **FT-01**

---

Exactly what you are looking for???

Link to our stocking distributors - most have "on-line" pricing, stock check and ordering!!!

[Our Distributors](#)

[Order from your favorite distributor](#)

---



[Home](#) | [Products](#) | [Distributors](#) | [Technical](#) | [Contact Us](#) | [Other Options](#)

---

Copyright; © 2007-2011 Hammond Mfg Co Inc  
URL: <http://www.hammondmfg.com>

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View FT-01 on WIN SOURCE](#)
-  [Hammond Manufacturing Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management