



THE DATASHEET OF BZM55B5V6



SURFACE MOUNT ZENER DIODES
VOLTAGE RANGE 2.4 to 75 Volts POWER 500 mWatt

FEATURES

- * Planar Die construction
- * 500mW Power Dissipation
- * Ideally Suited for Automated Assembly Processes
- * Unmarked with polarity only



MECHANICAL DATA

- * Case: Molded Glass MICRO-MELF
- * Terminals: Solderable per MIL-STD-750, Method 2026

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Resistive or inductive load.

MICRO-MELF



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Value	Units
Power Dissipation at TA= 25°C	P _{TOT}	500	mW
Junction Temperature	T _J	-65 to +175	°C
Storage Temperature Range	T _S	-65 to +175	°C

Valid provided that leads at a distance of 8mm from case are kept at ambient temperature.

Parameter	Symbol	Min.	Typ.	Max.	Units
Thermal Resistance Junction to Ambient Air	R _{θJA}	--	--	0.3	°C/mW
Forward Voltage at I _F = 200mA	V _F	--	--	1.5	V

Valid provided that leads at a distance of 8mm from case are kept at ambient temperature.

2022-06/62
REV:A

Part Number	Nominal Zener Voltage			Max. Zener Impedance				Max. Reverse Leakage Current	
	V _Z @ I _{ZT}			Z _{ZT} @ I _{ZT}		Z _{ZK} @ I _{ZK}		I _R @ V _R	
	Nom. V	Min. V	Max. V	Ω	mA	Ω	mA	μA	V
BZM55-B2V4	2.4	2.35	2.45	85	5	600	1	50	1
BZM55-B2V7	2.7	2.65	2.75	85	5	600	1	10	1
BZM55-B3V0	3	2.94	3.06	85	5	600	1	4	1
BZM55-B3V3	3.3	3.23	3.37	85	5	600	1	2	1
BZM55-B3V6	3.6	3.53	3.67	85	5	600	1	2	1
BZM55-B3V9	3.9	3.82	3.98	85	5	600	1	2	1
BZM55-B4V3	4.3	4.21	4.39	75	5	600	1	1	1
BZM55-B4V7	4.7	4.61	4.79	60	5	600	1	0.5	1
BZM55-B5V1	5.1	5.00	5.20	35	5	550	1	0.1	1
BZM55-B5V6	5.6	5.49	5.71	25	5	450	1	0.1	1
BZM55-B6V2	6.2	6.08	6.32	10	5	200	1	0.1	2
BZM55-B6V8	6.8	6.66	6.94	8	5	150	1	0.1	3
BZM55-B7V5	7.5	7.35	7.65	7	5	50	1	0.1	5
BZM55-B8V2	8.2	8.04	8.36	7	5	50	1	0.1	6
BZM55-B9V1	9.1	8.92	9.28	10	5	50	1	0.1	7
BZM55-B10	10	9.80	10.20	15	5	70	1	0.1	7.5
BZM55-B11	11	10.78	11.22	20	5	70	1	0.1	8.5
BZM55-B12	12	11.76	12.24	20	5	90	1	0.1	9
BZM55-B13	13	12.74	13.26	26	5	110	1	0.1	10
BZM55-B15	15	14.70	15.30	30	5	110	1	0.1	11
BZM55-B16	16	15.68	16.32	40	5	170	1	0.1	12
BZM55-B18	18	17.64	18.36	50	5	170	1	0.1	14
BZM55-B20	20	19.60	20.40	55	5	220	1	0.1	15
BZM55-B22	22	21.56	22.44	55	5	220	1	0.1	17
BZM55-B24	24	23.5	24.5	80	5	220	1	0.1	18
BZM55-B27	27	26.5	27.5	80	5	220	1	0.1	20
BZM55-B30	30	29.4	30.6	80	5	220	1	0.1	22
BZM55-B33	33	32.3	33.7	80	5	220	1	0.1	24
BZM55-B36	36	35.3	36.7	80	5	220	1	0.1	27
BZM55-B39	39	38.2	39.8	90	2.5	500	1	0.1	30
BZM55-B43	43	42.1	43.9	90	2.5	600	1	0.1	33
BZM55-B47	47	46.1	47.9	110	2.5	700	1	0.1	36
BZM55-B51	51	50	52	125	2.5	700	0.5	0.1	39
BZM55-B56	56	54.9	57.1	135	2.5	1000	0.5	0.1	43
BZM55-B62	62	60.8	63.2	150	2.5	1000	0.5	0.1	47
BZM55-B68	68	66.6	69.4	200	2.5	1000	0.5	0.1	51
BZM55-B75	75	73.5	76.5	250	2.5	1500	0.5	0.1	56

Notes. STANDARD VOLTAGE TOLERANCE IS + 5% AND :

- SUFFIX " A " FOR + 1%
- SUFFIX " B " FOR + 2%
- SUFFIX " C " FOR + 5%
- SUFFIX " D " FOR + 20%

RATING AND CHARACTERISTICS CURVES (BZM55B SERIES)




FIG. 1 POWER DERATING CURVE





Fig.2 BREAKDOWN CHARACTERISTICS


Mounting Pad Layout

MICRO-MELF



Unit : inch(mm)

Marking Description



PACKAGING OF DIODE AND BRIDGE RECTIFIERS

REEL PACK

PACKAGE	PACKING CODE	EA PER REEL	EA PER INNER BOX	COMPONENT SPACE (mm)	TAPE SPACE (mm)	REEL DIA (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
MICRO-MELF	-T	2,500	---	---	---	178	390*205*310	100,000	7.10



DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BZM55B5V6 on WIN SOURCE](#)
-  [Rectron USA Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management