



THE DATASHEET OF SMP-PR(LD)-SMT-1



Applicable standard		MIL-STD-348B		
Rating	Operating temperature range	-55 °C to +125 °C (95 %RH Max.) 	Storage temperature range	-20 °C to +70 °C (90 %RH Max.)
	Power	-- W	Characteristic impedance	50 Ω (0 to 30 GHz)
	Peculiarity	----	Applicable cable	----

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

General examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		-	-

ELECTRICAL CHARACTERISTICS

Contact resistance	100 mA (DC or 1000 Hz)	Center contact	6 mΩ Max.	X	X
		Outer contact	6 mΩ Max.	X	X
Insulation resistance	500 V DC.	1000 MΩ Min.		X	X
Withstanding voltage	500 V AC for 1 min. current leakage 2 mA Max.	No flashover or breakdown.		X	X
V.S.W.R. 	Frequency 0 to 30 GHz.	V.S.W.R.	1.5 Max.	X	-
Insertion loss	Frequency - to - GHz.	--- dB Max.		-	-

MECHANICAL CHARACTERISTICS

Contact insertion and extraction forces	φ --- by steel gauge.	Insertion force	--- N Max.	-	-
		Extraction force	--- N Min.	-	-
Insertion and extraction forces 	Measured by applicable connector. [SMPJ-HKJ]	Insertion force	45 N Max.	X	X
		Extraction force	9 N Min.	X	X
Mechanical operation 	500 times insertion and extractions.	1)Contact resistance:			
		Center contact	12 mΩ Max.	X	-
Vibration 	Frequency 10 to 500 Hz single amplitude 0.75 mm, 98 m/s ² at 10 cycles for 3 directions.	2)No damage, crack and looseness of parts.			
		1)No electrical discontinuity of 1 μs.		X	-
Shock 	490 m/s ² directions of pulse 11 ms at 3 times for 3 directions.	2)No damage, crack and looseness of parts.			
				X	-
Cable clamp strength (Against cable pull)	Using a pulling tester, pull the cable axially at a rate of --- mm/min. and record the strength at which the cable or connector breaks.	--- N Min.		-	-

ENVIRONMENTAL CHARACTERISTICS

Damp heat 	Exposed at +25 to +65 °C, 90 to 98 % total 10 cycles. (240 h)	1)Insulation resistance:	100 MΩ Min. (at high humidity)		
		2) Insulation resistance:	1000 MΩ Min. (at dry)	X	-
		3)No damage, crack and looseness of parts.			
Rapid change of temperature 	Temperature -55 → - → +125 → - °C Time 30 → 3 → 30 → 3 min. Under 5 cycles.	No damage, crack and looseness of parts.		X	-
Corrosion salt mist 	Exposed in 5 % salt water spray for 48 h.	V.S.W.R.	1.5 Max. [0 to 30 GHz]	X	-

Count	Description of revisions	Designed	Checked	Date
	1 DIS-D-00003210	TK.SAWAGUCHI	KY.SHIMIZU	18.06.07

Remark RoHS COMPLIANT Note The characteristic after mounting on the board.	Approved	TO.KATAYAMA	17.09.05
	Checked	KY.SHIMIZU	17.09.05
	Designed	TK.SAWAGUCHI	17.09.05
	Drawn	TK.SAWAGUCHI	17.09.05

Unless otherwise specified, refer to IEC 60512.

Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	Drawing No.	ELC-373488-00-00
	SPECIFICATION SHEET	Part No.	SMP-PR(LD)-SMT-1
	HIROSE ELECTRIC CO., LTD.	Code No.	CL338-1103-0-00

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View SMP-PR\(LD\)-SMT-1 on WIN SOURCE](#)
- [Hirose Electric Co Ltd Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management