



**THE DATASHEET OF
SPMWHT541MD5WAW0SD**



LM561B – 5630 Middle Power LED



Introduction

Features

- Beam Angle: 120°
- Precondition : JEDEC Level 2a
- Dimension : 5.6 x 3.0 x 0.8 mm
- ESD withstand Voltage : up to ± 5 KV [HBM]

Applications

- INDOOR LIGHTING : Ambient Light, LED tube, Down light, LED bulb and Ceiling Light

SAMSUNG ELECTRONICS

95, Samsung2-Ro, Giheung-Gu,
Yongin-City, Gyeonggi-Do 446-711, KOREA

Contents

| | | |
|----------------------------------------|-------|----|
| 1. Product Code Information | ----- | 3 |
| 2. Characteristics | ----- | 11 |
| 3. Typical Characteristics Graph | ----- | 13 |
| 4. Outline Drawing & Dimension | ----- | 21 |
| 5. Reliability Test Items & Conditions | ----- | 22 |
| 6. Solder Conditions | ----- | 23 |
| 7. Tape & Reel | ----- | 24 |
| 8. Label Structure | ----- | 26 |
| 9. Packing Structure | ----- | 27 |
| 10. Precaution For Use | ----- | 29 |
| 11. Hazard Substance Analysis Report | ----- | 31 |
| Revision History | ----- | 53 |

1. Product Code Information

1) Luminous Flux Bins ($T_s = 25^\circ\text{C}$)

| Nominal CCT | Product Code | Flux Rank | Sorting Condition $I_m @65\text{mA}$ |
|-------------|--------------------|-----------|--------------------------------------|
| | | | Flux Range (Φ_v, I_m) |
| 2700K | SPMWHT541MD5WAW☆SB | S2 | 26.0 ~ 28.0 |
| | | S3 | 28.0 ~ 30.0 |
| | SPMWHT541MD5WAW☆SC | S3 | 28.0 ~ 30.0 |
| | | S4 | 30.0 ~ 32.0 |
| | SPMWHT541MD5WAW☆SD | S4 | 30.0 ~ 32.0 |
| | | S5 | 32.0 ~ 34.0 |
| 3000K | SPMWHT541MD5WAV☆SB | S2 | 26.5 ~ 28.5 |
| | | S3 | 28.5 ~ 30.5 |
| | SPMWHT541MD5WAV☆SC | S3 | 28.5 ~ 30.5 |
| | | S4 | 30.5 ~ 32.5 |
| | SPMWHT541MD5WAV☆SD | S4 | 30.5 ~ 32.5 |
| | | S5 | 32.5 ~ 34.5 |
| 3500K | SPMWHT541MD5WAU☆SB | S2 | 27.0 ~ 29.0 |
| | | S3 | 29.0 ~ 31.0 |
| | SPMWHT541MD5WAU☆SC | S3 | 29.0 ~ 31.0 |
| | | S4 | 31.0 ~ 33.0 |
| | SPMWHT541MD5WAU☆SD | S4 | 31.0 ~ 33.0 |
| | | S5 | 33.0 ~ 35.0 |
| 4000K | SPMWHT541MD5WAT☆SB | S2 | 28.0 ~ 30.0 |
| | | S3 | 30.0 ~ 32.0 |
| | SPMWHT541MD5WAT☆SC | S3 | 30.0 ~ 32.0 |
| | | S4 | 32.0 ~ 34.0 |
| | SPMWHT541MD5WAT☆SD | S4 | 32.0 ~ 34.0 |
| | | S5 | 34.0 ~ 36.0 |
| 5000K | SPMWHT541MD5WAR☆SB | S2 | 29.0 ~ 31.0 |
| | | S3 | 31.0 ~ 33.0 |
| | SPMWHT541MD5WAR☆SC | S3 | 31.0 ~ 33.0 |
| | | S4 | 33.0 ~ 35.0 |
| | SPMWHT541MD5WAR☆SD | S4 | 33.0 ~ 35.0 |
| | | S5 | 35.0 ~ 37.0 |

1) Luminous Flux Bins ($T_s = 25^\circ\text{C}$)

| Nominal CCT | Product Code | Flux Rank | Sorting Condition I_m @65mA |
|-------------|--------------------|-----------|-------------------------------|
| | | | Flux Range (Φ_v, I_m) |
| 5700K | SPMWHT541MD5WAQ☆SB | S2 | 28.5 ~ 30.5 |
| | | S3 | 30.5 ~ 32.5 |
| | SPMWHT541MD5WAQ☆SC | S3 | 30.5 ~ 32.5 |
| | | S4 | 32.5 ~ 34.5 |
| | SPMWHT541MD5WAQ☆SD | S4 | 32.5 ~ 34.5 |
| | | S5 | 34.5 ~ 36.5 |
| 6500K | SPMWHT541MD5WAP☆SB | S2 | 28.0 ~ 30.0 |
| | | S3 | 30.0 ~ 32.0 |
| | SPMWHT541MD5WAP☆SC | S3 | 30.0 ~ 32.0 |
| | | S4 | 32.0 ~ 34.0 |
| | SPMWHT541MD5WAP☆SD | S4 | 32.0 ~ 34.0 |
| | | S5 | 34.0 ~ 36.0 |

Notes:

- 1) SAMSUNG ELECTRONICS maintains a tolerance of $\pm 5\%$ on Luminous Flux measurements.
- 2) Warm white : "☆" can be "0"(Whole Bin), "H"(Half Bin) or "M"(Quarter Bin) of the color binning.
Cool white : "☆" can be "0"(Whole Bin) or "M"(Quarter Bin) of the color binning.

2) Color Bins ($T_s = 25^\circ\text{C}$)

1) Color Binning

| Nominal CCT | Product Code | Color Rank | Chromaticity Bins |
|-------------|----------------------------------------------------------------|---------------------|-------------------------------------------------------------------|
| 2700K | SPMWHT541MD5WAW0SB SPMWHT541MD5WAW0SC SPMWHT541MD5WAW0SD | W0 (Whole bin) | W1, W2, W3, W4, W5, W6, W7, W8, W9, WA, WB, WC, WD, WE, WF, WG |
| | SPMWHT541MD5WAWHSB SPMWHT541MD5WAWHSC SPMWHT541MD5WAWHSD | WH (Half bin) | W5, W6, W7, W8, W9, WA, WB, WC |
| | SPMWHT541MD5WAWMSB SPMWHT541MD5WAWMSC SPMWHT541MD5WAWMSD | WM (Quarter bin) | W6, W7, WA, WB |
| 3000K | SPMWHT541MD5WAV0SB SPMWHT541MD5WAV0SC SPMWHT541MD5WAV0SD | V0 (Whole bin) | V1, V2, V3, V4, V5, V6, V7, V8, V9, VA, VB, VC, VD, VE, VF, VG |
| | SPMWHT541MD5WAVHSB SPMWHT541MD5WAVHSC SPMWHT541MD5WAVHSD | VH (Half bin) | V5, V6, V7, V8, V9, VA, VB, VC |
| | SPMWHT541MD5WAVMSB SPMWHT541MD5WAVMSC SPMWHT541MD5WAVMSD | VM (Quarter bin) | V6, V7, VA, VB |
| 3500K | SPMWHT541MD5WAU0SB SPMWHT541MD5WAU0SC SPMWHT541MD5WAU0SD | U0 (Whole bin) | U1, U2, U3, U4, U5, U6, U7, U8, U9, UA, UB, UC, UD, UE, UF, UG |
| | SPMWHT541MD5WAUHSB SPMWHT541MD5WAUHSC SPMWHT541MD5WAUHSD | UH (Half bin) | U5, U6, U7, U8, U9, UA, UB, UC |
| | SPMWHT541MD5WAUMSB SPMWHT541MD5WAUMSC SPMWHT541MD5WAUMSD | UM (Quarter bin) | U6, U7, UA, UB |

1) Color Binning (Continued)

| Nominal CCT | Product Code | Color Rank | Chromaticity Bins |
|-------------|----------------------------------------------------------------|---------------------|-------------------------------------------------------------------|
| 4000K | SPMWHT541MD5WAT0SB SPMWHT541MD5WAT0SC SPMWHT541MD5WAT0SD | T0 (Whole bin) | T1, T2, T3, T4, T5, T6, T7, T8, T9, TA, TB, TC, TD, TE, TF, TG |
| | SPMWHT541MD5WATHSB SPMWHT541MD5WATHSC SPMWHT541MD5WATHSD | TH (Half bin) | T5, T6, T7, T8, T9, TA, TB, TC |
| | SPMWHT541MD5WATMSB SPMWHT541MD5WATMSC SPMWHT541MD5WATMSD | TM (Quarter bin) | T6, T7, TA, TB |
| 5000K | SPMWHT541MD5WAR0SB SPMWHT541MD5WAR0SC SPMWHT541MD5WAR0SD | R0 (Whole bin) | R1, R2, R3, R4, R5 R6, R7, R8, R9 ,RA |
| | SPMWHT541MD5WARMSB SPMWHT541MD5WARMSC SPMWHT541MD5WARMSD | RM (Quarter bin) | R1, R2, R3, R4, R5, R6 |
| 5700K | SPMWHT541MD5WAQ0SB SPMWHT541MD5WAQ0SC SPMWHT541MD5WAQ0SD | Q0 (Whole bin) | Q1, Q2, Q3, Q4, Q5 Q6, Q7, Q8, Q9, QA |
| | SPMWHT541MD5WAQMSB SPMWHT541MD5WAQMSC SPMWHT541MD5WAQMSD | QM (Quarter bin) | Q1, Q2, Q3, Q4, Q5, Q6 |
| 6500K | SPMWHT541MD5WAP0SB SPMWHT541MD5WAP0SC SPMWHT541MD5WAP0SD | P0 (Whole bin) | P1, P2, P3, P4, P5 P6, P7, P8, P9, PA |
| | SPMWHT541MD5WAPMSB SPMWHT541MD5WAPMSC SPMWHT541MD5WAPMSD | PM (Quarter bin) | P1, P2, P3, P4, P5, P6 |

2) Chromaticity Region & Coordinates



2) Chromaticity Region & Coordinates (Continued)

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| W rank (2700K) | | | | | |
| W1 | 0.4373 | 0.3893 | W9 | 0.4465 | 0.4071 |
| | 0.4418 | 0.3981 | | 0.4513 | 0.4164 |
| | 0.4475 | 0.3994 | | 0.4573 | 0.4178 |
| | 0.4428 | 0.3906 | | 0.4523 | 0.4085 |
| W2 | 0.4428 | 0.3906 | WA | 0.4523 | 0.4085 |
| | 0.4475 | 0.3994 | | 0.4573 | 0.4178 |
| | 0.4532 | 0.4008 | | 0.4634 | 0.4193 |
| | 0.4483 | 0.3919 | | 0.4582 | 0.4099 |
| W3 | 0.4483 | 0.3919 | WB | 0.4582 | 0.4099 |
| | 0.4532 | 0.4008 | | 0.4634 | 0.4193 |
| | 0.4589 | 0.4021 | | 0.4695 | 0.4207 |
| | 0.4538 | 0.3931 | | 0.4641 | 0.4112 |
| W4 | 0.4538 | 0.3931 | WC | 0.4641 | 0.4112 |
| | 0.4589 | 0.4021 | | 0.4695 | 0.4207 |
| | 0.4646 | 0.4034 | | 0.4756 | 0.4221 |
| | 0.4593 | 0.3944 | | 0.4700 | 0.4126 |
| W5 | 0.4418 | 0.3981 | WD | 0.4513 | 0.4164 |
| | 0.4465 | 0.4071 | | 0.4562 | 0.4260 |
| | 0.4523 | 0.4085 | | 0.4624 | 0.4274 |
| | 0.4475 | 0.3994 | | 0.4573 | 0.4178 |
| W6 | 0.4475 | 0.3994 | WE | 0.4573 | 0.4178 |
| | 0.4523 | 0.4085 | | 0.4624 | 0.4274 |
| | 0.4582 | 0.4099 | | 0.4687 | 0.4289 |
| | 0.4532 | 0.4008 | | 0.4634 | 0.4193 |
| W7 | 0.4532 | 0.4008 | WF | 0.4634 | 0.4193 |
| | 0.4582 | 0.4099 | | 0.4687 | 0.4289 |
| | 0.4641 | 0.4112 | | 0.4750 | 0.4304 |
| | 0.4589 | 0.4021 | | 0.4695 | 0.4207 |
| W8 | 0.4589 | 0.4021 | WG | 0.4695 | 0.4207 |
| | 0.4641 | 0.4112 | | 0.4750 | 0.4304 |
| | 0.4700 | 0.4126 | | 0.4813 | 0.4319 |
| | 0.4646 | 0.4034 | | 0.4756 | 0.4221 |

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| V rank (3000K) | | | | | |
| V1 | 0.4147 | 0.3814 | V9 | 0.4221 | 0.3984 |
| | 0.4183 | 0.3898 | | 0.4259 | 0.4073 |
| | 0.4242 | 0.3919 | | 0.4322 | 0.4096 |
| | 0.4203 | 0.3833 | | 0.4281 | 0.4006 |
| V2 | 0.4203 | 0.3833 | VA | 0.4281 | 0.4006 |
| | 0.4242 | 0.3919 | | 0.4322 | 0.4096 |
| | 0.4300 | 0.3939 | | 0.4385 | 0.4119 |
| | 0.4259 | 0.3853 | | 0.4342 | 0.4028 |
| V3 | 0.4259 | 0.3853 | VB | 0.4342 | 0.4028 |
| | 0.4300 | 0.3939 | | 0.4385 | 0.4119 |
| | 0.4359 | 0.3960 | | 0.4449 | 0.4141 |
| | 0.4316 | 0.3873 | | 0.4403 | 0.4049 |
| V4 | 0.4316 | 0.3873 | VC | 0.4403 | 0.4049 |
| | 0.4359 | 0.3960 | | 0.4449 | 0.4141 |
| | 0.4418 | 0.3981 | | 0.4513 | 0.4164 |
| | 0.4373 | 0.3893 | | 0.4465 | 0.4071 |
| V5 | 0.4183 | 0.3898 | VD | 0.4259 | 0.4073 |
| | 0.4221 | 0.3984 | | 0.4299 | 0.4165 |
| | 0.4281 | 0.4006 | | 0.4364 | 0.4188 |
| | 0.4242 | 0.3919 | | 0.4322 | 0.4096 |
| V6 | 0.4242 | 0.3919 | VE | 0.4322 | 0.4096 |
| | 0.4281 | 0.4006 | | 0.4364 | 0.4188 |
| | 0.4342 | 0.4028 | | 0.4430 | 0.4212 |
| | 0.4300 | 0.3939 | | 0.4385 | 0.4119 |
| V7 | 0.4300 | 0.3939 | VF | 0.4385 | 0.4119 |
| | 0.4342 | 0.4028 | | 0.4430 | 0.4212 |
| | 0.4403 | 0.4049 | | 0.4496 | 0.4236 |
| | 0.4359 | 0.3960 | | 0.4449 | 0.4141 |
| V8 | 0.4359 | 0.3960 | VG | 0.4449 | 0.4141 |
| | 0.4403 | 0.4049 | | 0.4496 | 0.4236 |
| | 0.4465 | 0.4071 | | 0.4562 | 0.4260 |
| | 0.4418 | 0.3981 | | 0.4513 | 0.4164 |

2) Chromaticity Region & Coordinates (Continued)

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| U rank (3500K) | | | | | |
| U1 | 0.3889 | 0.3690 | U9 | 0.3941 | 0.3848 |
| | 0.3915 | 0.3768 | | 0.3968 | 0.3930 |
| | 0.3981 | 0.3800 | | 0.4040 | 0.3966 |
| | 0.3953 | 0.3720 | | 0.4010 | 0.3882 |
| U2 | 0.3953 | 0.3720 | UA | 0.4010 | 0.3882 |
| | 0.3981 | 0.3800 | | 0.4040 | 0.3966 |
| | 0.4048 | 0.3832 | | 0.4113 | 0.4001 |
| | 0.4017 | 0.3751 | | 0.4080 | 0.3916 |
| U3 | 0.4017 | 0.3751 | UB | 0.4080 | 0.3916 |
| | 0.4048 | 0.3832 | | 0.4113 | 0.4001 |
| | 0.4116 | 0.3865 | | 0.4186 | 0.4037 |
| | 0.4082 | 0.3782 | | 0.4150 | 0.3950 |
| U4 | 0.4082 | 0.3782 | UC | 0.4150 | 0.3950 |
| | 0.4116 | 0.3865 | | 0.4186 | 0.4037 |
| | 0.4183 | 0.3898 | | 0.4259 | 0.4073 |
| | 0.4147 | 0.3814 | | 0.4221 | 0.3984 |
| U5 | 0.3915 | 0.3768 | UD | 0.3968 | 0.3930 |
| | 0.3941 | 0.3848 | | 0.3996 | 0.4015 |
| | 0.4010 | 0.3882 | | 0.4071 | 0.4052 |
| | 0.3981 | 0.3800 | | 0.4040 | 0.3966 |
| U6 | 0.3981 | 0.3800 | UE | 0.4040 | 0.3966 |
| | 0.4010 | 0.3882 | | 0.4071 | 0.4052 |
| | 0.4080 | 0.3916 | | 0.4146 | 0.4089 |
| | 0.4048 | 0.3832 | | 0.4113 | 0.4001 |
| U7 | 0.4048 | 0.3832 | UF | 0.4113 | 0.4001 |
| | 0.4080 | 0.3916 | | 0.4146 | 0.4089 |
| | 0.4150 | 0.3950 | | 0.4222 | 0.4127 |
| | 0.4116 | 0.3865 | | 0.4186 | 0.4037 |
| U8 | 0.4116 | 0.3865 | UG | 0.4186 | 0.4037 |
| | 0.4150 | 0.3950 | | 0.4222 | 0.4127 |
| | 0.4221 | 0.3984 | | 0.4299 | 0.4165 |
| | 0.4183 | 0.3898 | | 0.4259 | 0.4073 |

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| T rank (4000K) | | | | | |
| T1 | 0.367 | 0.3578 | T9 | 0.3702 | 0.3722 |
| | 0.3726 | 0.3612 | | 0.3763 | 0.376 |
| | 0.3744 | 0.3685 | | 0.3782 | 0.3837 |
| | 0.3686 | 0.3649 | | 0.3719 | 0.3797 |
| T2 | 0.3726 | 0.3612 | TA | 0.3763 | 0.3760 |
| | 0.3783 | 0.3646 | | 0.3825 | 0.3798 |
| | 0.3804 | 0.3721 | | 0.3847 | 0.3877 |
| | 0.3744 | 0.3685 | | 0.3782 | 0.3837 |
| T3 | 0.3783 | 0.3646 | TB | 0.3825 | 0.3798 |
| | 0.3840 | 0.3681 | | 0.3887 | 0.3836 |
| | 0.3863 | 0.3758 | | 0.3912 | 0.3917 |
| | 0.3804 | 0.3721 | | 0.3847 | 0.3877 |
| T4 | 0.384 | 0.3681 | TC | 0.3887 | 0.3837 |
| | 0.3898 | 0.3716 | | 0.395 | 0.3875 |
| | 0.3924 | 0.3794 | | 0.3978 | 0.3958 |
| | 0.3863 | 0.3758 | | 0.3912 | 0.3917 |
| T5 | 0.3686 | 0.3649 | TD | 0.3719 | 0.3797 |
| | 0.3744 | 0.3685 | | 0.3782 | 0.3837 |
| | 0.3763 | 0.376 | | 0.3802 | 0.3916 |
| | 0.3702 | 0.3722 | | 0.3736 | 0.3874 |
| T6 | 0.3744 | 0.3685 | TE | 0.3782 | 0.3837 |
| | 0.3804 | 0.3721 | | 0.3847 | 0.3877 |
| | 0.3825 | 0.3798 | | 0.3869 | 0.3958 |
| | 0.3763 | 0.376 | | 0.3802 | 0.3916 |
| T7 | 0.3804 | 0.3721 | TF | 0.3847 | 0.3877 |
| | 0.3863 | 0.3758 | | 0.3912 | 0.3917 |
| | 0.3887 | 0.3836 | | 0.3937 | 0.4001 |
| | 0.3825 | 0.3798 | | 0.3869 | 0.3958 |
| T8 | 0.3863 | 0.3758 | TG | 0.3912 | 0.3917 |
| | 0.3924 | 0.3794 | | 0.3978 | 0.3958 |
| | 0.395 | 0.3875 | | 0.4006 | 0.4044 |
| | 0.3887 | 0.3836 | | 0.3937 | 0.4001 |



2) Chromaticity Region & Coordinates (Continued)

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| R rank (5000K) | | | | | |
| R1 | 0.3366 | 0.3369 | R6 | 0.3456 | 0.3601 |
| | 0.3441 | 0.3428 | | 0.3539 | 0.3669 |
| | 0.3449 | 0.3515 | | 0.3551 | 0.3760 |
| | 0.3369 | 0.3451 | | 0.3464 | 0.3688 |
| R2 | 0.3441 | 0.3428 | R7 | 0.3363 | 0.3287 |
| | 0.3515 | 0.3487 | | 0.3433 | 0.3341 |
| | 0.3527 | 0.3578 | | 0.3441 | 0.3428 |
| | 0.3449 | 0.3515 | | 0.3366 | 0.3369 |
| R3 | 0.3369 | 0.3451 | R8 | 0.3433 | 0.3341 |
| | 0.3449 | 0.3515 | | 0.3503 | 0.3396 |
| | 0.3456 | 0.3601 | | 0.3515 | 0.3487 |
| | 0.3373 | 0.3534 | | 0.3441 | 0.3428 |
| R4 | 0.3449 | 0.3515 | R9 | 0.3376 | 0.3616 |
| | 0.3527 | 0.3578 | | 0.3464 | 0.3688 |
| | 0.3539 | 0.3669 | | 0.3471 | 0.3775 |
| | 0.3456 | 0.3601 | | 0.3379 | 0.3698 |
| R5 | 0.3373 | 0.3534 | RA | 0.3464 | 0.3688 |
| | 0.3456 | 0.3601 | | 0.3551 | 0.3760 |
| | 0.3464 | 0.3688 | | 0.3564 | 0.3851 |
| | 0.3376 | 0.3616 | | 0.3471 | 0.3775 |
| Q rank (5700K) | | | | | |
| Q1 | 0.3222 | 0.3243 | Q6 | 0.3292 | 0.3461 |
| | 0.3294 | 0.3306 | | 0.3373 | 0.3534 |
| | 0.3293 | 0.3384 | | 0.3376 | 0.3616 |
| | 0.3217 | 0.3316 | | 0.3292 | 0.3539 |
| Q2 | 0.3294 | 0.3306 | Q7 | 0.3227 | 0.3170 |
| | 0.3366 | 0.3369 | | 0.3295 | 0.3228 |
| | 0.3369 | 0.3451 | | 0.3294 | 0.3306 |
| | 0.3293 | 0.3384 | | 0.3222 | 0.3243 |
| Q3 | 0.3217 | 0.3316 | Q8 | 0.3295 | 0.3228 |
| | 0.3293 | 0.3384 | | 0.3363 | 0.3287 |
| | 0.3292 | 0.3461 | | 0.3366 | 0.3369 |
| | 0.3212 | 0.3389 | | 0.3294 | 0.3306 |
| Q4 | 0.3293 | 0.3384 | Q9 | 0.3207 | 0.3462 |
| | 0.3369 | 0.3451 | | 0.3292 | 0.3539 |
| | 0.3373 | 0.3534 | | 0.3291 | 0.3617 |
| | 0.3292 | 0.3461 | | 0.3202 | 0.3535 |
| Q5 | 0.3212 | 0.3389 | QA | 0.3292 | 0.3539 |
| | 0.3292 | 0.3461 | | 0.3376 | 0.3616 |
| | 0.3292 | 0.3539 | | 0.3379 | 0.3698 |
| | 0.3207 | 0.3462 | | 0.3291 | 0.3617 |

| Region | CIE X | CIE Y | Region | CIE X | CIE Y |
|----------------|--------|--------|--------|--------|--------|
| P rank (6500K) | | | | | |
| P1 | 0.3068 | 0.3113 | P6 | 0.3126 | 0.3324 |
| | 0.3145 | 0.3187 | | 0.3210 | 0.3408 |
| | 0.3135 | 0.3256 | | 0.3205 | 0.3481 |
| | 0.3055 | 0.3177 | | 0.3117 | 0.3393 |
| P2 | 0.3145 | 0.3187 | P7 | 0.3081 | 0.3049 |
| | 0.3221 | 0.3261 | | 0.3154 | 0.3119 |
| | 0.3216 | 0.3334 | | 0.3145 | 0.3187 |
| | 0.3135 | 0.3256 | | 0.3068 | 0.3113 |
| P3 | 0.3055 | 0.3177 | P8 | 0.3154 | 0.3119 |
| | 0.3135 | 0.3256 | | 0.3226 | 0.3188 |
| | 0.3126 | 0.3324 | | 0.3221 | 0.3261 |
| | 0.3041 | 0.3240 | | 0.3145 | 0.3187 |
| P4 | 0.3135 | 0.3256 | P9 | 0.3028 | 0.3304 |
| | 0.3216 | 0.3334 | | 0.3117 | 0.3393 |
| | 0.3210 | 0.3408 | | 0.3107 | 0.3461 |
| | 0.3126 | 0.3324 | | 0.3015 | 0.3368 |
| P5 | 0.3041 | 0.3240 | PA | 0.3117 | 0.3393 |
| | 0.3126 | 0.3324 | | 0.3205 | 0.3481 |
| | 0.3117 | 0.3393 | | 0.3200 | 0.3554 |
| | 0.3028 | 0.3304 | | 0.3107 | 0.3461 |

Notes: SAMSUNG ELECTRONICS maintains ± 0.005 tolerance of Cx, Cy

2. Characteristics

1) Absolute Maximum Rating

| Item | Symbol | Rating | Condition |
|------------------------------|------------------|----------------|----------------------------|
| Operating temperature range | T _{op} | -40°C ~ +85°C | - |
| Storage temperature range | T _{stg} | -40°C ~ +120°C | - |
| LED junction temperature | T _J | 110°C | - |
| Forward Current | I _F | 150 mA | - |
| Peak Pulsed Forward Current | I _{FP} | 300 mA | Duty 1/10 pulse width 10ms |
| Assembly Process Temperature | - | 260°C, < 10sec | - |
| ESD | - | 5kV | HBM |

2) Electro-optical Characteristics

| Item | Unit | Nominal CCT | Product Code | Rank | Min | Typ | Max | |
|------------------------------------------------------------------------------------|---------|-------------|--------------|------|------|------|------|------|
| Forward Voltage ¹⁾ (V _F) (@65 mA, T _s = 25°C) | V | - | - | WA | AZ | 2.70 | - | 2.80 |
| | | | | | A1 | 2.80 | - | 2.90 |
| | | | | | A2 | 2.90 | - | 3.00 |
| | | | | | A3 | 3.00 | - | 3.10 |
| | | | | | A4 | 3.10 | - | 3.20 |
| Luminous Flux ²⁾ (Φ _v) (@65 mA, T _s = 25°C) | lm | 2700K | *WAW☆SB | S2 | 26.0 | - | 28.0 | |
| | | | | S3 | 28.0 | - | 30.0 | |
| | | | *WAW☆SC | S3 | 28.0 | - | 30.0 | |
| | | | | S4 | 30.0 | - | 32.0 | |
| | | | *WAW☆SD | S4 | 30.0 | - | 32.0 | |
| | | | | S5 | 32.0 | - | 34.0 | |
| | | 3000K | *WAV☆SB | S2 | 26.5 | - | 28.5 | |
| | | | | S3 | 28.5 | - | 30.5 | |
| | | | *WAV☆SC | S3 | 28.5 | - | 30.5 | |
| | | | | S4 | 30.5 | - | 32.5 | |
| | | | *WAV☆SD | S4 | 30.5 | - | 32.5 | |
| | | | | S5 | 32.5 | - | 34.5 | |
| | | 3500K | *WAU☆SB | S2 | 27.0 | - | 29.0 | |
| | | | | S3 | 29.0 | - | 31.0 | |
| | | | *WAU☆SC | S3 | 29.0 | - | 31.0 | |
| | | | | S4 | 31.0 | - | 33.0 | |
| | | | *WAU☆SD | S4 | 31.0 | - | 33.0 | |
| | | | | S5 | 33.0 | - | 35.0 | |
| | | 4000K | *WAT☆SB | S2 | 28.0 | - | 30.0 | |
| | | | | S3 | 30.0 | - | 32.0 | |
| | | | *WAT☆SC | S3 | 30.0 | - | 32.0 | |
| | | | | S4 | 32.0 | - | 34.0 | |
| | | | *WAT☆SD | S4 | 32.0 | - | 34.0 | |
| | | | | S5 | 34.0 | - | 36.0 | |
| | | 5000K | *WAR☆SB | S2 | 29.0 | - | 31.0 | |
| | | | | S3 | 31.0 | - | 33.0 | |
| | | | *WAR☆SC | S3 | 31.0 | - | 33.0 | |
| | | | | S4 | 33.0 | - | 35.0 | |
| | | | *WAR☆SD | S4 | 33.0 | - | 35.0 | |
| | | | | S5 | 35.0 | - | 37.0 | |
| | | 5700K | *WAQ☆SB | S2 | 28.5 | - | 30.5 | |
| | | | | S3 | 30.5 | - | 32.5 | |
| | | | *WAQ☆SC | S3 | 30.5 | - | 32.5 | |
| | | | | S4 | 32.5 | - | 34.5 | |
| | | | *WAQ☆SD | S4 | 32.5 | - | 34.5 | |
| | | | | S5 | 34.5 | - | 36.5 | |
| 6500K | *WAP☆SB | S2 | 28.0 | - | 30.0 | | | |
| | | S3 | 30.0 | - | 32.0 | | | |
| | *WAP☆SC | S3 | 30.0 | - | 32.0 | | | |
| | | S4 | 32.0 | - | 34.0 | | | |
| | *WAP☆SD | S4 | 32.0 | - | 34.0 | | | |
| | | S5 | 34.0 | - | 36.0 | | | |



2) Electro-optical Characteristics

| Item | Unit | Nominal CCT | Product Code | Rank | Min | Typ | Max |
|-------------------------------------------|------|-------------|--------------|------|-----|-----|-----|
| Reverse Voltage (@5 mA, Ts = 25°C) | V | - | - | - | 0.7 | - | 1.2 |
| Color Rendering Index ³⁾ (Ra) | - | - | - | 5 | 80 | - | - |
| Special CRI ⁴⁾ (R9) | - | - | - | - | 0 | - | - |
| Thermal resistance(R _{th, j-s}) | °C/W | - | - | - | - | 16 | - |

Notes:

1)~4) SAMSUNG ELECTRONICS maintains a tolerance of $V_F:\pm 0.1$ V, $\Phi_V:\pm 5$ %, $R_a:\pm 3.0$, $R_9:\pm 6.5$ on measurements

5) " * " is Product Code of "SPMWHT541MD5"


3. Typical Characteristics Graph ($T_s = 25^\circ\text{C}$)

1) Spectrum Distribution

[CCT : 2700K & 3000K]



[CCT : 3500K & 4000K]



[CCT : 5000K & 5700K]



[CCT : 6500K]



2) Forward Current Characteristics

[Relative Luminous Flux vs. Forward Current]

($T_s = 25^\circ\text{C}$)



[Forward Current vs. Forward Voltage]


($T_s = 25^\circ\text{C}$)



3) Temperature Characteristics


[Relative Luminous Flux vs. T_s]

($I_F = 65\text{mA}$)



[Forward Voltage vs. T_s]

($I_F = 65\text{mA}$)



4) Color shift Characteristics

[Color Δx , Δy vs. Forward Current]

($T_s = 25^\circ\text{C}$)



[Color Δx , Δy vs. T_s]

($I_F = 65\text{mA}$)



4) Color shift Characteristics

[Color x, y vs. Ts]

($I_F = 65\text{mA}$)



[Color Δx , Δy vs. Ts]

($I_F = 65\text{mA}$)



4) Color shift Characteristics

[Color x, y vs. Ts]

($T_s = 25^\circ\text{C}$)



5) Derating Curve



6) Beam Angle Characteristics

($I_f = 65\text{mA}$ & $T_a = 25^\circ\text{C}$)



4. Outline Drawing & Dimension

1. Tolerance is ± 0.10 mm
2. The maximum compressing force is 15N on the body (a)
3. Do not place pressure on the encapsulation resin (b)

Left Side View

Top View

Bottom View



Recommended Land Pattern

Notes:

- 1) This LED has built-in ESD protection device(s) connected in parallel to LED Chip(s).
- 2) Ts point & measurement method
 - ① Measure the nearest point to the thermal pad. If necessary, remove PSR of PCB to reach Ts point.
 - ② Thermal pad must be soldered to the PCB to dissipate heat properly. Otherwise, LED can be damaged.
- 3) The thermal pad is electrically connected to the cathode contact pads
- 4) Precautions
 - ① The pressure on the LEDs will influence to the reliability of the LEDs. Precautions should be taken to avoid the strong pressure on the LEDs. Do not put stress on the LEDs during heating.
 - ② Re-soldering should not be done after the LEDs have been soldered. If re-soldering is unavoidable, LED's characteristics should be carefully checked before and after such repair.
 - ③ Do not stack assembled PCBs together. Since materials of LEDs is soft, abrasion between two PCB assembled with LED might cause catastrophic failure of the LEDs.

5. Reliability Test Items and Conditions

1) Test Items

| Test Item | Test Conditions | Test Hours/Cycles | Sample No | |
|-------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------|-----------|---|
| MSL Test | 125 °C 24hrs drying → 60 °C, 60 %RH 120hrs → 260 °C 10sec 3 cycles | 1 cycle | 11 | |
| Room Temperature life test | 25 °C±3 °C, DC150 mA | 1,000 hrs | 22 | |
| High Temperature life test | 85 °C±3 °C, DC150 mA | 1,000 hrs | 22 | |
| High Temperature humidity life test | 85 °C±3 °C, 85 %±2 %RH, DC150 mA | 1,000 hrs | 22 | |
| Low Temperature life test | -40 °C±3 °C, DC150 mA | 1,000 hrs | 22 | |
| Powered Temperature Cycle test | -45°C/20 min ↔ 85°C/20 min, Sweep 100min cycle on/off: each 5 min, DC 150 mA | 100 cycle | 22 | |
| Thermal Shock | -45 °C/15 min ↔ 125 °C/15 min → Hot plate 180 °C | 500 cycle | 100 | |
| High Temperature Storage | Ta=120 °C±3 °C | 1000 hrs | 11 | |
| Low Temperature Storage | Ta=-40 °C±3 °C | 1000 hrs | 11 | |
| ESD(HBM) | | R1:10 MΩ, R2:1.5 kΩ, C:100 pF, V = ±5 kV | 5 times | 5 |
| ESD(MM) | | R1:10 MΩ, R2: 0, C:200 pF, V = ±0.5 kV | 5 times | 5 |
| Vibration Test | 20~2000~20 Hz 200 m/s ² , Sweep 4 min X, Y, Z 3 direction, each 1 cycle | 4 cycles | 11 | |
| Mechanical Shock Test | 1500G, 0.5 ms, | 5 cycles | 11 | |

2) Criteria for Judging the Damage

| Item | Symbol | Test Condition | Limit | |
|-----------------|----------------|------------------------|-----------------|-----------------|
| | | | Min | Max |
| Forward Voltage | V _F | I _F = 65 mA | Init. Value*0.9 | Init. Value*1.1 |
| Luminous Flux | Φ _v | I _F = 65 mA | Init. Value*0.7 | Init. Value*1.2 |

6. Solder Conditions

1) Reflow Conditions (Pb Free)

Reflow Frequency : 2 times max.





2) For Manual Soldering

Not more than 5 seconds @Max. 300°C, under soldering iron.

7. Tape & Reel

1) Taping Dimension

(unit : mm)



2) Reel Dimension (max 2,500 pcs)




Tolerance ± 0.2 , Unit:mm

- (1) Quantity : The quantity/Reel to be 2,500 pcs
- (2) Cumulative Tolerance : Cumulative tolerance/10 pitches to be ± 0.2 mm
- (3) Adhesion Strength of Cover Tape : Adhesion strength to be 0.1-0.7N when the cover tape is turned off from the carrier tape at 10°C angle to be the carrier tape.
- (4) Packaging : P/N, Manufacturing data code no. and quantity to be indicated on a damp proof Package.

8. Label Structure

1) Label Structure



N.B) Denoted rank is the only example.

'★' means All kind of Chromaticity Coordinate Rank.

Rank Code

- ⒶⒷ : Forward Voltage(V_F) Rank (refer to page. 11)
- ⒸⒹ : Chromaticity Coordinate Rank (refer to page. 5~10)
- ⒺⒻ : Luminous Flux(Φ_v , lm) Rank (refer to page. 3)

2) LOT Number

The Lot number is composed of the following characters



①②③④⑤⑥⑦⑧⑨ / 1ⒶⒷⒸ / 2,500 or 10,000 PCS

- ① : Production Site (S:SAMSUNG ELECTRONICS, G:TIAJIN CHINA)
- ② : L (LED)
- ③ : Product State (A:Normality, B:Bulk, C:First Production, R:Reproduction, S:Sample)
- ④ : Year (Y:2014, Z:2015, A:2016...)
- ⑤ : Month (1 ~ 9, A, B, C)
- ⑥ : Day (1 ~ 9, A, B ~ V)
- ⑦⑧⑨ : SAMSUNG ELECTRONICS LED Product number (1 ~ 999)
- ⒶⒷⒸ : Reel Number (1 ~ 999)



9. Packing Structure


1) Packing Process (The quantity of PKG on the Reel to be Max 2,500 pcs)

Reel

A1★1S2

SPMWHT541MD5WA★0SB A1★1S2 01

GLAW94001 / 1001 / 2,500 pcs




Aluminum Vinyl Bag

A1★1S2

SPMWHT541MD5WA★0SB A1★1S2 01

GLAW94001 / 1001 / 2,500 pcs



CAUTION LEVEL 2a

MOISTURE SENSITIVE DEVICES

1. Shelf life in sealed bag: 12 months at +30°C and +90% relative humidity (RH).
2. Pouch packer body temperature must be 10°C above or other high temperature protection must be provided within 10% from production conditions of input lot or less than 30°C / 86°F, RH, or less than 40% RH.
3. Do not use.
4. Devices require baking before mounting. If necessary, bake at 120°C / 248°F.
5. If baking is required, devices must be baked for 1 hour at 80±5°C. Note: If device containers cannot be subjected to high temperature or chemical bake then use instead, minimum 80°C/176°F for 24 hours for tube products. (See end use sheet)

■ 주의 사항
이 랩탑봉 봉의 백은 습기 및 광선으로부터 제품을 보호하기 위하여 제작되었습니다. 제품을 개봉하는 즉시 랩탑봉 봉 시키는 것은 권장합니다. 습기 및 광선으로부터 제품을 보호하기 위하여, 제품을 사용할 때는 랩탑봉 봉 백에 당겨 요격 하시기 바랍니다. 적용해 지 않는 라퍼를 고 백에 넣을 때는 반드시 봉합된 상태로 백의 랩탑봉 봉 백으로부터 제품을 꺼내야 합니다. 주의가 필요합니다.

■ Important
This A1 Zipper bag is designed to protect the enclosed products from moisture and ESD. Once opened, the products should be soldered onto the printed circuit board immediately. When not in use, please do not move the products inspected for the A1 Zipper bag. To re-pack unused products, please ensure the zip-lock is completely sealed with the zip-peak left inside.

Material : Paper(SW3B(B))

| TYPE | SIZE(mm) | | | Notes |
|---------|----------|-------|-------|----------------|
| | L | W | H | |
| 7inch L | 245±5 | 220±5 | 182±5 | Up to 10 Reels |
| 7inch S | 245±5 | 220±5 | 86±5 | Up to 5 Reels |

① SIDE

A1★1S2

SPMWHT541MD5WA★0SB A1★1S2 01

GLAW94001 / 1001 / 25,000 pcs



2) Aluminum Packing Bag



CAUTION

This bag contains
MOISTURE SENSITIVE DEVICES

LEVEL


2a

1. Shelf life in sealed bag: 12 months at <math>< 40^{\circ}\text{C}</math> and <math>< 90\%</math> relative humidity (RH)
2. Peak package body temperature: 240 °C
3. After this bag is opened, devices that will be subjected to reflow solder or other high temperature processes must be:
 - a. Mounted within 672 hours at factory conditions of equal to or less than 30°C / 60% RH, or
 - b. Stored at <math>< 10\%</math> RH
4. Devices require bake, before mounting, if:
 - a. Humidity Indicator Card is > 65% when read at 23±5°C, or
 - b. 2a is not met.
5. If baking is required, devices must be baked for 1 hours at 60±5°C

Note: if device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure,

Bag seal due date: _____
(if blank, see code label)


Note: Level and body temperature by IPC/JEDEC J-STD-020



A1★1S2

SPMWHT541MD5WA★0SB A1★1S2 01

GLAW94001 / 1001 / 2,500 pcs





주의 사항

이 알루미늄 지퍼 백은 습기 및 정전기로부터 제품을 보호하기 위하여 제작되었습니다. 개봉 후에는 즉시 솔더 작업을 실시하는 것을 권장합니다.

습기 및 정전기로부터 제품을 보호 하기 위해서 개봉 후 사용하지 않는 자재는 본 팩에 넣어 보관 하시기 바랍니다. 사용하지 않는 자재를 본 팩에 넣을 때는 반드시 동봉된 드라이 팩과 함께 넣고 지퍼부분을 완전하게 밀봉하여 주시기 바랍니다.

Important

This Al Zipper bag is designed to protect the enclosed products from moisture and ESD. Once opened, the products should be soldered onto the printed circuit board immediately. When not in use, please do not leave the products unprotected by the Al Zipper Bag. To repack unused products., please ensure the zip-lock is completely sealed with the dry pack left inside.

Silica gel & Humidity Indicator Card in Aluminum Vinyl Bag



10. Precaution for use

- 1) For over-current-proof function, customers are recommended to apply resistors to prevent sudden change of the current caused by slight shift of the voltage.
- 2) This device should not be used in any type of fluid such as water, oil, organic solvent, etc. When washing is required, IPA is recommended to use.
- 3) When the LEDs illuminate, operating current should be decided after considering the ambient maximum temperature.
- 4) LEDs must be stored in a clean environment.
If the LEDs are to be stored for 3 months or more after being shipped from Samsung Electronics, they should be packed by a sealed container with nitrogen gas injected.(Shelf life of sealed bags: 12 months, temp. $\sim 40^{\circ}\text{C}$, $\sim 90\% \text{RH}$)
- 5) After storage bag is open, device subjected to soldering, solder reflow, or other high temperature processes must be:
 - a. Mounted within 672 hours(28 days) at an assembly line with a condition of no more than $30^{\circ}\text{C}/60\% \text{RH}$
 - b. Stored at $<10\% \text{RH}$.
- 6) Repack unused Products with anti-moisture packing, fold to close any opening and then store in a dry place.
- 7) Devices require baking before mounting, if humidity card reading is $>60\%$ at $23\pm 5^{\circ}\text{C}$.
- 8) Devices must be baked for 1 hour at $60\pm 5^{\circ}\text{C}$, if baking is required.
- 9) The LEDs are sensitive to the static electricity and surge. It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs.

If voltage exceeding the absolute maximum rating is applied to LEDs, it may cause damage or even destruction to LED devices.

Damaged LEDs may show some unusual characteristics such as increase in leak current, lowered turn-on voltage, or abnormal lighting of LEDs at low current.

10) VOCs (volatile organic compounds) can be generated from adhesives, flux, hardener or organic additives used in luminaires (fixtures).

Transparent LED silicone encapsulant is permeable to those chemicals and they may lead a discoloration of encapsulant when they expose to heat or light.

This phenomenon can cause a significant loss of light emitted(output) from the luminaires(fixture).

In order to prevent these problems, we recommend you to know the physical properties of the materials used in luminaires, They must be selected carefully.

11) Risk of Sulfurization (or Tarnishing)

The LED from Samsung Electronics uses a silver-plated lead frame and its surface color may change to black(or dark colored) when it is exposed to sulfur(S), chlorine (Cl) or other halogen compound.

Sulfurization of lead frame may cause intensity degradation, change of chromaticity coordinates and, in extreme cases, open circuit. It requires caution.

Due to possible sulfurization of lead frame, LED should not be used and stored together with oxidizing substances made of materials in a following list,
: Rubber, plain paper, lead solder cream and so on.


Test Report No. F690101/LF-CTSAYAA13-55130

Issued Date: 2013. 12. 11 Page 2 of 6

Sample No. : AYAA13-55130.001
Sample Description : 5630 White PKG
Item No./Part No. : N/A
Materials : N/A

Heavy Metals

| Test Items | Unit | Test Method | MDL | Results |
|-----------------------------|-------|------------------------------------------|-----|---------|
| Cadmium (Cd) | mg/kg | With reference to IEC 62321:2013, ICP | 0.5 | N.D. |
| Lead (Pb) | mg/kg | With reference to IEC 62321:2013, ICP | 5 | N.D. |
| Mercury (Hg) | mg/kg | With reference to IEC 62321:2013, ICP | 2 | N.D. |
| Hexavalent Chromium (Cr VI) | mg/kg | With reference to IEC 62321:2008, UV-VIS | 1 | N.D. |

Flame Retardants-PBBs/PBDEs

| Test Items | Unit | Test Method | MDL | Results |
|--------------------------|-------|-----------------------------------------|-----|---------|
| Monobromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Dibromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Tribromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Tetrabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Pentabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Hexabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Heptabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Octabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Nonabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Decabromobiphenyl | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Monobromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Dibromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Tribromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Tetrabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Pentabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Hexabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Heptabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Octabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Nonabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |
| Decabromodiphenyl ether | mg/kg | With reference to IEC 62321:2008, GC-MS | 5 | N.D. |

NOTE:

- (1) N.D. = Not detected. (<MDL)
- (2) mg/kg = ppm
- (3) MDL = Method Detection Limit
- (4) - = No regulation
- (5) Negative = Undetectable / Positive = Detectable
- (6) ** = Qualitative analysis (No Unit)
- (7) * = Boiling-water-extraction:
 Negative = Absence of CrVI coating
 Positive = Presence of CrVI coating; the detected concentration in boiling-water-extraction solution is equal or greater than 0.02 mg/kg with 50 cm² sample surface area.

This document is issued by the Company subject to the General Conditions of Service printed hereon available on request or accessible at <http://www.sgs.com/GeneralConditions.html> and to electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/e-documentation. Attention is drawn to the limitation of liability, indemnification and jurisdiction clause defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its issuance only and shall not constitute a warranty. The Company's sole responsibility is to its Client and the document does not constitute parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced without the prior written approval of the Company. Any unauthorised alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

P052 Version5

SGS Korea Co., Ltd.

 322, The O valley, 555-8, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
 t +82 (0)31 4808 000 f +82 (0)31 4808 059 <http://www.sgslab.co.kr> www.kr.sgs.com/presslab

Member of the SGS Group (Société Générale de Surveillance)


Test Report No. F690101/LF-CTSAYAA13-55130

Issued Date: 2013. 12. 11 Page 3 of 6

Sample No. : AYAA13-55130.001
Sample Description : 5630 White PKG
Item No./Part No. : N/A
Materials : N/A

Halogen Content

| Test Items | Unit | Test Method | MDL | Results |
|--------------|-------|-----------------------|-----|---------|
| Bromine(Br) | mg/kg | BS EN 14582:2007 , IC | 30 | N.D. |
| Chlorine(Cl) | mg/kg | BS EN 14582:2007 , IC | 30 | N.D. |
| Fluorine(F) | mg/kg | BS EN 14582:2007 , IC | 30 | 67 |
| Iodine(I) | mg/kg | BS EN 14582:2007 , IC | 50 | N.D. |

Other(s)

| Test Items | Unit | Test Method | MDL | Results |
|---------------------------------------------------------|-------|---------------------------|-----|---------|
| PFOS (Perfluorooctane Sulfonates-Acid/Metal Salt/Amide) | mg/kg | US EPA 3540C/3550C, LC/MS | 1 | N.D. |

NOTE:

- (1) N.D. = Not detected.(<MDL)
- (2) mg/kg = ppm
- (3) MDL = Method Detection Limit
- (4) - = No regulation
- (5) Negative = Undetectable / Positive = Detectable
- (6) ** = Qualitative analysis (No Unit)
- (7) * = Boiling-water-extraction:
 Negative = Absence of CrVI coating
 Positive = Presence of CrVI coating; the detected concentration in boiling-water-extraction solution is equal or greater than 0.02 mg/kg with 50 cm² sample surface area.

This document is issued by the Company subject to its General Conditions of Service (printed version) available on request or accessible at <http://www.sgs.com/Products/Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/Products/Conditions.aspx>. Attention is drawn to the limitation of liability, identification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its issuance only and within the limits of Client's instructions. If any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and each sample(s) are retained for 90 days only.

F052 Version5

SGS Korea Co., Ltd.

 322, The O valley, 555-8, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
 t +82 (0)31 4808 000 f +82 (0)31 4808 059 <http://www.sgslab.co.kr> www.br.sgs.com/sgsweb

Member of the SGS Group (Société Générale de Surveillance)



NOTE:

- (1) N.D. = Not detected.(<MDL)
- (2) mg/kg = ppm
- (3) MDL = Method Detection Limit
- (4) - = No regulation
- (5) Negative = Undetectable / Positive = Detectable
- (6) ** = Qualitative analysis (No Unit)
- (7) * = Boiling-water-extraction:
 - Negative = Absence of CrVI coating
 - Positive = Presence of CrVI coating; the detected concentration in boiling-water-extraction solution is equal or greater than 0.02 mg/kg with 50 cm² sample surface area.

This document is issued by the Company subject to its General Conditions of Service printed/overlaid available on request or accessible at http://www.sgs.com/Products/Conditions_of_Service.html for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_of_service. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein remains the Company's property and within the limits of Client instructions, if any. The Company's sole responsibility is to its Client and this document does not constitute parties to a transaction from assuming all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and each sample(s) was retained for 90 days only.



Flow Chart for Halogen Test



NOTE:

- (1) N.D. = Not detected.(<MDL)
- (2) mg/kg = ppm
- (3) MDL = Method Detection Limit
- (4) - = No regulation
- (5) Negative = Undetectable / Positive = Detectable
- (6) ** = Qualitative analysis (No Unit)
- (7) * = Boiling-water-extraction:
 Negative = Absence of CrVI coating
 Positive = Presence of CrVI coating; the detected concentration in boiling-water-extraction solution is equal or greater than 0.02 mg/kg with 50 cm2 sample surface area.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/ProductsandConditions.htm>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/ProductsandConditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein remains the Company's property at the time of its issuance and falls within the scope of Client's confidential data. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and each sample(s) are retained for 90 days only.

Test Method:

SGS In-House method - Analyzed by ICP-OES, PLM, UV/VIS, LC/MS ,GC/MS and colorimetric method

Remarks:

1. The chemical analysis of specified SVHC is performed by means of currently available analytical techniques against the following SVHC related documents published by ECHA:
<http://echa.europa.eu/web/guest/candidate-list-table> (Candidate list)
http://echa.europa.eu/proposals-to-identify-substances-of-very-high-concern-previous-consultations?p_p_id=substancecvpelist_WAB_substanceportlet&p_p_lifecycle=0&p_p_state=normal&p_p_mode=view&p_p_col_id=column-1&p_p_col_pos=2&p_p_col_count=4&substancecvpelis
 (Proposals to identify SVHC consultations)
 This list is under evaluation by ECHA and may subject to change in the future.
2. In accordance with Regulation (EC) No 1907/2006, any producer or importer of articles shall notify ECHA, in accordance with paragraph 2 of Article 7, if a substance meets the criteria in Article 57 and is identified in accordance with Article 59(1) of the Regulation, if (a) the substance is present in those articles in quantities totaling over one tonne per producer or importer per year; and (b) the substance is present in those articles above a concentration of 0.1 % weight by weight (w/w).
3. Article 33 of Regulation (EC) No 1907/2006 requires supplier of an article containing a substance meeting the criteria in Article 57 and identified in accordance with Article 59(1) in a concentration above 0.1 % weight by weight (w/w) shall provide the recipient of the article with sufficient information, available to the supplier, to allow safe use of the article including, as a minimum, the name of that substance in the Candidate List.
4. SGS adopts the interpretation of ECHA for SVHC in article unless indicated otherwise. Detail explanation is available at the following link:
http://webstage.contribute.sgs.net/corpreach/documents/SGS-CTS_SVHC-paper-EN-11.pdf
5. Test results in this report are based on the tested sample. This report refers to testing result of composite material group by equal weight proportion. The material in each composite test group may come from one article.
6. If a SVHC is found over the reporting limit, client is suggested to identify the component which contains the SVHC and the exact concentration of the SVHC by requesting further quantitative analysis from the laboratory.

This document is issued by the Company subject to its General Conditions of Service printed averted, available on request or accessible at <http://www.sgs.com/termsandconditions>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/termsandconditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any reader of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any. The Company is sole responsible to its Client and this document does not assume parties to a transaction from searching all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alterations, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for six days only.

F052 Version 5

SGS Korea Co., Ltd.

 322, The O valley, 555-B, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
 t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greenlab

Member of the SGS Group (Société Générale de Surveillance)

Test Result(s)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|------------------------|-------------------|---------------------|-------------------------------------------------|
| Alkanes, C10-13, chloro (Short Chain Chlorinated Paraffins) | 85535-84-8 | 287-476-5 | N.D. | 0.05 | PBT |
| Anthracene | 120-12-7 | 204-371-1 | N.D. | 0.05 | PBT |
| Benzyl butyl phthalate (BBP) | 85-68-7 | 201-622-7 | N.D. | 0.05 | Toxic for Reproduction |
| Bis(2-ethylhexyl)phthalate (DEHP) | 117-81-7 | 204-211-0 | N.D. | 0.05 | Toxic for Reproduction |
| Bis(tributyltin)oxide | 56-35-9 | 200-268-0 | N.D. | 0.05 | PBT |
| Cobalt dichloride* | 7646-79-9 | 231-589-4 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| 4,4-Diaminodiphenylmethane | 101-77-9 | 202-974-4 | N.D. | 0.05 | Carcinogen |
| Diarsenic pentaoxide* | 1303-28-2 | 215-116-9 | N.D. | 0.005 | Carcinogen |
| Diarsenic trioxide* | 1327-53-3 | 215-481-4 | N.D. | 0.005 | Carcinogen |
| Dibutyl phthalate (DBP) | 84-74-2 | 201-557-4 | N.D. | 0.05 | Toxic for Reproduction |
| Hexabromocyclododecane (HBCDD) and all major diastereoisomers identified (α -HBCDD, β -HBCDD, γ -HBCDD) | 25637-99-4 3194-55-6 (134237-51-7, 134237-50-6, 134237-52-8) | 247-148-4 221-695-9 | N.D. | 0.05 | PBT |
| Lead hydrogen arsenate* | 7784-40-9 | 232-064-2 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| Sodium dichromate (Sodium dichromate, dehydrate) | 10588-01-9 (7789-12-0) | 234-190-3 | N.D. | 0.005 | Carcinogen Mutagen Toxic for Reproduction |
| 5-tert-butyl-2,4,6-trinitro-m-xylene (musk xylene) | 81-15-2 | 201-329-4 | N.D. | 0.05 | vPvB |
| Triethyl arsenate* | 15606-95-8 | 427-700-2 | N.D. | 0.005 | Carcinogen |

The document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/sgs-conditions-of-service](http://www.sgs.com/sgs/sgs-conditions-of-service) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/sgs-conditions-of-service>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its issuance only and within the limits of its accreditation, if any. The Company is also responsible to its Client and the document does not constitute parties to a transaction from asserting all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and each sample(s) are referred to as 'Sample(s) only'.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greenlab

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|------------------------------------------|--------------------------------------|------------------------|-------------------|---------------------|-------------------------------------------------|
| Boric acid* | 10043-35-3 11113-50-1 | 233-139-2 234-343-4 | N.D. | 0.005 | Toxic for Reproduction |
| Disodium tetraborate, anhydrous* | 1330-43-4 12179-04-3 1303-96-4 | 215-540-4 | N.D. | 0.005 | Toxic for Reproduction |
| Tetraboron disodium heptaoxide, hydrate* | 12267-73-1 | 235-541-3 | N.D. | 0.005 | Toxic for Reproduction |
| Trichloroethylene | 79-01-6 | 201-167-4 | N.D. | 0.05 | Carcinogen |
| Sodium chromate* | 7775-11-3 | 231-889-5 | N.D. | 0.005 | Carcinogen Mutagen Toxic for Reproduction |
| Ammonium dichromate* | 7789-09-5 | 232-143-1 | N.D. | 0.005 | Carcinogen Mutagen Toxic for Reproduction |
| Potassium dichromate* | 7778-50-9 | 231-906-6 | N.D. | 0.005 | Carcinogen Mutagen Toxic for Reproduction |
| Potassium chromate* | 7789-00-6 | 232-140-5 | N.D. | 0.005 | Carcinogen Mutagen |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/portal/terms_and_conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/portal/electronic_documents.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its instructions, if any. The Company's sole responsibility is to its Client and the document does not guarantee parties to a transaction from searching all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) were obtained for so-dip only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggia-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
t +82 (0)31 4608 000 f +82 (0)31 4608 059 <http://www.sgslab.co.kr> www.kr.sgs.com/traentab

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------|-------------------|---------------------|--------------------------------------|
| Cobalt(II) sulphate* | 10124-43-3 | 233-334-2 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| Cobalt(II) dinitrate* | 10141-05-6 | 233-402-1 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| Cobalt(II) carbonate* | 513-79-1 | 208-169-4 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| Cobalt(II) diacetate* | 71-48-7 | 200-755-8 | N.D. | 0.005 | Carcinogen Toxic for Reproduction |
| 2-Methoxyethanol | 109-86-4 | 203-713-7 | N.D. | 0.05 | Toxic for Reproduction |
| 2-Ethoxyethanol | 110-80-5 | 203-804-1 | N.D. | 0.05 | Toxic for Reproduction |
| Chromium trioxide* | 1333-82-0 | 215-607-8 | N.D. | 0.005 | Carcinogen Mutagen |
| Acids generated from chromium trioxide and their oligomers: Chromic acid Dichromic acid Oligomers of chromic acid and dichromic acid | 7738-94-5 13530-68-2 | 231-801-5 236-881-5 | N.D. | 0.005 | Carcinogen |
| 1-methyl-2-pyrrolidone | 872-50-4 | 212-828-1 | N.D. | 0.05 | Toxic for Reproduction |
| 2-ethoxyethyl acetate | 111-15-9 | 203-839-2 | N.D. | 0.05 | Toxic for Reproduction |
| 1,2-benzenedicarboxylic acid, di-C6-8-branched alkyl esters, C7-rich | 71888-89-6 | 276-158-1 | N.D. | 0.05 | Toxic for Reproduction |
| 1,2-benzenedicarboxylic acid, di-C7-11-branched and linear alkyl esters | 68515-42-4 | 271-084-6 | N.D. | 0.05 | Toxic for Reproduction |
| 1,2,3-trichloropropane | 96-18-4 | 202-486-1 | N.D. | 0.05 | Carcinogen Toxic for Reproduction |
| Hydrazine | 7803-57-8 302-01-2 | 206-114-9 | N.D. | 0.05 | Carcinogen |
| Strontium chromate* | 7789-06-2 | 232-142-6 | N.D. | 0.005 | Carcinogen |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/termsandconditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/termsandconditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of its own responsibilities. It is the Company's sole responsibility as to its Client and the document does not constitute parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such samples are retained for 90 days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-090
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greenlab

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|-------------------------------------------------------------------------|--------------------------|------------|-------------------|---------------------|--------------------------------------------------------------------------------|
| 1,2-Dichloroethane | 107-06-2 | 203-458-1 | N.D. | 0.05 | Carcinogenic |
| 2,2'-dichloro-4,4'-methylenedianiline (MOCA) | 101-14-4 | 202-918-9 | N.D. | 0.05 | Carcinogenic |
| 2-Methoxyaniline o-Anisidine | 90-04-0 | 201-963-1 | N.D. | 0.05 | Carcinogenic |
| 4-(1,1,3,3-tetramethylbutyl)phenol, (4-tert-Octylphenol) | 140-66-9 | 205-426-2 | N.D. | 0.05 | Equivalent level of concern having probable serious effects to the environment |
| Aluminosilicate Refractory Ceramic Fibres* (RCF) | 650-017-00-8 (Index no.) | - | N.D. | 0.005 | Carcinogenic |
| Arsenic acid* | 7778-39-4 | 231-901-9 | N.D. | 0.005 | Carcinogenic |
| Bis(2-methoxyethyl) ether | 111-96-6 | 203-924-4 | N.D. | 0.05 | Toxic for reproduction |
| Bis(2-methoxyethyl) phthalate | 117-82-8 | 204-212-6- | N.D. | 0.05 | Toxic for reproduction |
| Calcium arsenate* | 7778-44-1 | 231-904-5 | N.D. | 0.005 | Carcinogenic |
| Dichromium tris(chromate)* | 24613-89-6 | 246-356-2 | N.D. | 0.005 | Carcinogenic |
| Formaldehyde, oligomeric reaction products with aniline (technical MDA) | 25214-70-4 | 500-036-1 | N.D. | 0.05 | Carcinogenic |
| Lead diazide* | 13424-46-9 | 236-542-1 | N.D. | 0.005 | Toxic for reproduction |
| Lead dipicrate* | 6477-64-1 | 229-335-2 | N.D. | 0.005 | Toxic for reproduction |
| Lead styphnate* | 15245-44-0 | 239-290-2 | N.D. | 0.005 | Toxic for reproduction |
| N,N-dimethylacetamide (DMAC) | 127-19-5 | 204-826-4 | N.D. | 0.05 | Toxic for reproduction |
| Pentazinc chromate octahydroxide* | 49663-84-5 | 256-418-0 | N.D. | 0.005 | Carcinogenic |
| Phenolphthalein | 77-09-8 | 201-004-7 | N.D. | 0.05 | Carcinogenic |
| Potassium hydroxyocta-oxodizincatedichromate* | 11103-86-9 | 234-329-8 | N.D. | 0.005 | Carcinogenic |
| Trilead diarsenate* | 3687-31-8 | 222-979-5 | N.D. | 0.005 | Carcinogenic Toxic for reproduction |
| Zirconia Aluminosilicate Refractory Ceramic Fibres (Zr-RCF)* | 650-017-00-8 (Index no.) | - | N.D. | 0.005 | Carcinogenic |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/e-document.htm>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its accreditation. It is the Client's sole responsibility as to its Client and the document does not constitute parties to a transaction from attaching all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offences may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this report refer only to the sample(s) tested and such sample(s) are retained for six days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greentlab

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|-------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------|-------------------|---------------------|------------------------|
| 1,2-bis(2-methoxyethoxy) ethane (TEGDME; triglyme) | 112-49-2 | 203-977-3 | N.D. | 0.05 | Toxic for reproduction |
| 1,2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME) | 110-71-4 | 203-794-9 | N.D. | 0.05 | Toxic for reproduction |
| Diboron trioxide* | 1303-86-2 | 215-125-8 | N.D. | 0.005 | Toxic for reproduction |
| Formamide | 75-12-7 | 200-842-0 | N.D. | 0.05 | Toxic for reproduction |
| Lead(II) bis(methanesulfonate)* | 17570-76-2 | 401-750-5 | N.D. | 0.005 | Toxic for reproduction |
| TGIC(1,3,5-tris (oxiranyl methyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione) | 2451-62-9 | 219-514-3 | N.D. | 0.05 | Mutagenic |
| β -TGIC (1,3,5-tris[(2S and 2R)-2,3-epoxypropyl]-1,3,5-triazine-2,4,6-(1H,3H,5H)-trione)** | 59653-74-6 | 423-400-0 | N.D. | 0.05 | Mutagenic |
| 4,4'-bis(dimethylamino) benzophenone (Michler's ketone) | 90-94-8 | 202-027-5 | N.D. | 0.05 | Carcinogenic |
| N,N,N',N'-tetramethyl-4,4'-methylenedianiline (Michler's base) | 101-61-1 | 202-959-2 | N.D. | 0.05 | Carcinogenic |
| [4-[4,4'-bis(dimethylamino) benzhydrylidene]cyclohexa-2,5-dien-1-ylidene] dimethylammonium chloride (C.I. Basic Violet 3) | 548-62-9 | 208-953-6 | N.D. | 0.05 | Carcinogenic |
| [4-[[4-anilino-1-naphthyl][4-(dimethylamino)phenyl]methylene]cyclohexa-2,5-dien-1-ylidene] dimethylammonium chloride (C.I. Basic Blue 26) | 2580-56-5 | 219-943-6 | N.D. | 0.05 | Carcinogenic |
| α,α -Bis[4-(dimethylamino) phenyl]-4 (phenylamino) naphthalene-1-methanol (C.I. Solvent Blue 4) | 6786-83-0 | 229-851-8 | N.D. | 0.05 | Carcinogenic |
| 4,4'-bis(dimethylamino)-4''-(methylamino)trityl alcohol | 561-41-1 | 209-218-2 | N.D. | 0.05 | Carcinogenic |

This document is issued by the Company subject to its General Conditions of Service printed averted, available on request or accessible at <http://www.sgs.com/term-and-conditions>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/terms-a-conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any of the Company is sole responsibility is to its Client and this document does not assume parties to a transaction from searching all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for six days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoge-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-090
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kz.sgs.com/greentlab

Member of the SGS Group (Società Generale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------|-------------------|---------------------|---------------------------------------------------------------------------|
| Bis(pentabromophenyl) ether (DecaBDE) | 1163-19-5 | 214-604-9 | N.D. | 0.05 | PBT vPvB |
| Pentacosaflluorotridecanoic acid | 72629-94-8 | 276-745-2 | N.D. | 0.05 | vPvB |
| Tricosaflluorododecanoic acid | 307-55-1 | 206-203-2 | N.D. | 0.05 | vPvB |
| Henicosaflluoroundecanoic acid | 2058-94-8 | 218-165-4 | N.D. | 0.05 | vPvB |
| Heptacosaflluorotetradecanoic acid | 376-06-7 | 206-803-4 | N.D. | 0.05 | vPvB |
| 4-(1,1,3,3-tetramethylbutyl) phenol, ethoxylated - covering well-defined substances and UVCB substances, polymers and homologues | - | - | N.D. | 0.05 | Equivalent level of concern - probable serious effects on the environment |
| 4-Nonylphenol, branched and linear - substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof | - | - | N.D. | 0.05 | Equivalent level of concern - probable serious effects on the environment |
| Diazene-1,2-dicarboxamide (C,C'-azodi(formamide)) | 123-77-3 | 204-650-8 | N.D. | 0.05 | Equivalent level of concern - probable serious effects on human health |
| Cyclohexane-1,2-dicarboxylic anhydride (Hexahydrophthalic anhydride - HHPA) | 85-42-7 | 201-604-9 | N.D. | 0.05 | Equivalent level of concern - probable serious effects on human health |

This document is issued by the Company subject to its General Conditions of Service printed herein, available on request or accessible at <http://www.sgs.com/termsandconditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/termsandconditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issue defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its accreditation. Any third party is also responsible to its Client and the document does not constitute parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greentab

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|----------------------------------------|------------|-----------|-------------------|---------------------|------------------------|
| Dioxobis(stearato)trilead* | 12578-12-0 | 235-702-8 | N.D. | 0.005 | Toxic for reproduction |
| Fatty acids, C16-18, lead salts* | 91031-62-8 | 292-966-7 | N.D. | 0.005 | Toxic for reproduction |
| Lead bis(tetrafluoroborate)* | 13814-96-5 | 237-486-0 | N.D. | 0.005 | Toxic for reproduction |
| Lead cyanamidate* | 20837-86-9 | 244-073-9 | N.D. | 0.005 | Toxic for reproduction |
| Lead dinitrate* | 10099-74-8 | 233-245-9 | N.D. | 0.005 | Toxic for reproduction |
| Lead oxide (lead monoxide)* | 1317-36-8 | 215-267-0 | N.D. | 0.005 | Toxic for reproduction |
| Lead tetroxide (orange lead)* | 1314-41-6 | 215-235-6 | N.D. | 0.005 | Toxic for reproduction |
| Lead titanium trioxide* | 12060-00-3 | 235-038-9 | N.D. | 0.005 | Toxic for reproduction |
| Lead Titanium Zirconium Oxide* | 12626-81-2 | 235-727-4 | N.D. | 0.005 | Toxic for reproduction |
| Pentalead tetraoxide sulphate* | 12065-90-6 | 235-067-7 | N.D. | 0.005 | Toxic for reproduction |
| Pyrochlore, antimony lead yellow* | 8012-00-8 | 232-382-1 | N.D. | 0.005 | Toxic for reproduction |
| Silicic acid, barium salt, lead-doped* | 68784-75-8 | 272-271-5 | N.D. | 0.005 | Toxic for reproduction |
| Silicic acid, lead salt* | 11120-22-2 | 234-363-3 | N.D. | 0.005 | Toxic for reproduction |
| Sulfurous acid, lead salt, dibasic* | 62229-08-7 | 263-467-1 | N.D. | 0.005 | Toxic for reproduction |
| Tetraethyllead* | 78-00-2 | 201-075-4 | N.D. | 0.005 | Toxic for reproduction |
| Tetralead trioxide sulphate* | 12202-17-4 | 235-380-9 | N.D. | 0.005 | Toxic for reproduction |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/sgs/conditions/terms_and_conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_electronic_documents.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its issuance only and within the limits of Client's instructions. If any, the Company is also responsible to its Client and the document does not constitute parties to a transaction from asserting all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested and each sample(s) are retained for six days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-B, Hogeyp-dong, Dangan-gu, Anyang-si, Gyeonggi-do, Korea 431-090
t +82 (0)31 4608 000 f +82 (0)31 4608 059 <http://www.sgslab.co.kr/www.kr.sgs.com/greenlab>

Member of the SGS Group (Société Générale de Surveillance)

| Substance Name | CAS number | EC number | Concentration (%) | Reporting Limit (%) | Classification |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------|-------------------|---------------------|--------------------------------------------------------------------------------|
| Cadmium | 7440-43-9 | 231-152-8 | N.D. | 0.005 | Carcinogenic |
| Cadmium oxide | 1306-19-0 | 215-146-2 | N.D. | 0.005 | Carcinogenic |
| Dipentyl phthalate (DPP) | 131-18-0 | 205-017-9 | N.D. | 0.05 | Toxic for reproduction |
| 4-Nonylphenol, branched and linear, ethoxylated [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, ethoxylated covering UVCB- and well-defined substances, polymers and homologues, which include any of the individual isomers and/or combinations thereof] | - | - | N.D. | 0.05 | Equivalent level of concern having probable serious effects to the environment |
| Ammonium pentadecafluorooctanoate (APFO) | 3825-26-1 | 223-320-4 | N.D. | 0.05 | Toxic for reproduction |
| Pentadecafluorooctanoic acid (PFOA) | 335-67-1 | 206-397-9 | N.D. | 0.05 | Toxic for reproduction |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/ServiceTermsandConditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/ServiceTermsandConditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its revision in print and within the limits of its accreditation. Any use of this document is solely the responsibility of the Client and the document does not constitute parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offences may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and each sample(s) are retained for 30 days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hogya-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
T +82 (0)31 4608 000 F +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/traenlab

Member of the SGS Group (Società Generale de Surveillance)

Note:

1. RL = Reporting Limit
2. N.D. = Not detected (lower than RL)

N.A. = Not applicable for respective material type.


The submitted sample was found to contain significant amount of specific element(s) of SVHC. Upon further test verification and also information provided from client, the possibility that the element(s) content originate from SVHC is very unlikely, even though their presence cannot be exclude entirely. It may be assumed that the detected element(s) have a non-SVHC source.

3. Definition of classification is listed in Appendix A of this report in accordance with 67/548/EEC and Regulation (EC) No 1907/2006. For detail information, Detail explanation is available at the following link:
<http://echa.europa.eu/web/guest/candidate-list-table> (Candidate list)
http://echa.europa.eu/proposals-to-identify-substances-of-very-high-concern-previous-consultations?p_p_id=substancecvpelist_WAR_substanceportlet&p_p_lifecycle=0&p_p_state=normal&p_p_mode=view&p_p_col_id=column-1&p_p_col_pos=2&p_p_col_count=4&substancecvpelis
 (Proposals to identify SVHC consultations)
4. *.The test result is based on the calculation of selected element(s) / marker(s) and to the worst-case scenario. For detail information, please refer to the SGS REACH website: www.reach.sgs.com/substance-of-very-high-concern-analysis-information-page.htm

The client is advised to review the chemical formulation to ascertain above metal substances present in the article.
 RL = 0.005% is evaluated for element (i.e. cobalt, arsenic, lead, sodium, chromium, chromium(VI), silicon, aluminum, zirconium, boron, and potassium respectively), except molybdenum RL=0.0005%

0.1% (w/w) = 1,000 ppm = 1,000 mg/kg

5. **.β-TGIC is one of the isomers for TGIC compounds and hence, tested together. The reported test result is based the proposed ratio as according to ECHA dossier.



*** End of Report ***

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/terms-e-document.pdf>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its observation only and within the limits of Client's instructions. It is the Client's sole responsibility to its Client and the document does not ascribe parties to a transaction from ascribing all their rights and obligations under the transaction documents. The document cannot be reproduced except in full without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise indicated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The C valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
 t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greenlab

Member of the SGS Group (Société Générale de Surveillance)

Appendix A

| | |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Classification | Definition under 67/548/EEC and Regulation (EC) No 1907/2006 |
| Carcinogen Category 1: | <u>Substances known to be carcinogenic to man.</u> There is sufficient evidence to establish a causal association between human exposure to a substance and the development of cancer. |
| Carcinogen Category 2: | <u>Substances which should be regarded as if they are carcinogenic to man.</u> There is sufficient evidence to provide a strong presumption that human exposure to a substance may result in the development of cancer. Generally on the basis of: - appropriate long-term animal studies - other relevant information. |
| Mutagen Category 1: | <u>Substances known to be mutagenic to man.</u> There is sufficient evidence to establish a causal association between human exposure to a substance and heritable genetic damage. |
| Mutagen Category 2: | <u>Substances which should be regarded as if they are mutagenic to man.</u> There is sufficient evidence to provide a strong presumption that human exposure to the substance may result in the development of heritable genetic damage, generally on the basis of: - appropriate animal studies, - other relevant information. |
| Toxic to Reproduction Category 1: | <u>Substances known to impair fertility in humans.</u> There is sufficient evidence to establish a causal relationship between human exposure to the substance and impaired fertility. <u>Substances known to cause developmental toxicity in humans.</u> There is sufficient evidence to establish a causal relationship between human exposure to the substance and subsequent developmental toxic effects in the progeny. |
| Toxic to Reproduction Category 2: | <u>Substances which should be regarded as if they impair fertility in humans.</u> There is sufficient evidence to provide a strong presumption that human exposure to the substance may result in impaired fertility on the basis of: - clear evidence in animal studies of impaired fertility in the absence of toxic effects, or, evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary nonspecific consequence of the other toxic effects, - other relevant information. <u>Substances which should be regarded as if they cause developmental toxicity to humans.</u> There is sufficient evidence to provide a strong presumption that human exposure to the substance may result in developmental toxicity, generally on the basis of: - clear results in appropriate animal studies where effects have been observed in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of the other toxic effects, - other relevant information. |
| PBT & vPvB: | Substances which are persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) pose a particular challenge to the chemicals safety management. For these substances a "safe" concentration in the environment cannot be established with sufficient reliability. |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/Forms_electronic.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its field of competence. It is the Client's sole responsibility as to its Client and the document does not absolve parties to a transaction from assuming all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise indicated the results shown in the test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

F052 Version 5

SGS Korea Co., Ltd.

322, The O valley, 555-9, Hoggae-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080
t +82 (0)31 4608 000 f +82 (0)31 4608 050 <http://www.sgslab.co.kr> www.kr.sgs.com/greenlab

Member of the SGS Group (Société Générale de Surveillance)

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View SPMWHT541MD5WAW0SD on WIN SOURCE](#)
- ⊖ [Samsung Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management