



**THE DATASHEET OF
S29GL01GS11FAIV23**



S29GL-S (Pb Package)

**3 Volt-Only Flash Memory with Page Mode
featuring 65 nm MirrorBit® Process Technology
Device Documentation**



Supplement

General Description

This supplementary document provides information on a device designed for limited distribution. It describes how the features, operation, and ordering options of this device have been enhanced or changed from the standard device on which it is based. The information contained in this document modifies any information on the same topics established by the data sheets listed in the Affected Documents/Related Documents table and should be used in conjunction with those documents. This document may also contain information that was not previously covered by the S29GL-S data sheet. It is intended for hardware system designers and software developers of applications, operating systems, or tools.

Affected Documents/Related Documents

Title	Publication Number
S29GL-S MirrorBit Flash Family Data Sheet	S29GL_128S_01GS_00

Table of Contents

General Description	1
Affected Documents/Related Documents	1
1. Device Description	3
2. Device Bus Operation Changed	3
3. Embedded Algorithm Performance	3
4. Electrical Specifications	3
5. Timing Specifications	3
6. Ordering Information	4
7. Revision History	6

1. Device Description

None.

2. Device Bus Operation Changed

None.

3. Embedded Algorithm Performance

None.

4. Electrical Specifications

None.

5. Timing Specifications

None.

6. Ordering Information

Valid Combinations

The Recommended Combinations table lists configurations planned to be available in volume. The table below will be updated as new combinations are released. Consult your local sales representative to confirm availability of specific combinations and to check on newly released combinations.

S29GL-S Valid Combinations					
Base OPN	Speed (ns)	Package and Temperature	Model Number	Packing Type	Ordering Part Number (yy = Model Number, x = Packing Type)
S29GL01GS	100	FAI (Note 1)	01, 02	0, 3 (Note 2)	S29GL01GS10FAlyyx
	110		V1, V2		S29GL01GS11FAlyyx
S29GL512S	100		01, 02		S29GL512S10FAlyyx
	110		V1, V2		S29GL512S11FAlyyx
S29GL256S	90		01, 02		S29GL256S10FAlyyx
	100		V1, V2		S29GL256S90FAlyyx
S29GL128S	90		01, 02		S29GL128S10FAlyyx
	100		V1, V2		S29GL128S90FAlyyx

Notes:

1. Additional speed, package, and temperature options maybe offered in the future. Check with your local sales representative for availability.
2. Package Type 0 is standard option.

The ordering part number for the device is formed by a valid combination of the following:



7. Revision History

Section	Description
Revision 01 (October 21, 2011)	
	Initial release
Revision 02 (December 14, 2011)	
Ordering Information	Updated Valid Combinations table
Revision 03 (April 17, 2012)	
Ordering Information	Updated Valid Combinations table

Colophon

The products described in this document are designed, developed and manufactured as contemplated for general use, including without limitation, ordinary industrial use, general office use, personal use, and household use, but are not designed, developed and manufactured as contemplated (1) for any use that includes fatal risks or dangers that, unless extremely high safety is secured, could have a serious effect to the public, and could lead directly to death, personal injury, severe physical damage or other loss (i.e., nuclear reaction control in nuclear facility, aircraft flight control, air traffic control, mass transport control, medical life support system, missile launch control in weapon system), or (2) for any use where chance of failure is intolerable (i.e., submersible repeater and artificial satellite). Please note that Spansion will not be liable to you and/or any third party for any claims or damages arising in connection with above-mentioned uses of the products. Any semiconductor devices have an inherent chance of failure. You must protect against injury, damage or loss from such failures by incorporating safety design measures into your facility and equipment such as redundancy, fire protection, and prevention of over-current levels and other abnormal operating conditions. If any products described in this document represent goods or technologies subject to certain restrictions on export under the Foreign Exchange and Foreign Trade Law of Japan, the US Export Administration Regulations or the applicable laws of any other country, the prior authorization by the respective government entity will be required for export of those products.

Trademarks and Notice

The contents of this document are subject to change without notice. This document may contain information on a Spansion product under development by Spansion. Spansion reserves the right to change or discontinue work on any product without notice. The information in this document is provided as is without warranty or guarantee of any kind as to its accuracy, completeness, operability, fitness for particular purpose, merchantability, non-infringement of third-party rights, or any other warranty, express, implied, or statutory. Spansion assumes no liability for any damages of any kind arising out of the use of the information in this document.

Copyright © 2011-2012 Spansion Inc. All rights reserved. Spansion®, the Spansion logo, MirrorBit®, MirrorBit® Eclipse™, ORNAND™ and combinations thereof, are trademarks and registered trademarks of Spansion LLC in the United States and other countries. Other names used are for informational purposes only and may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View S29GL01GS11FAIV23 on WIN SOURCE](#)
- ⊖ [Cypress Semiconductor Corp Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management