



THE DATASHEET OF SRP1038C-150M





Features

- Shielded construction
- Metal alloy powder core
- High saturation current
- Low buzz noise
- Inductance range: 0.10 to 47 μ H
- RoHS compliant* and halogen free**



This series is currently available but not recommended for new designs.



SRP1038C Series - Shielded Power Inductors

Electrical Specifications @ 25 °C



Bourns Part Number	Inductance @ 100 kHz / 1 V		Q (Min.) @ 100 kHz / 1 V	SRF (MHz) Typ.	DCR (m Ω) Typ.	DCR (m Ω) Max.	Irms (A) Typ.	Isat (A) Typ.	Terminal Type
	L (μ H)	Tol. (%)							
SRP1038C-R10Y	0.10	30	10	215	0.32	0.38	53.0	85.0	Non-Lead Frame
SRP1038C-R15M	0.15	20	10	150	0.50	0.60	45.0	80.0	
SRP1038C-R20M	0.20	20	10	142	0.80	1.00	40.0	75.0	
SRP1038C-R22M	0.22	20	15	142	0.80	1.00	40.0	75.0	
SRP1038C-R30M	0.30	20	15	99	1.00	1.20	38.0	70.0	
SRP1038C-R33M	0.33	20	15	88	1.00	1.20	38.0	70.0	
SRP1038C-R36M	0.36	20	15	88	1.05	1.20	36.0	60.0	
SRP1038C-R47M	0.47	20	15	72	1.30	1.50	31.0	48.0	
SRP1038C-R68M	0.68	20	15	63	2.30	2.70	24.0	45.0	Lead Frame
SRP1038C-1R0M	1.00	20	15	45	3.50	4.00	20.0	39.0	
SRP1038C-1R5M	1.50	20	15	35	4.70	5.30	18.0	35.0	
SRP1038C-2R2M	2.20	20	15	27	6.50	7.20	15.0	27.0	
SRP1038C-3R3M	3.30	20	15	20	10.80	11.80	14.0	22.0	
SRP1038C-4R7M	4.70	20	15	15	14.50	15.50	13.0	20.0	
SRP1038C-5R6M	5.60	20	15	13	18.00	19.30	12.0	16.0	
SRP1038C-6R8M	6.80	20	15	12	19.00	23.30	10.0	15.0	
SRP1038C-8R2M	8.20	20	15	11	20.00	22.50	9.0	13.5	
SRP1038C-100M	10.0	20	15	10	29.00	32.00	8.5	12.5	
SRP1038C-150M	15.0	20	20	9	40.00	45.00	6.3	10.0	
SRP1038C-220M	22.0	20	20	8	62.00	74.00	5.2	7.5	
SRP1038C-270M	27.0	20	20	6.5	80.00	96.00	4.5	6.5	
SRP1038C-330M	33.0	20	20	6.5	94.00	112.00	4.0	6.0	
SRP1038C-470M	47.0	20	20	6	145.00	167.00	3.2	5.0	

Product Dimensions

Lead Frame



Non-Lead Frame



DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$

General Specifications


Operating Temperature -40 °C to +125 °C
(Temperature rise included)
Storage Temperature (Component) -40 °C to +125 °C
Rated Current Inductance drops 30 % at Isat
Temperature Rise 40 °C at rated Irms
Moisture Sensitivity Level 1
ESD Classification (HBM) N/A

¹ Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.


Materials

Core Metal alloy powder
Wire Enameled copper
Terminal Finish Sn/Ni
Packaging 500 pcs. per 13-inch reel

Electrical Schematic



Recommended Layout



WARNING Cancer and Reproductive Harm
www.P65Warnings.ca.gov

* RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

**Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.


Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific disclaimers as set forth on the last page of this document, and at www.bourns.com/legal/disclaimer.pdf.

SRP1038C Series - Shielded Power Inductors

BOURNS®

Soldering Profile



REFLOW TIMES: 3 MAX.










How to Order

SRP1038C - 100M

Model _____
Value Code (see table) _____

Please consult [Bourns® Model SRP-A Series Visual Inspection Guide](#) for detailed construction, processing and testing information.

L vs. I Charts



Specifications are subject to change without notice.















Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific disclaimers as set forth on the last page of this document, and at www.bourns.com/legal/disclaimer.pdf.

SRP1038C Series - Shielded Power Inductors

BOURNS®

L vs. I Charts (Continued)



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific disclaimers as set forth on the last page of this document, and at www.bourns.com/legal/disclaimer.pdf.

BOURNS®

Technical drawing of a 13mm diameter chip carrier, showing top, side, and plan views with dimensions in inches and millimeters.

Top View:

- Overall diameter: 13 ± 0.5 (.079 ± .020) DIA.
- Inner diameter: $13 + 0.5 / - 0.2$ (.512 ± .020 / -.008) DIA.
- Mounting hole diameter: 3.30 (12.99) DIA.
- Mounting hole offset: 2.0 ± 0.5 (.079 ± .020)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)

Side View:

- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)

Plan View:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Dimensions:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Features:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Mounting:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Assembly:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Dimensions:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Features:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Mounting:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

Carrier Assembly:

- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)
- Carrier width: $24.4 \pm 2 / - 0$ (.961 ± .079 / -0)
- Carrier thickness: 100.0 ± 2.0 (3.937 ± .079)

The products described herein and this document are subject to specific disclaimers as set forth on the last page of this document, and at www.bourns.com/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 View [SRP1038C-150M](#) on WIN SOURCE

 [Bourns Inc.](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management