



THE DATASHEET OF JCK1524S12

15 Watts

JCK Series



- 2:1 Input Range
- Industry Standard Package
- 1600 VDC Isolation
- Continuous Short Circuit Protection
- High Efficiency – up to 89%
- -40 °C to +100 °C Operating Temperature
- 3 Year Warranty

Specification

Input

Input Voltage Range	• 12 V (9-18 VDC) • 24 V (18-36 VDC) • 48 V (36-75 VDC)
Input Current	• See table
Input Reflected Ripple Current	• 20 mA rms through 12 μH inductor, 5 Hz to 20 MHz
Under Voltage Lockout	• 12 V models On 8.6 V, Off 7.9 V typical • 24 V models On 17.8 V, Off 16 V typical • 48 V models On 33.5 V, Off 30.5 V typical
Input Surge	• 12 V models 30 VDC for 100 ms • 24 V models 50 VDC for 100 ms • 48 V models 100 VDC for 100 ms

Output

Output Voltage	• See table
Minimum Load	• No minimum load required
Line Regulation	• $\pm 0.5\%$ max
Load Regulation	• $\pm 0.5\%$ max for single and $\pm 1\%$ max for dual outputs
Cross Regulation	• $\pm 5\%$ max on dual output models (see note 2)
Setpoint Accuracy	• $\pm 1.0\%$ max
Start Up Delay	• <20 ms
Start Up Rise Time	• <5 ms
Ripple & Noise	• 75 mV pk-pk max (see note 3)
Transient Response	• $\pm 3\%$ max deviation, recovery to within 1% in 250 μs for a 25% load change
Temperature Coefficient	• 0.02%/°C
Overload Protection	• >140% of full load at nominal input
Short Circuit Protection	• Trip & restart (hiccup mode) with auto recovery
Maximum Capacitive Load	• See table

General

Efficiency	• See table
Isolation Voltage	• 1600 VDC Input to Output, optional 3500 V (see note 4) • 1600 VDC Input to Case • 1600 VDC Output to Case
Isolation Capacitance	• 1200 pF typical
Isolation Resistance	• $10^9 \Omega$ min
Switching Frequency	• 300 kHz typical
Power Density	• 18.75 W/in³
MTBF	• >1.1 Mhrs to MIL-HDBK-217F at 25 °C, GB

Environmental

Operating Temperature	• -40 °C to +100 °C, derate from 100% load at +70 °C to 0% load at +100 °C
Case Temperature	• +100 °C max
Storage Temperature	• -40 °C to +125 °C
Cooling	• Convection-cooled
Operating Humidity	• Up to 95% RH, non-condensing

EMC

Emissions	• EN55022, Class A conducted & radiated with external components, see application note
ESD Immunity	• EN61000-4-2, 8 kV air, 6 kV contact, Perf Criteria A
Radiated Immunity	• EN61000-4-3 10 V/m, Perf Criteria A
EFT/Burst	• EN61000-4-4 level 3, Perf Criteria B*
Surge	• EN61000-4-5 level 2, Perf Criteria B*
Conducted Immunity	• EN61000-4-6 10 V/rms, Perf Criteria A
Magnetic Field	• EN61000-4-8 1 A/m, Perf Criteria A

Safety

Safety Approvals	• CE (Meets all applicable directives), UKCA (Meets all applicable legislation)
------------------	---

*External input capacitor required 220 μ F/100 V.

Models and Ratings


JCK15 **XP**

Input Voltage	Output Voltage	Output Current	Input Current ⁽¹⁾		Maximum Capacitive Load	Efficiency	Model Number ⁽⁴⁾
			No Load	Full Load			
9-18 VDC	3.3 V	3.00 A	30 mA	1.03 A	3300 μ F	82%	JCK1512S3V3
	5.0 V	3.00 A	30 mA	1.52 A	3300 μ F	84%	JCK1512S05
	12.0 V	1.250 A	30 mA	1.45 A	1000 μ F	88%	JCK1512S12
	15.0 V	1.000 A	30 mA	1.44 A	680 μ F	89%	JCK1512S15
	± 3.3 V	± 1.500 A	30 mA	1.03 A	± 1000 μ F	82%	JCK1512D03
	± 5.0 V	± 1.500 A	30 mA	1.50 A	± 1000 μ F	85%	JCK1512D05
	± 12.0 V	± 0.625 A	30 mA	1.45 A	± 470 μ F	88%	JCK1512D12
	± 15.0 V	± 0.500 A	30 mA	1.45 A	± 330 μ F	88%	JCK1512D15
18-36 VDC	3.3 V	3.000 A	25 mA	0.52 A	3300 μ F	82%	JCK1524S3V3
	5.0 V	3.000 A	25 mA	0.75 A	3300 μ F	85%	JCK1524S05
	12.0 V	1.250 A	25 mA	0.72 A	1000 μ F	89%	JCK1524S12
	15.0 V	1.000 A	25 mA	0.72 A	680 μ F	89%	JCK1524S15
	± 3.3 V	± 1.500 A	25 mA	0.52 A	± 1000 μ F	82%	JCK1524D03
	± 5.0 V	± 1.500 A	25 mA	0.75 A	± 1000 μ F	85%	JCK1524D05
	± 12.0 V	± 0.625 A	25 mA	0.72 A	± 470 μ F	88%	JCK1524D12
	± 15.0 V	± 0.500 A	25 mA	0.72 A	± 330 μ F	88%	JCK1524D15
36-75 VDC	3.3 V	3.000 A	20 mA	0.26 A	3300 μ F	82%	JCK1548S3V3
	5.0 V	3.000 A	20 mA	0.38 A	3300 μ F	85%	JCK1548S05
	12.0 V	1.250 A	20 mA	0.36 A	1000 μ F	89%	JCK1548S12
	15.0 V	1.000 A	20 mA	0.36 A	680 μ F	89%	JCK1548S15
	± 3.3 V	± 1.500 A	20 mA	0.26 A	± 1000 μ F	82%	JCK1548D03
	± 5.0 V	± 1.500 A	20 mA	0.38 A	± 1000 μ F	85%	JCK1548D05
	± 12.0 V	± 0.625 A	20 mA	0.36 A	± 470 μ F	88%	JCK1548D12
	± 15.0 V	± 0.500 A	20 mA	0.36 A	± 330 μ F	88%	JCK1548D15

Notes

1. Measured at nominal input voltage.
2. When one output is set at 100% load and other varied between 25% and 100% load.
3. Measured with 20 MHz bandwidth and 1 μ F ceramic capacitor across output rails.
4. For optional 3.5 kV isolation version, add suffix -H to part number eg. JCK1524S12-H.
5. For heatsink option add '-HK' to the end of the part number.


Mechanical Details




Notes

1. All dimensions are in inches (mm).
2. Weight: 0.07 lbs (30 g)
3. Pin diameter: 0.04 $\pm$ 0.002 (1.0 $\pm$ 0.05)
4. Pin pitch tolerance: $\pm$ 0.014 ($\pm$ 0.35)
5. Case tolerance: $\pm$ 0.02 ($\pm$ 0.5)

Derating Curve



Input Filter



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ View [JCK1524S12](#) on WIN SOURCE
- ⊖ [XP Power](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management