






**THE DATASHEET OF
9A0924G401**



92x92x25 mm

San Cooler 92 9A type   



General Specifications

- Material Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C, rated voltage)
Expected life at 40°C is for reference only.
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 599.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)
- Sound pressure level (SPL) At 1 m away from the air inlet
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire ⊕Red ⊖Black or Blue (Sensor) Yellow
- Mass 100 g

Specifications

The models listed below **have ribs and pulse sensors**. For models without ribs, append "1" to the end of model numbers.


Model no.	Rated voltage [V]	Operating voltage range [V]	Rated current [A]	Rated input [W]	Rated speed [min ⁻¹]	Max. airflow [m ³ /min] [CFM]	Max. static pressure [Pa] [inchH ₂ O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
▶▶ 9A0912G401	12	6 to 13.8	0.39	4.68	3900	1.76 62.1	66.5 0.267	43	-20 to +60	30000/60°C (53000/40°C)
▶▶ 9A0912S401			0.27	3.24	3550	1.66 58.6	56.1 0.225	39		
▶▶ 9A0912H401			0.21	2.52	3150	1.45 51.2	44 0.177	33		
▶▶ 9A0912F401			0.14	1.68	2650	1.24 43.8	32.2 0.129	30		
▶▶ 9A0912M401			0.12	1.44	2250	1.04 36.7	22.6 0.091	27		
▶▶ 9A0912L401			0.07	0.84	1750	0.8 28.2	13.4 0.054	23		
▶▶ 9A0924G401	24	12 to 27.6	0.19	4.56	3900	1.76 62.1	66.5 0.267	43	-20 to +60	30000/60°C (53000/40°C)
▶▶ 9A0924S401			0.15	3.6	3550	1.66 58.6	56.1 0.225	39		
▶▶ 9A0924H401			0.1	2.4	3150	1.45 51.2	44 0.177	33		
▶▶ 9A0924F401			0.08	1.92	2650	1.24 43.8	32.2 0.129	30		
▶▶ 9A0924M401			0.05	1.2	2250	1.04 36.7	22.6 0.091	27		
▶▶ 9A0924L401			0.04	0.96	1750	0.8 28.2	13.4 0.054	23		
▶▶ 9A0948S401	48	40.5 to 53	0.08	3.84	3550	1.66 58.6	56.1 0.225	39	-20 to +60	

Note 1: Sensor and control options are available for selection. Refer to the table on p. 624.
 Note 2: The ▶▶ mark indicates Short LeadTime Service applicable models. See p. 654 for details.

Airflow - Static Pressure Characteristics


9A0912G401 With pulse sensor

Operating voltage range




9A0912S401 With pulse sensor

Operating voltage range



9A0912H401 With pulse sensor


Operating voltage range



Airflow - Static Pressure Characteristics


9A0912F401 With pulse sensor

Operating voltage range




9A0912M401 With pulse sensor

Operating voltage range




9A0912L401 With pulse sensor

Operating voltage range




9A0924G401 With pulse sensor

Operating voltage range




9A0924S401 With pulse sensor

Operating voltage range




9A0924H401 With pulse sensor

Operating voltage range




9A0924F401 With pulse sensor

Operating voltage range




9A0924M401 With pulse sensor

Operating voltage range




9A0924L401 With pulse sensor

Operating voltage range




9A0948S401 With pulse sensor


Operating voltage range



Dimensions (unit: mm) (With ribs)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards page: p. 584
 Model no.: 109-099E, 109-099H, 109-099C

Resin finger guards page: p. 591
 Model no.: 109-1001G

Resin filter kits page: p. 592
 Model no.: 109-1001F13 (13PPI), 109-1001F20 (20PPI),
 109-1001F30 (30PPI), 109-1001F40 (40PPI)

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View 9A0924G401 on WIN SOURCE](#)
- [Sanyo Denki America Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management