



THE DATASHEET OF EKS-LM4F232

Stellaris® LM4F232 USB+CAN Evaluation Kit

The Stellaris LM4F232 USB+CAN Evaluation Kit is a compact and versatile evaluation platform for the Stellaris LM4F232 ARM® Cortex™-M4F-based microcontroller. The evaluation kit design highlights the LM4F232 microcontroller's integrated USB 2.0 On-the-Go/Host/Device interface, CAN, analog, and low-power capabilities.



Features

The evaluation kit features a Stellaris microcontroller in a 144-LQFP package, a color OLED display, USB OTG connector, a microSD card slot, a coin cell battery for use with the Stellaris low-power Hibernate mode, a temperature sensor, a three-axis accelerometer for motion detection, and easy access through holes to all of the available device signals.

The kit also includes extensive source code examples, allowing you to start building C code applications quickly. The evaluation kit includes the following features:

- Uses Stellaris LM4F232H5QD with 256KB internal Flash and 144-LQFP with excellent prototyping capability
- 96×64 color OLED display providing useful output and interface options
- USB Micro-AB for prototyping USB application
- microSD card slot for data storage
- 5-mm screw terminals for attaching external sensors and other analog inputs
- Precision 3.0-V reference for accurate analog-to-digital conversion
- Temperature sensor for temperature monitoring
- 3-axis accelerometer for position sensing
- All I/O brought out to headers for easy prototyping
- Five user/navigation buttons (including select/ wake) for user input
- One user LED
- 10-pin JTAG header providing standard debug interface

Kit Contents

The evaluation kit contains everything you need to develop and run applications for Stellaris microcontrollers including:

- Stellaris EK-LM4F232 evaluation board
- On-board Stellaris In-Circuit Debug Interface (ICDI)
- Cables
 - USB Mini-B cable for debug function
 - USB Micro-A-plug-to-Std-A receptacle cable (connects to USB Flash drive)
 - USB Micro-B-plug-to-USB-A plug cable (connects to PC as a USB device)
 - USB Flash drive
- 3-V CR2032 lithium coin-cell battery
- Evaluation Kit CD containing:
 - Complete documentation
 - StellarisWare® Peripheral Driver Library and example source code
- Stellaris Firmware Development Package with example source code
- Quickstart application with source code
 - Windows companion application for quickstart application
- A supported evaluation version of one of the following:
 - Keil™ RealView® Microcontroller Development Kit (MDK-ARM)
 - IAR Embedded Workbench® development tools
 - Sourcery CodeBench development tools
 - Code Red Technologies Red Suite
 - Texas Instruments' Code Composer Studio™ IDE

Ordering information

Product Number	Description
EKK-LM4F232	Stellaris LM4F232 Evaluation Kit for Keil™ RealView® MDK-ARM (32 KB code-size limited)
EKI-LM4F232	Stellaris LM4F232 Evaluation Kit for IAR Systems Embedded Workbench® (32 KB code-size limited)
EKC-LM4F232	Stellaris LM4F232 Evaluation Kit for Sourcery CodeBench (30-day limited)
EKT-LM4F232	Stellaris LM4F232 Evaluation Kit for Code Red Technologies Red Suite (90-day limited)
EKS-LM4F232	Stellaris LM4F232 Evaluation Kit for Code Composer Studio™ IDE (board-locked)

Texas Instruments • 108 Wild Basin, Suite 350 • Austin, TX 78746

<http://www.ti.com/stellaris>

Copyright © 2011 Texas Instruments, Inc. All rights reserved. Stellaris and StellarisWare are registered trademarks of Texas Instruments. ARM and Thumb are registered trademarks, and Cortex is a trademark of ARM Limited. Other names and brands may be claimed as the property of others.



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 View [EKS-LM4F232](#) on WIN SOURCE

 [Texas Instruments](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management