



# THE DATASHEET OF NCV8135AMTW040TBG

# 500 mA, Very Low Dropout Bias Rail CMOS Voltage Regulator NCV8135

The NCV8135 is a 500 mA VLDO equipped with NMOS pass transistor and a separate bias supply voltage ( $V_{BIAS}$ ). The device provides very stable, accurate output voltage with low noise suitable for space constrained, noise sensitive applications. In order to optimize performance for battery operated portable applications, the NCV8135 features low  $I_Q$  consumption. The NCV8135 is offered in WDFN6 2 mm x 2 mm package, wettable flanks option available for Enhanced Optical Inspection.

## Features

- Input Voltage Range: 0.4 V to 5.5 V
- Bias Voltage Range: 2.5 V to 5.5 V
- Fixed Output Voltage Versions Available
- $\pm 1\%$  Accuracy over Temperature,  $0.5\% V_{OUT}$  @  $25^\circ\text{C}$
- Ultra-Low Dropout: Typ. 53 mV at 500 mA
- Very Low Bias Input Current of Typ.  $35 \mu\text{A}$
- Logic Level Enable Input for ON/OFF Control
- Output Active Discharge Option Available
- Stable with a  $10 \mu\text{F}$  Ceramic Capacitor
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

## Typical Applications

- Automotive, Consumer and Industrial Equipment Point of Load Regulation
- Battery-powered Equipment
- Smartphones, Tablets
- Cameras, DVRs, STB and Camcorders





Figure 1. Typical Application Schematic




WDFN6  
CASE 511BR

## MARKING DIAGRAM



XX = Specific Device Code  
M = Date Code


## PIN CONNECTIONS



## ORDERING INFORMATION

See detailed ordering, marking and shipping information on page 9 of this data sheet.

## NCV8135



\*Active output discharge function is present only in NCV8135A option devices.

**Figure 2. Simplified Schematic Block Diagram**

## PIN FUNCTION DESCRIPTION

| Pin No. | Pin Name | Description                                                                                                          |
|---------|----------|----------------------------------------------------------------------------------------------------------------------|
| 1       | VIN      | Input Voltage Supply pin                                                                                             |
| 2       | GND      | Ground pin                                                                                                           |
| 3       | VBIAS    | Bias voltage supply for internal control circuits. This pin is monitored by internal Under-Voltage Lockout Circuit.  |
| 4       | EN       | Enable pin. Driving this pin high enables the regulator. Driving this pin low puts the regulator into shutdown mode. |
| 5       | SNS      | Output voltage Sensing Input. Connect to Output voltage node on the PCB.                                             |
| 6       | VOOUT    | Regulated Output Voltage pin                                                                                         |
| Pad     | Pad      | Should be soldered to the ground plane for increased thermal performance.                                            |

## ABSOLUTE MAXIMUM RATINGS

| Rating                                    | Symbol                      | Value                         | Unit |
|-------------------------------------------|-----------------------------|-------------------------------|------|
| Input Voltage (Note 1)                    | $V_{IN}$                    | -0.3 to 6                     | V    |
| Output Voltage                            | $V_{OUT}$                   | -0.3 to $(V_{IN}+0.3) \leq 6$ | V    |
| Chip Enable, Bias and SNS Input           | $V_{EN}, V_{BIAS}, V_{SNS}$ | -0.3 to 6                     | V    |
| Output Short Circuit Duration             | $t_{SC}$                    | unlimited                     | s    |
| Maximum Junction Temperature              | $T_J$                       | 125                           | °C   |
| Storage Temperature                       | $T_{STG}$                   | -55 to 150                    | °C   |
| ESD Capability, Human Body Model (Note 2) | ESD <sub>HBM</sub>          | 2000                          | V    |
| ESD Capability, Machine Model (Note 2)    | ESD <sub>MM</sub>           | 200                           | V    |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
- This device series incorporates ESD protection (except OUT pin) and is tested by the following methods:  
 ESD Human Body Model tested per AEC-Q100-002  
 ESD Machine Model tested per AEC-Q100-003  
 Latchup Current Maximum Rating  $\pm 100$  mA per AEC-Q100-004.

## THERMAL CHARACTERISTICS

| Rating                                                                                     | Symbol          | Value | Unit |
|--------------------------------------------------------------------------------------------|-----------------|-------|------|
| Thermal Characteristics, WDFN6 2 mm x 2 mm<br>Thermal Resistance, Junction-to-Air (Note 3) | $R_{\theta JA}$ | 97    | °C/W |

- This data was derived by thermal simulations based on the JEDEC JESD51 series standards methodology. Only a single device mounted at the center of a high K (2s2p) 3 in x 3 in multilayer board with 1-ounce internal planes and 1-ounce copper on top and bottom. Top copper layer has a dedicated 25 sq mm copper area.

**ELECTRICAL CHARACTERISTICS**  $-40^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$ ;  $V_{\text{BIAS}} = 2.7\text{ V}$  or  $(V_{\text{OUT}} + 1.6\text{ V})$ , whichever is greater,  $V_{\text{IN}} = V_{\text{OUT(NOM)}} + 0.3\text{ V}$ ,  $I_{\text{OUT}} = 1\text{ mA}$ ,  $V_{\text{EN}} = 1\text{ V}$ ,  $C_{\text{IN}} = 4.7\text{ }\mu\text{F}$ ,  $C_{\text{OUT}} = 10\text{ }\mu\text{F}$ ,  $C_{\text{BIAS}} = 1\text{ }\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^{\circ}\text{C}$ . Min/Max values are for  $-40^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  unless otherwise noted. (Note 4)

| Parameter                         | Test Conditions                                                                                                                                                                                                                                                                                                                 | Symbol                    | Min                                | Typ                  | Max  | Unit               |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------|----------------------|------|--------------------|
| Operating Input Voltage Range     |                                                                                                                                                                                                                                                                                                                                 | $V_{\text{IN}}$           | $V_{\text{OUT}} + V_{\text{DO}}$   |                      | 5.5  | V                  |
| Operating Bias Voltage Range      |                                                                                                                                                                                                                                                                                                                                 | $V_{\text{BIAS}}$         | $(V_{\text{OUT}} + 1.50) \geq 2.5$ |                      | 5.5  | V                  |
| Undervoltage Lock-out             | $V_{\text{BIAS}}$ Rising Hysteresis                                                                                                                                                                                                                                                                                             | UVLO                      |                                    | 1.6<br>0.2           |      | V                  |
| Output Voltage Accuracy           |                                                                                                                                                                                                                                                                                                                                 | $V_{\text{OUT}}$          |                                    | $\pm 0.5$            |      | %                  |
| Output Voltage Accuracy           | $-40^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$ , $V_{\text{OUT(NOM)}} + 0.3\text{ V} \leq V_{\text{IN}} \leq V_{\text{OUT(NOM)}} + 1.0\text{ V}$ , $2.7\text{ V}$ or $(V_{\text{OUT(NOM)}} + 1.6\text{ V})$ , whichever is greater $< V_{\text{BIAS}} < 5.5\text{ V}$ , $1\text{ mA} < I_{\text{OUT}} < 500\text{ mA}$ | $V_{\text{OUT}}$          | -1.0                               |                      | +1.0 | %                  |
| $V_{\text{IN}}$ Line Regulation   | $V_{\text{OUT(NOM)}} + 0.3\text{ V} \leq V_{\text{IN}} \leq 5.0\text{ V}$                                                                                                                                                                                                                                                       | LineReg                   |                                    | 0.01                 |      | %/V                |
| $V_{\text{BIAS}}$ Line Regulation | $2.7\text{ V}$ or $(V_{\text{OUT(NOM)}} + 1.6\text{ V})$ , whichever is greater $< V_{\text{BIAS}} < 5.5\text{ V}$                                                                                                                                                                                                              | LineReg                   |                                    | 0.01                 |      | %/V                |
| Load Regulation                   | $I_{\text{OUT}} = 1\text{ mA}$ to $500\text{ mA}$                                                                                                                                                                                                                                                                               | LoadReg                   |                                    | 0.5                  |      | mV                 |
| $V_{\text{IN}}$ Dropout Voltage   | $I_{\text{OUT}} = 500\text{ mA}$ (Note 5)                                                                                                                                                                                                                                                                                       | $V_{\text{DO}}$           |                                    | 53                   | 100  | mV                 |
| $V_{\text{BIAS}}$ Dropout Voltage | $I_{\text{OUT}} = 500\text{ mA}$ , $V_{\text{IN}} = V_{\text{BIAS}}$ (Notes 5, 6)                                                                                                                                                                                                                                               | $V_{\text{DO}}$           |                                    | 1.1                  | 1.5  | V                  |
| Output Current Limit              | $V_{\text{OUT}} = 90\% V_{\text{OUT(NOM)}}$                                                                                                                                                                                                                                                                                     | $I_{\text{CL}}$           | 600                                | 820                  | 1200 | mA                 |
| SNS Pin Operating Current         |                                                                                                                                                                                                                                                                                                                                 | $I_{\text{SNS}}$          |                                    | 0.01                 | 0.5  | $\mu\text{A}$      |
| Bias Pin Quiescent Current        | $V_{\text{BIAS}} = 2.7\text{ V}$ , $I_{\text{OUT}} = 0\text{ mA}$                                                                                                                                                                                                                                                               | $I_{\text{BIASQ}}$        |                                    | 35                   | 55   | $\mu\text{A}$      |
| Bias Pin Disable Current          | $V_{\text{EN}} \leq 0.4\text{ V}$                                                                                                                                                                                                                                                                                               | $I_{\text{BIAS(DIS)}}$    |                                    | 0.2                  | 1    | $\mu\text{A}$      |
| Vinut Pin Disable Current         | $V_{\text{EN}} \leq 0.4\text{ V}$                                                                                                                                                                                                                                                                                               | $I_{\text{VIN(DIS)}}$     |                                    | 0.01                 | 1    | $\mu\text{A}$      |
| EN Pin Threshold Voltage          | EN Input Voltage "H"                                                                                                                                                                                                                                                                                                            | $V_{\text{EN(H)}}$        | 0.9                                |                      |      | V                  |
|                                   | EN Input Voltage "L"                                                                                                                                                                                                                                                                                                            | $V_{\text{EN(L)}}$        |                                    |                      | 0.4  |                    |
| EN Pull Down Current              | $V_{\text{EN}} = 5.5\text{ V}$                                                                                                                                                                                                                                                                                                  | $I_{\text{EN}}$           |                                    | 0.3                  | 1    | $\mu\text{A}$      |
| Turn-On Time                      | From assertion of $V_{\text{EN}}$ to $V_{\text{OUT}} = 98\% V_{\text{OUT(NOM)}}$<br>$V_{\text{OUT(NOM)}} = 0.4\text{ V}$<br>$V_{\text{OUT(NOM)}} = 1.2\text{ V}$<br>$V_{\text{OUT(NOM)}} = 0.75\text{ V}$                                                                                                                       | $t_{\text{ON}}$           |                                    | 150<br>275<br>198    |      | $\mu\text{s}$      |
| Power Supply Rejection Ratio      | $V_{\text{IN}}$ to $V_{\text{OUT}}$ , $f = 1\text{ kHz}$ , $I_{\text{OUT}} = 10\text{ mA}$ , $V_{\text{IN}} \geq V_{\text{OUT}} + 0.5\text{ V}$ , $V_{\text{OUT(NOM)}} = 0.4\text{ V}$                                                                                                                                          | PSRR( $V_{\text{IN}}$ )   |                                    | 73                   |      | dB                 |
|                                   | $V_{\text{BIAS}}$ to $V_{\text{OUT}}$ , $f = 1\text{ kHz}$ , $I_{\text{OUT}} = 10\text{ mA}$ , $V_{\text{IN}} \geq V_{\text{OUT}} + 0.5\text{ V}$ , $V_{\text{OUT(NOM)}} = 0.4\text{ V}$                                                                                                                                        | PSRR( $V_{\text{BIAS}}$ ) |                                    | 90                   |      | dB                 |
| Output Noise Voltage              | $V_{\text{IN}} = V_{\text{OUT}} + 0.5\text{ V}$ , $f = 10\text{ Hz}$ to $100\text{ kHz}$<br>$V_{\text{OUT(NOM)}} = 0.4\text{ V}$<br>$V_{\text{OUT(NOM)}} = 1.2\text{ V}$<br>$V_{\text{OUT(NOM)}} = 0.75\text{ V}$                                                                                                               | $V_{\text{N}}$            |                                    | 28.7<br>40.3<br>35.3 |      | $\mu\text{VRMS}$   |
| Thermal Shutdown Threshold        | Temperature increasing                                                                                                                                                                                                                                                                                                          |                           |                                    | 160                  |      | $^{\circ}\text{C}$ |
|                                   | Temperature decreasing                                                                                                                                                                                                                                                                                                          |                           |                                    | 140                  |      |                    |
| Output Discharge Pull-Down        | $V_{\text{EN}} \leq 0.4\text{ V}$ , $V_{\text{OUT}} = 0.5\text{ V}$ , NCV8135A options only                                                                                                                                                                                                                                     | $R_{\text{DISCH}}$        |                                    | 150                  |      | $\Omega$           |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Performance guaranteed over the indicated operating temperature range by design and/or characterization. Production tested at  $T_A = 25^{\circ}\text{C}$ .


Low duty cycle pulse techniques are used during the testing to maintain the junction temperature as close to ambient as possible.

5. Dropout voltage is characterized when  $V_{\text{OUT}}$  falls 3% below  $V_{\text{OUT(NOM)}}$ .


6. For output voltages below  $0.9\text{ V}$ ,  $V_{\text{BIAS}}$  dropout voltage does not apply due to a minimum Bias operating voltage of  $2.5\text{ V}$ .

# TYPICAL CHARACTERISTICS


At  $T_J = +25^\circ\text{C}$ ,  $V_{IN} = V_{OUT(NOM)} + 0.3\text{ V}$ ,  $V_{BIAS} = 2.7\text{ V}$ ,  $V_{EN} = 1.0\text{ V}$ ,  $V_{OUT(NOM)} = 0.4\text{ V}$ ,  $I_{OUT} = 500\text{ mA}$ ,  $C_{IN} = 1\text{ }\mu\text{F}$ ,  $C_{BIAS} = 0.1\text{ }\mu\text{F}$ , and  $C_{OUT} = 10\text{ }\mu\text{F}$  (effective capacitance value), unless otherwise noted.




**Figure 3.  $V_{IN}$  Dropout Voltage vs.  $I_{OUT}$  and Temperature  $T_J$**




**Figure 4.  $V_{IN}$  Dropout Voltage vs.  $(V_{BIAS} - V_{OUT})$  and Temperature  $T_J$**




**Figure 5.  $V_{IN}$  Dropout Voltage vs.  $(V_{BIAS} - V_{OUT})$  and Temperature  $T_J$**



**Figure 6.  $V_{IN}$  Dropout Voltage vs.  $(V_{BIAS} - V_{OUT})$  and Temperature  $T_J$**




**Figure 7. Load Transient Response,  $I_{OUT} = 50\text{ mA}$  to  $500\text{ mA}$ ,  $C_{OUT} = 10\text{ }\mu\text{F}$**




**Figure 8. Load Transient Response,  $I_{OUT} = 50\text{ mA}$  to  $500\text{ mA}$ ,  $C_{OUT} = 22\text{ }\mu\text{F}$**

# TYPICAL CHARACTERISTICS


At  $T_J = +25^\circ\text{C}$ ,  $V_{IN} = V_{OUT(NOM)} + 0.3\text{ V}$ ,  $V_{BIAS} = 2.7\text{ V}$ ,  $V_{EN} = 1.0\text{ V}$ ,  $V_{OUT(NOM)} = 0.4\text{ V}$ ,  $I_{OUT} = 500\text{ mA}$ ,  $C_{IN} = 1\text{ }\mu\text{F}$ ,  $C_{BIAS} = 0.1\text{ }\mu\text{F}$ , and  $C_{OUT} = 10\text{ }\mu\text{F}$  (effective capacitance value), unless otherwise noted.




**Figure 9. Load Transient Response,**  
 $I_{OUT} = 1\text{ mA to } 500\text{ mA}$ ,  $C_{OUT} = 10\text{ }\mu\text{F}$




**Figure 10. Load Transient Response,**  
 $I_{OUT} = 1\text{ mA to } 500\text{ mA}$ ,  $C_{OUT} = 22\text{ }\mu\text{F}$




**Figure 11. Load Transient Response,**  
 $I_{OUT} = 1\text{ mA to } 20\text{ mA}$ ,  $C_{OUT} = 10\text{ }\mu\text{F}$



**Figure 12. Load Transient Response,**  
 $I_{OUT} = 1\text{ mA to } 20\text{ mA}$ ,  $C_{OUT} = 22\text{ }\mu\text{F}$




**Figure 13. Enable Transient Response,**  
 $I_{OUT} = 0\text{ mA}$ ,  $C_{OUT} = 10\text{ }\mu\text{F}$




**Figure 14. Enable Transient Response, Output**  
**Resistive Load 500 mA**,  $C_{OUT} = 22\text{ }\mu\text{F}$

# TYPICAL CHARACTERISTICS


At  $T_J = +25^\circ\text{C}$ ,  $V_{IN} = V_{OUT(NOM)} + 0.3\text{ V}$ ,  $V_{BIAS} = 2.7\text{ V}$ ,  $V_{EN} = 1.0\text{ V}$ ,  $V_{OUT(NOM)} = 0.4\text{ V}$ ,  $I_{OUT} = 500\text{ mA}$ ,  $C_{IN} = 1\text{ }\mu\text{F}$ ,  $C_{BIAS} = 0.1\text{ }\mu\text{F}$ , and  $C_{OUT} = 10\text{ }\mu\text{F}$  (effective capacitance value), unless otherwise noted.




**Figure 15.  $V_{IN}$  Line Transient Response,**  
 $V_{IN} = 0.7\text{ V to }1.7\text{ V}$ ,  $I_{OUT} = 100\text{ mA}$ ,  $C_{IN} = 0$ ,  
 $C_{OUT} = 10\text{ }\mu\text{F}$




**Figure 16.  $V_{IN}$  Line Transient Response,**  
 $V_{IN} = 0.7\text{ V to }1.7\text{ V}$ ,  $I_{OUT} = 100\text{ mA}$ ,  $C_{IN} = 0$ ,  
 $C_{OUT} = 22\text{ }\mu\text{F}$



**Figure 17.  $V_{IN}$  Power Supply Rejection Ratio**  
**vs. Frequency**




**Figure 18.  $V_{BIAS}$  Power Supply Rejection Ratio**  
**vs. Frequency**



**Figure 19. Output Voltage Noise Spectral**  
**Density at NCV8135AMT040TBG**

| $I_{OUT}$ | $C_{OUT}$        | RMS Output Noise Voltage ( $\mu\text{V}$ ) |                  |
|-----------|------------------|--------------------------------------------|------------------|
|           |                  | 10 Hz – 100 kHz                            | 100 Hz – 100 kHz |
| 1 mA      | 10 $\mu\text{F}$ | 28.67                                      | 27.54            |
| 1 mA      | 22 $\mu\text{F}$ | 28.19                                      | 27.28            |
| 10 mA     | 22 $\mu\text{F}$ | 36.23                                      | 35.49            |
| 100 mA    | 22 $\mu\text{F}$ | 45.44                                      | 44.87            |
| 500 mA    | 22 $\mu\text{F}$ | 54.54                                      | 54.04            |





**Figure 20. Output Voltage Noise Spectral Density at NCV8135AMTW075TBG**

|                  |                  | RMS Output Noise Voltage (μV) |                  |
|------------------|------------------|-------------------------------|------------------|
| I <sub>OUT</sub> | C <sub>OUT</sub> | 10 Hz – 100 kHz               | 100 Hz – 100 kHz |
| 1 mA             | 10 μF            | 35.34                         | 34.22            |
| 1 mA             | 22 μF            | 33.39                         | 32.22            |
| 10 mA            | 22 μF            | 41.85                         | 40.91            |
| 100 mA           | 22 μF            | 51.70                         | 50.98            |
| 500 mA           | 22 μF            | 59.78                         | 59.16            |

## APPLICATIONS INFORMATION

The NCV8135 dual-rail very low dropout voltage regulator is using NMOS pass transistor for output voltage regulation from  $V_{IN}$  voltage. All the low current internal control circuitry is powered from the  $V_{BIAS}$  voltage.

The use of an NMOS pass transistor offers several advantages in applications. Unlike PMOS topology devices, the output capacitor has reduced impact on loop stability.  $V_{in}$  to  $V_{out}$  operating voltage difference can be very low compared with standard PMOS regulators in very low  $V_{in}$  applications.

When enabled from Enable (EN) input, the NCV8135 offers smooth monotonic start-up. The controlled voltage rising limits the inrush current.

The Enable (EN) input is equipped with internal hysteresis.

### Dropout Voltage

Because of two power supply inputs  $V_{IN}$  and  $V_{BIAS}$  and one  $V_{OUT}$  regulator output, there are two Dropout voltages specified.

The first, the  $V_{IN}$  Dropout voltage is the voltage difference ( $V_{IN} - V_{OUT}$ ) when  $V_{OUT}$  starts to decrease by percent specified in the Electrical Characteristics table.  $V_{BIAS}$  is high enough; specific value is published in the Electrical Characteristics table.

The second,  $V_{BIAS}$  dropout voltage is the voltage difference ( $V_{BIAS} - V_{OUT}$ ) when  $V_{IN}$  and  $V_{BIAS}$  pins are joined together and  $V_{OUT}$  starts to decrease.

### Input and Output Capacitors

The device is designed to be stable for ceramic output capacitors with Effective capacitance in the range from 10  $\mu$ F to 22  $\mu$ F. The device is also stable with multiple capacitors in parallel, having the total effective capacitance in the specified range.

In applications where no low input supplies impedance available (PCB inductance in  $V_{IN}$  and/or  $V_{BIAS}$  inputs as example), the recommended  $C_{IN} = 1 \mu$ F and  $C_{BIAS} = 0.1 \mu$ F or greater. Ceramic capacitors are recommended. For the best performance all the capacitors should be connected to

the NCV8135 respective pins directly in the device PCB copper layer, not through vias having not negligible impedance.

When using small ceramic capacitor, their capacitance is not constant but varies with applied DC biasing voltage, temperature and tolerance. The effective capacitance can be much lower than their nominal capacitance value, most importantly in negative temperatures and higher LDO output voltages. That is why the recommended Output capacitor capacitance value is specified as Effective value in the specific application conditions.

### Enable Operation

The enable pin will turn the regulator on or off. The threshold limits are covered in the electrical characteristics table in this data sheet. To get the full functionality of soft-start, it is recommended to turn on the  $V_{IN}$  and  $V_{BIAS}$  supply voltages first and activate the Enable pin no sooner than when  $V_{IN}$  and  $V_{BIAS}$  are on their nominal levels. If the enable function is not to be used then the pin should be connected to  $V_{IN}$  or  $V_{BIAS}$ .

### Current Limitation

The internal Current Limitation circuitry allows the device to supply the full nominal current and surges but protects the device against Current Overload or Short.

### Thermal Protection

Internal thermal shutdown (TSD) circuitry is provided to protect the integrated circuit in the event that the maximum junction temperature is exceeded. When TSD activated, the regulator output turns off. When cooling down under the low temperature threshold, device output is activated again. This TSD feature is provided to prevent failures from accidental overheating.

Activation of the thermal protection circuit indicates excessive power dissipation or inadequate heatsinking. For reliable operation, junction temperature should be limited to +125°C maximum.


## ORDERING INFORMATION

| Device            | Marking | Voltage | Option                  | Package                                    | Shipping†          |
|-------------------|---------|---------|-------------------------|--------------------------------------------|--------------------|
| NCV8135AMT040TBG  | KA      | 0.4 V   | Output Active Discharge | WDFN6<br>(Non-Wettable Flank)<br>(Pb-Free) | 3000 / Tape & Reel |
| NCV8135BMT040TBG  | KC      | 0.4 V   | Non-Active Discharge    |                                            |                    |
| NCV8135AMT120TBG  | KE      | 1.2 V   | Output Active Discharge |                                            |                    |
| NCV8135AMTW040TBG | K2      | 0.4 V   | Output Active Discharge | WDFN6<br>(Wettable Flank)<br>(Pb-Free)     |                    |
| NCV8135BMTW040TBG | K3      | 0.4 V   | Non-Active Discharge    |                                            |                    |
| NCV8135AMTW120TBG | K4      | 1.2 V   | Output Active Discharge |                                            |                    |
| NCV8135AMTW075TBG | KL      | 0.75 V  | Output Active Discharge |                                            |                    |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


To order other package and voltage variants, please contact your ON Semiconductor sales representative

# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS




## WDFN6 2x2, 0.65P CASE 511BR ISSUE C


DATE 01 DEC 2021



TOP VIEW



SIDE VIEW



BOTTOM VIEW

### GENERIC MARKING DIAGRAM\*




XX = Specific Device Code  
M = Date Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.


### NOTES:

1. DIMENSION AND TOLERANCING PER ASME Y14.5, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.



DETAIL B


ALTERNATE CONSTRUCTION



DETAIL A

ALTERNATE CONSTRUCTIONS

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.70        | 0.75 | 0.80 |
| A1  | 0.00        | ---  | 0.05 |
| A3  | 0.20 REF    |      |      |
| b   | 0.25        | 0.30 | 0.35 |
| D   | 1.90        | 2.00 | 2.10 |
| D2  | 1.50        | 1.60 | 1.70 |
| E   | 1.90        | 2.00 | 2.10 |
| E2  | 0.90        | 1.00 | 1.10 |
| e   | 0.65 BSC    |      |      |
| K   | 0.20 REF    |      |      |
| L   | 0.20        | 0.30 | 0.40 |
| L1  | ---         | ---  | 0.15 |



### RECOMMENDED MOUNTING FOOTPRINT

For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

|                  |                  |                                                                                                                                                                                  |
|------------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON55829E      | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | WDFN6 2X2, 0.65P | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

⊖ View [NCV8135AMTW040TBG](#) on WIN SOURCE

⊖ [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management