



**THE DATASHEET OF
DMP2123L-7**




Features


- Low $R_{DS(ON)}$
 - 72 mΩ @ $V_{GS} = -4.5V$
 - 108 mΩ @ $V_{GS} = -2.7V$
 - 123 mΩ @ $V_{GS} = -2.5V$
- Low Input/Output Leakage
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data


- Case: SOT23
- Case Material - Molded Plastic, "Green" Molding Compound. UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Finish - Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208 ^③
- Terminal Connections: See Diagram Below
- Weight: 0.008 grams (approximate)



TOP VIEW



Internal Schematic




TOP VIEW

Ordering Information (Note 4)

| Part Number | Case | Packaging |
|-------------|--------|------------------|
| DMP2123L-7 | SOT-23 | 3000/Tape & Reel |

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
 2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 4. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>

Marking Information



Chengdu A/T Site

Shanghai A/T Site

M1P = Product Type Marking Code
 YM = Date Code Marking for SAT (Shanghai Assembly/ Test site)
 Y̅M = Date Code Marking for CAT (Chengdu Assembly/ Test site)
 Y or Y̅ = Year (ex: A = 2013)
 M = Month (ex: 9 = September)

Date Code Key

| Year | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 | 2016 | 2017 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | U | V | W | X | Y | Z | A | B | C | D | E |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit | |
|--|------------------|--|--------------|---|
| Drain-Source Voltage | V _{DSS} | -20 | V | |
| Gate-Source Voltage | V _{GSS} | ±12 | V | |
| Drain Current (Note 5) Continuous | I _D | T _A = +25°C T _A = +70°C | -3.0 -2.4 | A |
| Pulsed Drain Current (Note 6) | | I _{DM} | -15 | A |
| Body-Diode Continuous Current (Note 5) | I _S | 2.0 | A | |

Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|--|-----------------------------------|-------------|------|
| Total Power Dissipation (Note 5) | P _D | 1.4 | W |
| Thermal Resistance, Junction to Ambient (Note 5); Steady-State | R _{θJA} | 90 | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | °C |

Notes: 5. Device mounted on 1"x1", FR-4 PC board with 2 oz. Copper and test pulse width t ≤ 10s.
6. Repetitive Rating, pulse width limited by junction temperature.

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|--|---------------------|------|----------------|------------------|------|---|
| STATIC PARAMETERS | | | | | | |
| Drain-Source Breakdown Voltage | BV _{DSS} | -20 | — | — | V | I _D = -250μA, V _{GS} = 0V |
| Zero Gate Voltage Drain Current | I _{DSS} | — | — | -1 | μA | T _J = +25°C V _{DS} = -20V, V _{GS} = 0V |
| Gate-Body Leakage Current | I _{GSS} | — | — | ±100 | nA | V _{DS} = 0V, V _{GS} = ±12V |
| Gate Threshold Voltage | V _{GS(th)} | -0.6 | — | -1.25 | V | V _{DS} = V _{GS} , I _D = -250μA |
| On State Drain Current (Note 7) | I _{D(ON)} | -15 | — | — | A | V _{GS} = -4.5V, V _{DS} = -5V |
| Static Drain-Source On-Resistance (Note 7) | R _{DS(ON)} | — | 51 87 99 | 72 108 123 | mΩ | V _{GS} = -4.5V, I _D = -3.5A V _{GS} = -2.7V, I _D = -3.0A V _{GS} = -2.5V, I _D = -2.6A |
| Forward Transconductance (Note 7) | g _{FS} | — | 7.3 | — | S | V _{DS} = -10V, I _D = -3.0A |
| Diode Forward Voltage (Note 5) | V _{SD} | — | 0.79 | -1.26 | V | I _S = -1.7A, V _{GS} = 0V |
| Maximum Body-Diode Continuous Current (Note 5) | I _S | — | — | 1.7 | A | — |
| DYNAMIC PARAMETERS (Note 8) | | | | | | |
| Total Gate Charge | Q _g | — | 7.3 | — | nC | V _{GS} = -4.5V, V _{DS} = -10V, I _D = -3.0A |
| Gate-Source Charge | Q _{gs} | — | 2.0 | — | nC | V _{GS} = -4.5V, V _{DS} = -10V, I _D = -3.0A |
| Gate-Drain Charge | Q _{gd} | — | 1.9 | — | nC | V _{GS} = -4.5V, V _{DS} = -10V, I _D = -3.0A |
| Turn-On Delay Time | t _{D(on)} | — | 12 | — | ns | V _{DS} = -10V, V _{GS} = -4.5V, R _L = 10Ω, R _G = 6Ω |
| Turn-On Rise Time | t _r | — | 20 | — | ns | |
| Turn-Off Delay Time | t _{D(off)} | — | 38 | — | ns | |
| Turn-Off Fall Time | t _f | — | 41 | — | ns | |
| Input Capacitance | C _{iss} | — | 443 | — | pF | V _{DS} = -16V, V _{GS} = 0V f = 1.0MHz |
| Output Capacitance | C _{oss} | — | 128 | — | pF | |
| Reverse Transfer Capacitance | C _{rss} | — | 101 | — | pF | |

Notes: 7. Test pulse width t = 300μs.
8. Guaranteed by design. Not subject to production testing.




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 On-Resistance vs. Drain Current and Gate Voltage




Fig. 4 Typical Total Capacitance




Fig. 5 Gate Threshold Voltage vs. Ambient Temperature




Fig. 6 Normalized Static Drain-Source On-Resistance vs. Ambient Temperature





Fig. 7 Reverse Drain Current vs. Source-Drain Voltage

Package Outline Dimensions


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.



| SOT23 | | |
|----------------------|-------|-------|
| Dim | Min | Max |
| A | 0.37 | 0.51 |
| B | 1.20 | 1.40 |
| C | 2.30 | 2.50 |
| D | 0.89 | 1.03 |
| F | 0.45 | 0.60 |
| G | 1.78 | 2.05 |
| H | 2.80 | 3.00 |
| J | 0.013 | 0.10 |
| K | 0.903 | 1.10 |
| L | 0.45 | 0.61 |
| M | 0.085 | 0.180 |
| α | 0° | 8° |
| All Dimensions in mm | | |

Suggested Pad Layout

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for latest version.



| Dimensions | Value (in mm) |
|------------|---------------|
| Z | 2.9 |
| X | 0.8 |
| Y | 0.9 |
| C | 2.0 |
| E | 1.35 |

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.



Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2013, Diodes Incorporated

www.diodes.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View DMP2123L-7 on WIN SOURCE](#)
-  [Diodes Incorporated Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management