



## Features and Benefits

- Glass Passivated Die Construction
- High Current Capability and Low Forward Voltage Drop
- Surge Overload Rating to 30A Peak
- **Lead Free Finish, RoHS Compliant (Note 1)**

## Mechanical Data

- Case: DO-41 Plastic
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Tin. Plated Leads Solderable per MIL-STD-202, Method 208 **(E3)**
- Polarity: Cathode Band
- Marking: Type Number
- Weight: 0.30 grams (approximate)

## Ordering Information (Note 2)


| Device    | Packaging     | Shipping                |
|-----------|---------------|-------------------------|
| 1N4001G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4002G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4003G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4004G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4005G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4006G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |
| 1N4007G-T | DO-41 Plastic | 5K/Tape & Reel, 13-inch |

## Maximum Ratings and Electrical Characteristics @T<sub>A</sub> = 25°C unless otherwise specified


Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

| Characteristic   | Symbol                            | 1N4001<br>G | 1N4002<br>G | 1N4003<br>G | 1N4004<br>G | 1N4005<br>G | 1N4006<br>G | 1N4007<br>G | Unit |
|--|-----------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|------|
| Peak Repetitive Reverse Voltage  | V <sub>RRM</sub>                  | 50          | 100         | 200         | 400         | 600         | 800         | 1000        | V    |
| Working Peak Reverse Voltage   | V <sub>RWM</sub>                  |             |             |             |             |             |             |             |      |
| DC Blocking Voltage  | V <sub>R</sub>                    |             |             |             |             |             |             |             |      |
| RMS Reverse Voltage  | V <sub>R(RMS)</sub>               | 35          | 70          | 140         | 280         | 420         | 560         | 700         | V    |
| Average Rectified Output Current (Note 3) @ T <sub>A</sub> = 75°C                                | I <sub>O</sub>                    | 1.0         |             |             |             |             |             |             | A    |
| Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load | I <sub>FSM</sub>                  | 30          |             |             |             |             |             |             | A    |
| Forward Voltage @ I <sub>F</sub> = 1.0A  | V <sub>FM</sub>                   | 1.0         |             |             |             |             |             |             | V    |
| Peak Reverse Current @T <sub>A</sub> = 25°C  | I <sub>RM</sub>                   | 5.0         |             |             |             |             |             |             | μA   |
| at Rated DC Blocking Voltage @ T <sub>A</sub> = 125°C  |                                   | 50          |             |             |             |             |             |             |      |
| Typical Reverse Recovery Time (Note 4)   | t <sub>rr</sub>                   | 2.0         |             |             |             |             |             |             | μs   |
| Typical Total Capacitance (Note 5)   | C <sub>T</sub>                    | 8.0         |             |             |             |             |             |             | pF   |
| Typical Thermal Resistance Junction to Ambient   | R <sub>θJA</sub>                  | 100         |             |             |             |             |             |             | °C/W |
| Operating and Storage Temperature Range  | T <sub>J</sub> , T <sub>STG</sub> | -65 to +175 |             |             |             |             |             |             | °C   |


- Notes:
1. EU Directive 2002/95/EC (RoHS). All applicable RoHS exemptions applied, see EU Directive 2002/95/EC Annex Notes.
  2. For packaging details, visit our website at <http://www.diodes.com>.
  3. Leads maintained at ambient temperature at a distance of 9.5mm from the case.
  4. Measured with I<sub>F</sub> = 0.5A, I<sub>R</sub> = -1A, I<sub>rr</sub> = 0.25A.
  5. Measured at 1.0 MHz and applied reverse voltage of 4.0V DC.




$T_A$ , AMBIENT TEMPERATURE (°C)  
Fig. 1 Forward Current Derating Curve




$V_F$ , INSTANTANEOUS FORWARD VOLTAGE (V)  
Fig. 2 Typical Forward Characteristics



NUMBER OF CYCLES AT 60 Hz  
Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




$V_R$ , REVERSE VOLTAGE (V)  
Fig. 4 Typical Total Capacitance



PERCENT OF RATED PEAK REVERSE VOLTAGE (%)  
Fig. 5 Typical Reverse Characteristics

## Package Outline Dimensions



| DO-41 Plastic        |       |       |
|----------------------|-------|-------|
| Dim                  | Min   | Max   |
| A                    | 25.40 | —     |
| B                    | 4.06  | 5.21  |
| C                    | 0.71  | 0.864 |
| D                    | 2.00  | 2.72  |
| All Dimensions in mm |       |       |

### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View 1N4006G-T on WIN SOURCE](#)
- [Diodes Incorporated Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management