



# THE DATASHEET OF 1609030000

**Accessories**  
**ZQV 4/10 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Spring connection with tension clamp Technology**

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

**General ordering data**

|            |                                    |
|------------|------------------------------------|
| Type       | ZQV 4/10 GE                        |
| Order No.  | <a href="#">1609030000</a>         |
| Version    | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4008190263300                      |
| Qty.       | 20 pc(s).                          |

## Accessories

### ZQV 4/10 GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 2.8 mm  | Width (inches)  | 0.11 inch  |
| Height     | 59.3 mm | Height (inches) | 2.335 inch |
| Depth      | 31.6 mm | Depth (inches)  | 1.244 inch |
| Net weight | 8.8 g   |                 |            |

### Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |
|----------------------------------|--------|----------------------------------|--------|

### Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | Yellow |
| UL 94 flammability rating | V-0   |        |        |

### System specifications

|         |                   |               |      |
|---------|-------------------|---------------|------|
| Version | For the terminals | Mounting rail | none |
|---------|-------------------|---------------|------|

### Additional technical data

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | Yes     | Installation advice | Direct mounting |
| Type of fixing           | Plugged |                     |                 |

### Dimensions

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

### Rating data

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | ETIM 4.0   | EC000489    |
| ETIM 5.0   | EC000489    | ETIM 6.0   | EC000489    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                             |
|--------------------|-------------------------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>                         |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                    |
| Engineering Data   | <a href="#">STEP</a>                                        |
| User Documentation | <a href="#">Operating instructions_ZDU1.5-ZDU35_ZQV.pdf</a> |

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 1609030000](#) on WIN SOURCE

 [Weidmuller](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management