



**THE DATASHEET OF
10053363-201LF**



POWER CARD EDGE

Low profile AC/DC power distribution connector system

OVERVIEW

The Power Card Edge connectors are a cost-effective system that can be used for DC power output from embedded AC/DC power supplies or for power distribution between boards within an enclosure. The narrow connector body helps maximize airflow for increased cooling and is well-suited for use in 1U rack-mount servers or on power distribution boards inside 1U redundant power supply assemblies.

Adjacent power contacts are positioned on 2.54mm pitch along the card edge. Power contacts are manufactured using a high-conductivity copper alloy. Each power contact is rated for up to 7A current measured at 30°C temperature rise in still air. Signal contacts are positioned on 1.27mm pitch.

The connector range includes options for right-angle, vertical, or straddle-mount solder termination with a full complement of power contacts. Right-angle options also include versions that combine power and power control signal contacts or power contacts and an integrated AC pass-through port in a single connector.



FEATURES & BENEFITS

- One-piece card edge design provides cost-effective power delivery with capacity for up to 7A per power contact
- An arrow connector body enables use in 1U servers and power supplies
- Low-profile design helps maximize airflow for system cooling
- Option for integration of signals and power in a single right-angle connector supports both power control and power distribution
- Integrated connector design simplifies board assembly
- Right-angle product range includes versions with molded posts or metal fork-locks for retention

- Straddle-mount connectors feature mounting ears for secure PCB attachment
- An optional AC cable port enables a cable pass-through solution
- RoHS compatible design enables compliance with environmental regulations

TARGET MARKETS/APPLICATIONS

- Servers
- Storage
- Telecommunications
- Datacom / Networking



TECHNICAL INFORMATION

MATERIALS

- Housings: high-temperature thermoplastic (UL94V-0), black
- Contact base material:
 - Power – high-conductivity copper alloy
 - Signal – copper alloy
- Contact area finish: gold over nickel
- Solder area finish: matte pure tin over nickel

ELECTRICAL PERFORMANCE

- Current rating: 7A/power contact measured at 30°C temperature rise in still air
- Insulation resistance: 5000MΩ min. for power contact
- Withstanding voltage: 1000V AC for power contact
- Contact resistance:
 - Right-angle: 55mΩ max.
 - Straddle-mount: 20mΩ max.
 - Vertical: 20mΩ max.

MECHANICAL PERFORMANCE

- Durability: 200 mating/un-mating cycles
- Insertion force for an add-in board:
 - Right-angle: 13.62kg max.
 - Vertical or straddle-mount: 8.0kg max.
- Operating temperature range: -5°C to +105°C

SPECIFICATIONS

- Right-angle product specification: GS-12-259
- Vertical product specification: GS-12-338
- Straddle-mount product specification: GS-12-279

APPROVALS AND CERTIFICATIONS

- UL, CSA and TUV approved

PACKAGING

- Trays

PART NUMBERS



Description	Base Number
Right Angle Solutions	
5 power + 12 signal + 5 power	10028886
7 power + 12 signal + 7 power	
10 power + 12 signal + 10 power	
14 power + 12 signal + 14 power	
With AC Power port	10055090
2x14, 2x17, 2x22, 2x25, 2x28, 2x29, 2x31, 2x32 power	10035388
Vertical Solutions	
2x19, 2x31, 2x32, 2x35 power	10046972
2x8 power	10046972
Straddle-Mount Options	
2x19, 2x23 power	10035388

Use the base numbers to reference the product drawings to obtain detailed dimensions and complete part numbers.

PWRPWRCE0613EA4

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 10053363-201LF](#) on WIN SOURCE
-  [Amphenol](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management