



**THE DATASHEET OF  
10058831-110LF**



# Micro-TCA Card Edge Connectors

## FULLY COMPLIANT CONNECTOR FOR ADVANCED MC™ MODULES

Micro-TCA ( $\mu$ TCA) vertical card edge connectors provide 170 contacts on a 0.75mm pitch and enable advanced MC™ modules to be plugged directly to a backplane. Micro-TCA card edge connector's conventional press-fit or surface mount assembly and connector designs require no costly hardware, resulting in low total applied cost.

- Up to 18Gb/s data rate per lane
- Press-fit and SMT version are available
- Modules can be plugged directly to the backplane



### TARGET MARKETS



### FEATURES

- Vertical card edge connectors with 170 contacts on a 0.75mm pitch
- Press-fit and SMT version are available
- No secondary mechanical retention or compensating board stiffeners needed
- Very low loss and crosstalk for low voltage differential signaling
- Surface mount mechanical hold-downs
- RoHS compliant and lead-free

### BENEFITS

- Fully compliant with Micro-TCA specification
- Provides a solderless alternative for termination to thick PCBs
- Low total applied cost
- Allows data rates up to 18Gb/s
- Provide additional mechanical strength after soldering
- Meets environmental, health and safety standards

# TECHNICAL INFORMATION

## MATERIAL

- Contact Base Metal: Copper alloy
- Contact Area Finish: Gold over nickel
- Solder Area Finish: Tin over nickel or tin-lead over nickel
- Metal Board Locks: Copper alloy

## ELECTRICAL PERFORMANCE

- Contact Resistance:
  - Initial: 25mΩ max.
  - Variation: Less than 10mΩ max.
- Current Rating: 0.5A min. per pin
- Voltage Rating: 12V AC (rms)

## MECHANICAL PERFORMANCE

- Durability: Up to 500 mating cycles
- Insertion Force: 100N max. for whole connector
- Withdrawal Force: 65N max. for whole connector

## ENVIRONMENTAL

- Salt Spray: Contact Resistance 35Ω max. final
- Thermal Shock: Contact Resistance (35Ω max. final)
- Solderability: 90% of immersed area must show no voids and pin holes

## APPROVALS AND CERTIFICATIONS

- UL

## SPECIFICATIONS

- Amphenol Product Specification:
  - GS-12-1132 for High Speed Micro-TCA 18G Press-fit IMLA type connector
  - GS-12-422 for Micro TCA 6.25G Press-fit IMLA type connector
  - GS-12-362 for Micro TCA 6.25G SMT type connector
- Industry Specification:
  - PICMG® specification MTCA.0 R1.0

## PACKAGING

- Tray

## TOOLING INFORMATION

- Tooled Up

## TARGET MARKETS/APPLICATIONS





Switches  
Routers  
Network Interface Cards (NICs)  
Host Bus Adapters (HBAs)



Servers  
Storage Systems  
Storage Controller Cards

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 10058831-110LF on WIN SOURCE](#)
-  [Amphenol Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management