



**THE DATASHEET OF
10058835-1002LF**



Micro-TCA Card Edge Connectors

FULLY COMPLIANT CONNECTOR FOR ADVANCED MC™ MODULES

Micro-TCA (μ TCA) vertical card edge connectors provide 170 contacts on a 0.75mm pitch and enable advanced MC™ modules to be plugged directly to a backplane. Micro-TCA card edge connector's conventional press-fit or surface mount assembly and connector designs require no costly hardware, resulting in low total applied cost.

- Up to 18Gb/s data rate per lane
- Press-fit and SMT version are available
- Modules can be plugged directly to the backplane



TARGET MARKETS



FEATURES

- Vertical card edge connectors with 170 contacts on a 0.75mm pitch
- Press-fit and SMT version are available
- No secondary mechanical retention or compensating board stiffeners needed
- Very low loss and crosstalk for low voltage differential signaling
- Surface mount mechanical hold-downs
- RoHS compliant and lead-free

BENEFITS

- Fully compliant with Micro-TCA specification
- Provides a solderless alternative for termination to thick PCBs
- Low total applied cost
- Allows data rates up to 18Gb/s
- Provide additional mechanical strength after soldering
- Meets environmental, health and safety standards

TECHNICAL INFORMATION

MATERIAL

- Contact Base Metal: Copper alloy
- Contact Area Finish: Gold over nickel
- Solder Area Finish: Tin over nickel or tin-lead over nickel
- Metal Board Locks: Copper alloy

ELECTRICAL PERFORMANCE

- Contact Resistance:
 - Initial: 25mΩ max.
 - Variation: Less than 10mΩ max.
- Current Rating: 0.5A min. per pin
- Voltage Rating: 12V AC (rms)

MECHANICAL PERFORMANCE

- Durability: Up to 500 mating cycles
- Insertion Force: 100N max. for whole connector
- Withdrawal Force: 65N max. for whole connector

ENVIRONMENTAL

- Salt Spray: Contact Resistance 35Ω max. final
- Thermal Shock: Contact Resistance (35Ω max. final)
- Solderability: 90% of immersed area must show no voids and pin holes

APPROVALS AND CERTIFICATIONS

- UL

SPECIFICATIONS

- Amphenol Product Specification:
 - GS-12-1132 for High Speed Micro-TCA 18G Press-fit IMLA type connector
 - GS-12-422 for Micro TCA 6.25G Press-fit IMLA type connector
 - GS-12-362 for Micro TCA 6.25G SMT type connector
- Industry Specification:
 - PICMG® specification MTCA.0 R1.0

PACKAGING

- Tray

TOOLING INFORMATION

- Tooled Up

TARGET MARKETS/APPLICATIONS



Switches
Routers
Network Interface Cards (NICs)
Host Bus Adapters (HBAs)



Servers
Storage Systems
Storage Controller Cards

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 10058835-1002LF](#) on WIN SOURCE

 [Amphenol](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management