



**THE DATASHEET OF
K292-A-PJ**



CONNECTOR TERM TRANSLATION

■Parts List

| 部品名 | DESCRIPTION |
|------------|----------------------------|
| 接続スリーブ | SHELL |
| 絶縁体 | INSULATOR |
| ガスケット | GASKET |
| ウェーブワッシャー | WAVE WASHER |
| ワッシャー | WASHER |
| 本体、シェル | BODY |
| 中心コンタクト | CENTER PIN |
| 圧着スリーブ | FERRULE |
| 締付ナット | NUT |
| 保持リング | HOLDING RING |
| ブッシング | BUSHING |
| 平ワッシャー | FLAT WASHER |
| 半円平ワッシャー | HALF FLAT WASHER |
| スペーサー | SPACER |
| 接続ナット | COUPLING NUT |
| 外部コンタクト | OUTER CONTACT |
| Oリング | O-RING |
| 六角ナット | HEX NUT |
| クランプ | CLAMP |
| ホルダー | BARREL |
| フタ | COVER |
| 割りクランプ | SPLIT CLAMP |
| 留めネジ | SCREW |
| バネリング | SPRING |
| ヒートシンク | HEAT SINK |
| 抵抗器、抵抗素子 | RESISTOR |
| スプリングワッシャー | SPRING WASHER |
| 六角穴留めネジ | SOCKET HEAD CAP SCREW |
| ブラケット | BRACKET |
| ブッシュ | BUSH |
| 同軸型避雷管 | COAXIAL LIGHTNING ARRESTER |
| 丸型端子 | ROUND TERMINAL |
| 減衰素子 | ATTENUATION TERMINAL |

■Parts List

| 部品名 | DESCRIPTION |
|---------|------------------|
| 表示シール | STICKER |
| 熱収縮チューブ | HEAT SHRINK TUBE |
| 丸ナット | RING NUT |

■Material List

| 材質 | MATERIAL |
|---------|--------------------|
| 亜鉛ダイカスト | ZnDC |
| ジラコン | POM |
| シリコンゴム | SILICONE |
| テフロン | PTFE |
| 鉄、炭素工具鋼 | CARBON STEEL |
| 黄銅 | BRASS |
| ベリリウム銅 | BERYLLIUM COPPER |
| リン青銅 | PHOSPHOR BRONZE |
| 無酸素銅 | OXYGEN-FREE COPPER |
| アルミニウム | ALUMINUM |
| ステンレス | STAINLESS STEEL |

■List of Notations on Drawings

| | |
|------------------|-----------------|
| 取付穴参考寸法 | MOUNTING HOLE |
| 最大パネル厚さ、使用可能パネル厚 | PANEL THICKNESS |
| 識別No. | SERIAL No. |
| 刻印 | STAMP |
| Dカット幅 | D FLAT |
| Hカット幅 | H FLAT |
| アヤメローレット | DIAMOND KNURL |
| タテメローレット | STRAIGHT KNURL |
| 識別溝、目印、溝 | GROOVE |
| | |
| | |

■Surface List

| 処理 | FINISH |
|---------|-------------------|
| 三元めっき | TERNARY PLATING |
| 黒色アルマイト | ANODAIZING(BLACK) |
| パッシベイト | PASSIVATE |

PRODUCT SPECIFICATIONS

Part No. K292-A-PJ

No. 1042141

DWG No. K-1045486

Nominal 1 Standard IEC 61169-35、MIL-STD-348A
 2 Voltage rating AC 250V
 3 Frequency range 40GHz
 4 Impedance 50Ω
 5 [OPR]Temp-Range -40°C~+105°C



| | | Test Items | Procedures/Test method | Requirements |
|------------|----|--|---|--------------------------------------|
| DESIGN | 1 | Design & construction | Specified on relevant product drawing | |
| | 2 | Materials | (DWG No. K-1045486) | No defects or abnormalities |
| | 3 | Finishes | | |
| ELECTRICAL | 4 | Insulation Resistance | DC 500V | 5000MΩ (Min.) |
| | 5 | Withstanding voltage | AC 750V (1 minute.) | No defects or abnormalities |
| | 6 | Contact resistance | The voltage drop of the contact duration should not exceed 1-kHz AC or 1mV DC | Inner 3mΩ (Max.) Outer 2mΩ (Max.) |
| | 7 | V. S. W. R | DC~40GHz | 1.25 (Max.) |
| MECHANICAL | 8 | Compatibility | Connecting with a standard-compliant connector | No defects or abnormalities |
| | 9 | Tensile strength of coupling mechanism | At axial tensile force 270N | No defects or abnormalities |
| | 10 | Center contact retaining force | When using the standard pin gauge 0.28N (Min.) | No defects or abnormalities |
| | 11 | Durability | 500 matings | Contact resistance 4mΩ (Max.) |
| | 12 | Coupling torque | 0.8Nm~1.1Nm | No defects or abnormalities |
| | | | | |



| | Remarks | Date |
|---|---------|------|
| 1 | | |
| 2 | | |
| 3 | | |

| Checked | Approved | Inspected | Prepared |
|-------------------|--------------------|-------------------|--------------------|
| 19.06.14 村 | 19.06.14 山本 | 19.06.14 澤 | 19.06.14 栗原 |

GKQM-25

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View K292-A-PJ on WIN SOURCE](#)
-  [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management