



**THE DATASHEET OF
NP50TD6G-30W**



PRODUCT SPECIFICATIONS

Part No. NP50TD6G-30W

No. 0512123

DWG No. W-0515452

Nominal 1 Standard JIS C 5411
 2 Frequency range 6GHz
 3 Impedance 50Ω
 4 Power handling 30W
 5 [OPR]Temp-Range -45°C~+85°C



	Test Items	Procedures/Test method	Requirements
DESIGN	1 Design & construction	Specified on relevant product drawing (DWG No. W-0515452)	No defects or abnormalities
	2 Materials		
	3 Finishes		
ELECTRICAL	4 V. S. W. R	DC~6GHz	1.3(Max.)
MECHANICAL	5 Compatibility	Connecting with a standard-compliant connector	No defects or abnormalities
	6 Tensile strength of coupling mechanism	At axial tensile force 300N	No defects or abnormalities
	7 Connection nut tightening torque	0.7~1.1N·m	No defects or abnormalities
ENVIRONMENTAL	8 Waterproof	IPX7	No water ingress inside the connector

	Remarks	Date
1		
2		
3		

Checked	Approved	Inspected	Prepared
三	山	檜	渡邊
19.05.10	19.05.10	19.05.10	'19.05.10
村	本	澤	直弘

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View NP50TD6G-30W on WIN SOURCE](#)
- ⊖ [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management