



THE DATASHEET OF SHV-BR



PRODUCT SPECIFICATION

Part number: SHV-BR

No. 1022009

Drawing number: X-1034462

Nominal 1 参考規格/Standard

MIL-C-39012

2 定格電圧/Voltage rating

AC 3500V

3 定格周波数/Frequency range

適用しない/Not applicable

4 公称インピーダンス/Impedance

不整合/Mismatch

5 使用温度範囲/Operating Temperature Range

-40°C~+85°C



		Test Items	Test Method/Value	Remarks	
1	E L E C T R I C A L	絶縁抵抗 Insulation Resistance	1000MΩ(Min.) at DC 500V		
2		耐電圧 Withstand voltage	1 minute at AC 5000V		
3		接触抵抗 Contact resistance	Inner conductor : 3mΩ(Max.)		
4	M E C H A N I C A L	互換性 Compatibility	異常なく結合すること/No defects or abnormalities	規格に準ずるコネクタと 結合したとき Mating with connector complying with the standard	
5		結合部接続強度 Tensile strength of coupling mechanism	245N	軸方向引張力にて At axial tensile force	

※構造形状は添付図に示す (図番 : X-1034462)

The structural shape is shown in the attached drawing (Drawing number: X-1034462)

	REVISIONS	DATE
1	書式変更、「構造形状」削除、使用温度範囲・英訳追記	2023.07.28
2		

Checked	Approved	Proof mark	Prepared
三	山	檜	渡邊
23.07.28	23.07.28	23.07.28	'23.07.28
村	本	澤	直弘

GKQM-20

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View SHV-BR on WIN SOURCE](#)
- ⊖ [TYCLON Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management