



**THE DATASHEET OF
FDMC8878**



FDMC8878

N-Channel POWERTRENCH[®] MOSFET 30 V, 16.5 A, 14 mΩ

This N-Channel MOSFET is a rugged gate version of ON Semiconductor's advanced PowerTrench process. It has been optimized for power management applications.

Features

- $R_{DS(on)} = 14 \text{ m}\Omega$ (Max.) @ $V_{GS} = 10 \text{ V}$, $I_D = 9.6 \text{ A}$
- $R_{DS(on)} = 17 \text{ m}\Omega$ (Max.) @ $V_{GS} = 4.5 \text{ V}$, $I_D = 8.7 \text{ A}$
- Low Profile – 0.8 mm Max in MLP 3.3 x 3.3
- These Devices are Pb-Free and are RoHS Compliant

Application

- DC – DC Conversion

MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit		
Drain-to-Source Voltage	V_{DS}	30	V		
Gate-to-Source Voltage	V_{GS}	± 20	V		
Continuous Drain Current	$T_C = 25^\circ\text{C}$ (Package limited)	I_D	16.5	A	
	$T_C = 25^\circ\text{C}$ (Silicon limited)				38
	$T_A = 25^\circ\text{C}$ (Figure 1)				9.6
Drain Current	Pulsed	I_D	60	A	
Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	31	W	
	$T_A = 25^\circ\text{C}$ (Figure 1)				2.1
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$		

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	4	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient (Figure 1)	$R_{\theta JA}$	60	



PACKAGE MARKING AND ORDERING INFORMATION

Part Number	Top Mark	Package	Reel Size	Tape Width	Quantity
FDMC8878	FDMC8878	MLP 3.3 x 3.3	13"	12 mm	3000 units




ON Semiconductor[®]

www.onsemi.com



WDFN8
CASE 511DH



ORDERING INFORMATION

See detailed ordering, marking and shipping information on page 1 of this data sheet.

FDMC8878

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{DSS}	Drain-to-Source Breakdown Voltage	$I_D = 250 \mu\text{A}$, $V_{GS} = 0 \text{ V}$	30	-	-	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	$I_D = 250 \mu\text{A}$, Referenced to 25°C	-	20	-	$\text{mV}/^\circ\text{C}$
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 24 \text{ V}$, $V_{GS} = 0 \text{ V}$	-	-	1	μA
		$V_{DS} = 24 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_J = 125^\circ\text{C}$	-	-	100	
I_{GSS}	Gate-to-Source Leakage Current	$V_{GS} = \pm 20 \text{ V}$, $V_{DS} = 0 \text{ V}$	-	-	± 100	nA

ON CHARACTERISTICS

$V_{GS(th)}$	Gate-to-Source Breakdown Voltage	$I_D = 250 \mu\text{A}$, $V_{GS} = V_{DS}$	1	1.7	3	V
$\Delta BV_{DSS}/\Delta T_J$	Gate-to-Source Threshold Voltage Temperature Coefficient	$I_D = 250 \mu\text{A}$, Referenced to 25°C	-	-5.7	-	$\text{mV}/^\circ\text{C}$
$R_{DS(on)}$	Drain-to-Source On Resistance	$V_{GS} = 10 \text{ V}$, $I_D = 9.6 \text{ A}$	-	9.6	14.0	$\text{m}\Omega$
		$V_{GS} = 4.5 \text{ V}$, $I_D = 8.7 \text{ A}$	-	12.1	17.0	
		$V_{GS} = 10 \text{ V}$, $I_D = 9.6 \text{ A}$, $T_J = 125^\circ\text{C}$	-	13.5	20.0	
g_{FS}	Forward Transconductance	$V_{DS} = 5 \text{ V}$, $I_D = 9.6 \text{ A}$	-	35	-	S

DYNAMIC CHARACTERISTICS

C_{iss}	Input Capacitance	$V_{DS} = 15 \text{ V}$, $V_{GS} = 0 \text{ V}$, $f = 1 \text{ MHz}$	-	1000	1230	pF
C_{oss}	Output Capacitance		-	183	255	pF
C_{rss}	Reverse Transfer Capacitance		-	118	180	pF
R_g	Reverse Transfer Capacitance	$f = 1 \text{ MHz}$	-	1.1	-	Ω

SWITCHING CHARACTERISTICS

$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = 15 \text{ V}$, $I_D = 9.6 \text{ A}$, $V_{GS} = 10 \text{ V}$, $R_{GEN} = 6 \Omega$	-	8	16	ns
t_r	Rise Time		-	4	10	
$t_{d(off)}$	Turn-Off Delay Time		-	20	36	
t_f	Fall Time		-	3	10	
$Q_{g(tot)}$	Total Gate Charge	$V_{GS} = 10 \text{ V}$, $V_{DD} = 15 \text{ V}$, $I_D = 9.6 \text{ A}$	-	18	26	nC
Q_{gs}	Gate-to-Source Gate Charge		-	2.8	-	
Q_{gd}	Gate-to-Drain "Miller" Charge		-	3.9	-	

DRAIN-SOURCE DIODE CHARACTERISTICS

V_{SD}	Source-to-Drain Diode Forward Voltage	$V_{GS} = 0 \text{ V}$, $I_S = 9.6 \text{ A}$ (Note 2)	-	0.8	1.2	V
t_{rr}	Reverse Recovery Time	$I_F = 9.6 \text{ A}$, $di/dt = 100 \text{ A}/\mu\text{s}$	-	23	35	ns
Q_{rr}	Reverse Recovery Charge		-	14	21	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. $R_{\theta JA}$ is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.




Figure 1.

a. $60^\circ\text{C}/\text{W}$ when mounted on a 1 in² pad of 2 oz copper



Figure 2.

b. $135^\circ\text{C}/\text{W}$ when mounted on a minimum pad of 2 oz copper

2. Pulse Test: Pulse Width < 300 μs , Duty cycle < 2.0%.

TYPICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 3. Gate Charge Characteristics




Figure 4. Capacitance vs. Drain to Source Voltage




Figure 5. Unclamped Inductive Switching Capability




Figure 6. Maximum Continuous Drain Current vs. Ambient Temperature




Figure 7. Forward Bias Safe Operating Area




Figure 8. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 9. On-Region Characteristics




Figure 10. Transfer Characteristics




Figure 11. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 12. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 13. Capacitance Characteristics




Figure 14. Gate Charge Characteristics

TYPICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)






Figure 15. Transient Thermal Response Curve

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS



WDFN8 3.3x3.3, 0.65P
CASE 511DH
ISSUE O



DATE 31 JUL 2016



RECOMMENDED LAND PATTERN

NOTES:

- A. DOES NOT CONFORM TO JEDEC REGISTRATION MO-229
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.
- D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.



BOTTOM VIEW

DOCUMENT NUMBER:	98AON13625G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	WDFN8 3.3X3.3, 0.65P	PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com



ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View FDMC8878 on WIN SOURCE](#)
-  [Fairchild/ON Semiconductor Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management