



**THE DATASHEET OF
FSLU2520-470J=P2**




FSLU2520 Wirewound Chip Inductor

The FSLU2520 Series is a ferrite core wirewound surface mount chip inductor which conforms to the EIA standard 1008 footprint. Its proprietary welded termination architecture offers superior reliability and high heat-resistance for flow and reflow soldering capability. It is recommended for general signal conditioning, RF or IF filtering applications, or as matching elements.




Dimensions




Features

- Inductance: 10nH ~ 220 μ H
- Typical max Q: 40 ~ 50
- Proprietary wire-wound structure with welded terminations offers high reliability
- Operating Temperature Range: -40°C ~ + 85°C
- Superior solderability and high heat-resistance for flow and reflow soldering

Part Numbering



Q-Frequency Characteristics



FSLU2520 Wirewound Chip Inductor

Part Number Table

Part Number	Lo (μ H)	Inductance Tolerance	Q Min.	Test Frequency (MHz)	DC Resistance (Ω) Max.	Rated DC Current (mA) Max	Self Resonant Frequency (MHz) Min.
FSLU2520-10N*	0.010	M, K	15	100	0.15	730	2300
FSLU2520-12N*	0.012	M, K	15	100	0.17	690	2100
FSLU2520-15N*	0.015	M, K	15	100	0.19	660	2000
FSLU2520-18N*	0.018	M, K	15	100	0.20	600	1750
FSLU2520-22N*	0.022	M, K	15	100	0.21	550	1550
FSLU2520-27N*	0.027	M, K	15	100	0.25	520	1400
FSLU2520-33N*	0.033	M, K	20	100	0.29	480	1200
FSLU2520-39N*	0.039	M, K	20	100	0.32	460	1100
FSLU2520-47N*	0.047	M, K	20	100	0.34	440	1000
FSLU2520-56N*	0.056	M, K	20	100	0.37	420	900
FSLU2520-68N*	0.068	M, K	20	100	0.41	400	850
FSLU2520-82N*	0.082	M, K	20	100	0.42	390	700
FSLU2520-R10*	0.10	M, K	20	100	0.53	380	500
FSLU2520-R12*	0.12	M, K	30	25.2	0.25	550	720
FSLU2520-R15*	0.15	M, K	30	25.2	0.27	500	570
FSLU2520-R18*	0.18	M, K	30	25.2	0.29	460	540
FSLU2520-R22*	0.22	M, K	30	25.2	0.34	430	480
FSLU2520-R27*	0.27	M, K	30	25.2	0.38	420	425
FSLU2520-R33*	0.33	M, K	30	25.2	0.42	400	360
FSLU2520-R39*	0.39	M, K	30	25.2	0.44	375	290
FSLU2520-R47*	0.47	M, K	30	25.2	0.49	350	260
FSLU2520-R56*	0.56	M, K	30	25.2	0.53	330	230
FSLU2520-R68*	0.68	M, K	30	25.2	0.59	320	200
FSLU2520-R82*	0.82	M, K	30	25.2	0.65	290	180
FSLU2520-1R0*	1.0	K, J	30	7.96	0.89	250	170
FSLU2520-1R2*	1.2	K, J	30	7.96	0.95	235	150
FSLU2520-1R5*	1.5	K, J	30	7.96	1.1	230	130
FSLU2520-1R8*	1.8	K, J	30	7.96	1.2	220	115
FSLU2520-2R2*	2.2	K, J	30	7.96	1.3	210	105
FSLU2520-2R7*	2.7	K, J	30	7.96	1.4	200	85
FSLU2520-3R3*	3.3	K, J	30	7.96	1.7	190	75
FSLU2520-3R9*	3.9	K, J	30	7.96	1.8	185	70
FSLU2520-4R7*	4.7	K, J	30	7.96	2.2	180	60
FSLU2520-5R6*	5.6	K, J	30	7.96	2.3	175	55
FSLU2520-6R8*	6.8	K, J	30	7.96	2.7	165	50
FSLU2520-8R2*	8.2	K, J	30	7.96	2.9	160	40
FSLU2520-100*	10	K, J	25	2.52	2.4	155	33
FSLU2520-120*	12	K, J	25	2.52	2.7	150	30
FSLU2520-150*	15	K, J	25	2.52	3.1	145	27
FSLU2520-180*	18	K, J	25	2.52	3.3	135	24
FSLU2520-220*	22	K, J	25	2.52	3.9	125	22
FSLU2520-270*	27	K, J	25	2.52	4.3	120	21
FSLU2520-330*	33	K, J	25	2.52	5.1	115	20
FSLU2520-390*	39	K, J	25	2.52	5.8	90	16
FSLU2520-470*	47	K, J	25	2.52	10.0	80	15
FSLU2520-560*	56	K, J	25	2.52	11.0	75	13
FSLU2520-680*	68	K, J	25	2.52	12.0	70	12
FSLU2520-820*	82	K, J	25	2.52	14.0	66	11
FSLU2520-101*	100	K, J	15	0.796	19.0	60	10
FSLU2520-121*	120	K, J	15	0.796	20.5	52	8
FSLU2520-151*	150	K, J	15	0.796	24.5	50	8
FSLU2520-181*	180	K, J	15	0.796	28.5	48	7
FSLU2520-221*	220	K, J	15	0.796	31.5	45	7

* Add tolerance to part number: J = 5%, K = 10%, M = 20%

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View FSLU2520-470J=P2 on WIN SOURCE](#)

 [Toko America Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management