


NPCAP™-PXG Series *Upgrade!*

- Super low ESR, high ripple current capability
- Rated voltage range : 16 to 25V_{dc}, Capacitance range : 22 to 1,000μF
- Case size : φ 5×5.8L to φ 10×12.2L
- Solvent resistant type (see PRECAUTIONS AND GUIDELINES)
- RoHS2 Compliant
- Halogen Free




◆ SPECIFICATIONS

| Items | Characteristics | | | | | | | | | | | | | | | | | | |
|--|--|----------------------------------|-----------------------|--------------------|--------------------------------------|----------------------------------|---------------------------------------|-----|---------------------------------------|-----------------|---|--------------------|-----------------------------|--------------|---------------------------------------|-----|---------------------------------------|-----------------|-------------------------------|
| Category | | | | | | | | | | | | | | | | | | | |
| Temperature Range | -55 to +105°C | | | | | | | | | | | | | | | | | | |
| Rated Voltage Range | 16 to 25V _{dc} | | | | | | | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% (M) (at 20°C, 120Hz) | | | | | | | | | | | | | | | | | | |
| Leakage Current | Shall not exceed values shown in STANDARD RATINGS. (at 20°C after 2 minutes) | | | | | | | | | | | | | | | | | | |
| *Note | | | | | | | | | | | | | | | | | | | |
| Dissipation Factor (tan δ) | 0.12 max. (at 20°C, 120Hz) | | | | | | | | | | | | | | | | | | |
| Low Temperature Characteristics (Max. Impedance Ratio) | Z(-25°C)/Z(+20°C) ≤ 1.15 Z(-55°C)/Z(+20°C) ≤ 1.25 (at 100kHz) | | | | | | | | | | | | | | | | | | |
| Endurance | The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for 15,000 hours (F46 : 3,000 hours) at 105°C. <table border="1"> <tr><td>Appearance</td><td>No significant damage</td></tr> <tr><td>Capacitance change</td><td>≤ ±20% of the initial value</td></tr> <tr><td>D.F. (tan δ)</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>ESR</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>Leakage current</td><td>≤ The initial specified value</td></tr> </table> | Appearance | No significant damage | Capacitance change | ≤ ±20% of the initial value | D.F. (tan δ) | ≤ 150% of the initial specified value | ESR | ≤ 150% of the initial specified value | Leakage current | ≤ The initial specified value | | | | | | | | |
| Appearance | No significant damage | | | | | | | | | | | | | | | | | | |
| Capacitance change | ≤ ±20% of the initial value | | | | | | | | | | | | | | | | | | |
| D.F. (tan δ) | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| ESR | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| Leakage current | ≤ The initial specified value | | | | | | | | | | | | | | | | | | |
| Bias Humidity | The following specifications shall be satisfied when the capacitors are restored to 20°C after subjecting them to the DC rated voltage at 60°C, 90 to 95% RH for 1,000 hours (F46 : 500 hours). <table border="1"> <tr><td>Appearance</td><td>No significant damage</td></tr> <tr><td>Capacitance change</td><td>≤ ±20% of the initial value</td></tr> <tr><td>D.F. (tan δ)</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>ESR</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>Leakage current</td><td>≤ The initial specified value</td></tr> </table> | Appearance | No significant damage | Capacitance change | ≤ ±20% of the initial value | D.F. (tan δ) | ≤ 150% of the initial specified value | ESR | ≤ 150% of the initial specified value | Leakage current | ≤ The initial specified value | | | | | | | | |
| Appearance | No significant damage | | | | | | | | | | | | | | | | | | |
| Capacitance change | ≤ ±20% of the initial value | | | | | | | | | | | | | | | | | | |
| D.F. (tan δ) | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| ESR | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| Leakage current | ≤ The initial specified value | | | | | | | | | | | | | | | | | | |
| Surge Voltage | The capacitors shall be subjected to 1,000 cycles each consisting of charge with the surge voltage specified at 105°C for 30 seconds through a protective resistor(R=1kΩ) and discharge for 5 minutes 30 seconds. <table border="1"> <tr><td>Rated voltage (V_{dc})</td><td>16</td><td>20</td><td>25</td></tr> <tr><td>Surge voltage (V_{dc})</td><td>18</td><td>23</td><td>29</td></tr> </table> <table border="1"> <tr><td>Appearance</td><td>No significant damage</td></tr> <tr><td>Capacitance change</td><td>≤ ±20% of the initial value</td></tr> <tr><td>D.F. (tan δ)</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>ESR</td><td>≤ 150% of the initial specified value</td></tr> <tr><td>Leakage current</td><td>≤ The initial specified value</td></tr> </table> | Rated voltage (V _{dc}) | 16 | 20 | 25 | Surge voltage (V _{dc}) | 18 | 23 | 29 | Appearance | No significant damage | Capacitance change | ≤ ±20% of the initial value | D.F. (tan δ) | ≤ 150% of the initial specified value | ESR | ≤ 150% of the initial specified value | Leakage current | ≤ The initial specified value |
| Rated voltage (V _{dc}) | 16 | 20 | 25 | | | | | | | | | | | | | | | | |
| Surge voltage (V _{dc}) | 18 | 23 | 29 | | | | | | | | | | | | | | | | |
| Appearance | No significant damage | | | | | | | | | | | | | | | | | | |
| Capacitance change | ≤ ±20% of the initial value | | | | | | | | | | | | | | | | | | |
| D.F. (tan δ) | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| ESR | ≤ 150% of the initial specified value | | | | | | | | | | | | | | | | | | |
| Leakage current | ≤ The initial specified value | | | | | | | | | | | | | | | | | | |
| Soldering Heat | The following specifications shall be satisfied when the solder temperature is reduced back to 20°C after soldering has been performed under the recommended soldering conditions. <table border="1"> <tr><td>Appearance</td><td>No significant damage</td></tr> <tr><td>Capacitance value</td><td>Within the specified tolerance range</td></tr> <tr><td>D.F. (tan δ)</td><td>≤ The initial specified value</td></tr> <tr><td>ESR</td><td>≤ The initial specified value</td></tr> <tr><td>Leakage current</td><td>≤ The initial specified value (Voltage treatment)</td></tr> </table> | Appearance | No significant damage | Capacitance value | Within the specified tolerance range | D.F. (tan δ) | ≤ The initial specified value | ESR | ≤ The initial specified value | Leakage current | ≤ The initial specified value (Voltage treatment) | | | | | | | | |
| Appearance | No significant damage | | | | | | | | | | | | | | | | | | |
| Capacitance value | Within the specified tolerance range | | | | | | | | | | | | | | | | | | |
| D.F. (tan δ) | ≤ The initial specified value | | | | | | | | | | | | | | | | | | |
| ESR | ≤ The initial specified value | | | | | | | | | | | | | | | | | | |
| Leakage current | ≤ The initial specified value (Voltage treatment) | | | | | | | | | | | | | | | | | | |

*Note : If any doubt arises, measure the leakage current after the following voltage treatment.
Voltage treatment : DC rated voltage is applied to the capacitors for 120 minutes at 105°C.

◆ DIMENSIONS [mm]

● Terminal Code : A



Note : L^{+0.1}_{-0.2} for F46
L±0.5 for JC0

| Size Code | φD | L | A | B | C | W | P |
|-----------|-----|------|------|------|------|------------|-----|
| E61 | 5 | 5.8 | 5.3 | 5.3 | 5.9 | 0.5 to 0.8 | 1.4 |
| F46 | 6.3 | 4.5 | 6.6 | 6.6 | 7.2 | 0.5 to 0.8 | 1.9 |
| F61 | 6.3 | 5.8 | 6.6 | 6.6 | 7.2 | 0.5 to 0.8 | 1.9 |
| F80 | 6.3 | 7.7 | 6.6 | 6.6 | 7.2 | 0.5 to 0.8 | 1.9 |
| H70 | 8 | 6.7 | 8.3 | 8.3 | 9.0 | 0.7 to 1.1 | 3.1 |
| J80 | 10 | 7.7 | 10.3 | 10.3 | 11.0 | 0.7 to 1.1 | 4.5 |
| JC0 | 10 | 12.2 | 10.3 | 10.3 | 11.0 | 0.7 to 1.1 | 4.5 |

◆ MARKING


EX) 25V47μF





NPCAP™-P^{Upgrade!}XG Series

◆PART NUMBERING SYSTEM



(Note1) : P^{Upgrade!}XG Series 16V68μF (ESR 20mΩ max.) and 16V82μF (ESR 20mΩ max.) have supplement code "J". Terminal and terminal plating are the same as all other in P^{Upgrade!}XG series.

Please refer to "Product code guide (conductive polymer type)"

◆STANDARD RATINGS

| WV (V _{dc}) | Cap (μF) | Size code | Leakage current (μA max./after 2min.) | ESR (mΩ max./20°C, 100k to 300kHz) | Rated ripple current (mA rms/105°C, 100kHz) | Part No. |
|-----------------------|-----------|------------|---------------------------------------|------------------------------------|---|---------------------------|
| 16 | 68 | F46 | 544 | 20 | 3,200 | APXG160ARA680MF46J |
| | 68 | F46 | 544 | 40 | 2,450 | APXG160ARA680MF46G |
| | 82 | F46 | 656 | 20 | 3,200 | APXG160ARA820MF46J |
| | 82 | F46 | 656 | 40 | 2,450 | APXG160ARA820MF46G |
| | 100 | E61 | 320 | 27 | 3,000 | APXG160ARA101ME61G |
| | 180 | F61 | 576 | 22 | 3,300 | APXG160ARA181MF61G |
| | 220 | F80 | 704 | 22 | 3,300 | APXG160ARA221MF80G |
| | 270 | H70 | 864 | 22 | 3,300 | APXG160ARA271MH70G |
| | 330 | H70 | 1,050 | 22 | 3,300 | APXG160ARA331MH70G |
| 20 | 560 | J80 | 1,790 | 20 | 3,800 | APXG160ARA561MJ80G |
| | 820 | JC0 | 2,620 | 12 | 5,400 | APXG160ARA821MJC0G |
| | 1,000 | JC0 | 3,200 | 12 | 5,400 | APXG160ARA102MJC0G |
| | 47 | E61 | 188 | 30 | 2,800 | APXG200ARA470ME61G |
| | 47 | F46 | 470 | 42 | 2,400 | APXG200ARA470MF46G |
| | 56 | E61 | 224 | 30 | 2,800 | APXG200ARA560ME61G |
| | 120 | F61 | 480 | 25 | 3,200 | APXG200ARA121MF61G |
| 25 | 150 | F80 | 600 | 25 | 3,200 | APXG200ARA151MF80G |
| | 180 | H70 | 720 | 25 | 3,200 | APXG200ARA181MH70G |
| | 390 | J80 | 1,560 | 22 | 3,650 | APXG200ARA391MJ80G |
| | 22 | E61 | 110 | 40 | 2,450 | APXG250ARA220ME61G |
| | 22 | F46 | 275 | 45 | 2,350 | APXG250ARA220MF46G |
| | 27 | E61 | 135 | 40 | 2,450 | APXG250ARA270ME61G |
| | 27 | F46 | 337 | 45 | 2,350 | APXG250ARA270MF46G |
| | 39 | F61 | 195 | 30 | 2,800 | APXG250ARA390MF61G |
| | 47 | F61 | 235 | 30 | 2,800 | APXG250ARA470MF61G |
| | 56 | F61 | 280 | 30 | 2,800 | APXG250ARA560MF61G |
| | 56 | F80 | 280 | 28 | 2,800 | APXG250ARA560MF80G |
| | 68 | F61 | 340 | 30 | 2,800 | APXG250ARA680MF61G |
| | 68 | H70 | 340 | 28 | 3,000 | APXG250ARA680MH70G |
| | 120 | F80 | 600 | 28 | 2,800 | APXG250ARA121MF80G |
| 150 | H70 | 750 | 28 | 3,000 | APXG250ARA151MH70G | |
| 150 | J80 | 750 | 25 | 3,400 | APXG250ARA151MJ80G | |
| 180 | J80 | 900 | 25 | 3,400 | APXG250ARA181MJ80G | |

New products are indicated in red text.

◆RATED RIPPLE CURRENT MULTIPLIERS

● Frequency Multipliers

| Frequency (Hz) | 120 | 1k | 10k | 50k | 100k to 500k |
|----------------|------|------|------|------|--------------|
| SMD type | 0.05 | 0.30 | 0.55 | 0.70 | 1.00 |



- Always read "Notes on Use" before using the product in order to enable you to use the product correctly and prevent any faults and accidents from occurring.
- Request the Product Specification on the product of NIPPON CHEMI-CON CORPORATION to refer to it as well as this brochure prior to the order of the products. Some specific notes on use of the ordered product may be described in the specifications.
- The products listed in this catalog are designed and manufactured for general electronics equipment use and are not intended for use in applications that can adversely affect human life; where the malfunction of equipment may cause damage to life or property. In addition, our products are not intended to be used in specific applications that may cause a major social impact. Please consult with us in advance of usage of our products in the following listed applications. ① Aerospace equipment ② Power generation equipment such as thermal power, nuclear power etc. ③ Medical equipment ④ Transport equipment (automobiles, trains, ships, etc.) ⑤ Transportation control equipment ⑥ Disaster prevention / crime prevention equipment ⑦ Highly publicized information processing equipment ⑧ Submarine equipment ⑨ Other applications that are not considered general-purpose applications.
- The circuits described as examples in this catalog and the "delivery specifications" are featured in order to show the operations and usage of our products, however, this fact does not guarantee that the circuits are available to function in your equipment systems. We are not in any case responsible for any failures or damage caused by the use of information contained herein. You should examine our products, of which the characteristics are described in the "delivery specifications" and other documents, and determine whether or not our products suit your requirements according to the specifications of your equipment systems. Therefore, you bear final responsibility regarding the use of our products.
Please make sure that you take appropriate safety measures such as use of redundant design and malfunction prevention measures in order to prevent fatal accidents and/or fires in the event any of our products malfunction.
- We strongly recommend our customers to purchase Nippon Chemi-Con products only through our official sales channels. We assume no responsibility for any defects or damages caused by using products purchased from outside our official sales channel or of counterfeit goods. In addition, we will ask the customer to pay the investigation cost for products purchased outside our official sales channel.
- We reserve the right to discontinue production and delivery of products. We do not guarantee that all the products included in this catalog will be available in the future.
The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products
- We continually strive to improve the quality and reliability of our products, but in any case that our product does not meet our published specifications, please stop using it promptly and contact us immediately. As for compensation for non-conforming goods delivered by Chemi-Con, we will limit it only to goods found in non-compliance of our published specifications. This may be accomplished by a no cost replacement of non-conforming individual products, a credit of the piece price paid per each individual non-conforming product, or in other ways deemed necessary.
In addition, we have an established system with enhanced traceability, therefore we will limit the applicable lot items for any potential compensation.

[Part Numbering System](#)

[Part Numbering System \(Appendix\)](#)

[Standardization](#)

[Available Items by Manufacturing Locations](#)

[Environmental Measures](#)

[Technical Note](#)

[Precautions and Guidelines](#)

[Recommended Soldering Conditions](#)

[Taping, Lead-preforming, Terminal and Packaging Options](#)

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View APXG200ARA391MJ80G on WIN SOURCE](#)
- ⊖ [United Chemi-Con Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management