


SIPMOS[®] Small-Signal-Transistor
Features

- N-channel
- Enhancement mode
- Logic level
- dv/dt rated
- Pb-free lead-plating; RoHS compliant
- Qualified according to AEC Q101
- Halogen free according to IEC61249-2-21


Product Summary

| | | |
|------------------|------|----------|
| V_{DS} | 60 | V |
| $R_{DS(on),max}$ | 3.5 | Ω |
| I_D | 0.23 | A |

PG-SOT-23


| Type | Package | Tape and Reel | Marking |
|---------|-----------|---------------|---------|
| BSS138N | PG-SOT-23 | H6327: 3000 | SKs |
| BSS138N | PG-SOT-23 | H6433: 10000 | SKs |

| Parameter | Symbol | Conditions | Value | Unit |
|-------------------------------------|-------------------|---|-----------------|-------------------|
| Continuous drain current | I_D | $T_A=25\text{ }^\circ\text{C}$ | 0.23 | A |
| | | $T_A=70\text{ }^\circ\text{C}$ | 0.18 | |
| Pulsed drain current | $I_{D,pulse}$ | $T_A=25\text{ }^\circ\text{C}$ | 0.92 | |
| Reverse diode dv/dt | dv/dt | $I_D=0.23\text{ A}$, $V_{DS}=48\text{ V}$, $di/dt=200\text{ A}/\mu\text{s}$, $T_{j,max}=150\text{ }^\circ\text{C}$ | 6 | kV/ μs |
| Gate source voltage | V_{GS} | | ± 20 | V |
| ESD sensitivity | | JESD22-A114 (HBM) | Class 0 (<250V) | |
| Power dissipation | P_{tot} | $T_A=25\text{ }^\circ\text{C}$ | 0.36 | W |
| Operating and storage temperature | T_j , T_{stg} | | -55 ... 150 | $^\circ\text{C}$ |
| IEC climatic category; DIN IEC 68-1 | | | 55/150/56 | |

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Thermal characteristics

| | | | | | | |
|--|------------|--|---|---|-----|-----|
| Thermal resistance, junction - minimal footprint | R_{thJA} | | - | - | 350 | K/W |
|--|------------|--|---|---|-----|-----|

Electrical characteristics, at $T_j=25\text{ }^\circ\text{C}$, unless otherwise specified
Static characteristics

| | | | | | | |
|----------------------------------|---------------|--|-----|-----|-----|---------------|
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | $V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$ | 60 | - | - | V |
| Gate threshold voltage | $V_{GS(th)}$ | $V_{GS}=V_{DS}, I_D=26\text{ }\mu\text{A}$ | 0.6 | 1.0 | 1.4 | |
| Drain-source leakage current | $I_{D(off)}$ | $V_{DS}=60\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ }^\circ\text{C}$ | - | - | 0.1 | μA |
| | | $V_{DS}=60\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ }^\circ\text{C}$ | - | - | 5 | |
| Gate-source leakage current | I_{GSS} | $V_{GS}=20\text{ V}, V_{DS}=0\text{ V}$ | - | 1 | 10 | nA |
| Drain-source on-state resistance | $R_{DS(on)}$ | $V_{GS}=4.5\text{ V}, I_D=0.03\text{ A}$ | - | 3.3 | 4.0 | Ω |
| | | $V_{GS}=4.5\text{ V}, I_D=0.19\text{ A}$ | - | 3.5 | 6.0 | |
| | | $V_{GS}=10\text{ V}, I_D=0.23\text{ A}$ | - | 2.2 | 3.5 | |
| Transconductance | g_{fs} | $ V_{DS} >2 I_D R_{DS(on)max}, I_D=0.18\text{ A}$ | 0.1 | 0.2 | - | S |

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Dynamic characteristics

| | | | | | | |
|------------------------------|--------------|---|---|-----|------|----|
| Input capacitance | C_{iss} | $V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$ | - | 32 | 41 | pF |
| Output capacitance | C_{oss} | | - | 7.2 | 9.5 | |
| Reverse transfer capacitance | C_{rss} | | - | 2.8 | 3.8 | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD}=30\text{ V}, V_{GS}=10\text{ V},$ $I_D=0.23\text{ A}, R_G=6\ \Omega$ | - | 2.3 | 3.5 | ns |
| Rise time | t_r | | - | 3.0 | 4.5 | |
| Turn-off delay time | $t_{d(off)}$ | | - | 6.7 | 10 | |
| Fall time | t_f | | - | 8.2 | 12.3 | |

Gate Charge Characteristics


| | | | | | | |
|-----------------------|---------------|--|---|------|------|----|
| Gate to source charge | Q_{gs} | $V_{DD}=48\text{ V}, I_D=0.23\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$ | - | 0.10 | 0.14 | nC |
| Gate to drain charge | Q_{gd} | | - | 0.3 | 0.4 | |
| Gate charge total | Q_g | | - | 1.0 | 1.4 | |
| Gate plateau voltage | $V_{plateau}$ | | - | 3.3 | - | V |

Reverse Diode

| | | | | | | |
|----------------------------------|---------------|---|---|------|------|----|
| Diode continuous forward current | I_S | $T_A=25\text{ }^\circ\text{C}$ | - | - | 0.23 | A |
| Diode pulse current | $I_{S,pulse}$ | | - | - | 0.92 | |
| Diode forward voltage | V_{SD} | $V_{GS}=0\text{ V}, I_F=0.23\text{ A},$ $T_J=25\text{ }^\circ\text{C}$ | - | 0.83 | 1.2 | V |
| Reverse recovery time | t_{rr} | $V_R=30\text{ V}, I_F=0.23\text{ A},$ $di_F/dt=100\text{ A}/\mu\text{s}$ | - | 9.1 | 14.5 | ns |
| Reverse recovery charge | Q_{rr} | | - | 3.3 | 5 | nC |


1 Power dissipation

$P_{tot}=f(T_A)$



2 Drain current


$I_D=f(T_A); V_{GS} \geq 10\text{ V}$



3 Safe operating area

$I_D=f(V_{DS}); T_A=25\text{ °C}; D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p)$


parameter: $D=t_p/T$



5 Typ. output characteristics

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



6 Typ. drain-source on resistance


$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$

parameter: V_{GS}




7 Typ. transfer characteristics

$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$




8 Typ. forward transconductance

$g_{fs} = f(I_D); T_j = 25\text{ }^\circ\text{C}$



9 Drain-source on-state resistance


$R_{DS(on)}=f(T_j)$; $I_D=0.23\text{ A}$; $V_{GS}=10\text{ V}$



10 Typ. gate threshold voltage


$V_{GS(th)}=f(T_j)$; $V_{DS}=V_{GS}$; $I_D=26\text{ }\mu\text{A}$

parameter: I_D



11 Typ. capacitances


$C=f(V_{DS})$; $V_{GS}=0\text{ V}$; $f=1\text{ MHz}$; $T_j=25^\circ\text{C}$



12 Forward characteristics of reverse diode

$I_F=f(V_{SD})$


parameter: T_j



13 Typ. gate charge


$V_{GS}=f(Q_{gate}); I_D=0.23\text{ A pulsed}$

parameter: V_{DD}




14 Drain-source breakdown voltage


$V_{BR(DSS)}=f(T_j); I_D=250\ \mu\text{A}$




Package Outline:



Footprint:



Packaging:



Dimensions in mm

Published by
Infineon Technologies AG
Bereich Kommunikation
St.-Martin-Straße 53
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices, please contact your nearest Infineon Technologies office in Germany or our Infineon Technologies representatives worldwide (see address list).


Warnings

Due to technical requirements, components may contain dangerous substances.
For information on the types in question, please contact your nearest Infineon Technologies office.

Infineon Technologies' components may only be used in life-support devices or systems with the expressed written approval of Infineon Technologies if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BSS138N H6433 on WIN SOURCE](#)
-  [Infineon Technologies Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management