




# High Voltage Transistors

## PNP Silicon

# MMBTA92L, SMMBTA92L, MMBTA93L



### Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### MAXIMUM RATINGS

| Rating                         | Symbol    | 92   | 93   | Unit |
|--------------------------------|-----------|------|------|------|
| Collector–Emitter Voltage      | $V_{CEO}$ | -300 | -200 | Vdc  |
| Collector–Base Voltage         | $V_{CBO}$ | -300 | -200 | Vdc  |
| Emitter–Base Voltage           | $V_{EBO}$ | -5.0 | -5.0 | Vdc  |
| Collector Current – Continuous | $I_C$     | -500 |      | mAdc |

### DEVICE MARKING


MMBTA92L, SMMBTA92L = 2D; MMBTA93LT1 = 2E

### THERMAL CHARACTERISTICS

| Characteristic   | Symbol          | Max            | Unit                      |
|--|-----------------|----------------|---------------------------|
| Total Device Dissipation FR-5 Board<br>(Note 1) $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$                        | $P_D$           | 225            | mW                        |
|  |                 | 1.8            | mW/ $^\circ\text{C}$      |
| Thermal Resistance, Junction to Ambient  | $R_{\theta JA}$ | 556            | $^\circ\text{C}/\text{W}$ |
| Total Device Dissipation (Note 2)<br>Alumina Substrate, <sup>(2)</sup> $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 300            | mW                        |
|  |                 | 2.4            | mW/ $^\circ\text{C}$      |
| Thermal Resistance, Junction to Ambient  | $R_{\theta JA}$ | 417            | $^\circ\text{C}/\text{W}$ |
| Junction and Storage Temperature   | $T_J, T_{stg}$  | -55 to<br>+150 | $^\circ\text{C}$          |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. FR-5 = 1.0 x 0.75 x 0.062 in.
2. Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.



SOT-23 (TO-236AF)  
CASE 318  
STYLE 6

### MARKING DIAGRAM



- 2x = Specific Device Code
- M = Date Code\*
- = Pb-Free Package

(\*Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon manufacturing location.

### ORDERING INFORMATION

| Device       | Package             | Shipping <sup>†</sup> |
|--------------|---------------------|-----------------------|
| MMBTA92LT1G  | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel    |
| SMMBTA92LT1G | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel    |
| MMBTA92LT3G  | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel   |
| SMMBTA92LT3G | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel   |
| MMBTA93LT1G  | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MMBTA92L, SMMBTA92L, MMBTA93L

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic   | Symbol                       | Min           | Max          | Unit           |               |
|--|------------------------------|---------------|--------------|----------------|---------------|
| <b>OFF CHARACTERISTICS</b>   |                              |               |              |                |               |
| Collector–Emitter Breakdown Voltage (Note 3)<br>( $I_C = -1.0\text{ mA}$ , $I_B = 0$ )                               | MMBTA92, SMMBTA92<br>MMBTA93 | $V_{(BR)CEO}$ | -300<br>-200 | -<br>-         | Vdc           |
| Collector–Base Breakdown Voltage<br>( $I_C = -100\text{ }\mu\text{A}$ , $I_E = 0$ )                                  | MMBTA92, SMMBTA92<br>MMBTA93 | $V_{(BR)CBO}$ | -300<br>-200 | -<br>-         | Vdc           |
| Emitter–Base Breakdown Voltage<br>( $I_E = -100\text{ }\mu\text{A}$ , $I_C = 0$ )                                    |                              | $V_{(BR)EBO}$ | -5.0         | -              | Vdc           |
| Collector Cutoff Current<br>( $V_{CB} = -200\text{ Vdc}$ , $I_E = 0$ )<br>( $V_{CB} = -160\text{ Vdc}$ , $I_E = 0$ ) | MMBTA92, SMMBTA92<br>MMBTA93 | $I_{CBO}$     | -<br>-       | -0.25<br>-0.25 | $\mu\text{A}$ |
| Emitter Cutoff Current<br>( $V_{EB} = -3.0\text{ Vdc}$ , $I_C = 0$ )   |                              | $I_{EBO}$     | -            | -0.1           | $\mu\text{A}$ |

## ON CHARACTERISTICS (Note 3)

|   |  |               |                      |                  |     |
|---|--|---------------|----------------------|------------------|-----|
| DC Current Gain<br>( $I_C = -1.0\text{ mA}$ , $V_{CE} = -10\text{ Vdc}$ )<br>( $I_C = -10\text{ mA}$ , $V_{CE} = -10\text{ Vdc}$ )<br><br>( $I_C = -30\text{ mA}$ , $V_{CE} = -10\text{ Vdc}$ ) | Both Types<br>Both Types<br>MMBTA92, SMMBTA92<br>MMBTA93 | $h_{FE}$      | 25<br>40<br>25<br>25 | -<br>-<br>-<br>- | -   |
| Collector–Emitter Saturation Voltage<br>( $I_C = -20\text{ mA}$ , $I_B = -2.0\text{ mA}$ )  | MMBTA92, SMMBTA92<br>MMBTA93                             | $V_{CE(sat)}$ | -<br>-               | -0.5<br>-0.5     | Vdc |
| Base–Emitter Saturation Voltage<br>( $I_C = -20\text{ mA}$ , $I_B = -2.0\text{ mA}$ )   |  | $V_{BE(sat)}$ | -                    | -0.9             | Vdc |

## SMALL-SIGNAL CHARACTERISTICS

|  |                              |          |        |            |     |
|--|------------------------------|----------|--------|------------|-----|
| Current–Gain — Bandwidth Product<br>( $I_C = -10\text{ mA}$ , $V_{CE} = -20\text{ Vdc}$ , $f = 100\text{ MHz}$ ) |                              | $f_T$    | 50     | -          | MHz |
| Collector–Base Capacitance<br>( $V_{CB} = -20\text{ Vdc}$ , $I_E = 0$ , $f = 1.0\text{ MHz}$ )                   | MMBTA92, SMMBTA92<br>MMBTA93 | $C_{cb}$ | -<br>- | 6.0<br>8.0 | pF  |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width  $\leq 300\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .




Figure 1. DC Current Gain

# MMBTA92L, SMMBTA92L, MMBTA93L




Figure 2. Capacitance




Figure 3. Current-Gain - Bandwidth




Figure 4. "ON" Voltages








Figure 5. Safe Operating Area



SCALE 4:1

**SOT-23 (TO-236) 2.90x1.30x1.00 1.90P**  
CASE 318  
ISSUE AU

DATE 14 AUG 2024




| MILLIMETERS |      |      |      |
|-------------|------|------|------|
| DIM         | MIN  | NOM  | MAX  |
| A           | 0.89 | 1.00 | 1.11 |
| A1          | 0.01 | 0.06 | 0.10 |
| b           | 0.37 | 0.44 | 0.50 |
| c           | 0.08 | 0.14 | 0.20 |
| D           | 2.80 | 2.90 | 3.04 |
| E           | 1.20 | 1.30 | 1.40 |
| e           | 1.78 | 1.90 | 2.04 |
| L           | 0.30 | 0.43 | 0.55 |
| L1          | 0.35 | 0.54 | 0.69 |
| HE          | 2.10 | 2.40 | 2.64 |
| T           | 0°   | ---  | 10°  |


NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSIONS: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

**GENERIC MARKING DIAGRAM\***



XXX = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package



\* For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

**STYLES ON PAGE 2**

|                         |   |  |
|-------------------------|---|--|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42226B</b>                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23 (TO-236) 2.90x1.30x1.00 1.90P</b> | <b>PAGE 1 OF 2</b>   |

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**SOT-23 (TO-236) 2.90x1.30x1.00 1.90P**  
**CASE 318**  
**ISSUE AU**

DATE 14 AUG 2024

STYLE 1 THRU 5:  
CANCELLED

STYLE 6:  
PIN 1. BASE  
2. EMITTER  
3. COLLECTOR

STYLE 7:  
PIN 1. EMITTER  
2. BASE  
3. COLLECTOR

STYLE 8:  
PIN 1. ANODE  
2. NO CONNECTION  
3. CATHODE

STYLE 9:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 10:  
PIN 1. DRAIN  
2. SOURCE  
3. GATE

STYLE 11:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE-ANODE

STYLE 12:  
PIN 1. CATHODE  
2. CATHODE  
3. ANODE

STYLE 13:  
PIN 1. SOURCE  
2. DRAIN  
3. GATE

STYLE 14:  
PIN 1. CATHODE  
2. GATE  
3. ANODE

STYLE 15:  
PIN 1. GATE  
2. CATHODE  
3. ANODE

STYLE 16:  
PIN 1. ANODE  
2. CATHODE  
3. CATHODE

STYLE 17:  
PIN 1. NO CONNECTION  
2. ANODE  
3. CATHODE

STYLE 18:  
PIN 1. NO CONNECTION  
2. CATHODE  
3. ANODE

STYLE 19:  
PIN 1. CATHODE  
2. ANODE  
3. CATHODE-ANODE

STYLE 20:  
PIN 1. CATHODE  
2. ANODE  
3. GATE

STYLE 21:  
PIN 1. GATE  
2. SOURCE  
3. DRAIN

STYLE 22:  
PIN 1. RETURN  
2. OUTPUT  
3. INPUT

STYLE 23:  
PIN 1. ANODE  
2. ANODE  
3. CATHODE

STYLE 24:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE

STYLE 25:  
PIN 1. ANODE  
2. CATHODE  
3. GATE

STYLE 26:  
PIN 1. CATHODE  
2. ANODE  
3. NO CONNECTION

STYLE 27:  
PIN 1. CATHODE  
2. CATHODE  
3. CATHODE

STYLE 28:  
PIN 1. ANODE  
2. ANODE  
3. ANODE

|                         |   |   |
|-------------------------|---|---|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42226B</b>                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-23 (TO-236) 2.90x1.30x1.00 1.90P</b> | <b>PAGE 2 OF 2</b>  |

**onsemi** and **ONSEMI** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SMMBTA92LT3G on WIN SOURCE](#)

 [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management