



THE DATASHEET OF IAA.01.121111



TAOGLAS®



Datasheet

Iridium Certified Antenna

Part No:
IAA.01.121111

Description:

External magnetic mount Iridium antenna

Features:

1616 – 1626.5 MHz

Designed to work in conjunction with a 30*30cm Ground plane

Connector: SMA(M) ST

Cable: 1.2m RG-174

Custom cables and connectors available

Iridium has certified the IAA.01.121111 antenna for commercial use in connection with the Iridium Communications System

RoHS & REACH Compliant

1. Introduction	3
2. Specifications	4
3. Antenna Characteristics	5
4. 2D Radiation Patterns	8
5. 3D Radiation Patterns	10
6. Mechanical Drawing	11
7. Packaging	12
Changelog	13

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



1. Introduction



The IAA.01 is a high-performance magnetic mount antenna which is designed specific to communicate efficiently with the Iridium[®] Satellite Communication system. The IAA.01 has been specifically designed to work on a 30*30cm ground plane.

The IAA.01 utilises the Taoglas expertise in ceramics by incorporating a ceramic patch tuned specifically for the antenna environment, giving greater stability. The antenna housing is strong, corrosive proof and waterproof to IP67. The magnetic mount allows for easy installation and removal between vehicles or assets, it is easily converted to an adhesive type for greater flexibility.

Iridium[®] has certified the IAA.01.121111 Antenna for commercial use in connection with the Iridium Communications System. Iridium Satellite LLC is the owner of “Iridium” and all other Iridium trademarks, service marks and logos contained herein.


The cable and connector are fully customizable, for more information contact your regional Taoglas Customer Support Team.

2. Specifications


Electrical	
Frequency Range (MHz)	1616-1626.5MHz
Centre Frequency	1621MHz
Peak Gain (dBi)	
With Ground plane(30x30cm)	3.7
Average Gain (dB)	
With Ground plane(30x30cm)	-2.1
Efficiency (%)	
With Ground plane(30x30cm)	62
Impedance	50Ω
VSWR	1.2
Polarization	RHCP
Bandwidth	31.5kHz
Mechanical	
Dimensions	40.5 x 38 x 12.3mm
Cable	1.2m of RG-174
Casing	ABS
Connector	SMA Male Straight
Ground Plane Size	30 x 30cm
Environmental	
Operation Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Relative Humidity	40% to 95% RH
Termination	Ag (Environmentally Friendly PB Free)

3. Antenna Characteristics


3.1 Return Loss




3.2 Efficiency




3.3 Average Gain



3.4 Peak Gain




3.5 VSWR




4. 2D Radiation Patterns


4.1 Test Setup on a 30*30 Ground Plane




XY Plane



ZX Plane




ZY Plane




5. 3D Radiation Patterns

5.1 Mounted on 30cm x 30cm metal ground plane





6. Mechanical Drawing (Units: mm)




7. Packaging



100pcs IAA.01.121111 per Carton
 Dimensions - 370*370*300mm
 Weight - 105g



Upper Layer: 46 Pieces



Lower Layer: 54 Pieces



Changelog for the datasheet

SPE-13-8-009 – IAA.01.12111

Revision: E (current version)

Date:	2020-02-07
Changes:	New Test Data
Changes Made by:	Jack Conroy

Previous Revisions

Revision: D

Date:	2019-05-02
Changes:	New Test Data
Changes Made by:	Jack Conroy

Revision: C

Date:	2019-02-19
Changes:	Updated the drawing
Changes Made by:	Jack Conroy

Revision: B

Date:	2014-02-27
Changes:	Iridium Certification
Changes Made by:	Aine Doyle

Revision: A (Original Release)

Date:	2013-01-25
Changes:	
Changes Made by:	Aine Doyle



www.taoglas.com



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View IAA.01.121111](#) on WIN SOURCE

 [Taoglas Limited](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management