



## Isobar 12-Outlet Network Server Surge Protector, 15 ft. (4.57 m) Cord, 3840 Joules, Diagnostic LEDs, 1U Rackmount

MODEL NUMBER: ISOBAR12ULTRA



Rack-mount protection for A/V components, network hardware, retail displays, appliances, power tools and other expensive electronics against dangerous surges, spikes and line noise in home, office and industrial environments.

### Features

#### Network-Grade 3840-Joule Surge Protection for Home or Office Electronics

- Protects rack-mounted network hardware, retail displays, appliances, power tools and other expensive electronics against even the strongest surges and spikes
- Recommended for network workstations, telecom systems, point-of-sale equipment and audio/video systems requiring AC line protection
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Exceeds IEEE 587 Category A and B surge suppression specifications

#### 12 Outlets Accept Wide Range of Electronic Devices

- 12 NEMA 5-15R AC outlets accept most computer, networking and telecom equipment
- 2 outlets located in front of unit and 10 outlets in rear

#### Isolated Filter Banks Provide Extra Protection

- Outlets arranged in 2 exclusive isolated filter banks to limit noise interaction among connected equipment
- Blocks disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Black outlets provide basic protection for less sensitive equipment
- White outlets provide highest level of protection (up to 80 dB) for more sensitive equipment

#### Premium Safety Features

- Lighted on/off switch with locking cover provides one-touch control over connected equipment
- Integrated 15A circuit breaker shuts down outlets in case of power overload
- Diagnostic LEDs confirm power, protection and line fault status at a glance

### Highlights

- 12 NEMA 5-15R outlets in exclusive isolated filter banks
- Network-grade 3840-joule surge protection rating
- Durable metal housing designed for tough environments
- 15A resettable circuit breaker prevents dangerous overloads
- 15-ft. (4.57 m) AC power cord with NEMA 5-15P plug

### Package Includes

- ISOBAR12ULTRA Isobar 12-Outlet Surge Protector, 1U Rack-Mount
- Rack-mounting brackets
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

- Conforms to current UL 1449 3rd Edition safety standards

**Flexible Mounting Options**

- Mounts into 1U of space in EIA-standard 19 in. racks
- Included mounting hardware also allows installation on wall or under counter
- Long 15-ft. (4.6 m) AC power cord with NEMA 5-15P reaches distant outlets
- All-metal housing designed for long life

**Backed by Ultimate Lifetime Insurance**

- \$25,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications

| OVERVIEW                           |                 |
|------------------------------------|-----------------|
| UPC Code                           | 037332011039    |
| INPUT                              |                 |
| Nominal Input Voltage(s) Supported | 120V AC         |
| Recommended Electrical Service     | 120V (110-125V) |
| Input Cord Gauge (AWG)             | 14              |
| Voltage Compatibility (VAC)        | 120             |
| Maximum Surge Amps                 | 150000          |
| Input Plug Type                    | NEMA 5-15P      |
| Input Cord Details                 | SJT             |
| Input Cord Length (ft.)            | 15              |
| Right-Angle Plug                   | No              |
| Input Cord Length (m)              | 4.57            |
| Integrated Cord Clip               | No              |
| OUTPUT                             |                 |
| Frequency Compatibility            | 50 / 60 Hz      |
| Output (Watts)                     | 1800            |
| Output Receptacles                 | (12) 5-15R      |
| Circuit Breaker (amps)             | 15              |
| Right-Angle Outlets                | No              |
| USER INTERFACE, ALERTS & CONTROLS  |                 |
| Diagnostic LED(s)                  | Yes             |



Powering Business Worldwide

TRIPP LITE  
SERIES

|  |   |
|--|---|
| Switches                               | Red illuminated power switch controls power to all outlets  |
| Diagnostic LED Details                 | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)  |
| Locking Switch Cover                   | Transparent locking switch cover prevents accidental shutoff  |
| <b>SURGE / NOISE SUPPRESSION</b>       |   |
| AC Suppression Joule Rating            | 3840  |
| AC Suppression Response Time           | NM = 0 ns. CM = <1 ns   |
| Protection Modes                       | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression  |
| AC Suppression Surge Current Rating    | 96,000 amps   |
| AC Suppression Components Used         | Metal oxide varistors, toroidal balanced chokes and VHF capacitors  |
| Safe Thermal Fusing                    | Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences   |
| UL1449 Let Through Rating              | 330V  |
| EMI / RFI Filtering                    | 40-80 dB  |
| Isolated Filter Banks                  | Yes   |
| Immunity                               | Conforms to IEE 587 / ANSI C62.41   |
| Automatic Shut-Off                     | No  |
| <b>DATALINE SURGE SUPPRESSION</b>      |   |
| Cable (Coax) Protection                | No  |
| Network (Ethernet) Protection          | No  |
| Telephone/DSL Protection               | No  |
| <b>PHYSICAL</b>                        |   |
| Material of Construction               | Metal   |
| Power Cord Color                       | Black   |
| Form Factors Supported                 | 1U rackmount, 0U vertical rackmount, wallmount and under-counter mounting supported - detachable flanges can be re-configured to support a variety of additional mounting options |
| Housing Color                          | Black   |
| Mounting Holes or Slots                | No  |
| Outlets Measurement (Center to Center) | Distance between front outlets = 38.9mm; Distance between rear outlets = 38.9mm   |
| Receptacle Color                       | Black   |
| Shipping Dimensions (hwd / in.)        | 9.30 x 2.60 x 20.40   |
| Shipping Dimensions (hwd / cm)         | 23.62 x 6.60 x 51.82  |
| Shipping Weight (lbs.)                 | 6.00  |
| Shipping Weight (kg)                   | 2.72  |
| Unit Dimensions (hwd / in.)            | 1.750 x 17.500 x 4.000  |
| Unit Dimensions (hwd / cm)             | 4.45 x 44.45 x 10.16  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|  |   |
|--|---|
| Unit Weight (lbs.)   | 4.6   |
| Unit Weight (kg)   | 2.09  |
| Mounting Details   | Includes flanges  |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |   |
| Rotatable Outlets  | No  |
| Antimicrobial  | No  |
| Mounting Accessory Included                                | Yes   |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |   |
| Product Certifications                                     | CAN/CSA-C22.2 No. 369.3:2017 (2nd Ed.); UL 1449 5th Ed. Rev: 2021   |
| Product Compliance   | RoHS  |
| <b>WARRANTY &amp; SUPPORT</b>                              |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 & <a href="https://tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View ISOBAR12 ULTRA on WIN SOURCE](#)

 [Tripp Lite Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management