THE DATASHEET OF

AC3MJ

Amphenol
Australia











ENTERTAINMENT@AMPHENOL
TRUSTED GLOBALLY

ENTERTAINMENT INTERCONNECT CATALOGUE

Amphenol Australia Pty Ltd



Amphenol Australia Pty. Ltd.


Amphenol Australia's head office is based in Melbourne, Victoria and is the Sales, Marketing and Engineering centre of excellence for an extensive range of professional connector and cabling products.

Amphenol's global presence allows us to take full advantage of our numerous corporate resources and product portfolio to provide you with a vast offering and choice. Our extensive range is designed to meet the specific needs of the entertainment markets to make the selection of your interconnect partner an easy choice.

The company has been producing products for the pro-audio industry for over fifty years. Since the development of our XLR AC Series connectors, we have continued to provide our customers with exacting quality in an increasingly competitive environment.

Continuous improvement through ISO9001, a focus on environmental awareness and development of next generation industry leading products is our philosophy. As the entertainment industry moves into the future the emerging technologies from other industries has become more prevalent and more challenging. Amphenol Australia's global presence combined with its close technical relationships with other Amphenol sister divisions, each a specialist and leader in their own interconnect field, places it well to support innovation and meet this challenge head on.

The ability of Amphenol to provide a full range of design services required to support the customers applications design and modelling, applications engineering, fabrication, value-added assembly and testing, coupled with the largest interconnect offering on the market means that we can support all of your system level needs.



XLR Connectors

AX Series XLR Cable Connectors ---- 4
AC Series XLR Cable Connectors ---- 11
AC/AX Series XLR Metal Chassis Mount Connectors ---- 18
XLR IP65 Connectors ---- 30
XLRnet IP65 Range ---- 36
AC Series XLR PCB Chassis Mount Connectors ---- 43
AC Series Dual 1/4" (6.35mm) / XLR Chassis Mount ---- 57
G-Type Miniature XLR Connectors ---- 66



Plugs & Jacks

T Series Plugs ---- 112
T Series (Jumbo) Plugs ---- 114
T-Series SwitchPlug ---- 116
Q Series Plugs ---- 118
Musician Series II Plugs ---- 121
1/4" / 3.5mm Phone Jack Connectors ---- 126
K Series Plugs (3.5mm) ---- 136



Data Connectors

Amphe-Dante Adapters ---- 90
XLRnet Series Cable Connector ---- 94
XLRnet Series A & B Type Chassis Receptacles ---- 97
XLRnet Series D Type Chassis Receptacles ---- 103
USB/HDMI Series ---- 108



Speaker Connectors

SP Series ---- 71
EP Series ---- 80
AP Series ---- 82




Power Connectors

HP Series ---- 85
HPT Series ---- 87




Plugs & Sockets

RCA Series ---- 140



Multipin Connectors

MP-41 Series ---- 144
MP-62/65 Series ---- 149



Miscellaneous

Accessories ---- 152
Connector Wiring Information ---- 156
Index ---- 158
Product Safety Information ---- 162

XLR Connectors

AX Series XLR Cable Connectors



AX SERIES XLR CABLE CONNECTORS

The revolutionary AX series of XLR connectors introduce an exciting contemporary look and feel to the professional audio interconnect market. They are designed to complement modern audio architecture and truly “fit” within their environment. An impressive list of features guarantees pure sound performance in the most demanding applications providing unrivalled value.

Features

- Unique Australian designed shell and housing.
- One piece ground / latch spring design incorporating twin wipe contacts for a direct connection path from mating shell to ground providing enhanced connection and EMI performance.
- Ergonomic sleeve design for improved grip.
- Channel I.D capability with coloured sleeves.
- Oversized ergonomic latch for quick and easy mating.
- Leading first mate last break pin 1 on socket connectors.
- Chuck style cable clamp to suit 3mm - 8mm (0.118” - 0.314”) cable O.D. with integrated split to allow inclusion after soldering.
- Concealed latching point for improved aesthetics, sealing and strength.
- Overmolded boot with flex bend relief for improved aesthetics, cable protection and boot retention.
- Concentric socket contact design provides optimal contact resistance
- Precision machined pin contacts as standard.
- Compact solder buckets to reduce termination time and material wastage during the soldering process.
- Zinc diecast shell housing for robustness and wear with Satin nickel or Black finish.
- Available in 3,4 and 5 contact arrangements.

Options

- Coloured I.D sleeves.
- Satin nickel or Black shell finish.
- Single or Bulk packaging.
- Gold plated contacts.

Ordering Codes

We have listed the more common ordering codes in each section. For further options please refer to the part number breakdown charts. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.

XLR Connectors

AX Series XLR Cable Connectors



Features:

- Unique Australian designed shell and housing.
- Ergonomic stylish sleeve design for improved grip.
- Oversized latch lever preserves your thumb.
- Leading first mate last break pin 1 on socket connectors.
- Chuck style cable clamp to suit 3mm - 8mm (0.118" - 0.314") cable O.D. with integrated split to allow inclusion after soldering.
- Overmolded cable support boot.
- New socket contact design for improved contact resistance.
- Precision machined pin contacts as standard.
- Compact solder buckets to reduce soldering time and wastage.
- Zinc diecast shell housing with Satin nickel or Matt black finish.
- Available in 3,4 and 5 contact arrangements.





Options:

- Coloured I.D sleeves.
- Satin nickel or Matt black shell finish.
- Single or Bulk packaging.

Part Number Breakdown: Page 7

Specifications: Page 10









Assembly Instructions: Page 8 & 9

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male Machined contacts Nickel Finish	Standard	AX3M
			Bulk Pack	AX3M BULK
		XLR 3 pole male Machined contacts Black Finish	Standard	AX3MB
			Gold Plated Contacts	AX3MB-AU
			Bulk Pack	AX3MB BULK
		XLR 3 pole female Stamped contacts Nickel Finish	Standard	AXX3F
			Bulk Pack	AXX3F BULK
		XLR 3 pole female Stamped contacts Nickel Finish	Standard	AXX3FB
			Gold Plated Contacts	AXX3FB-AU
			Bulk Pack	AXX3FB BULK

*PI538 is available for download at www.amphenolaudio.com

XLR Connectors


AX Series XLR Cable Connectors

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 4 pole male Machined contacts Nickel Finish	Standard	AX4M
			Bulk Pack	AX4M BULK
		XLR 4 pole male Machined contacts Black Finish	Standard	AX4MB
			Gold Plated Contacts	AX4MB-AU
			Bulk Pack	AX4MB BULK
		XLR 4 pole female Machined contacts Nickel Finish	Standard	AX4F
			Bulk Pack	AX4F BULK
		XLR 4 pole female Machined contacts Black Finish	Standard	AX4FB
			Gold Plated Contacts	AX4FB-AU
			Bulk Pack	AX4FB BULK
		XLR 5 pole male Machined contacts Nickel Finish	Standard	AX5M
			Bulk Pack	AX5M BULK
		XLR 5 pole male Machined contacts Black Finish	Standard	AX5MB
			Gold Plated Contacts	AX5MB-AU
			Bulk Pack	AX5MB BULK
		XLR 5 pole female Machined contacts Nickel Finish	Standard	AX5F
			Bulk Pack	AX5F BULK
		XLR 5 pole female Machined contacts Black Finish	Standard	AX5FB
			Gold Plated Contacts	AX5FB-AU
			Bulk Pack	AX5FB BULK

PART NUMBER BREAKDOWN

METAL SHELL TYPE - SOLDER

E. G . **AX3MB2M-AU BULK**
AX (Series Prefix), **3** contacts, **M**ale, **B**lack Finish,
2 (Red Sleeve) **M** (Sleeve Marking) - **AU** (Gold Plated Contacts), **Bulk** Packaged.




SERIES PREFIX	AX	=	Series Prefix
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
SHELL FINISH	Blank	=	Nickel Plated Finish
	B	=	Black Finish
SLEEVE COLOUR OPTION	Blank	=	Black
	1	=	Brown
	2	=	Red
	3	=	Orange
	4	=	Yellow
	5	=	Green
	6	=	Blue
	7	=	Violet
	8	=	Grey
	9	=	White
SLEEVE MARKING	Blank	=	Standard Sleeve
	0M	=	Marking Sleeve (Black)
	M	=	Marking Sleeve (Colour)
CONTACT PLATING	Blank	=	Standard Plating (Silver or Tin) (Refer to Standard Data)
	AU	=	Gold Plated
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

PI539 ASSEMBLY INSTRUCTIONS

AX SERIES FEMALE XLR CABLE CONNECTOR



Slide the nut (Backshell) onto the cable



Strip the cable




Push back the insert only enough to expose the solder buckets. It is not necessary to remove the insert. Solder the wires to the contacts.




Install the cable clamp, flush to the insert making sure to align the top slot with the spring. Then push the insert & cable clamp together into the shell.



Thread the nut (Backshell) onto the shell (Torque 0.8Nm - 1.2Nm) to activate the cable clamp and close the connector assembly.



Close the cable clamp slightly and push the boot over the clamp ensuring the wires fit inside the boot.



Final assembly can be achieved either by manually screwing the boot on, or by using an Amphenol Australia T2860 termination tool.


Rev 1 - 03/2009

PI538 ASSEMBLY INSTRUCTIONS

AX SERIES MALE XLR CABLE CONNECTOR



Slide the nut (Backshell) onto the cable



Strip the cable



Solder the wires to the contacts.



Install the cable clamp flush to the insert making sure to align the slot with the ground contact.






Align the key of the insert with the keyway on the shell then push the pin insert & cable clamp together in the shell.



Thread the nut (Backshell) onto the shell (Torque 0.8Nm - 1.2Nm) to activate the cable clamp and close the connector assembly.

Rev 1 - 03/2009

STANDARD DATA AX SERIES CABLE CONNECTORS

		VALUE		
GENERAL CHARACTERISTICS	Number of contacts	3	4	5
	AX Series Contact Arrangements (Front view of pin inserts)			
	Termination	SOLDER		
	Max. Wire Gauge - Stranded wire: Solder	14AWG	16AWG	18AWG
	Flammability rating of insulator plastics and housings	UL94V-0		
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU		
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	133V [1]		
	Test Voltage AC RMS	1400V		
	Current carrying capacity: Solder	15A	10A	7.5A
	Typicial Contact Resistance	≤3m Ω		
	Insulation Resistance	≥1G Ω		
CLIMATIC CHARACTERISTICS	Protection Class	IP40		
	Operating Temperature	-25˚C to +75˚C (-13°F to -167°F)		
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal force	≥10N - ≤30N		
	Weight [2]	31g (0.068lb)	33g (0.073lb)	33g (0.073lb)
	Typical Cable retention force	22Kg to 44Kg (50lb to 100lb) - Dependent on cable material and diameter.		
	Cable O.D. range	3mm to 8mm (0.118" to 0.314")		
	Mechanical Operations	1000 mating cycles		
MATERIALS	Connector shell - Metal Shell finish	Diecast Zinc Alloy Satin nickel or Black		
	Insulators	UL94V-0 PA66, 30% Glass Filled		
	Boot / Backshell Finish	UL94V-0 Noryl N190 / Santoprene Black, other colours available - see page 80		
	Cable clamp	Noryl N190		
	Sleeve	Noryl N190		
	Male Contact Machined - Solder / Plating	Brass / Silver or Gold (Optional)		
	Female Contact Stamped - Solder / Plating	Phosphor Bronze / Tin or Gold (Optional)		

[1] Not suitable for domestic applications above 50V

[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.

Rev 3 - 03/2013



AC SERIES XLR CABLE CONNECTORS

Amphenol Australia have been manufacturing and designing innovative XLR connectors since 1955 The AC series cable connector range complies with IEC268-12 and AES 14-1992 standards.
CSA File Number 68598.

Features

- AC series XLR connectors feature the unique Australian design and patented “Jaws” cable retention system
- A leading first mate last break socket contact is standard on all female connectors (Pin 1).
- The “Jaws” cable retention system provides up to 44kg (100lb) of strain.
- The AC series connector can be quickly and easily assembled without screws – by hand or portable termination tool. (Part number T2860)
- Available in 3, 4, 5, 6A and 7 contact arrangements.
- Compatible with all major XLR brands.

Options

- Solder Bucket termination
- Thermoplastic shell
- Zinc Diecast shell - Satin Nickel Finish
- Zinc Diecast shell - Black Polyester Finish
- Gold, Silver or Tin Plated contacts
- Bulk Style Packaging
- Single Bag packs
- Precision machined contacts
- Cost effective stamped contacts on 3 pole
- Standard Jaws cable clamp, Cable O.D 3mm to 6.5mm (0.118” to 0.255”)
- Large Jaws cable clamp, Cable O.D 6.5mm to 8mm (0.255” to 0.314”)
- Metal Boots / Backshells
- Coloured Boots / Backshells
- Coloured Identification rings
- Termination / Assembly tooling

Jaws Cable Clamp Options



Standard Jaws cable clamp (Black), Cable O.D 3mm to 6.5mm (0.118” to 0.255”)



Large Jaws cable clamp (Purple), Cable O.D 6.5mm to 8mm (0.255” to 0.314”)

Ordering Codes

We have listed the more common ordering codes in each section. For further options please refer to the part number breakdown charts. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.

XLR Connectors

AC Series XLR Cable Connectors









Features:









- Zinc Diecast Shell.
- Solder Bucket connections.
- "Jaws" Cable Retention System.
- Contact layouts in 3, 4, 5, 6A and 7.
- Precision machined or Stamped contacts.
- Leading first mate last break socket contact.
- Quick and easy assembly without screws – by hand or portable termination tool. (Part number T2860.)

Options: Stamped Contacts (3 contact only), Gold plated contacts, Large or Small Jaws Cable Clamp, Black Finish Shell, Bulk Pack, Coloured Boots / Backshells

Part Number Breakdown: Page 15









Specifications: Page 17

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC3MM
			Bulk Pack	AC3MM BULK
		XLR 3 pole male, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC3MMB
			Gold Plated Contacts	AC3MMB-AU
			Bulk Pack	AC3MMB BULK
		XLR 3 pole male, Stamped contacts, Nickel Finish, Jaws cable clamp	Standard	AC3M
			Large Cable Clamp	AC3MJ
			Bulk Pack	AC3M BULK
		XLR 3 pole male, Stamped contacts, Black Finish, Jaws cable clamp	Standard	AC3MB
			Gold Plated Contacts	AC3MB-AU
			Large Cable Clamp	AC3MBJ
			Bulk Pack	AC3MB BULK
		XLR 3 pole female, Stamped contacts, Nickel Finish, Jaws cable clamp	Standard	AC3F
			Large Cable Clamp	AC3FJ
			Bulk Pack	AC3F BULK
		XLR 3 pole female, Stamped contacts, Black Finish, Jaws cable clamp	Standard	AC3FB
			Gold Plated Contacts	AC3FB-AU
			Large Cable Clamp	AC3FBJ
			Bulk Pack	AC3FB BULK

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 4 pole male, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC4M
			Large Cable Clamp	AC4MJ
			Bulk Pack	AC4M BULK
		XLR 4 pole male, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC4MB
			Gold Plated Contacts	AC4MB-AU
			Large Cable Clamp	AC4MBJ
			Bulk Pack	AC4MB BULK
		XLR 4 pole female, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC4F
			Large Cable Clamp	AC4FJ
			Bulk Pack	AC4F BULK
		XLR 4 pole female, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC4FB
			Gold Plated Contacts	AC4FB-AU
			Large Cable Clamp	AC4FBJ
			Bulk Pack	AC4FB BULK
		XLR 5 pole male, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC5M
			Large Cable Clamp	AC5MJ
			Bulk Pack	AC5M BULK
		XLR 5 pole male, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC5MB
			Gold Plated Contacts	AC5MB-AU
			Large Cable Clamp	AC5MBJ
			Bulk Pack	AC5MB BULK
		XLR 5 pole female, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC5F
			Large Cable Clamp	AC5FJ
			Bulk Pack	AC5F BULK
		XLR 5 pole female, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC5FB
			Gold Plated Contacts	AC5FB-AU
			Large Cable Clamp	AC5FBJ
			Bulk Pack	AC5FB BULK

XLR Connectors


AC Series XLR Cable Connectors

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 6A pole male, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC6AM
			Large Cable Clamp	AC6AMJ
			Bulk Pack	AC6AM BULK
		XLR 6A pole male, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC6AMB
			Gold Plated Contacts	AC6AMB-AU
			Large Cable Clamp	AC6AMBJ
			Bulk Pack	AC6AMB BULK
		XLR 6A pole female, Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC6AF
			Large Cable Clamp	AC6AFJ
			Bulk Pack	AC6AF BULK
		XLR 6A pole female, Machined contacts, Black Finish, Jaws cable clamp	Standard	AC6AFB
			Gold Plated Contacts	AC6AFB-AU
			Large Cable Clamp	AC6AFBJ
			Bulk Pack	AC6AFB BULK
		XLR 7 pole male, Gold plated Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC7M
			Large Cable Clamp	AC7MJ
			Bulk Pack	AC7M BULK
		XLR 7 pole male, Gold plated Machined contacts, Black Finish, Jaws cable clamp	Standard	AC7MB
			Large Cable Clamp	AC7MBJ
			Bulk Pack	AC7MB BULK
		XLR 7 pole female, Gold plated Machined contacts, Nickel Finish, Jaws cable clamp	Standard	AC7F
			Large Cable Clamp	AC7FJ
			Bulk Pack	AC7F BULK
		XLR 7 pole female, Gold plated Machined contacts, Black Finish, Jaws cable clamp	Standard	AC7FB
			Large Cable Clamp	AC7FBJ
			Bulk Pack	AC7FB BULK

PART NUMBER BREAKDOWN

METAL SHELL TYPE - SOLDER

E. G . **AC3MMBJ-AU BULK**
AC (Series Prefix), **3** contacts, **M**ale, **M**achined Contacts, **B**lack Polyester Finish, **J** (Large Jaws),- **AU** (Gold Plated Contacts), **Bulk** Packaged.



SERIES PREFIX	AC	=	Series Prefix
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
	6A	=	6 Contacts
	7	=	7 Contacts
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
CONTACT[1]	Blank	=	Stamped Contacts
	M	=	Machined Contacts
	G	=	Stamped Contacts, Ground Tag
	MG	=	Machined Contacts, Ground Tag (Applicable 3 male pin contacts, option M & MG only)
SHELL FINISH[2]	Blank	=	Nickel Plated Finish
	B	=	Black Polyester Finish
CABLE CLAMP	Blank	=	Standard Jaws 3mm - 6.5mm cable O.D. (0.118" to 0.255")
	J	=	Large Jaws 6.5mm - 8mm cable O.D. (0.255" to 0.314")
CONTACT PLATING[3]	Blank	=	Standard Plating (Silver or Tin) (Refer to Standard Data)
	AU	=	Gold Plated
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

Note:

[1] 4 - 7 contact connectors have machined contacts and grounding as standard.

[2] Ground contacts are not supplied with the black polyester finish shell option.

[3] 7 Contact is gold plated as standard.

[4] All AC Series Connectors are available with optional colour coded boot / backshell. Refer to page 156 and simply add colour to end of part number. Example: AC3MM - RED

XLR Connectors

AC Series XLR Cable Connectors






Features:

- Thermoplastic Shell.
- Solder Bucket Connections.
- "Jaws" Cable Retention System.
- Stamped or Machined Contacts.
- Leading first mate last break socket contact.
- Quick and easy assembly without screws – by hand or portable termination tool. (Part number T2860.)






Options: Gold Plated Contacts, Stamped Contacts (3 Contact only), Bulk Pack, Coloured Boots / Backshells
3, 4, 5, 6A and 7 Contacts.

Specifications: Page 17

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male, Machined contacts, Thermoplastic shell, Jaws cable clamp	Standard	AC3MMCP
			Bulk Pack	AC3MMCP BULK
		XLR 3 pole male, Stamped contacts, Thermoplastic shell, Jaws cable clamp	Standard	AC3MCP
			Bulk Pack	AC3MCP BULK
		XLR 3 pole female, Stamped contacts, Thermoplastic shell, Jaws cable clamp	Standard	AC3FCP
			Bulk Pack	AC3FCP BULK

Note: Thermoplastic shell connectors are also available in 4 - 7 contact arrangements, please contact us for ordering code.

STANDARD DATA AC CABLE CONNECTORS


			VALUE				
GENERAL CHARACTERISTICS	Number of contacts		3	4	5	6A	7
	AC Series Contact Arrangements (Front view of pin inserts)						
	Termination		SOLDER				
	Max. Wire Gauge - Stranded wire: Solder		14AWG	16AWG	18AWG		20AWG
	Flammability rating (insulator plastics & housings)		UL94V-0				
	Environmental		Complies with EU RoHS 2 Directive 2011/65/EU				
ELECTRICAL CHARACTERISTICS	Service Voltage RMS		133V [1]				
	Test Voltage AC RMS		1400V				
	Current carrying capacity: Solder		15A	10A	7.5A		5A
	Typical Contact Resistance		≤3mΩ				
	Insulation Resistance		≥1GΩ				
CLIMATIC CHARACTERISTICS	Protection Class		IP40				
	Operating Temperature		-25˚C to +75˚C (-13°F to +167°F)				
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal force		≥10N - ≤30N				
	Weight - Metal [2]		36g (0.080lb)	37g (0.081lb)	38g (0.083lb)		
	Weight - Thermoplastic [2]		18g (0.039lb)	19g (0.041lb)	20g (0.044lb)		
	Typical Cable retention force		22Kg to 44Kg (50lb to 100lb) - Dependent on cable material and diameter.				
	Cable O.D. range - JAWS clamp	Standard Large	3mm to 6.5mm (0.118” to 0.255”) 6.5mm to 8mm (0.255” to 0.314”)				
	Mechanical Operations		1000 mating cycles				
MATERIALS	Connector shell - Metal Shell finish		Diecast Zinc Alloy Satin nickel or Black polyester				
	Connector shell - Thermoplastic Shell finish		Thermoplastic, UL94V-0 Modified PPE Resin Black				
	Insulators		UL94V-0 PBT Resin or Modified PPE Resin				
	Boot / Backshell Finish		UL94V-0 Modified PPE Resin or Machined Brass Black, other colours available - see page 156				
	Cable clamp (JAWS)	Standard Solder Large Solder	UL94V-0 Modified PPO Resin (Black) UL94V-0 Modified PPO Resin (Purple)				
	Cable Bushing		Santoprene				
	Male Contact (Solder / Plating)	Stamped Machined	Phosphor Bronze / Silver or Gold (Optional) Brass / Silver or Gold (Optional)				
	Female Contact (Solder / Plating)	Stamped Machined	Phosphor Bronze / Tin or Gold (Optional) Brass / Silver or Gold (Optional)				

[1] Not suitable for domestic applications above 50V
[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.

Rev 6 - 03/2015

XLR Connectors

AC/AX Series XLR Metal Chassis Mount Connectors



AC/AX SERIES XLR METAL CHASSIS MOUNT CONNECTORS

The metal chassis mount connectors are designed for the audio user where durability, reliability and strength across a wide range of applications are important. All products are manufactured to the highest quality standards and will withstand the harshest environments. This range complies with IEC268-12 and AES 14-1992 standards. CSA File Number 68598

Features

- The “D” size housing can be either front or rear mounted using the same panel cutout.
- The “P” size housing is the original wide flange front mounting XLR connector. “PN” is the original narrow flange front mounting male connector.
- A leading first mate last break socket contact is standard on all female connectors (Pin 1).
- Solder cup or Vertical PCB versions.
- Connectors are fitted with a grounding system for RFI shielding applications.
- Available in 3, 4, 5, 6A and 7 contact arrangements.
- Compatible with all other XLR brands.

Options

- Solder Bucket termination
- Vertical PCB contacts
- Zinc Diecast Shell - Satin Nickel Finish
- Zinc Diecast Shell - Black Polyester Finish
- Gold, Silver or Tin Plated Contacts
- Bulk Packaging
- Single Bag packs
- Precision machined contacts
- Cost effective stamped contacts on 3 pole
- Latchless versions (Non-Latching) (Female only)

Note: A ground tag is standard on all AC “Z” series connectors. Although the ground tag is intended for RFI shielding applications, Amphenol cannot guarantee its effectiveness in all cases.
The non-conductive Black polyester finish insulates the ground tag from the shell and should not be used in applications requiring ground contact to the shell.

Ordering Codes

We have listed the more common ordering codes in each section. For further options please refer to the part number breakdown charts. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.
2) Each product group cover page then details information and options available.
3) Refer to the product detail pages and identify the product you require pictorially.
4) Read the product description column for the products standard features.
5) Use variations column to determine your choice.
6) Identify part number.
7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.
8) Please contact us directly if you have any further problems.





Features:

- Zinc Diecast Shell.
- D size housing can be front or rear mounted using the same panel cutout.
- Solder Bucket connections.
- Vertical PCB mounting.
- Precision machined or Stamped contacts (3 pin only).
- Leading first mate last break socket contact.
- Positive latch lock system.
- M3 threaded holes (Optional).

Options: Stamped contacts (3 contact only), Gold plated contacts, Vertical PCB contacts, Black finish, Non-Latching (Female only), Bulk Pack.




Part Number Breakdown: Page 22




Specifications: Page 28

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NO.
		XLR 3 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AX3MD
			M3 Threaded Holes	AX3MD-M3
			Vertical PCB	AX3MDV
			M3 Threaded Holes	AX3MDV-M3
		XLR 3 pole male, D Flange, Machined contacts, Black Finish	Standard	AX3MDB
			M3 Threaded Holes	AX3MDB-M3
			Gold Plated Contacts	AX3MDB-AU
			Vertical PCB	AX3MDVB
			M3 Threaded Holes	AX3MDVB-M3
		XLR 3 pole female, D Flange, Stamped contacts, Nickel Finish	Standard	AX3FD
			M3 Threaded Holes	AX3FD-M3
		XLR 3 pole female, D Flange, Stamped contacts, Black Finish	Standard	AX3FDB
			M3 Threaded Holes	AX3FDB-M3
			Gold Plated Contacts	AX3FDB-AU

XLR Connectors

AC/AX Series XLR Metal Chassis Mount Connectors

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NO.
		XLR 4 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AX4MD
			M3 Threaded Holes	AX4MD-M3
			Vertical PCB	AX4MDV
			M3 Threaded Holes	AX4MDV-M3
		XLR 4 pole male, D Flange, Machined contacts, Black Finish	Standard	AX4MDB
			Gold Plated Contacts	AX4MDB-AU
			Vertical PCB	AX4MDVB
		XLR 4 pole female, D Flange, Machined contacts, Nickel Finish	Standard	AX4FD
			M3 Threaded Holes	AX4FD-M3
			Vertical PCB	AX4FDV
			M3 Threaded Holes	AX4FDV-M3
		XLR 4 pole female, D Flange, Machined contacts, Black Finish	Standard	AX4FDB
			Gold Plated Contacts	AX4FDB-AU
			Vertical PCB	AX4FDVB
		XLR 5 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AX5MD
			M3 Threaded Holes	AX5MD-M3
			Vertical PCB	AX5MDV
			M3 Threaded Holes	AX5MDV-M3
		XLR 5 pole male, D Flange, Machined contacts, Black Finish	Standard	AX5MDB
			Gold Plated Contacts	AX5MDB-AU
			Vertical PCB	AX5MDVB


PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NO.
		XLR 5 pole female, D Flange, Machined contacts, Nickel Finish	Standard	AX5FD
			M3 Threaded Holes	AX5FD-M3
			Vertical PCB	AX5FDV
			M3 Threaded Holes	AX5FDV-M3
		XLR 5 pole female, D Flange, Machined contacts, Black Finish	Standard	AX4FDB
			Gold Plated Contacts	AX4FDB-AU
			Vertical PCB	AX4FDVB
		XLR 6A pole male, D Flange, Machined contacts, Nickel Finish	Standard	AX6AMD
			M3 Threaded Holes	AX6AMD-M3
			Vertical PCB	AX6AMDV
			M3 Threaded Holes	AX6AMDV-M3
		XLR 6A pole male, D Flange, Machined contacts, Black Finish	Standard	AX6AMDB
			Gold Plated Contacts	AX6AMDB-AU
			Vertical PCB	AX6AMDVB
		XLR 6A pole female, D Flange, Machined contacts, Nickel Finish	Standard	AX6AFD
			M3 Threaded Holes	AX6AFD-M3
			Vertical PCB	AX6AFDV
			M3 Threaded Holes	AX6AFDV-M3
		XLR 6A pole female, D Flange, Machined contacts, Black Finish	Standard	AX6AFDB
			Gold Plated Contacts	AX6FADB-AU
			Vertical PCB	AX6AFDVB

PART NUMBER BREAKDOWN

METAL TYPE FLANGE

E. G . **AX3MDVB-AU-M3 BULK**
AX (Series Prefix), **3** contacts, **M**ale, **D** Small Flange, **V**ertical PCB Contact, **B**lack Polyester Finish, **- AU** (Gold Plated Contacts), **- M3** Mounted Holes, **BULK** Packaged.

SERIES PREFIX	AX	=	Series Prefix
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
	6A	=	6 Contacts
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
SHELL STYLE	D	=	Small Flange (front or rear mounting)
SHELL SERIES	Blank	=	Solder Bucket
	V	=	Vertical PCB Contact
SHELL FINISH[1]	Blank	=	Nickel Plated Finish
	B	=	Black Polyester Finish
CONTACT PLATING[2]	Blank	=	Standard Plating
	AU	=	Gold Plated
MOUNTING HOLES	Blank	=	Through Holes
	M3	=	M3 Threaded Holes
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed



Note:

[1] Ground contacts are not supplied with the black polyester finish shell option.

[3] Non-Latching Versions (Female) available - Please contact us for part number options.






Features:

- Zinc Diecast Shell.
- D size housing can be front or rear mounted using the same panel cutout.
- Solder Bucket connections.
- Precision machined or Stamped contacts (3 pin only).
- Leading first mate last break socket contact.
- Positive latch lock system.





Options: Stamped contacts (3 contact only), Gold plated contacts, Black finish, Non-Latching (Female only), Bulk Pack.





Part Number Breakdown: Page 27
Specifications: Page 28
PCB Footprints: Page 29
Panel Cutouts: Page 29

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AC3MMDZ
			Bulk Pack	AC3MMDZ BULK
		XLR 3 pole male, D Flange, Machined contacts, Black Finish	Standard	AC3MMDZB
			Gold Plated Contacts	AC3MMDZB-AU
		XLR 3 pole male, D Flange, Stamped contacts, Nickel Finish	Standard	AC3MDZ
			Bulk Pack	AC3MDZ BULK
		XLR 3 pole male, D Flange, Stamped contacts, Black Finish	Standard	AC3MDZB
			Gold Plated Contacts	AC3MDZB-AU
		XLR 3 pole female, D Flange, Stamped contacts, Nickel Finish	Standard	AC3FDZ
			Bulk Pack	AC3FDZ BULK
		XLR 3 pole female, D Flange, Stamped contacts, Black Finish	Standard	AC3FDZB
			Gold Plated Contacts	AC3FDZB-AU

XLR Connectors

AC/AX Series XLR Metal Chassis Mount Connectors

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 4 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AC4MDZ
			Bulk Pack	AC4MDZ BULK
		XLR 4 pole male, D Flange, Machined contacts, Black Finish	Standard	AC4MDZB
			Gold Plated Contacts	AC4MDZB-AU
		XLR 4 pole female, D Flange, Machined contacts, Nickel Finish	Standard	AC4FDZ
			Bulk Pack	AC4FDZ BULK
		XLR 4 pole female, D Flange, Machined contacts, Black Finish	Standard	AC4FDZB
			Gold Plated Contacts	AC4FDZB-AU
		XLR 5 pole male, D Flange, Machined contacts, Nickel Finish	Standard	AC5MDZ
			Bulk Pack	AC5MDZ BULK
		XLR 5 pole male, D Flange, Machined contacts, Black Finish	Standard	AC5MDZB
			Gold Plated Contacts	AC5MDZB-AU
		XLR 5 pole female, D Flange, Machined contacts, Nickel Finish	Standard	AC5FDZ
			Bulk Pack	AC5FDZ BULK
		XLR 5 pole female, D Flange, Machined contacts, Black Finish	Standard	AC5FDZB
			Gold Plated Contacts	AC5FDZB-AU

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
 		XLR 6A pole male, D Flange, Machined contacts, Nickel Finish	Standard	AC6AMDZ
			Bulk Pack	AC6AMDZ BULK
		XLR 6A pole male, D Flange, Machined contacts, Black Finish	Standard	AC6AMDZB
			Gold Plated Contacts	AC6AMDZB-AU
 		XLR 6A pole female, D Flange, Machined contacts, Nickel Finish	Standard	AC6AFDZ
			Bulk Pack	AC6AFDZ BULK
		XLR 6A pole female, D Flange, Machined contacts, Black Finish	Standard	AC6AFDZB
			Gold Plated Contacts	AC6AFDZB-AU
 		XLR 7 pole male, D Flange, Gold Plated Machined contacts, Nickel Finish	Standard	AC7MDZ
			Vertical PCB	AC7MDZV
			Bulk Pack	AC7MDZ BULK
		XLR 7 pole male, D Flange, Gold Plated Machined contacts, Black Finish	Standard	AC7MDZB
			Vertical PCB	AC7MDZVB
 		XLR 7 pole female, D Flange, Gold Plated Machined contacts, Nickel Finish	Standard	AC7FDZ
			Vertical PCB	AC7FDZV
			Bulk Pack	AC7FDZ BULK
		XLR 7 pole female, D Flange, Gold Plated Machined contacts, Black Finish	Standard	AC7FDZB
			Vertical PCB	AC7FDZVB

XLR Connectors

AC/AX Series XLR Metal Chassis Mount Connectors








Features:

- Zinc Diecast shell.
- The P size housing is the original wide flange front mounting XLR connector. PN is the original narrow, front mounting male connector.
- Solder Bucket connections.
- Precision Machined or Stamped contacts (3 pin only).
- Leading first mate last break socket contact.
- Positive latch lock system.

Options: Stamped contacts (3 contact only), Gold plated contacts, Black Finish, Non-Latching (Female only), Bulk Pack.

Part Number Breakdown: Page 22 **Specifications: Page 28**
PCB Footprints: Page 29 **Panel Cutouts: Page 29**

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	POLES	PART NUMBER
		XLR male, Narrow flange, Machined contacts	3	AC3MMPNZ
		XLR male, Narrow flange, Stamped contacts,	3	AC3MPNZ
			4	AC4MPNZ
			5	AC5MPNZ
			6	AC6AMPNZ
			7	AC7MPNZ
		XLR male, Wide flange, Machined contacts	3	AC3MMP
		XLR male, Wide flange, Stamped contacts	3	AC3MP
			4	AC4MP
			5	AC5MP
			6	AC6AMP
			7	AC7MP
		XLR female, Wide flange, Stamped contacts	3	AC3FPZ
			4	AC4FPZ
			5	AC5FPZ
			6	AC6AFPZ
			7	AC7FPZ


*Black finish available on special request please contact factory.

PART NUMBER BREAKDOWN

METAL TYPE FLANGE

E. G . **AC3MMPNZVB-AU BULK**
AC (Series Prefix), **3** contacts, **M**ale, **M**achined Contacts, **PN** (Narrow Flange), **Z** (Metal Chassis Series), **B**lack Polyester Finish, - **AU** (Gold Plated Contacts), **Bulk** Packaged.

SERIES PREFIX	AC	=	Series Prefix
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
	6A	=	6 Contacts
	7	=	7 Contacts
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
MACHINED CONTACTS[1]	Blank	=	Stamped Contacts
	M	=	Machined Contacts (Applicable 3 male pin contacts only)
SHELL STYLE	D	=	Small Flange (front or rear mounting)
	P	=	Large Shell with Wide Flange
	PN	=	Large Shell with Narrow Flange (male only)
SHELL SERIES	Blank	=	Male P Shell Style Only
	Z	=	Metal Chassis Series
SHELL FINISH[2]	Blank	=	Nickel Plated Finish
	B	=	Black Polyester Finish
CONTACT PLATING[3]	Blank	=	Standard Plating (Silver or Tin - refer to Standard Data)
	AU	=	Gold Plated
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed



Note:






[1] 4 - 7 contact connectors have machined contacts and grounding as standard. They are not available in stamped contacts.

[2] Ground contacts are not supplied with the black polyester finish shell option.

[3] 7 Contact is gold plated as standard.

[4] Non-Latching Versions (Female) available - Please contact us for part number options.

STANDARD DATA AC / AX SERIES CHASSIS - METAL "Z"

		VALUE				
GENERAL CHARACTERISTICS	Number of contacts	3	4	5	6A	7
	Contact Arrangement (Front view of pin inserts)					
	Termination	Solder Bucket / Printed Circuit Board (PCB)				
	Max. Wire Gauge - Stranded wire: Solder Printed Circuit Board - PCB	 14AWG N/A	 16AWG N/A	 18AWG N/A	 18AWG N/A	 20AWG N/A
	Flammability rating of plastics	UL94V-0				
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU				
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	133V[1)]				
	Test Voltage AC RMS	1400V				
	Current carrying capacity: Solder Printed Circuit Board (PCB)	 15A 15A	 10A 10A	 7.5A 7.5A	 7.5A 7.5A	 5A 5A
	Typical Contact Resistance	≤3mΩ				
	Insulation Resistance	≥1000MΩ				
CLIMATIC CHARACTERISTICS	Protection Class	IP40				
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)				
MECHANICAL CHARACTERISTICS	Weight - Metal [2)]	31g (0.068lb)	32g (0.070lb)	33g (0.072lb)	33g (0.072lb)	33g (0.072lb)
	Mechanical Operations	1000 mating cycles				
MATERIALS	Connector Shell	Diecast Zinc Alloy				
	Shell Finish	Satin Nickel or Black Polyester				
	Insulators	PA66 30% Glass Filled Resin				
	Male Contact Stamped Solder and PCB-(Material/Plating) Machined Solder-(Material/Plating)	 Phosphor Bronze / Silver or Gold (optional) Brass / Silver or Gold (optional)				
	Female Contact Stamped Solder and PCB-(Material/Plating) Machined Solder-(Material/Plating)	 Phosphor Bronze / Tin or Gold (optional) Brass / Silver or Gold (Optional)				

Rev 4 - 02/2020


[1)] Not suitable for domestic applications above 50V

[2)] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.


AC / AX SERIES CHASSIS METAL "Z"

PCB FOOTPRINTS STRAIGHT (V) CONNECTOR SIDE OF PCB


○ ø1.2mm(.05") + Panel Cutout CL




AC3MM*ZV




AC4F*ZV




AC4M*ZV




AC5F*ZV




AC7M*ZV




AC5M*ZV




AC6AF*ZV




AC6AM*ZV




AC7F*ZV




AX3FD




AX3MD




AX4FD




AX4MD




AX5FD



AX5MD




AX6AFD




AX6AMD


PANEL CUTOUT DIMENSIONS FRONT VIEW




AC*FDZ / AX*FD




AC*MDZ / AX*MD



AC*FPZ



AC*MP



AC*MPNZ



XLR IP65 CONNECTORS




Features:






- IP65 Rated.
- Rear mounted thermoplastic shell housing aids in pre-assembly for PCB applications.
- Front mounted overmolded metal gasket sealing plate for superior panel sealing .
- Solder Bucket connections.
- Vertical or Horizontal PCB mounting.
- Available to suit three different panel thicknesses 1mm to 1.5mm, 1.5mm to 2mm, 2mm to 3mm
- Leading first mate last break socket contact.
- Positive latch lock system.
- Protective sealing cap .

Options:

3, 4 or 5 contacts, Gold plated contacts, Solder buckets, Vertical or Horizontal PCB contacts






Part Number Breakdown: Page 34
Specifications: Page 35






PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS3MP
			Panel 1.5mm to 2mm	AXS3MP1
			Panel 2mm to 3mm	AXS3MP2
		XLR 3 pole female chassis chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS3FP
			Panel 1.5mm to 2mm	AXS3FP1
			Panel 2mm to 3mm	AXS3FP2
		XLR 3 pole male chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS3MPH
			Panel 1.5mm to 2mm	AXS3MP1H
			Panel 2mm to 3mm	AXS3MP2H

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole female chassis chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS3FPH
			Panel 1.5mm to 2mm	AXS3FP1H
			Panel 2mm to 3mm	AXS3FP2H
		XLR 3 pole male chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS3MPV
			Panel 1.5mm to 2mm	AXS3MP1V
			Panel 2mm to 3mm	AXS3MP2V
		XLR 3 pole female chassis chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS3FPV
			Panel 1.5mm to 2mm	AXS3FP1V
			Panel 2mm to 3mm	AXS3FP2V
		XLR 4 pole male chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS4MP
			Panel 1.5mm to 2mm	AXS4MP1
			Panel 2mm to 3mm	AXS4MP2
		XLR 4 pole female chassis chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS4FP
			Panel 1.5mm to 2mm	AXS4FP1
			Panel 2mm to 3mm	AXS4FP2

XLR Connectors

XLR IP65 Connectors


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 4 pole male chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS4MPH
			Panel 1.5mm to 2mm	AXS4MP1H
			Panel 2mm to 3mm	AXS4MP2H
		XLR 4 pole female chassis chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS4FPH
			Panel 1.5mm to 2mm	AXS4FP1H
			Panel 2mm to 3mm	AXS4FP2H
		XLR 4 pole male chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS4MPV
			Panel 1.5mm to 2mm	AXS4MP1V
			Panel 2mm to 3mm	AXS4MP2V
		XLR 4 pole female chassis chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS4FPV
			Panel 1.5mm to 2mm	AXS4FP1V
			Panel 2mm to 3mm	AXS4FP2V
		XLR 5 pole male chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS5MP
			Panel 1.5mm to 2mm	AXS5MP1
			Panel 2mm to 3mm	AXS5MP2

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 5 pole female chassis chassis with protective cap , IP65, Solder bucket, Rear mount	Panel 1.0mm to 1.5mm	AXS5FP
			Panel 1.5mm to 2mm	AXS5FP1
			Panel 2mm to 3mm	AXS5FP2
		XLR 5 pole male chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS5MPH
			Panel 1.5mm to 2mm	AXS5MP1H
			Panel 2mm to 3mm	AXS5MP2H
		XLR 5 pole female chassis chassis with protective cap , IP65, Horizontal PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS5FPH
			Panel 1.5mm to 2mm	AXS5FP1H
			Panel 2mm to 3mm	AXS5FP2H
		XLR 5 pole male chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS5MPV
			Panel 1.5mm to 2mm	AXS5MP1V
			Panel 2mm to 3mm	AXS5MP2V
		XLR 5 pole female chassis chassis with protective cap , IP65, Vertical PCB, Rear mount	Panel 1.0mm to 1.5mm	AXS5FPV
			Panel 1.5mm to 2mm	AXS5FP1V
			Panel 2mm to 3mm	AXS5FP2V

PART NUMBER BREAKDOWN





CHASSIS CONNECTORS

E. G . **AXS3MP1V**
AXS (Series Prefix), **3** contacts, **M**ale, **P1** (Thermoplastic 1.5mm to 2mm (Rear Mounting), **V** (Vertical Mount- PCB Thru Hole)



SERIES PREFIX	AXS	=	Sealed IP65 with cap
	AXP	=	Sealed IP65 no cap
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
	6A	=	6 Contacts
GENDER	F	=	Socket receptacle housing
	M	=	Pin plug housing
SHELL SIZE	P	=	Thermoplastic 1mm to 1.5mm (Rear Mounting)
	P1	=	Thermoplastic 1.5mm to 2mm (Rear Mounting)
	P2	=	Thermoplastic 2mm to 3mm (Rear Mounting)
TERMINATION	Blank	=	Solder buckets
	H	=	Horizontal Mount (PCB thru hole)
	V	=	Vertical Mount (PCB thru hole)
SHELL MATERIAL / FINISH	Thermoplastic Black		
CONTACT PLATING	Blank	=	Standard
	AU	=	Gold plated
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

STANDARD DATA AX SERIES CHASSIS - IP65

		VALUE			
GENERAL CHARACTERISTICS	Number of contacts	3	4	5	6A Available
	Contact Arrangement (Front view of pin inserts)				
	Termination	Solder Bucket / Printed Circuit Board (PCB)			
	Max. Wire Gauge - Stranded wire: Solder Printed Circuit Board - PCB	14AWG N/A	16AWG N/A	18AWG N/A	18AWG N/A
	Flammability rating of plastics & rubber	UL94V-0			
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU			
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	133V [1]			
	Test Voltage AC RMS	1400V			
	Current carrying capacity: Solder Printed Circuit Board (PCB)	15A 15A	10A 10A	7.5A 7.5A	7.5A 7.5A
	Typical Contact Resistance	≤3mΩ			
	Insulation Resistance	≥1000MΩ			
CLIMATIC CHARACTERISTICS	Protection Class	IP65			
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)			
MECHANICAL CHARACTERISTICS	Weight [2]	31g (0.068lb)	32g (0.070lb)	33g (0.072lb)	33g (0.072lb)
	Mechanical Operations	1000 mating cycles			
MATERIALS	Connector Flange Finish	Rubber Black / Stainless Steel			
	Insulators	PA66 30% Glass Filled Resin			
	Male Contact Machined Solder and PCB-(Material/Plating)	Brass / Tin or Gold (Optional)			
	Female Contact Machined Solder and PCB-(Material/Plating)	Brass / Tin or Gold (Optional)			





[1] Not suitable for domestic applications above 50V
[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.





Rev 2 - 10/2024



XLRNET IP65 RANGE



Part Number Breakdown: Page 39

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLRnet chassis, CAT5E with protective cap, IP65, Horizontal PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP5H
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP5HP
			Panel 2.5mm to 3.8mm	RJXS8FP15H
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP15HP
			Panel 3.8mm to 5mm	RJXS8FP25H
			Panel 3.8mm to 5mm, Potted	RJXS8FP25HP
		XLRnet chassis, CAT6 with protective cap, IP65, Horizontal PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP6H
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP6HP
			Panel 2.5mm to 3.8mm	RJXS8FP16H
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP16HP
			Panel 3.8mm to 5mm	RJXS8FP26H
			Panel 3.8mm to 5mm, Potted	RJXS8FP26HP
		XLRnet chassis, CAT5E with protective cap, IP65, Shielded Hood,Horizontal PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP5HE
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP5HPE
			Panel 2.5mm to 3.8mm	RJXS8FP15HE
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP15HPE
			Panel 3.8mm to 5mm	RJXS8FP25HE
			Panel 3.8mm to 5mm, Potted	RJXS8FP25HPE
		XLRnet chassis, CAT6 with protective cap, IP65, Shielded Hood,Horizontal PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP6HE
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP6HPE
			Panel 2.5mm to 3.8mm	RJXS8FP16HE
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP16HPE
			Panel 3.8mm to 5mm	RJXS8FP26HE
			Panel 3.8mm to 5mm, Potted	RJXS8FP26HPE

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLRnet chassis, CAT5E with protective cap, IP65, Vertical PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP5V
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP5VP
			Panel 2.5mm to 3.8mm	RJXS8FP15V
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP15VP
			Panel 3.8mm to 5mm	RJXS8FP25V
			Panel 3.8mm to 5mm, Potted	RJXS8FP25VP
		XLRnet chassis, CAT6 with protective cap, IP65, Vertical PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP6V
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP6VP
			Panel 2.5mm to 3.8mm	RJXS8FP16V
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP16VP
			Panel 3.8mm to 5mm	RJXS8FP26V
			Panel 3.8mm to 5mm, Potted	RJXS8FP26VP
		XLRnet chassis, CAT5E with protective cap, IP65, Shielded Hood,Vertical PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP5VE
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP5VPE
			Panel 2.5mm to 3.8mm	RJXS8FP15VE
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP15VPE
			Panel 3.8mm to 5mm	RJXS8FP25VE
			Panel 3.8mm to 5mm, Potted	RJXS8FP25VPE
		XLRnet chassis, CAT6 with protective cap, IP65, Shielded Hood,Vertical PCB, Rear mount	Panel 1.2m to 2.5mm	RJXS8FP6VE
			Panel 1.2mm to 2.5mm, Potted	RJXS8FP6VPE
			Panel 2.5mm to 3.8mm	RJXS8FP16VE
			Panel 2.5mm to 3.8mm, Potted	RJXS8FP16VPE
			Panel 3.8mm to 5mm	RJXS8FP26VE
			Panel 3.8mm to 5mm, Potted	RJXS8FP26VPE

XLR Connectors


XLRnet IP65 Range

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLRnet cable plug housing to suit preassembled RJ45 ethernet cables	Nickel finish	RJXS8M
			Black finish	RJXS8MB
		XLRnet cable plug cap assembly to suit RJX series XLRnet cable plugs with coloured I.D. ring	Brown I.D. ring	RJXS-CAPC-1
			Red I.D. ring	RJXS-CAPC-2
			Orange I.D. ring	RJXS-CAPC-3
			Yellow I.D. ring	RJXS-CAPC-4
			Green I.D. ring	RJXS-CAPC-5
			Blue I.D. ring	RJXS-CAPC-6
			Violet I.D. ring	RJXS-CAPC-7
			Grey I.D. ring	RJXS-CAPC-8
			White I.D. ring	RJXS-CAPC-9

PART NUMBER BREAKDOWN

PANEL

E. G . **RJXS8FP26VP**
RJXS (Series Prefix), **8** RJ45 Style, **F** (Four hole receptacle housing IP65 - Black - Rear Mounting), **P2** (Thermoplastic 3.8mm to 5mm with cap (Rear Mounting), **6** Cat6 Compliant, **V** Vertical Mount (PCB Thru Hole), **P** Potted (IP65 unmated)




SERIES PREFIX	RJX	=	Standard
	RJXS	=	Sealed IP54 or IP65
	RJXP	=	Sealed IP65 without cap
CONTACT LAYOUTS	8	=	RJ45 Style
GENDER	F	=	Receptacle Housing
SHELL SERIES	P	=	Thermoplastic 1.2mm-2.5mm (Rear mounting IP65)
	P1	=	Thermoplastic 2.5mm to 3.8 mm with cap (Rear mounting IP65)
	P2	=	Thermoplastic 3.8mm to 5 mm with cap (Rear mounting)
TRANSMISSION CLASS	5	=	Cat5e Compliant
	6	=	Cat6 Compliant
TERMINATION	H	=	Horizontal Mount (PCB Thru hole)
	V	=	Vertical Mount (PCB Thru hole)
SEALED IP65 (RJXX)	P	=	Potted (IP65 unmated)
LOCKING MECHANISM	Blank	=	Latching
	P	=	Push lever supplied seperately for customer installation.
PACKAGING	Blank	=	Individual Bags
	B	=	Bulk Packed

PART NUMBER BREAKDOWN

PLUG CONNECTORS

E. G . **RJX8MB2**
RJX (Series Prefix), **8** RJ45 style, **M** Plug Housing,
Black Finish, **2** Red Ring Colour Option




SERIES PREFIX	RJX	=	Standard
	RJXS	=	Sealed IP65 with cap
	RJXP	=	Sealed IP65 without cap
CONTACT LAYOUTS	8	=	RJ45 style
GENDER	M	=	Plug Housing
SHELL SERIES	Blank	=	Nickel plated finish
	B	=	Black finish
RING COLOUR OPTION	Blank	=	Black
	1	=	Brown
	2	=	Red
	3	=	Orange
	4	=	Yellow
	5	=	Green
	6	=	Blue
	7	=	Violet
	8	=	Grey
	9	=	White
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

PART NUMBER BREAKDOWN

PROTECTIVE CAP

E. G . **RJX-CAPC**
RJX (Series Prefix), **CAP** Type, **C** Cable Plug male



SERIES PREFIX	RJX	=	Standard
	RJXS	=	Sealed IP54 or IP65
TYPE	CAP		
SHELL SERIES	F	=	Female panel
	M	=	Male Panel (Not available)
	C	=	Cable Plug male
	D	=	Cable Plug female
RING COLOUR OPTION	Blank	=	Black
	1	=	Brown
	2	=	Red
	3	=	Orange
	4	=	Yellow
	5	=	Green
	6	=	Blue
	7	=	Violet
	8	=	Grey
	9	=	White
OPTION	Blank	=	Lanyard
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

STANDARD DATA XLRnet IP65 CHASSIS RECEPTACLES

		VALUE		
		Class D	**CAT5E**	**CAT6**
GENERAL CHARACTERISTICS	Number of contacts	8		
	Contact Arrangement	RJ45		
	Termination	Printed Circuit Board (PCB) - through hole, Feedthrough, IDC Terminal		
	Flammability	UL94V-0		
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU		
	Solderability	MIL-STD 202, Method 208		
ELECTRICAL CHARACTERISTICS	Rated current per contact	1.5 A		
	Rated Voltage	125V AC		
	Typical Contact Resistance	20mΩ		
	Insulation Resistance	> 500MΩ		
	Dielectric Strength	1000 VAC, 60 secs		
	Max. Frequency	100Mhz	100MHz	250MHz
	Ethernet Standard	10/100 BASE-T	1000 BASE-T	10GBASE-T
	Transmission Spec.	EIA/ TIA568-C.2, ISO/IEC 11801, EN50173		
	PoE	802.3at Type 2	Types 1 to 4 and IEC60603-7 compliant	
	LED Type	Round, single pole, indicator		
CLIMATIC CHARACTERISTICS	Protection Class - RJX - RJXS	IP40 (with EMI/RFI shield) IP54 (non potted) IP65 (potted)		
	Operating Temperature	-40°C to +80°C (-40°F to +176°F)		
MECHANICAL CHARACTERISTICS	Weight** - A & B Housing - Shielded Housing - D Shell	11g (0.024lb) 17g (0.037lb) 25g (0.055lb)		
	Mechanical Operations	1000		
	Insertion and Withdrawal Force	≤ 21N		
	Latch	Spring Steel		
	Panel Thickness max.	RJXS series panel thickness variable, three groups: S: 1.2-2.5, M: 2.5-3.5, L: 3.8-5.0		
	Mounting screw torque max.	0.35Nm		
	Fastener	Self-Tapping screw M2.5		
MATERIALS	Connector Shell / Housing	PA66-R10G251(fff)(f1) KINGFA SCI&TECH, E171666		
	Front Panel Gasket	121-80 SANTOPRENE		
	Potting Compound	AW8829 RESIN GLUE		
	Contact	Phosphor Bronze		
	Contact Finish - Ground - RJ45	0.38μm Au over 1.27μm Ni 1.27μm Au over 1.27μm Ni		
	Metal Hood Shield EMI/RFI	BRASS UNS #26800 PRE-PLATED 0.25mm THK		
	Latch lock and Spring	CARBON STEEL SAE 1055		
PANEL THICKNESS	Option "P" Option "P1" Option "P2"	1.5mm - 2.5mm (0.059" - 0.098") 2.5mm - 3.5mm (0.098" - 0.137") 3.8mm - 5mm (0.149" - 0.196")		

Rev 2 - 04/2025

**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.



AC SERIES XLR PCB CHASSIS MOUNT CONNECTORS

The AC series, A and B type XLR chassis receptacles have been designed and manufactured with the Original Equipment Manufacturers' (OEM) needs in mind. The compact shell design allows a significant space saving over the traditional 'D' type shell. Gold plated contacts improve the performance, ensuring a reliable contact and the unique grounding link options offer flexibility in design.

Features

- A leading first mate last break socket contact is standard on all female connectors (Pin 1).
- Vertical and Horizontal PCB versions available.
- Latching and Non-latching versions available.
- A range of different grounding options are available including:
  - Mating connector shell to Pin 1
  - Mating connector shell to Chassis
  - Mating connector shell to pin 1 to Chassis
- A type is available in 3, 4 or 5 contacts.
- B type is available in 3 contact only.
- Compatible with all other XLR brands.
- Metal Mounting Flange (B type)

Options

- Vertical PCB contacts
- Horizontal PCB contacts
- Precision Machined Pin contacts
- Cost effective Stamped Socket contacts
- Gold Plated contacts (Standard)
- Silver Plated contacts (Optional)
- Bulk Packaging
- Integrated Switch

Ordering Codes

We have listed the more common ordering codes in each section. For further options please refer to the part number breakdown charts. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.
2) Each product group cover page then details information and options available.
3) Refer to the product detail pages and identify the product you require pictorially.
4) Read the product description column for the products standard features.
5) Use variations column to determine your choice.
6) Identify part number.
7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.
8) Please contact us directly if you have any further problems.

XLR Connectors

AC Series XLR PCB Chassis Mount Connectors








A TYPE











Features:

- Thermoplastic Shell
- Contact layouts in 3,4 or 5
- Industry standard PCB footprints.
- Vertical or Horizontal PCB mounting.
- Precision machined pin contacts.
- Gold plated contacts.
- Leading first mate last break socket contact.
- Bulk packed in trays, 100 to a box as standard.
- Positive latch lock system.

Options: Vertical or Horizontal PCB, Various grounding methods, Latching or Non-Latching.










Part Number Breakdown: Page 51 **Specifications: Page 54**
PCB Footprints: Page 55 **Panel Cutouts: Page 56**
Recommended Fastener: Page 154

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	GROUND LINK VARIATIONS	PART NUMBER
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3MAH-AU-PRE
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Pin 1 to Chassis to Mating connector shell	AC3MAH1-AU-PRE
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground	AC3MAH2-AU-PRE
		XLR 3 pole male with integrated switch, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis to PCB, Pin 1 sep. Ground	AC3MAH4-SW-B
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3MAV-AU-PRE

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	GROUND LINK VARIATIONS	PART NUMBER
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground	AC3MAV2-AU-PRE
		XLR 3 pole male, Solder Buckets, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3MA-AU-B
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3FAH-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Pin 1 to Chassis to Mating connector shell	AC3FAH1-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground	AC3FAH2-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack	No Ground Link	AC3FAHL-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack	Pin 1 to Chassis to mating connector shell	AC3FAHL1-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground.	AC3FAHL2-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3FAV-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Pin 1 to Chassis to Mating connector shell	AC3FAV1-AU-PRE

XLR Connectors

AC Series XLR PCB Chassis Mount Connectors

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	GROUND LINK VARIATIONS	PART NUMBER
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground.	AC3FAV2-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack	No Ground Link	AC3FAVL-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack	Pin 1 to Chassis to Mating connector shell	AC3FAVL1-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground.	AC3FAVL2-AU-PRE
		XLR 4 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis - Pin 1 sep. Ground	AC4MAH-AU-B
		XLR 5 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis to PCB, Pin 1 sep. Ground	AC5MAH-AU-B
		XLR 5 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis to PCB, Pin 1 sep. Ground	AC5MAV-AU-B
		XLR 5 pole female, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis to PCB, Pin 1 sep. Ground	AC5FAH-AU-B
		XLR 5 pole female, Vertical PCB, Gold Plated Contacts, Bulk Pack	Mating connector shell to Chassis to PCB, Pin 1 sep. Ground	AC5FAV-AU-B









B TYPE

Features:

- Thermoplastic Shell with Metal Mounting Flange
- Contact layouts in 3 or 5
- Industry standard PCB footprints
- Improved grounding performance
- Vertical or Horizontal PCB mounting
- Precision machined pin contacts
- Gold plated contacts
- Leading first mate last break socket contact
- Bulk packed in trays, 100 to a box as standard
- Positive latch lock system









Options: Silver plated contacts, Vertical or Horizontal PCB, Various grounding methods, Latching or Non-Latching.









Part Number Breakdown: Page 51 **Specifications: Page 54**
PCB Footprints: Page 55 **Panel Cutouts: Page 56**
Recommended Fastener: Page 154

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION/ GROUND LINK	MOUNTING FLANGE VARIATIONS	PART NUMBER
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3MBH-AU-PRE
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to Mating connector shell	Nickel Finish	AC3MBH1-AU-PRE
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis - Pin 1 sep. Ground	Nickel Finish	AC3MBH2-AU-PRE
		XLR 3 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack Mating connector shell to Pin 1	Nickel Finish	AC3MBH3-AU-PRE
		XLR 3 pole male, Horizontal PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3MBHL-AU-PRE
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3MBV-AU-PRE

XLR Connectors








AC Series XLR PCB Chassis Mount Connectors

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION/ GROUND LINK	MOUNTING FLANGE VARIATIONS	PART NUMBER
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to Mating connector shell	Nickel Finish	AC3MBV1-AU-PRE
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis - Pin 1 sep. Ground	Nickel Finish	AC3MBV2-AU-PRE
		XLR 3 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack Mating connector shell to Pin 1	Nickel Finish	AC3MBV3-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3FBH-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to Mating connector shell	Nickel Finish	AC3FBH1-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis - Pin 1 sep. Ground	Nickel Finish	AC3FBH2-AU-PRE
		XLR 3 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis	Nickel Finish	AC3FBH3-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3FBHL-AU-PRE

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION/ GROUND LINK	FINISH	PART NUMBER
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to mating connector shell	Nickel Finish	AC3FBHL1-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis - Pin 1 sep. Ground.	Nickel Finish	AC3FBHL2-AU-PRE
		XLR 3 pole female, Horizontal PCB, Non-Latching Type Gold Plated Contacts, Bulk Pack Pin 1 to Chassis	Nickel Finish	AC3FBHL3-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3FBV-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to mating connector shell	Nickel Finish	AC3FBV1-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis - Pin 1 sep. Ground.	Nickel Finish	AC3FBV2-AU-PRE
		XLR 3 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis	Nickel Finish	AC3FBV3-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack No Ground Link	Nickel Finish	AC3FBVL-AU-PRE

XLR Connectors

AC Series XLR PCB Chassis Mount Connectors


PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION/ GROUND LINK	FINISH	PART NUMBER
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis to Mating connector shell	Nickel Finish	AC3FBVL1-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack Mating connector shell to Chassis -Pin 1 sep. Ground.	Nickel Finish	AC3FBVL2-AU-PRE
		XLR 3 pole female, Vertical PCB, Non-Latching Type, Gold Plated Contacts, Bulk Pack Pin 1 to Chassis	Nickel Finish	AC3FBVL3-AU-PRE
		XLR 5 pole female, Horizontal PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Nickel Finish	AC5FBH-AU-PRE
		XLR 5 pole female, Vertical PCB, Latching Type, Gold Plated Contacts, Bulk Pack	Nickel Finish	AC5FBV-AU-PRE
		XLR 5 pole male, Horizontal PCB, Gold Plated Contacts, Bulk Pack	Nickel Finish	AC5MBH-AU-PRE
		XLR 5 pole male, Vertical PCB, Gold Plated Contacts, Bulk Pack	Nickel Finish	AC5MBV-AU-PRE

PART NUMBER BREAKDOWN

AC SERIES A AND B TYPE MALE - 3 CONTACT


E. G . **AC3MAVL3-AU PRE**
AC (series prefix),**3** contacts, **M**ale, **A** Type, **V**ertical Printed Circuit Board, **L**atchless, **3** (Mating Shell to Pin 1 Grounding), - **AU** (Gold Plated Contacts), **PRE** Bulk Packaged.

SERIES PREFIX	AC	=	Series Prefix
CONTACT LAYOUT	3	=	3 Contact only
GENDER	M	=	Male Socket Contacts
SHELL SERIES	A	=	A Type
	B	=	B Type
TERMINATION	H	=	Horizontal Printed Circuit Board
	V	=	Vertical Printed Circuit Board
	Blank	=	Solder Bucket Contacts
MOUNTING FLANGE FINISH (B TYPE ONLY)	Blank	=	Nickel
LOCKING MECHANISM	Blank	=	Latching
	L	=	Latchless
GROUNDING LINK OPTIONS	Blank	=	No Ground Link
	1	=	Pin 1 to Chassis to mating connector shell
	2	=	Mating Connector shell to Chassis, Pin 1 to separate ground
	3	=	Mating connector to Pin 1
	4	=	Mating connector to Shell to Chassis to PCB, Pin 1 separate ground
CONTACT PLATING	AU	=	Gold Plated Contacts
	AG	=	Silver Plated Contacts (Non-Standard)
PACKAGING	PRE	=	Bulk Packed
	PRD	=	Disassembled push latch



PART NUMBER BREAKDOWN

AC SERIES A AND B TYPE FEMALE - 3 CONTACT




E. G . **AC3MAVL3-AU B**
AC (series prefix),**3** contacts, **F**emale, **A** Type, **V**ertical Printed Circuit Board,**L**atchless, **3** (Pin 1 to Chassis Grounding), - **AU** (Gold Plated Contacts), **PRE** Bulk Packaged.

SERIES PREFIX	AC	=	Series Prefix
CONTACT LAYOUT	3	=	3 Contact only
GENDER	F	=	Female Socket Contacts
SHELL SERIES	A	=	A Type
	B	=	B Type
TERMINATION	H	=	Horizontal Printed Circuit Board
	V	=	Vertical Printed Circuit Board
LOCKING MECHANISM	Blank	=	Latching
	L	=	Latchless
GROUNDING LINK OPTIONS	Blank	=	No Ground Link
	1	=	Pin 1 to Chassis to mating connector shell
	2	=	Mating Connector shell to Chassis, Pin 1 to separate ground
	3	=	Pin 1 to Chassis
CONTACT PLATING	AU	=	Gold Plated Contacts
	AG	=	Silver Plated Contacts (Non-Standard)
PACKAGING	PRE	=	Bulk Packed
	PRD	=	Disassembled push latch

PART NUMBER BREAKDOWN

AC SERIES A AND B TYPE MALE AND FEMALE - 4 / 5 CONTACT

E. G . **AC5FAV-AU-B**
AC (series prefix),**5** contacts, **F**emale, **A** Type, **V**ertical Printed Circuit Board, **AU** (Gold Plated Contacts) - **B**ulk Packaged.



SERIES PREFIX	AC	=	Series Prefix
CONTACT LAYOUT	4	=	4 Contact
	5	=	5 Contact
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
SHELL SERIES	A	=	A Type
	B	=	B Type
TERMINATION	H	=	Horizontal Printed Circuit Board
	V	=	Vertical Printed Circuit Board
CONTACT PLATING	AU	=	Gold Plated Contacts
PACKAGING	B	=	Bulk Packed
	PRE	=	PRE Series Bulk Packed

STANDARD DATA AC SERIES A AND B TYPE CHASSIS

		VALUE		
GENERAL CHARACTERISTICS	Number of contacts	3	4	5
	Contact Arrangements (Front view of pin insert)			
	Termination	Printed Circuit Board (PCB)		
	Flammability rating of plastics	UL94V-0		
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU		
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	133V[1]		
	Test Voltage AC RMS	1500V		
	Current carrying capacity	6A		3A
	Typical Contact Resistance	≤5mΩ		
	Insulation Resistance (initial)	≥2GΩ		
	Insulation Resistance (after damp heat test)	≥1GΩ		
CLIMATIC CHARACTERISTICS	Protection Class	IP40		
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)		
MECHANICAL CHARACTERISTICS	Weight[2]	14g (0.030lb)		
	Retention Spring separating force	≥20N		
	Mounting Screw torque max.	1.5Nm		
	Mechanical Operations	1500 mating cycles		
	Fastening A Type Connectors[3]	Self-Tapping PT screw with thread 2.9 x 1.06 and of Tri-rondular configuration		
	Fastening B Type Connectors[3]	Self-Tapping screw M2.5		
MATERIALS	Connector Flange - B-Type	Diecast Zinc Alloy		
	Flange Finish - B-Type	Nickel		
	Insulators	PA6.6+25% glass fibre reinforced, UL94V-0		
	Male Contact Material	Brass		
	Male Contact Plating	gold over nickel		
	Female Contact Material	Bronze		
	Female Contact Plating	gold over nickel		
	Latch lock and Spring	Spring Steel		
	Ground element	Spring Steel		

Rev 12- 11/2025


[1] Not suitable for domestic applications above 50V

[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.


[3] Refer to page 154

AC SERIES A AND B TYPE CHASSIS


PCB FOOTPRINTS - CONNECTOR SIDE OF PCB




AC3FAH2
AC3FBH2




AC3FAV1
AC3FAV3
AC3FBV1
AC3FBV3
AC3FAV
AC3FBV




AC5FAH




AC3FAV2
AC3FBV2




AC3MAH1
AC3MAH3
AC3MBH1
AC3MBH3
AC3MAH
AC3MBH
AC3MBHL




AC5FAV




AC3MAH2
AC3MAH4
AC3MBH2




AC3MAV1
AC3MAV3
AC3MBV1
AC3MBV3
AC3MAV
AC3MBV




AC5MAH




AC3MAV2
AC3MAV4
AC3MBV2




AC3MAH4SWB



AC5MAV




AC3FAH1
AC3FAH3
AC3FBH1
AC3FBH3
AC3FAH
AC3FBH




AC4MAH

AC SERIES A AND B TYPE CHASSIS
PANEL CUTOUT DIMENSIONS - FRONT VIEW


A TYPE






B TYPE

A AND B TYPE MALE MOUNTING PITCH







A AND B TYPE FEMALE MOUNTING PITCH

AC3FA/BH/V SCHEMATIC CHART


AC3FA/BH/V3–AU
AC3FA/BH/VL3–AU




AC3FA/BH/V2–AU
AC3FA/BH/VL2–AU




AC3FA/BH/V1–AU
AC3FA/BH/VL1–AU




AC3FA/BH/V–AU
AC3FA/BH/VL–AU




AC3MA/BH/V3–AU
AC3MA/BH/VL3–AU




AC3MA/BH/V2/4–AU
AC3MA/BH/VL2/4–AU



AC3MA/BH/V1–AU
AC3MA/BH/VL1–AU



AC3MA/BH/V–AU
AC3MA/BH/VL–AU





AC SERIES DUAL 1/4" (6.35MM) / XLR CHASSIS MOUNT

The AC Series C type chassis receptacles feature two connectors in the one space saving housing. A combined XLR female receptacle together with a 6.35mm (1/4") phone jack give the designer more flexibility ensuring premium board space is saved. The new low profile high density C type offers a 15% space saving over the traditional C type. Various configurations are available in either stereo or mono layouts with Vertical, Horizontal Printed Circuit Board or Solder contacts.

Features

- Standard or low profile / high density shell design
- Two connectors in the one housing.
- Industry standard PCB footprint layout on standard C type.
- Vertical or Horizontal PCB mounting.
- Bulk packed.
- Positive latch lock system (XLR).

Options

- Solder contacts
- Vertical PCB contacts
- Horizontal PCB contacts
- Bulk Packaging
- Overmoldable connector housing

Ordering Codes

We have listed the more common ordering codes in each section. For further options please refer to the part number breakdown charts. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.

XLR Connectors







AC Series Dual 1/4" (6.35mm) / XLR Chassis Mount









Features:

- Two connectors in the one housing.
- Low profile design offers a 15% space saving over the traditional design.
- Vertical or Horizontal PCB mounting.
- Bulk packed in trays, 100 to a box as standard.
- Positive latch lock system (XLR).


Part Number Breakdown: Page 63
Specifications: Page 65
PCB Footprints: Page 64
Recommended Fastener: Page 154

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		Low Profile XLR 3 pole female receptacle with 1/4" stereo jack without switching contact, Horizontal PCB mount, Bulk Pack	Latching	ACJC6AH BULK
		Low Profile XLR 3 pole female receptacle with 1/4" stereo jack without switching contact, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC6AHL BULK
		Low Profile XLR 3 pole female receptacle with 1/4" stereo jack without switching contact, Vertical PCB mount, Bulk Pack	Latching	ACJC6AV2 BULK
		Low Profile XLR 3 pole female receptacle with 1/4" stereo jack without switching contact, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC6AV2L BULK
		Low Profile XLR 3 pole female receptacle with 1/4" switching stereo jack, Horizontal PCB mount, Bulk Pack	Latching	ACJC9AH BULK
		Low Profile XLR 3 pole female receptacle with 1/4" switching stereo jack, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC9AHL BULK

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack, Vertical PCB mount, Bulk Pack	Latching	ACJC9AV2 BULK
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC9AV2L BULK
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Horizontal PCB mount, Bulk Pack	Latching	ACJC10AH BULK
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC10AHL BULK
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Vertical PCB mount, Bulk Pack	Latching	ACJC10AV2 BULK
		Low Profile XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC10AV2L BULK

XLR Connectors







AC Series Dual 1/4” (6.35mm) / XLR Chassis Mount











Features:

- Two connectors in the one housing.
- Space saving design.
- Industry standard PCB footprint layout.
- Vertical or Horizontal PCB mounting.
- Bulk packed in trays, 100 to a box as standard.
- Positive latch lock system (XLR).









Part Number Breakdown: Page 63
Specifications: Page 65
PCB Footprints: Page 64
Recommended Fastener: Page 154



PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Horizontal PCB mount, Bulk Pack	Latching	ACJC5H BULK
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC5HL BULK
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Vertical PCB mount, Bulk Pack	Latching	ACJC5V BULK
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC5VL BULK
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Solder Contacts, Bulk Pack	Latching	ACJC5S BULK
		XLR 3 pole female receptacle with 1/4” mono jack without switching contact, Solder Contacts, Bulk Pack	Non-latching, Retention Spring	ACJC5SL BULK

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Horizontal PCB mount, Bulk Pack	Latching	ACJC6H BULK
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC6HL BULK
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Vertical PCB mount, Bulk Pack	Latching	ACJC6V BULK
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC6VL BULK
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Solder Contacts, Bulk Pack	Latching	ACJC6S BULK
		XLR 3 pole female receptacle with 1/4” stereo jack without switching contact, Solder Contacts, Bulk Pack	Non-latching, Retention Spring	ACJC6SL BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Horizontal PCB mount, Bulk Pack	Latching	ACJC9H BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC9HL BULK

XLR Connectors

AC Series Dual 1/4” (6.35mm) / XLR Chassis Mount


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Vertical PCB mount, Bulk Pack	Latching	ACJC9V BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC9VL BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Solder Contacts, Bulk Pack	Latching	ACJC9S BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack, Solder Contacts, Bulk Pack	Non-latching, Retention Spring	ACJC9SL BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Horizontal PCB mount, Bulk Pack	Latching	ACJC10H BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Horizontal PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC10HL BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Vertical PCB mount, Bulk Pack	Latching	ACJC10V BULK
		XLR 3 pole female receptacle with 1/4” switching stereo jack and switching ground contact, Vertical PCB mount, Bulk Pack	Non-latching, Retention Spring	ACJC10VL BULK

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole female receptacle with 1/4" switching stereo jack and switching ground contact, Solder Contacts, Bulk Pack	Latching	ACJC10S BULK
		XLR 3 pole female receptacle with 1/4" switching stereo jack and switching ground contact, Solder Contacts, Bulk Pack	Non-latching, Retention Spring	ACJC10SL BULK

PART NUMBER BREAKDOWN

AC SERIES THERMOPLASTIC C TYPE

E. G . **ACJC5HL BULK**
AC (Series Prefix),**JC** Jack/Connector XLR, **5** Mono, **H**orizontal Printed Circuit Board, **L**atchless, **Bulk** Packaged.




SERIES PREFIX	AC	=	Series Prefix
CONNECTOR TYPE	JC	=	Jack / Connector XLR
CONTACT OPTIONS	5	=	Mono, Non Switching, XLR Grounded
	6	=	Stereo, Non Switching, XLR Grounded
	9	=	Stereo, Switching, XLR Grounded
	10	=	Stereo, Switching, XLR with Ground Switch
HOUSING TYPE	Blank	=	Standard
	A	=	Low Profile / High Density
CONTACT TYPE	V	=	Vertical Pritned Circuit Board
	V2	=	Vertical Printed Circuit Board (24mm)
	H	=	Horizontal Printed Circuit Board
	S	=	Solder Contacts
LOCKING MECHANISM	Blank	=	Latching
	L	=	Latchless
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed
	PRD	=	Disassembled push lever


XLR Connectors

AC Series Dual 1/4" (6.35mm) / XLR Chassis Mount


AC SERIES C TYPE SERIES




ACJC5H & ACJC5HL




ACJC5V & ACJC5VL




ACJC6H & ACJC6HL




ACJC6V & ACJC6VL




ACJC9H & ACJC9HL




ACJC9V & ACJC9VL




ACJC10H & ACJC10HL




ACJC10V & ACJC10VL




ACJC6AH & ACJC6AHL




ACJC6AV2 & ACJC6AV2L




ACJC9AH & ACJC9AHL




ACJC9AV2 & ACJC9AV2L




ACJC10AH & ACJC10AHL




ACJC10AV2 & ACJC10AV2L




C TYPE PANEL CUTOUT



C TYPE MOUNTING PITCH



C TYPE LOW PROFILE PANEL CUTOUT



C TYPE LOW PROFILE MOUNTING PITCH

STANDARD DATA C TYPE CHASSIS RECEPTACLES

		VALUE	
		LOW PROFILE TYPE	STANDARD C TYPE
GENERAL CHARACTERISTICS	Number of contacts	5, 6, 9 or 10	
	Termination	Printed Circuit Board (PCB)	Printed Circuit Board (PCB) or Solder Bucket
	Flammability	UL 94HB	
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU	
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	50V	
	Test Voltage AC RMS	1500V	
	Current carrying capacity	7.5A	
	Typical Contact Resistance	≤50mΩ	
	Insulation Resistance (initial)	> 0.5GΩ	
	Insulation Resistance (after damp heat test)	> 0.2GΩ	
CLIMATIC CHARACTERISTICS	Protection Class	IP40	
	Operating Temperature	-25˚C to +70˚C	
MECHANICAL CHARACTERISTICS	Weight**	9.2g (0.02lb)	14g (0.030lb)
	Retention Spring separating force	≥20N	
	Mounting Screw torque max.	1.5Nm	
	Mechanical Operations	1500 mating cycles	
	Fastening***	Self-Tapping PT screw with thread 2.9 x 1.06 and of Tri-rondular configuration	
MATERIALS	Connector Shell Shell Finish	PA6.6 + 30% glass fibre reinforced, UL94HB	PA6.6 + 20% glass fibre reinforced, UL94HB Black
	Insulators	PA6.6 glass fibre reinforced, UL94HB	PA6.6 + 20% glass fibre reinforced, UL94HB
	XLR Contact Material Plating	Bronze Gold over Nickel plated	
	Jack Contact Material Plating	Bronze Gold over Nickel plated	Brass Silver over Copper plated
	Latch lock and Spring	Nickel Plated	
	Ground element	Nickel Plated	Silver over Copper plated

Rev 6 - 03/2013

**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.

***Refer to Page 154












G-TYPE MINIATURE XLR CONNECTORS

Features:

- Miniature version of the standard XLR series
- Diecast or Precision machined metal housings
- Metal cable clamp
- Precision machined pin contacts
- Stamped socket contacts
- Solder cup or Printed Circuit board contacts
- Available in 3, 4, 5 or 6 contacts
- Postive latchlock
- Flexible cable grommet

Part Number Breakdown: Page 67 **Specifications: Page 68**
PCB Footprints: Page 69 **Panel Cutouts: Page 69**


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		Male cable connector, Machined contacts, Nickel Finish	3 pole	AG3M
			4 pole	AG4M
			5 pole	AG5M
			6 pole	AG6M
		Female cable connector, Stamped contacts, Nickel Finish	3 pole	AG3F
			4 pole	AG4F
			5 pole	AG5F
			6 pole	AG6F
		Female cable connector with locking ring, Stamped contacts, Nickel Finish.	3 pole	AG3FL
			4 pole	AG4FL
			5 pole	AG5FL
			6 pole	AG6FL
		Male chassis connector, Machined contacts, Nickel Finish	3 pole	AG3MCC
			4 pole	AG4MCC
			5 pole	AG5MCC
			6 pole	AG6MCC
		Female chassis connector, Stamped contacts, Nickel Finish	3 pole	AG3FCE
			4 pole	AG4FCE
			5 pole	AG5FCE
			6 pole	AG6FCE
		Male chassis connector, Horizontal PCB, Machined contacts, Nickel Finish	3 pole	AG3MCCH
			4 pole	AG4MCCH
			5 pole	AG5MCCH
			6 pole	AG6MCCH
		Female chassis connector, Horizontal PCB, Stamped contacts, Nickel Finish	3 pole	AG3FCCH
			4 pole	AG4FCCH
			5 pole	AG5FCCH
			6 pole	AG6FCCH

		Male chassis connector, Horizontal PCB, Machined contacts, Thermoplastic shell	4 pole	AG4MPCH
		Female chassis connector, Stamped contacts, Nickel Finish	3 pole	AG3FCRV
			4 pole	AG4FCRV
			5 pole	AG5FCRV
			6 pole	AG6FCRV

PART NUMBER BREAKDOWN

G TYPE CONNECTORS

E. G . **AG3MCCHB**
AG (Series Prefix), **3** contacts, **M**ale, **C**hassis **C**onnector,**H**orizontal PCB Contacts, **B**lack finish.



SERIES PREFIX	AG	=	Series Prefix
CONTACT LAYOUTS	3	=	3 Contacts
	4	=	4 Contacts
	5	=	5 Contacts
	6	=	6 Contacts
GENDER	F	=	Female Socket Contacts
	M	=	Male Pin Contacts
	Blank	=	Cable Connector Standard (Male or Female)
SHELL STYLE	J	=	Cable Connector Large Cable clamp / boot O.D (Male or Female)
	L	=	Cable Connector with locking ring (Female)
	LL	=	Latchless (Chassis Connector)
	CC	=	Chassis Connector Circular Metal (Male)
	CE	=	Rear Mount (Chassis Connector)
	CM	=	Mid Mount (Chassis Connector)
	CR	=	Chassis Connector Rectangular Metal (Female)
	PC	=	Chassis Connector Plastic (Male)
	Blank	=	Solder Buckets (All styles except PC, CR)
CONTACT TYPE	H	=	Horizontal PCB (Style CC, PC only)
	V	=	Vertical PCB (Style CR only)
	Blank	=	Nickel Plated Finish
SHELL FINISH	B	=	Black Finish


STANDARD DATA G TYPE

			VALUE			
GENERAL CHARACTERISTICS	Number of Contacts		3	4	5	6
	Termination		Printed Circuit Board (PCB) or Solder Bucket			
	Max. Wire Gauge - Stranded Wire		AWG 24 - 0.2mm²			AWG 28 - 0.08mm²
	Flammability		UL94V-HB			
	Environmental		Complies with EU RoHS 2 Directive 2011/65/EU			
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity		5A	5A	4A	1.2A
	Typical Contact Resistance		≤10mΩ			
	Insulation resistance (initial) After Damp Heat Test		≥510MΩ ≥10MΩ			
	Dielectric Strength		1000 V dc			250 V dc
CLIMATIC CHARACTERISTICS	Protection Class		IP00			
	Operating Temperature		-30˚C to +80˚C (-20F - +176F)			
MECHANICAL CHARACTERISTICS	Insertion Spring Separating Force		≥20N			
	Cable O.D.	Standard	2mm to 3.5mm (0.078" to 0.137")			
		Large clamp / boot (Option "J")	3mm to 5mm (0.118" to 0.196")			
	Mechanical Operations		5000 mating cycles			2000 mating cycles
	Weight		13.5g (0.029lb)			
MATERIALS	Connector Shell		Bronze & Zinc			
	Connector Shell Finish		Nickel Plated			
	Insulators		PPS - Black			
	Male Contact		Material - Brass C3604 Plating - Gold over Silver Plated			
	Female Contact		Material - Brass C5210P Plating - Gold over Silver Plated			
	Latch Lock and Spring		SUS (AISI - 301) - Nickel Plated			
	Adaptor		PPS - Black			
	Cable Clamp		Bronze - Nickel Plated			
	Boot/Backshell		ABS - Black			
	Grommet		PU - Black			


Rev 7 - 09/2023

[1)]Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.
Not suitable for voltages over 50V.


PANEL CUTOUTS
- CONNECTOR SIDE OF PCB




AG3MCC




AG4MCC




AG5MCC




AG6MCC




AG3FCCH




AG3MCCH




AG4FCCH




AG4MCCH




AG5FCCH




AG5MCCH




AG6FCCH




AG6MCCH




AG3FCRV




AG4FCRV




AG5FCRV



AG6FCRV




AG4MPCH




AG3FCE


PANEL CUTOUTS
- FRONT VIEW



AG3MCC
AG4MCC
AG5MCC
AG6MCC



AG3MCCH
AG4MCCH
AG5MCCH
AG6MCCH
AG4MPCH



AG3FCRV
AG4FCRV
AG5FCRV
AG6FCRV

Speaker Connectors

G-Type Miniature XLR Connectors



SP/EP/AP SERIES LOUDSPEAKER CONNECTORS

SP Series

The SP Series are available in 2 or 4 pole chassis mount connectors. The durable thermoplastic housings are fitted with high power contacts to ensure optimal current carrying capacity. Completely intermatable with industry standard loudspeaker connections.

Features

- High current contacts for distortion free signal.
- Cost effective durable thermoplastic shell
- Available in 2 and 4 contact arrangements.
- Overmolded cable support boot or PG gland with or without cable support strain relief.
- Quick release, vibration resistant latch lock.
- UL, cUL recognized components (File no. E339831)
- Precision machined contacts
- Thermoplastic shell

Options

- Solder termination / Tab or Printed Circuit Board versions, Screw Terminals
- Nickel Plated Zinc Alloy shell
- Black finished Zinc Alloy shell

EP Series

The EP Series incorporates a rugged zinc diecast shell to give it maximum durability when used in demanding situations. The EP cable connector cable flex relief design minimises cable bend stress at point of entry into the connector housing.

Features

- High current contacts for distortion free signal.
- Tough, durable zinc diecast shell
- Cable clamp capable of supporting cables from 9mm (0.35") to 16mm (0.63") in diameter.
- Quick release, vibration resistant latch lock.
- AP & EP series are completely intermatable.
- Precision machined contacts

Options

- Nickel Plated Zinc Alloy shell
- Black finished Zinc Alloy shell
- Available in 3, 4, 5, 6 and 8 contact arrangements

AP Series

The AP Series Shell is manufactured from tough, durable thermoplastic, and ideal for fixed indoor installations. Both the EP and AP Series utilise the same contact and insulator components.

Features

- High current contacts for distortion free signal.
- Cost effective durable thermoplastic shell
- Quick release, vibration resistant latch lock.
- AP & EP series are completely intermatable.
- Precision machined contacts
- Thermoplastic shell

Options

- Available in 4, 5, 6, and 8 contact arrangements.

Ordering Codes

We have listed the more common ordering codes in each section. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.









SP SERIES

Amphenol's range of loudspeaker connectors have been further enhanced with the introduction of the SP Series. Designed to complement the popular EP/AP Series, we now offer a range of loudspeaker connectors to suit most applications. SP Series chassis connectors are available in industry standard PCB footprints with solder tabs. SP Series cable plugs are available with screw or solder terminals.

Features:







- Quick release, vibration resistant latch lock
- 2 or 4 pole
- Solder tabs, PCB Contacts, Solder or Screw Terminals
- Chuck type or PG Gland cable clamp
- Various mounting hole options
- 20A Current rating
- Thermoplastic or Metal housing (Cable Plugs)
- UL, cUL recognized components (File no. E339831)
- Industry standard mating









Part Number Breakdown: Page 75
PCB Footprints: Page 77
Specifications: Page 79
Assembly Instructions: 78

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	CONTACT TYPE	SHELL COLOUR	PART NUMBER
		2 pole, Cable connector, Thermoplastic shell, Blue sleeve	Screw	Black	SP-2-F
			Torx	Black	SP-2-FTX
			Solder	Black	SP-2-FS
		2 pole, Cable connector, Thermoplastic shell, Blue sleeve, PG Gland	Screw	Black	SP-2-FG
			Torx	Black	SP-2-FGTX
			Solder	Black	SP-2-FSG
		2 pole, Cable connector, Thermoplastic shell, Blue sleeve, PG Gland strain relief	Screw	Black	SP-2-FL
			Torx	Black	SP-2-FLTX
			Solder	Black	SP-2-FSL
		2 pole, Cable connector, Metal shell, Blue sleeve	Screw	Nickel	SP-2-FN
			Torx	Nickel	SP-2-FNTX
			Solder	Nickel	SP-2-FNS
			Screw	Black	SP-2-FB
			Torx	Black	SP-2-FBTX
			Solder	Black	SP-2-FBS
		2 pole, Cable connector, Metal shell, Blue sleeve, PG Gland	Screw	Nickel	SP-2-FNG
			Torx	Nickel	SP-2-FNGTX
			Solder	Nickel	SP-2-FNSG
			Screw	Black	SP-2-FBG
			Torx	Black	SP-2-FBGTX
			Solder	Black	SP-2-FBSG
		2 pole, Cable connector, Metal shell, Blue sleeve, PG Gland strain relief	Screw	Nickel	SP-2-FNL
			Torx	Nickel	SP-2-FNLTX
			Solder	Nickel	SP-2-FNSL
			Screw	Black	SP-2-FBL
			Torx	Black	SP-2-FBLTX
			Solder	Black	SP-2-FBSL

Speaker Connectors










SP Series

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	CONTACT TYPE	SHELL COLOUR	PART NUMBER
		4 pole, Cable connector, Thermoplastic black shell, Blue sleeve	Screw	Black	SP-4-F
			Torx	Black	SP-4-FTX
			Solder	Black	SP-4-FS
		4 pole, Cable connector, Thermoplastic black shell, Blue sleeve, PG Gland	Screw	Black	SP-4-FG
			Torx	Black	SP-4-FGTX
			Solder	Black	SP-4-FSG
		4 pole, Cable connector, Thermoplastic black shell, Blue sleeve, PG Gland strain relief	Screw	Black	SP-4-FL
			Torx	Black	SP-4-FLTX
			Solder	Black	SP-4-FSL
		4 pole, Cable connector, Metal shell, Blue sleeve	Screw	Nickel	SP-4-FN
			Torx	Nickel	SP-4-FNTX
			Solder	Nickel	SP-4-FNS
			Screw	Black	SP-4-FB
			Torx	Black	SP-4-FBTX
			Solder	Black	SP-4-FBS
		4 pole, Cable connector, Metal shell, Blue sleeve, PG Gland	Screw	Nickel	SP-4-FNG
			Torx	Nickel	SP-4-FNGTX
			Solder	Nickel	SP-4-FNSG
			Screw	Black	SP-4-FBG
			Torx	Black	SP-4-FBGTX
			Solder	Black	SP-4-FBSG
		4 pole, Cable connector, Metal shell, Blue sleeve, PG Gland strain relief	Screw	Nickel	SP-4-FNL
			Torx	Nickel	SP-4-FNLTX
			Solder	Nickel	SP-4-FNSL
			Screw	Black	SP-4-FBL
			Torx	Black	SP-4-FBLTX
			Solder	Black	SP-4-FBSL

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		2 pole, D flange, Thru holes, Solder tabs 3/16”	Black	SP-2-MD
		2 pole, D flange, Thru holes, Horizontal PCB	Black	SP-2-MDH
		2 pole, D flange, Thru holes, Vertical PCB	Black	SP-2-MDV
		Airtight 4 pole, D flange Self Tapping holes, Solder Tabs 3.16”	Black	SP-4-MDAT
		Airtight 4 pole, D flange Thru holes, Solder tabs 3/16”	Black	SP-4-MDA
		4 pole, D flange, Thru holes, Solder tabs 3/16”	Black	SP-4-MD
		4 pole, D flange, Thru holes, Solder tabs 3/16”	Grey	SP-4-MD-8
		4 pole, D flange, Self Tapping holes, Solder tabs 3/16”	Black	SP-4-MDT


Speaker Connectors

SP Series

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		4 pole, D flange, Thru holes, Horizontal PCB	Black	SP-4-MDH
		4 pole, D flange, Thru holes, Solder tabs ¼”	Black	SP-4-MDQ
		4 pole, D flange, Self Tapping holes, Horizontal PCB	Grey	SP-4-MDHT-8
		4 pole, D flange, Self Tapping holes, Horizontal PCB	Black	SP-4-MDHT
		4 pole, D flange, Thru holes, Vertical PCB	Black	SP-4-MDV
		4 pole, D flange, Thru holes, Vertical PCB	Red	SP-4-MDV-2
		4 pole, D flange, Self Tapping holes, Vertical PCB	Grey	SP-4-MDVT-8
		4 pole, EP flange, Thru holes, Solder tabs 3/16”	Black	SP-4-MC

PART NUMBER BREAKDOWN

SP SERIES - CABLE CONNECTORS




E. G . **SP-4-FNSG**
SP (Series Prefix), **4** contacts, **F** (Cable Connector), **N** (Metal Shell Nickel Finish), **S** (Solder Terminals), **G** (PG Gland)

SERIES PREFIX	SP	=	Series Prefix
CONTACT LAYOUT	2	=	2 Contacts
	4	=	4 Contacts
GENDER	F	=	Cable Connector
SHELL FINISH	Blank	=	Thermoplastic - Black
	N	=	Metal - Nickel Finish
	B	=	Metal - Black Finish
TERMINATION	Blank	=	Screw Terminals
	S	=	Solder Terminals
BACKSHELL TYPE	Blank	=	Standard
	G	=	PG Gland
	L	=	PG Gland Strain Relief
SCREW TYPE	Blank	=	Slotted
	TX	=	Torx T8
PACKAGING	Blank	=	Individual Bags
	B	=	Bulk Packed
	B1	=	Supplied with small and large cable clamps

PART NUMBER BREAKDOWN

SP SERIES - CHASSIS CONNECTORS





E. G . **SP-4-MDHT-8B**
SP (Series Prefix),**4** contacts, **M**(Chassis Connector), **D** (D Shell), **H**orizontal Printed Circuit Board, Self Tapping mounting holes - **8** (Grey), **B**ulk Packaged.

SERIES PREFIX	SP	=	Series Prefix
CONTACT LAYOUT	2	=	2 Contacts
	4	=	4 Contacts
GENDER	M	=	Chassis Connector
SHELL STYLE	D	=	Standard 'D' Type flange
	C	=	EP Series Circular flange
TERMINATION	Blank	=	Solder tabs - 3/16" terminals
	Q	=	Solder tabs - 1/4" terminals
	V	=	Vertical Printed Circuit Board
	H	=	Horizontal Printed Circuit Board
MOUNTING HOLE	Blank	=	Thru Hole
	T	=	Self Tapping
SHELL COLOUR	Blank	=	Black
	2	=	Red
	8	=	Grey
PACKAGING	Blank	=	Individual Bags
	B	=	Bulk Packed

SP SERIES


SP-2-MDH






SP-2-MDV

SP-4-MDH
SP-4-MDHT-8
SP-4-MDHT







SP-4-MDV
SP-4-MDV-2
SP-4-MDVT-8

SP SERIES PANEL CUTOUT

SP-2-MD_***
SP-4-MD_***






SP-4-MC

PI 1070 ASSEMBLY INSTRUCTIONS


SP SERIES CABLE CONNECTOR



Slide the nut onto the cable



Strip the cable and twist the conductors.



Insert the conductors into the rear of contacts on the insert. Tighten the screws to 0.35Nm (3.0 lb-in) using a flat screwdriver with tip width of 2.5mm max.




Insert the conductors into the rear of contacts on the insert. Tighten the screws to 0.35Nm (3.0 lb-in) using a T8 Torx screwdriver.



Install the cable clamp, flush to the insert making sure to align the slot as shown in the picture.



Orientate the insert and cable clamp as shown then push all together into the shell.



Thread the nut onto the shell to activate the cable clamp and close the connector assembly.

Rev 2 - 10/2025

STANDARD DATA SP SERIES CONNECTORS

		VALUE	
GENERAL CHARACTERISTICS	Number of contacts	2 or 4	
	Termination (Chassis)	Printed Circuit Board (PCB) or Solder Tabs 3/16"	
	Termination (Cable Plugs)	Screw or Solder Terminals	
	Flammability	UL94HB	
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU	
ELECTRICAL CHARACTERISTICS	Service Voltage RMS	133V [1)]	
	Test Voltage AC RMS	1500V	
	Current carrying capacity	20A	
	Typical Contact Resistance	≤3mΩ	
	Insulation Resistance (initial)	≥2GΩ	
	Insulation Resistance (after damp heat test)	≥1GΩ	
CLIMATIC CHARACTERISTICS	Protection Class (Mated Condition)	IP20 (IP40)	
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)	
MECHANICAL CHARACTERISTICS	Weight** - Chassis Connectors	12g (0.026lb)	
	Weight** - Cable Plug - Thermoplastic - Metal	 44g (0.097lb) 65g (0.143lb)	
	Weight** - Cable Plug PG - Thermoplastic - Metal	 44g (0.097lb) 65g (0.143lb)	
	Weight** - Cable Plug PG S/Relief - Thermoplastic - Metal	 68g (0.150lb) 89g (0.196lb)	
	Typical Cable retention force	200N (Subject to cable material and O.D.)	
	Cable O.D range - Chuck Clamp - PG16 Gland - PG16 Gland S/Relief	2 pole 5-10mm (0.19" - 0.39") 6-12mm (0.23" - 0.47") 9-14mm (0.35" - 0.55")	4 pole 9-14mm (0.35" - 0.55") 8-14mm (0.31" - 0.55") 9-14mm (0.35" - 0.55")
	Conductor Size - Screw Terminals - Solder Bucket	 1.5mm² - 4mm² (AWG16 - AWG12) 1.5mm² - 6mm² (AWG16 - AWG10)	
	Mechanical Operations	5000 mating cycles	
MATERIALS	Connector Shell / Finish - Cable Plug Thermoplastic - Cable Plug Metal	 PA66 GF30 / Black Diecast Zinc Alloy / Nickel or Black	
	Insulators - Chassis - Cable Plugs	 PA66 GF20 PA66 GF30	
	Cable Boot / Backshell	Santoprene / PA6 GF 15	
	Cable Clamp (Chuck)	P.O.M	
	Cable Clamp (PG)	Polyemide / EPDM	
	Sleeve	PBT	
	Contact Chassis - Material / Plating Contact Cable Plug - Material / Plating	 Phosphor Bronze / Silver Brass / Silver	

Rev 7 - 12/2020

**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.
[1] Not suitable for domestic applications above 50V

Speaker Connectors

EP Series



EP SERIES





The EP Series has set the standard in high performance speaker connectors. Apart from its durability and strength, it offers consistent superior power handling capabilities.



Features:

- Solder Bucket connections.
- Precision machined contacts.
- Diecast Metal Housings
- High current contacts
- Male and female cable and chassis connectors available.

Options: Black Finish Shell **Specifications: Page 83**

Panel Cutouts: Page 84

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
 **ISO ASSEMBLY OF EP MALE**		EP Male cable connector, Machined contacts, Metal Shell	3 pole nickel finish	EP-3-12
			3 pole black finish	EP-3-12B
			4 pole nickel finish	EP-4-12
			4 pole black finish	EP-4-12B
			5 pole nickel finish	EP-5-12
			5 pole black finish	EP-5-12B
			6 pole nickel finish	EP-6-12
			6 pole black finish	EP-6-12B
			8 pole nickel finish	EP-8-12
			8 pole black finish	EP-8-12B
 **ISO ASSEMBLY OF EP FEMALE**		EP Female cable connector, Machined contacts, Metal Shell	3 pole nickel finish	EP-3-11P
			3 pole black finish	EP-3-11PB
			4 pole nickel finish	EP-4-11P
			4 pole black finish	EP-4-11PB
			5 pole nickel finish	EP-5-11P
			5 pole black finish	EP-5-11PB
			6 pole nickel finish	EP-6-11P
			6 pole black finish	EP-6-11PB
			8 pole nickel finish	EP-8-11P
			8 pole black finish	EP-8-11PB

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		EP Male chassis mount, Round Flange, Machined contacts, Metal Shell	3 pole nickel finish	EP-3-14
			3 pole black finish	EP-3-14B
			4 pole nickel finish	EP-4-14
			4 pole black finish	EP-4-14B
			5 pole nickel finish	EP-5-14
			5 pole black finish	EP-5-14B
			6 pole nickel finish	EP-6-14
			6 pole black finish	EP-6-14B
			8 pole nickel finish	EP-8-14
			8 pole black finish	EP-8-14B
		EP Female chassis mount, Round Flange, Machined contacts, Metal Shell	3 pole nickel finish	EP-3-13P
			3 pole black finish	EP-3-13PB
			4 pole nickel finish	EP-4-13P
			4 pole black finish	EP-4-13PB
			5 pole nickel finish	EP-5-13P
			5 pole black finish	EP-5-13PB
			6 pole nickel finish	EP-6-13P
			6 pole black finish	EP-6-13PB
			8 pole nickel finish	EP-8-13P
			8 pole black finish	EP-8-13PB

Speaker Connectors

AP Series







AP SERIES

The AP Series provides the same power handling performance as the EP Series in a cost effective, yet durable Thermoplastic housing.


Features:

- Solder Bucket connections.
- Precision machined contacts.
- Thermoplastic Housings
- High current contacts
- Male & Female Cable and Chassis connectors available.

Specifications: Page 83 **Panel Cutouts: Page 84**

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		AP Male cable connector, Machined contacts, Thermoplastic Black shell.	4 pole	AP-4-12
			5 pole	AP-5-12
			6 pole	AP-6-12
			8 pole	AP-8-12
		AP Female cable connector, Machined contacts, Thermoplastic Black shell.	4 pole	AP-4-11
			5 pole	AP-5-11
			6 pole	AP-6-11
			8 pole	AP-8-11
		AP Male chassis mount, Rectangular Flange, Machined contacts, Thermoplastic Black shell.	4 pole	AP-4-22
			5 pole	AP-5-22
			6 pole	AP-6-22
			8 pole	AP-8-22
		AP Female chassis mount, Rectangular Flange, Machined contacts, Thermoplastic Black shell.	4 pole	AP-4-21
			5 pole	AP-5-21
			6 pole	AP-6-21
			8 pole	AP-8-21

STANDARD DATA EP/AP

		VALUE				
GENERAL CHARACTERISTICS	Number of contacts	3	4	5	6	8
	Contact Arrangements (Front view of pin insert)					
	Termination	SOLDER				
	Wire Gauge - Stranded wire:	12AWG	12AWG	12AWG	12AWG	14AWG
	Flammability	UL94V-0				
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU				
ELECTRICAL CHARACTERISTICS	Service Voltage RMS [1)]	460V	660V	200V	200V	100V
	Test Voltage AC RMS	2400V	3000V	1600V	1600V	1300V
	Current carrying capacity	20A	20A	20A	20A	15A
	Typicial Contact Resistance	≤3mΩ				
	Insulation Resistance	≥1000MΩ				
CLIMATIC CHARACTERISTICS	Protection Class	IP40				
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)				
MECHANICAL CHARACTERISTICS	Weight - EP 11 & 12 [2)]	80g (0.176lb)	84g (0.185lb)	86g (0.189lb)	86g (0.189lb)	86g (0.189lb)
	Weight - EP 13 & 14 [2)]	48g (0.105lb)	50g (0.110lb)	54g (0.119lb)	54g (0.119lb)	54g (0.119lb)
	Weight - AP 11 & 12 [2)]	N/A	42g (0.092lb)	44g (0.097lb)	44g (0.097lb)	44g (0.097lb)
	Weight - AP 13, 14, 21 & 22 [2)]	N/A	26g (0.057lb)	30g (0.066lb)	30g (0.066lb)	28g (0.061lb)
	Typical Cable retention force	22Kg to 44Kg (50lb to 100lb) - Dependant on cable material and diameter				
	Mechanical operations	1000 mating cycles				

Rev 3 - 03/2013

[1)] Not suitable for domestic applications above 50V

[2)] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.


STANDARD DATA EP/AP (CONT'D)

		DETAILS	
MATERIALS	TYPE	**AP**	**EP**
	Connector shell	Modified PPE Resin	Diecast Zinc Alloy
	Shell finish	Black	Satin Nickel or Black
	Insulators	UL94V-0 PBT Resin	
	Cable Bushing	Silicon Rubber	UL94 HB Thermoplastic Elastomer
	Male contact Machined - Solder Material / Plating	Brass / Bright Tin	
	Female contact Machined - Solder Material / Plating	Brass / Bright Tin	
CLAMPING CHARACTERISTICS	Cable OD Range	11mm to 17mm (0.43" to 0.67")	9mm to 16mm (0.35" to 0.63")
	Retention Method	Two opposing plastic screws	Metal saddle clamp


Rev 3 - 03/2013

EP/AP SERIES PANEL CUTOUT DATA - FRONT VIEW

EP 13/AP 13/AP 21



EP 14/AP 14/AP 22











HP SERIES

HP Series connectors are suitable for AC power supply where a latch locking connector is required. They are rated at 25 A / 250 Vac. Connectors are keyed and colour coded for power-in (Blue) and power-out (Grey).

THE HP SERIES OF CONNECTORS ARE NOT DESIGNED TO BE "HOT PLUGGED" AND SO ARE WITHOUT "BREAKING CAPACITY". IN OTHER WORDS, THE CONNECTORS SHOULD NOT BE CONNECTED OR DISCONNECTED LIVE OR WHEN UNDER LOAD

Features:

- Quick release, vibration resistant latch lock
- 3 pole
- Screw Terminals or Solder Tab 3/16"
- Chuck type cable clamp
- 25A Current rating
- Thermoplastic housing
- Industry standard mating
- UL, cUL recognized components (File no. E339831)

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	CONTACT TYPE	SHELL COLOUR	PART NO.
		3 pole, Cable connector, Thermoplastic shell, Blue sleeve, keyed for power-in	Screw	Blue	HP-3-F
		3 pole, Cable connector, Thermoplastic shell, Grey sleeve, keyed for power-out	Screw	Grey	HP-3-FG
		3 pole, Chassis connector, Thermoplastic shell, Blue, keyed for power-in	Solder Tab 3/16"	Blue	HP-3-MD
		3 pole, Chassis connector, Thermoplastic shell, Grey, keyed for power-out	Solder Tab 3/16"	Grey	HP-3-MDG
		3 pole, Chassis connector, Thermoplastic shell, Blue, keyed for power-in, without insulation divider	Solder Tab 3/16"	Blue	HP-3-MDW
		3 pole, Chassis connector, Thermoplastic shell, Grey, keyed for power-out, without insulation divider	Solder Tab 3/16"	Grey	HP-3-MDGW

STANDARD DATA HP SERIES CONNECTORS

		VALUE
GENERAL CHARACTERISTICS	Number of contacts	2 + PE
	Termination	Screw or Solder Tab 3/16”
	Flammability	UL94V-0
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
ELECTRICAL CHARACTERISTICS	Rated Operating Voltage	250VAC
	Test Voltage AC RMS	3200V
	Current carrying capacity	25A
	Typical Contact Resistance	≤3mΩ
	Insulation Resistance (initial)	≥2GΩ
	Insulation Resistance (after damp heat test)	≥1GΩ
CLIMATIC CHARACTERISTICS	Protection Class	IP20
	Operating Temperature	-25˚C to +75˚C (-13°F to +167°F)
MECHANICAL CHARACTERISTICS	Weight** - Chassis Connector - Cable Plug	 12g (0.026lb) 32g (0.070lb)
	Typical Cable retention force	200N (Subject to cable material and O.D.)
	Cable O.D range - Blue Chuck Clamp - Black Chuck Clamp	 5mm - 7.5mm (0.19” - 0.29”) 7.5mm - 15mm (0.29” - 0.59”)
	Conductor Size - Screw Terminals	 2.5mm² (AWG14)
MATERIALS	Connector Shell / Finish	PA66 GF30 / Black
	Insulators	PA66 GF30
	Cable Boot / Backshell	Santoprene / PBT
	Cable Clamp (Chuck)	P.O.M
	Contact Plug - Material / Plating	 Brass / Silver
	Contact Chassis - Material / Plating	 Phosphor Bronze / Silver

Rev 4 - 08/2016

**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.












HPT SERIES

HPT Series connectors are suitable for AC power supply where a durable latch locking connector is required. They are rated at 16A, 250 Vac. HPT Series connectors can be connected or disconnected under load and are IP65 rated.

c UL us

Features:








- 2+PE contact layout
- Quick release, vibration resistant latch lockable
- High impact UV resistant material
- True Mains Connector with Current Breaking Capacity (CBC)
- 16A current rating (20A USA)
- Industry standard mating interface
- IP65 rated
- Patent Protected*
- UL498 certified
- UL50E enclosure type 4 (when mated or in combination with protective caps)

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	CONTACT TYPE	SHELL COLOUR	PART NUMBER
		3 pole, Outlet Cable connector, Locking, Thermoplastic shell, Screw terminals, **Lockable backshell**	Screw	Black	HPT-3-F
		3 pole, Outlet Cable connector, Locking, Thermoplastic shell, Screw terminals	Screw	Black	HPT-3-FJ
		3 pole, Inlet Cable connector, Locking, Thermoplastic shell, Screw terminals, **Lockable backshell**	Screw	Black	HPT-3-M
		3 pole, Inlet Cable connector, Locking, Thermoplastic shell, Screw terminals	Screw	Black	HPT-3-MJ
		3 pole, Chassis Inlet connector, Thermoplastic shell, ¼" flat tab terminals	Tab 1/4"	Black/ Yellow	HPT-3-MD
		3 pole, Chassis Inlet connector, Thermoplastic shell, without insulation divider, ¼" flat tab terminals	Tab 1/4"	Black/ Yellow	HPT-3-MDW
		3 pole, Chassis Outlet connector, Thermoplastic shell, ¼" flat tab terminals	Tab 1/4"	Black/ Yellow	HPT-3-FD
		3 pole, Chassis Outlet connector, Thermoplastic shell, without insulation divider, ¼" flat tab terminals	Tab 1/4"	Black/ Yellow	HPT-3-FDW
		3 pole, Chassis Inlet-Outlet combination, Thermoplastic shell, ¼" flat tab terminals	Tab 1/4"	Black/ Yellow	HPT-3-CC

*Patent Protected refer to http://www.amphenolaudio.com/patents/

Power Connectors

HPT Series

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	COLOUR	PART NUMBER
		Protective sealing cap with stainless steel lanyard to suit HPT-3-MD / HPT-3-MDW	Black	HPT-CAPM
		Protective sealing cap with stainless steel lanyard to suit HPT-3-FD / HPT-3-FDW	Black	HPT-CAPF
		Protective sealing cap with stainless steel lanyard to suit HPT-3-CC	Black	HPT-CAPD
		Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-MD / HPT-3-MDW	Black	HPT-CAPSM
		Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-FD / HPT-3-FDW	Black	HPT-CAPSF
		Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-CC	Black	HPT-CAPSD
		Cable connector backshell lock release tool	Black	HPT-RT

STANDARD DATA HPT SERIES CONNECTORS

		VALUE
GENERAL CHARACTERISTICS	Number of contacts	2 + PE
	Termination - Cable Connector - Chassis Mount	 2mm Hex key screw terminal Flat Tab 1/4”
	Flammability	UL94V-0
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
ELECTRICAL CHARACTERISTICS	Rated Operating Voltage	250VAC
	Test Voltage AC RMS	1500V
	Current carrying capacity	16A (20A USA)
	Typical Contact Resistance	≤2mΩ
	Insulation Resistance (initial)	≥2GΩ
	Insulation Resistance (after damp heat test)	≥0.1GΩ
	Breaking Cycles	5000
CLIMATIC CHARACTERISTICS	Protection Class	IP65, UL50E enclosure type 4 (in mated or in combination with protective caps)
	Operating Temperature	-25˚C to +80˚C (-13°F to +176°F)
MECHANICAL CHARACTERISTICS	Weight** - Chassis Connector - Cable Plug	 15g (0.033lb) / 25g (0.055lb) 40g (0.088lb)
	Typical Cable retention force	Subject to cable material and O.D.
	Cable O.D range	6.0 -12.0 mm with lockable backshell 7.5 -16.0 mm with non-lockable backshell
	Conductor Size - Screw Terminals	 2.5mm² (AWG12)
	Mating Cycles	5000
MATERIALS	Connector Shell / Finish	PA66 GF30 / Black
	Insulators	PA66 GF30
	Cable Boot / Backshell	Neoprene / PBT
	Contact Plug - Material / Plating	Copper Alloy / Silver
	Contact Chassis - Material / Plating	Copper Alloy / Silver
	Protective Caps - Base - Overmolded Cap - Chain	 Santoprene, UV resistant PA66 & Santoprene, UV resistance Stainless Steel SS304
	Protective Caps (Self closing) - Base - Overmolded Cap - Gasket - Spring	 Polycarbonate, UV resistant Polycarbonate & Santoprene, UV resistant Silicone Rubber Stainless Steel SS304

Rev 5 - 03/2023

**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.



AMPHE-DANTE ADAPTERS

Amphe-Dante are Dante™ audio to analogue audio adapters, available for Input, Output, AES3 and USB applications. Featuring premium quality Amphenol AX series XLR and RJ45 connectors in a robust molded housing.

Amphe-Dante products enable simple connection of analogue equipment to a Dante network and can receive and transmit audio channels from a Dante network and provide studio-quality, low-latency audio via XLR connectors to and from analogue audio equipment.

Amphe-Dante feature high-quality digital-to-analogue converters, and support a range of sample rates and bit depths. They can provide a hardware master clock for a Dante network. As with other Dante products, the freely available Dante Controller software application is used to automatically discover and configure Amphe-Dante devices connected to the Dante network. Device names, channel labels, signal routing and other parameters (for example, sample rate and latency) can be configured via the network using Dante Controller. A variety of network and clock synchronisation diagnostic tools are also available in Dante Controller.

Amphe-Dante products use Power over Ethernet (PoE). Power can be provided through the Ethernet cable from a PoE-capable network switch, or from a separate PoE injector.

Available Software Options (required)

Dante Controller

Dante Controller is a free software application that enables you to route audio and configure devices on a Dante network. As well as automatic device discovery, one-click signal routing and user-editable device and channel labels, Dante Controller provides essential device status information and powerful real-time network monitoring, including device-level latency and clock stability stats, multicast bandwidth usage, and customized event logging, enabling you to quickly identify and resolve any potential network issues.

Dante Via

Dante Via is powerful and easy-to-use software that delivers unprecedented routing of computer-based audio, allowing a wide range of applications and devices to be networked and interconnected, easily and inexpensively. Dante Via network-enables locally-connected USB and Firewire devices, and a huge range of software applications, allowing you to route computer -based audio across an existing Dante network, and create standalone Dante networks without dedicated Dante hardware.

Dante Virtual Soundcard

Dante Virtual Soundcard turns your computer into a Dante-powered workstation, seamlessly integrating your PC or Mac with Dante audio devices on your network. You can instantly connect to a Dante network to record, process and playout using any audio application and any combination of Dante-enabled devices.

Dante Controller









All software can be purchased and downloaded at **amphenolaudio.com/products/dante**

Dante™ is a trademark of Audinate Pty Ltd. Audinate® is a registered trademark of Audinate Pty Ltd.



Features:

- Dante™ to analogue XLR output adapters
- Line level analogue input to Dante™ audio output adapters
- Dante™ AES3 2 channel input/output adapters
- Dante™ USB input/output adapters
- One channel or Two channel analogue input or output
- Durable overmolded housing
- Resilient cable strain relief
- Shielded RJ45 metal connectors with integrated LED's
- Premium AX Series XLR connectors


PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	PART NO.
ANALOGUE OUTPUT			
		Analogue Output - 1 channel, RJ45 input to XLR output, Durable overmolded housing Dante™	RJD1112-0050
		Analogue Output - 2 channel, RJ45 input to XLR output, Durable overmolded housing Dante™	RJD1212-0050
ANALOGUE INPUT			
		Analogue line level Input - 1 channel XLR input to RJ45 output, Durable overmolded housing Dante™	RJD2103-0050
		Analogue line level Input - 2 channel XLR input to RJ45 output, Durable overmolded housing Dante™	RJD2203-0050
AES3			
		AES3 Input / Output - 2 channel XLR I/O to RJ45 I/O, Durable overmolded housing Dante™	RJD32A3-0050
USB			
		USB Input / Output - 2 channel USB I/O to RJ45 I/O Durable overmolded housing Dante™	RJD32U1-0050

SPECIFICATIONS

		ANALOG INPUT 1CH	ANALOG INPUT 2CH	ANALOG OUT-PUT 1CH	ANALOG OUT-PUT 2CH	AES3 I/O 2 IN 2 OUT	USB I/O 2 IN 2 OUT
GENERAL	Connectors	1 XLR-F	2 XLR-F	RJ45	RJ45	RJ45	RJ45
		RJ45	RJ45	1 XLR-M	2 XLR-M	1 XLR-M, 1 XLR-F	USB 2.0 Type A
ELECTRICAL	Power Consumption	< 2 Watt					
	Power over Ethernet (Required)	Class 1 IEEE 802.3af POE PD compliant					PoE or USB
ANALOG / DIGITAL AUDIO	Max Signal Level (Balanced)	**+24dBu** / +4dBu / 0dBu 0dBV / -10dBV		+18dBu / **+4dBu** / 0dBu 0dBV / -10dBV		-	-
	Impedance	20k Ohm balanced 10k Ohm unbalanced		150 Ohm balanced 75 Ohm unbalanced		110 Ohm balanced	-
	Frequency Response	20Hz to 20 kHz (+/-0.5db)		20Hz to 20 kHz (+/-0.5db)		-	-
	Dynamic Range	> 100dB		> 100dB		-	-
	Signal to Noise	> 100dB		> 100dB		> 135dB	-
	Total Harmonic Distortion	< 0.01% at +4dBu		< 0.01% at +4dBu		-	-
	Channel Separation	N/A	> 100 dB	N/A	> 100 dB		-
	Channel Matching	N/A	< 0.25 dB	N/A	< 0.25 dB		-
DANTE® AUDIO	Asynchronous Sample Rate Conversion	-		-		Yes	-
	Sample Rate	44.1 kHz, 48 kHz (default), and 96 kHz					48 kHz
	Bit Depth	24 bits					
	Network Speed	100 Mbps					
	Network Interface	Latency from 1ms					
	Network Transport	Dante Audio over IP, AES67 RTP					
CLIMATIC	Protection Class	IP40					
	Operating Temperature	-5ºC to +60ºC (23ºF to +140ºF)					
MECHANICAL	Insertion and Withdrawal Force	≥10N - ≤35N					
	Weight	136g (0.299lb)	192g (0.423lb)	136g (0.299lb)	192g (0.423lb)	192g (0.423lb)	110g (0.243lb)
MATERIALS	Housing	PVC 60P Black					

Rev 4 - 08/2018

LED STATUS



FUNCTION	LEFT LED	RIGHT LED	COMMENT
Off	OFF	OFF	No Power
Device is booting	Solid GREEN	Solid RED	
Slave with sync	Blinking GREEN	Solid GREEN	Normal operation
Clock Master	Blinking GREEN	Blinking GREEN	Normal operation
Any runtime error	Blinking GREEN	Blinking RED	Normal operation
Identify	Alternating RED and GREEN	Alternating RED and GREEN	Blinking for 6 seconds (cycle every 0.5 seconds)
Failsafe (bootloader)	Blinking RED	Blinking RED	Failsafe, Corrupt Capability (red in DC)
Upgrade (bootloader)	Blinking ORANGE	Blinking ORANGE	Device is upgrading



XLRnet Connectors

XLRnet was designed in conjunction with the Amphenol Data / Telecom product group of Amphenol Canada Corp., a subsidiary of Amphenol Corporation. Utilising our combined expertise and knowledge of the professional audio and high-speed data markets we are proud to offer the XLRnet series. Featuring Class D (10/100 BASE-T), CAT5E (1000 BASE-T) or CAT6 (10GBASE-T) ethernet performance in A, B or D shell housings with integrated LED's or light pipes and complete shielding options we have your high-speed data requirements covered.

Features

- Class D (10/100 BASE-T), CAT5E (1000 BASE-T) or CAT6 (10GBASE-T) ethernet performance
- A, B or D type chassis housings
- IDC or IDC 110 punch down terminals
- RJ45 feedthrough panel connectors
- Shielded or non-shielded
- LED indicators in a variety of colours.
- Light pipes
- Compact design
- Cable plug housings
- Quick and simple installation

Options

- Horizontal or Vertical PCB contacts
- Bulk Packaging
- LED colour - Red, Green, Yellow or Blue combinations
- Light Pipes

Ordering Codes

We have listed the more common ordering codes in each section. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.







XLRNET SERIES CABLE CONNECTOR


Features/Benefits:
- XLR RJ45 Cable plug housing.
- Designed for pre-assembled RJ45 cables.
- Quick and simple installation.
- Cost effective method for harsh environments.
- No cabling in field required.
- No tools required for installation.
- Available in Nickel or Black housings.
- Coloured boots / Backshells

Specifications: Page 95
Part Number Breakdown : Page 95 **Assembly Instructions: Page 98**

NOTE*RJ45 preassembled cable sold separately and is not included with the XLRnet connector.


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Nickel Finish	Standard	RJX8M
			Bulk Pack	RJX8M BULK
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Black Finish	Standard	RJX8MB
			Bulk Pack	RJX8MB BULK
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Nickel Finish	Standard	RJXX8M
			Bulk Pack	RJXX8M BULK
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Black Finish	Standard	RJXX8MB
			Bulk Pack	RJXX8MB BULK

ISO VIEW OF RJX8M



PART NUMBER BREAKDOWN

XLRnet SERIES



E. G . **RJX8MB BULK**
RJX (Series Prefix), **8** contacts, **M** (Cable Connector), **B** (Black Finish),
Bulk Packaged

SERIES PREFIX	RJX RJXX	= =	Series Prefix Series Prefix
CONTACT LAYOUT	8	=	RJ45 Cable Housing
GENDER	M	=	Male Cable Plug
SHELL FINISH	Blank B	= =	Nickel Plated Finish Metal - Black Finish
PACKAGING	Blank BULK	= =	Individual Bags Bulk Packed

STANDARD DATA XLRnet SERIES

		VALUE
GENERAL CHARACTERISTICS	Termination	Preassembled RJ45 Cable (Not supplied)
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
CLIMATIC CHARACTERISTICS	Protection Class	IP40
	Operating Temperature	-25˚C to +75˚C (-13°F to -167°F)
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal force	≥10N - ≤20N
	Weight [2]	26g (0.057lb)
	Cable O.D. range	5 or 8mm (0.20" or 0.31")
	Mechanical Operations	1000 mating cycles
MATERIALS	Connector shell - Metal Shell finish	Diecast Zinc Alloy Satin nickel or Black
	Boot / Backshell Finish	UL94V-0 Noryl N190 / Valox (RJX8M / RJX8MB) UL94 V-0 PBT-RG151(f1) (RJXX8M / RJXX8MB) Black
	Cable clamp	PA6
	Sleeve	Valox

Rev 1 - 03/2013

[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.





XLRNET SERIES CABLE CONNECTOR

Features/Benefits:


- XLR RJ45 Cable plug housing.
- Designed for pre-assembled RJ45 cables.
- Quick and simple installation.
- Cost effective method for harsh environments.
- No cabling in field required.
- No tools required for installation.
- Available in Nickel or Black housings.
- Coloured boots / Backshells

Specifications: Page 95
Part Number Breakdown : Page 95 **Assembly Instructions: Page 98**

NOTE*RJ45 preassembled cable sold separately and is not included with the XLRnet connector.


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Nickel Finish	Standard	RJX8M
			Bulk Pack	RJX8M BULK
		XLRnet, XLR cable plug housing to suit preassembled RJ45 cables, Black Finish	Standard	RJX8MB
			Bulk Pack	RJX8MB BULK

ISO VIEW OF RJX8M



PART NUMBER BREAKDOWN

XLRnet SERIES



E. G . **RJX8MB BULK**
RJX (Series Prefix), **8** contacts, **M** (Cable Connector), **B** (Black Finish),
Bulk Packaged

SERIES PREFIX	RJX	=	Series Prefix
CONTACT LAYOUT	8	=	RJ45 Cable Housing
GENDER	M	=	Male Cable Plug
SHELL FINISH	Blank	=	Nickel Plated Finish
	B	=	Metal - Black Finish
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed


STANDARD DATA XLRnet SERIES

		VALUE
GENERAL CHARACTERISTICS	Termination	Preassembled RJ45 Cable (Not supplied)
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
CLIMATIC CHARACTERISTICS	Protection Class	IP40
	Operating Temperature	-25˚C to +75˚C (-13°F to -167°F)
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal force	≥10N - ≤20N
	Weight [2]	26g (0.057lb)
	Cable O.D. range	5 or 8mm (0.20" or 0.31")
	Mechanical Operations	1000 mating cycles
MATERIALS	Connector shell - Metal Shell finish	Diecast Zinc Alloy Satin nickel or Black
	Boot / Backshell Finish	UL94V-0 Noryl N190 / Valox Black
	Cable clamp	PA6
	Sleeve	Valox

Rev 1 - 03/2013


[2] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.

XLRnet SERIES CABLE ASSEMBLY INSTRUCTIONS



Snap or cut off release tab of the RJ45 plug.

⚠ *Failure to remove the RJ45's Release Tab will make the XLRnet assembly permanently latching. The XLRnet series has an independent panel side latching system.*



Slide the nut (backshell) onto the cable.




Install the cable clamp-boot.



Close clamp-boot, fasten the two tabs together to lock.



Push clamp-boot & cable together into the shell



Thread the nut (backshell) onto the shell (torque 0.8Nm-1.2Nm) to close the connector assembly.







XLRNET SERIES A & B TYPE CHASSIS RECEPTACLES

Features:

- RJ45 Class D (10/100 BASE-T), CAT5E (1000 BASE-T) or CAT6 (10GBASE-T) Ethernet performance
- A or B type chassis housings
- Shielded or non-shielded
- LED indicators in a variety of colours
- Light pipes
- Horizontal or Vertical PCB
- Mates with XLRnet cable plugs or standard RJ45 plug.








Part Number Breakdown: Page 102
Specifications: Page 109 **PCB Footprints: Page 103**
Recommended Fastener: Page 155

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	LED* LHS/RHS		PART NUMBER
		XLRnet chassis, A type, Horizontal PCB	Class D	-	-	RJX8FA3HB
			CAT5E			RJX8FA5HB
			CAT6			RJX8FA6HB
		XLRnet chassis B type, Horizontal PCB	Class D	-	-	RJX8FB3HB
			CAT5E			RJX8FB5HB
			CAT6			RJX8FB6HB
		XLRnet chassis, B type, Light pipes, Horizontal PCB, Bulk packed	CAT5E	-	-	RJX8FB5HLPB
			CAT6	-	-	RJX8FB6HLPB
		XLRnet chassis, B type, LEDs, Horizontal PCB, Bulk packed	CAT5E	R	G	RJX8FB5HRGB
				R	Y	RJX8FB5HRYB
				R	R	RJX8FB5HRRB
				G	R	RJX8FB5HGRB
				G	Y	RJX8FB5HGYB
				U	U	RJX8FB5HUUB
			CAT6	R	G	RJX8FB6HRGB
				R	Y	RJX8FB6HRYB
				R	R	RJX8FB6HRRB
				G	R	RJX8FB6HGRB
				G	Y	RJX8FB6HGYB
				U	U	RJX8FB6HUUB







*Note: LED colours are denoted left to right from the panel side front view. Refer page 108 R = Red, G = Green, Y = Yellow, U = Blue

Data Connectors

XLRnet Series A & B Type Chassis Receptacles

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	LED* LHS/RHS		PART NUMBER
		XLRnet chassis, B type, Shielded Hood, Horizontal PCB, Bulk packed	Class D	-	-	RJX8FB3HEB
			CAT5E			RJX8FB5HEB
			CAT6			RJX8FB6HEB
		XLRnet chassis, B type, Shielded Hood, Light pipes, Horizontal PCB, Bulk packed	CAT5E	-	-	RJX8FB5HLPEB
			CAT6	-	-	RJX8FB6HLPEB
		XLRnet chassis, B type, Shielded Hood, LEDs, Horizontal PCB, Bulk packed	CAT5E	R	G	RJX8FB5HRGEB
				R	Y	RJX8FB5HRYEB
				R	R	RJX8FB5HRREB
				G	R	RJX8FB5HGREB
				G	Y	RJX8FB5HGYEB
				U	U	RJX8FB5HUUEB
			CAT6	R	G	RJX8FB6HRGEB
				R	Y	RJX8FB6HRYEB
				R	R	RJX8FB6HRREB
				G	R	RJX8FB6HGREB
				G	Y	RJX8FB6HGYEB
				U	U	RJX8FB6HUUEB
		XLRnet chassis, A type, Vertical PCB - 18.3mm, Bulk packed	Class D	-	-	RJX8FA3VB
			CAT5E			RJX8FA5VB
			CAT6			RJX8FA6VB
		XLRnet chassis, A type, Vertical PCB - 24mm, Bulk packed	CAT5E			RJX8FA5V2B
			CAT6			RJX8FA6V2B
		XLRnet chassis, B Type, Vertical PCB - 18.3mm, Bulk packed	Class D	-	-	RJX8FB3VB
			CAT5E			RJX8FB5VB
			CAT6			RJX8FB6VB
		XLRnet chassis, B type, Vertical PCB - 24mm, Bulk packed	CAT5E	-	-	RJX8FB5V2B
			CAT6	-	-	RJX8FB6V2B

*Note: LED colours are denoted left to right from the panel side front view. Refer page 108 R = Red, G = Green, Y = Yellow, U = Blue


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	LED* LHS/RHS		PART NUMBER
		XLRnet chassis, B type, Light pipes, Vertical PCB - 24mm, Bulk packed	CAT5E	-	-	RJX8FB5V2LPB
			CAT6	-	-	RJX8FB6V2LPB
		XLRnet chassis, B type, LEDs, Vertical PCB, Bulk packed	CAT5E	R	G	RJX8FB5VRGB
				R	Y	RJX8FB5VRYB
				R	R	RJX8FB5VRRB
				G	R	RJX8FB5VGRB
				G	Y	RJX8FB5VGYB
				U	U	RJX8FB5VUUB
			CAT6	R	G	RJX8FB6VRGB
				R	Y	RJX8FB6VRYB
				R	R	RJX8FB6VRRB
				G	R	RJX8FB6VGRB
				G	Y	RJX8FB6VGYB
				U	U	RJX8FB6VUUB
		XLRnet chassis, B type, Shielded Hood, Vertical PCB, - 18.3mm, Bulk packed	Class D	-	-	RJX8FB3VEB
			CAT5E			RJX8FB5VEB
			CAT6			RJX8FB6VEB
		XLRnet chassis, B type, Shielded Hood, Vertical PCB - 24mm, Bulk packed	CAT5E	-	-	RJX8FB5V2EB
			CAT6	-	-	RJX8FB6V2EB
		XLRnet chassis, B type, Shielded Hood, Light pipes, Vertical PCB - 24mm, Bulk packed	CAT5E	-	-	RJX8FB5V2LPEB
			CAT6	-	-	RJX8FB6V2LPEB
		XLRnet chassis, B type, Shielded Hood, LEDs, Vertical PCB, - 18.3mm, Bulk packed	CAT5E	R	G	RJX8FB5VRGEB
				R	Y	RJX8FB5VRYEB
				R	R	RJX8FB5VRREB
				G	R	RJX8FB5VGREB
				G	Y	RJX8FB5VGYEB
				U	U	RJX8FB5VUUEB
			CAT6	R	G	RJX8FB6VRGEB
				R	Y	RJX8FB6VRYEB
				R	R	RJX8FB6VRREB
				G	R	RJX8FB6VGREB
				G	Y	RJX8FB6VGYEB
				U	U	RJX8FB6VUUEB

*Note: LED colours are denoted left to right from the panel side front view. Refer page 108 R = Red, G = Green, Y = Yellow, U = Blue

PART NUMBER BREAKDOWN

XLRnet A and B Type Printed Circuit Board Connectors

E. G . **RJX8FB5HLRREB**
RJX (Series Prefix), **8** (Contacts), **F**emale **B** type, **5** Cat5E **H**orizontal, **L**atchless, **R**ed - **R**ed LEDs, **E**MI / RFI Hood, **Bulk** Packaged.




SERIES PREFIX	RJX	=	Series Prefix
CONTACT LAYOUT	8	=	RJ45 type
GENDER	F	=	Receptacle housing
SHELL SERIES	A B	= =	A Type B Type
TRANSMISSION CLASS	3 5 6	= = =	Class D CAT 5e CAT 6
TERMINATION	H V V2	= = =	Horizontal Printed Circuit Board Vertical Printed Circuit Board Vertical PCB 24mm
LOCKING MECHANISM	Blank P	= =	Latching Push lever supplied separately for customer installation (Contact factory for detailed fitting instructions)
LED COLOUR SEQUENCE*	Blank RG RY RR GR GY GG YR YY YG UU LP	= = = = = = = = = = = =	No LEDs Red / Green Red / Yellow Red / Red Green / Red Green / Yellow Green / Green Yellow / Red Yellow / Yellow Yellow / Green Blue / Blue Light Pipes**
EMI / RFI SHIELDING HOOD	Blank E	= =	No shield hood EMI / RFI shield hood
PACKAGING	Blank B	= =	Individual Bulk packed

*Note: LED colours are denoted left to right from the panel side front view. Refer Page 108
** Light Pipes not available with termination option V, order V2 or H only


XLRNET A AND B TYPE PRINTED CIRCUIT BOARD CONNECTORS

PCB LAYOUT FRONT VIEW

HORIZONTAL




RJX8FB5HLPB
RJX8FB6HLPB




RJX8FB5HLPEB
RJX8FB6HLPEB

VERTICAL




RJX8FB5V2LPB
RJX8FB6V2LPB



RJX8FB5V2LPEB
RJX8FB6V2LPEB


PANEL CUTOUT DIMENSIONS FRONT VIEW

HORIZONTAL



RJX8FB5HLPEB
RJX8FB6HLPEB
RJX8FB5HLPB
RJX8FB6HLPB

VERTICAL



RJX8FB5V2LPEB
RJX8FB6V2LPEB
RJX8FB5V2LPB
RJX8FB6V2LPB








XLRNET SERIES D TYPE CHASSIS RECEPTACLES

Features:











- RJ45 Class D (10/100 Base-T), CAT5E (1000 Base-T) or CAT6 (10GBASE-T) Ethernet performance
- D type XLR standard housings
- IDC Punchdown block
- Thru-adaptor / Feedthrough
- Horizontal or Vertical PCB

Part Number Breakdown: Page 107
Specifications: Page 109
PCB Footprints: Page 108
Recommended Fastener: Page 155

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	PART NUMBER
		XLRnet chassis, D type, Feedthrough, Nickel Finish	CAT5E	RJX8FD5T
		XLRnet chassis, D type, IDC Terminals, 110 type, Nickel Finish	CAT5E	RJX8FD5110
			CAT6	RJX8FD6110
		XLRnet chassis, D type, IDC Terminals, Nickel Finish	CAT5E	RJX8FD5I
			CAT6	RJX8FD6I
		XLRnet chassis, D type, Horizontal PCB, Nickel Finish	Class D	RJX8FD3HB
			CAT5E	RJX8FD5HB
			CAT6	RJX8FD6HB
		XLRnet chassis, D type, Vertical PCB, Nickel Finish	Class D	RJX8FD3VB
			CAT5E	RJX8FD5VB
			CAT6	RJX8FD6VB

Data Connectors

XLRnet Series D Type Chassis Receptacles

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	PART NUMBER
		XLRnet chassis, D type (IP54), Feedthrough, Nickel Finish	CAT5E	RJXS8FD5T
		XLRnet chassis, D type (IP54), IDC Terminals, 110 type, Nickel Finish	CAT5E	RJXS8FD5110
			CAT6	RJXS8FD6110
		XLRnet chassis, D type (IP54), IDC Terminals, Nickel Finish	CAT5E	RJXS8FD5I
			CAT6	RJXS8FD6I
		XLRnet chassis, D type (IP54), Horizontal PCB, Nickel Finish	Class D	RJXS8FD3HB
			CAT5E	RJXS8FD5HB
			CAT6	RJXS8FD6HB
		XLRnet chassis, D type (IP54), Vertical PCB, Nickel Finish	Class D	RJXS8FD3VB
			CAT5E	RJXS8FD5VB
			CAT6	RJXS8FD6VB
		XLRnet chassis with Protective cap, D type (IP54), Feedthrough, Nickel Finish	CAT5E	RJXS8FG5T
		XLRnet chassis with Protective cap, D type (IP54), IDC Terminals, 110 type, Nickel Finish	CAT5E	RJXS8FG5110
			CAT6	RJXS8FG6110
		XLRnet chassis with Protective cap, D type (IP54), IDC Terminals, Nickel Finish	CAT5E	RJXS8FG5I
			CAT6	RJXS8FG6I
		XLRnet chassis with Protective cap, D type (IP54), Horizontal PCB, Nickel Finish	Class D	RJXS8FG3HB
			CAT5E	RJXS8FG5HB
			CAT6	RJXS8FG6HB
		XLRnet chassis with Protective cap, D type (IP54), Vertical PCB, Nickel Finish	Class D	RJXS8FG3VB
			CAT5E	RJXS8FG5VB
			CAT6	RJXS8FG6VB

PART NUMBER BREAKDOWN

XLRnet D TYPE Chassis Connectors

E. G . **RJX8FD3TB**
RJX (Series Prefix), **8** (Contacts), **F**emale **D** type, **3** Class D **T**hru Adaptor, **B**ulk Packaged




SERIES PREFIX	RJX	=	Series Prefix
CONTACT LAYOUT	8	=	RJ45 type
GENDER	F	=	Receptacle housing
SHELL SERIES	D	=	D Type
TRANSMISSION CLASS	3 5 6	= = =	Class D CAT 5e CAT 6
TERMINATION	H I 110 T V	= = = = =	Horizontal Printed Circuit Board IDC Punch Down Block IDC 110 Punch Down Block Thru adaptor / Feedthrough Vertical Printed Circuit Board
LOCKING MECHANISM	Blank P	= =	Latching Push lever supplied separately for customer installation (Contact factory for detailed fitting instructions)
PACKAGING	Blank B	= =	Individual Bulk packed


*Note: LED colours are denoted left to right from the panel side front view. Refer Page 108

XLRNET A, B AND D TYPE SERIES


*** Applicable to 3 (Class D), 5 (CAT5E) and 6 (CAT6), where available**




RJX8FA*H
RJX8FA*HB




RJX8FB*HRGB
RJX8FB*HRYB
RJX8FB*HRRB
RJX8FB*HGRB
RJX8FB*HGYB
RJX8FB*HGGB




RJX8FB*HEB




RJX8FB*HRGEB
RJX8FB*HRYEB
RJX8FB*HRREB
RJX8FB*HGREB
RJX8FB*HGYEB
RJX8FB*HGGEB




RJX8FA*VB
RJX8FB*VB




RJX8FB*VRGB
RJX8FB*VRYB
RJX8FB*VRRB
RJX8FB*VGRB
RJX8FB*VGYB
RJX8FB*VUUB




RJX8FB*VEB




RJX8FB*VRGEB
RJX8FB*VRYEB
RJX8FB*VRREB
RJX8FB*VGREB
RJX8FB*VGYEB
RJX8FB*VUUEB




RJX8FD*HB
(Front Mounting)




RJX8FD*HB
(Rear Mounting)




RJX8FD*VB




LED Arrangement (Front view)




PANEL CUTOUT
A and B type with LED's



XLRnet MOUNTING PITCH / A and B Type



D Type



A and B Type

STANDARD DATA XLRnet CHASSIS RECEPTACLES

		VALUE		
		Class D	CAT5E	CAT6
GENERAL CHARACTERISTICS	Number of contacts	8		
	Contact Arrangement	RJ45		
	Termination	Printed Circuit Board (PCB) - through hole, Feedthrough, IDC Terminal		
	Flammability	UL94V-0		
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU		
	Solderability	MIL-STD 202, Method 208		
ELECTRICAL CHARACTERISTICS	Rated current per contact	1.5 A		
	Rated Voltage	125V AC		
	Typical Contact Resistance	20mΩ		
	Insulation Resistance	> 500MΩ		
	Dielectric Strength	1000 VAC, 60 secs		
	Max. Frequency	100Mhz	100MHz	250MHz
	Ethernet Standard	10/100 BASE-T	1000 BASE-T	10GBASE-T
	Transmission Spec.	EIA/ TIA568-C.2, ISO/IEC 11801, EN50173		
	PoE	802.3at Type 2	Types 1 to 4 and IEC60603-7 compliant	
	LED Type	Round, single pole, indicator		
CLIMATIC CHARACTERISTICS	Protection Class - RJX - RJXS	IP40 (with EMI/RFI shield) IP54		
	Operating Temperature	-40°C to +80°C (-40°F to +176°F)		
MECHANICAL CHARACTERISTICS	Weight** - A & B Housing - Shielded Housing - D Shell	11g (0.024lb) 17g (0.037lb) 25g (0.055lb)		
	Mechanical Operations	1000		
	Insertion and Withdrawal Force	≤ 21N		
	Latch	Spring Steel		
	Panel Thickness max.	3mm		
	Mounting screw torque max.	0.35Nm		
	Fastener	Self-Tapping screw M2.5		
MATERIALS	Connector Shell / Housing	Thermoplastic, DSM Stanyl UL94V-0, 30% GF / PA66 30% GF		
	Flange (A type)	Thermoplastic, DSM Stanyl UL94V-0, 30% GF		
	Flange (B type)	Diescast Zinc Alloy 3		
	Flange Finish (B type)	Satin Nickel		
	Contact	Phosphor Bronze		
	Contact Finish - Ground - RJ45	0.38μm Au over 1.27μm Ni 1.27μm Au over 1.27μm Ni		
	Metal Hood Shield EMI/RFI	Brass, nickel plated		
	Latch lock and Spring	Spring steel		

Rev 5 - 11/2023



**Approximate weight in grams not including packaging. Please contact us for exact weight for shipping purposes.




USB/HDMI SERIES

Features:
- Data connectors
- Feedthrough adaptors
- USB 3 Type A
- HDMI receptacles

Options: Nickel or Black Shell Finish

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		USB 3.0, Feedthrough adapter, D Flange, Nickel Finish	Type A / Type A	AC-USB3-AA
		USB 3.0, Feedthrough adapter, D Flange, Black Finish	Type A / Type A	AC-USB3-AAB
		HDMI, Feedthrough adapter, D Flange, Nickel Finish	HDMI / HDMI	AC-HDMI-RR
		HDMI, Feedthrough adapter, D Flange, Black Finish	HDMI / HDMI	AC-HDMI-RRB



AC-****

PANEL CUTOUT DIMENSIONS

FRONT VIEW

USB/HDMI TECHNICAL DATA

		VALUE	
GENERAL CHARACTERISTICS	Type	USB 3.0	HDMI 2.0
	Termination	Thru-adaptor	
	Max. Wire Gauge - Stranded Wire	AWG 14 - 2.5mm²	
	Flammability rating of insulating plastics	UL94V-0	
	Solderability, complies with	IEC 68-2-20	
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU	
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity	10A (Depends on Mating Connector)	
	Typical Contact Resistance	≤10mΩ (Depends on Mating Connector)	
	Insulation resistance (initial) After Damp Heat Test	>2GΩ ≥ 10^3 Meg Ω	
	Dielectric Strength	1500 V dc	
CLIMATIC CHARACTERISTICS	Protection Class	IP40	
	Operating Temperature	-25ºC to +75ºC (-13ºF to +167ºF)	
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force	≥10N - ≤30N (depends on mating connector)	
	Cable O.D.	3mm to 7mm (0.118" to 0.275")	
	Mechanical Operations	1000 mating cycles	
	Weight - Cable Mount - Panel Mount	 18g (0.039lb) 30g (0.066lb)	
MATERIALS	Connector Shell Material (Plugs)	Diecast Zinc Alloy EZDA No.3	
	Connector Shell Finish	Satin Nickel or Coloured Polyester	
	Insulators	PA66	
	Cable Bushing	Thermoplastic Polyurethane	
	Contacts	Brass Alloy	
	Plating	Gold Flash	

Rev 2 - 03/2021

[1)]Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.



1/4” PHONE CONNECTORS

Amphenol offers two ranges of 1/4” Phone plug connectors to satisfy the needs of the manufacturer and the end user. The PRO – a heavy duty on-road plug and the MUSICIAN - a solid performing general use plug. Both series offer different features and benefits and the most suitable type will be determined by application, budget and personal choice.

Applications

- Audio Cables and Snakes
- Amplifiers
- Mixing desks
- Patch panel

PRO RANGE 1/4” Phone Plug T-Series

Features / Options

- Mono or Stereo (TRS)
- Switching Plugs
- Nickel or Gold contact plating
- Straight or Right Angle
- Optional heavy duty metal backshell / boot
- Increased solder area on ground contact
- “Jaws” Cable Clamp
- Precision machined contacts
- Coloured Grommet
- JUMBO Series Plugs

PRO RANGE 1/4” Phone Plug Q-Series

Features / Options

- Mono or Stereo (TRS)
- Slimline design
- Quick and Easy to assemble
- Nickel or Gold contact plating
- Chuck style cable clamp
- Nickel or Black shell finish
- Molded backshell

MUSICIAN RANGE 1/4” Phone Plug

Features / Options

- Mono or Stereo (TRS)
- Compact Shell
- Straight or Right angle
- Flexible grommet cable protection
- Nickel or Gold contact plating
- Satin Nickel or Black finish
- Coloured Grommet

Jaws Cable Clamp Options for T-Series*



Standard Jaws cable clamp (Black), Cable O.D 3mm to 6mm (0.118” to 0.236”)



Large Jaws cable clamp (Purple), Cable O.D 6mm to 7mm (0.236” to 0.275”)

*Note: Applicable to T-Series straight cable connectors only. Refer to page 122 for right angle connector Jaws cable clamp specifications.

Chuck Clamp for Q-Series



Standard Chuck clamp (Black), Cable O.D 3mm to 7mm (0.118” to 0.275”)

Musician Range Cable Clamp Options



M-Series, Cable O.D 3mm to 6.5mm (0.118” to 0.256”)



M-Series II, Cable O.D 6.5mm to 8mm (0.256” to 0.315”)

Ordering Codes

We have listed the more common ordering codes in each section. Refer to our 1/4” plug product feature matrix found on the next page for assistance on selecting the right plug for your application.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.

1/4” PLUG FEATURE MATRIX

FEATURES		T SERIES (STRAIGHT)	T SERIES (RIGHT ANGLE)	JUMBO T SERIES	SWITCHPLUG T SERIES (STRAIGHT)	SWITCHPLUG T SERIES (RIGHT ANGLE)	Q SERIES	M SERIES	M SERIES II	CUSTOM SERIES[1]
PRECISION MACHINED CONTACTS		X	X	X	X	X	X	X	X	X
CENTER CONTACT	1 pc. Center Contact	X	X	X	X	X				X*
	2 pc Press Fit Tip/Center Contact						X	X	X	X*
BARREL:	Machined Tube	X	X	X	X	X				
	Precision Extruded Tube						X	X	X	X
JAWS CABLE CLAMP		X	X		X	X				
MIN. CABLE OD	Black Jaw: 3mm/0.118”	X	X		X	X				
	Purple Jaw: 6mm/0.236”	X			X					
	Purple Jaw: 5.5mm/0.216”		X			X				
MAX. CABLE OD	Black Jaw: 6mm/0.236”	X			X					
	Black Jaw: 5.5mm/0.216”		X			X				
	Purple Jaw: 7.5mm/0.295”	X			X					
	Purple Jaw: 6.5mm/0.255”		X			X				
CHUCK CABLE CLAMP										
MIN. CABLE OD	Black Chuck: 3.5mm/0.137”						X			
MAX. CABLE OD	Black Jaw: 7mm/0.275”						X			
STANDARD CABLE CLAMP				X				X	X	X
MIN. CABLE OD	7.5mm/0.295”			X						
MAX. CABLE OD	6mm/0.236”							X		
	8mm/0.315”								X	
	8.8mm/0.345”									X
	10.5mm/0.413”			X						
BACKSHELL FINISH	Satin Nickel	X	X	X	X	X	X	X	X	
	Black	X	X	X	X	X	X	X	X	
	Bright Nickel									X
	Bright Gold									X
CONTACT MATERIAL/ FINISH OPTIONS	Brass/Nickel (Ni)	X	X	X	X	X	X	X	X	X
	Brass/Gold over 2μm (Ni)	X	X	X	X	X	X	X	X	X

[1]Custom Series - Minimum order quantities apply. Contact us for further details.












T SERIES PLUGS

Features:
- Mono or Stereo (TRS).
- Stylised shell design with Ergonomic grip.
- Straight or Right Angle.
- Robust diecast shell in Satin nickel or Black finish.
- Nickel or Gold contact plating.
- Keyed shell.
- Optional heavy duty metal backshell / boot.
- Great solderability.
- Increased solder area on ground contact.
- "Jaws" Cable Clamp.
- Precision machined contacts.
- Quick and easy assembly.

Options: Gold Contacts, Large or Small Jaws Cable Clamp, Black Shell, Metal Backshell / Boot, Bulk Pack. Coloured grommets (ordered separately)

Part Number Breakdown: Page 97 **Specifications: Page 98**

PRODUCT - FIGURE	DRAWING	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Jaws cable clamp, Thermoplastic back-shell, Satin finish.	Standard	TM2P
			Gold Plated Contacts	TM2P-AU
			Large Cable Clamp	TM2PJ
			Bulk Pack	TM2P BULK
		1/4" (6.35mmø) Mono Phone plug, Jaws cable clamp, Thermoplastic back-shell, Black finish.	Standard	TM2PB
			Gold Plated Contacts	TM2PB-AU
			Large Cable Clamp	TM2PBJ
			Bulk Pack	TM2PB BULK
		1/4" (6.35mmø) Stereo Phone plug, Jaws cable clamp, Thermoplastic back-shell, Satin finish.	Standard	TS3P
			Gold Plated Contacts	TS3P-AU
			Large Cable Clamp	TS3PJ
			Bulk Pack	TS3P BULK
		1/4" (6.35mmø) Stereo Phone plug, Jaws cable clamp, Thermoplastic back-shell, Black finish.	Standard	TS3PB
			Gold Plated Contacts	TS3PB-AU
			Large Cable Clamp	TS3PBJ
			Bulk Pack	TS3PB BULK

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Jaws cable clamp, Metal backshell, Satin finish.	Standard	TM2PN
			Gold Plated Contacts	TM2PN-AU
			Large Cable Clamp	TM2PNJ
			Bulk Pack	TM2PN BULK
		1/4" (6.35mmø) Mono Phone plug, Right angle, Jaws cable clamp*, Thermoplastic back-shell, Satin finish.	Standard	TM2RJ
			Gold Plated Contacts	TM2RJ-AU
		1/4" (6.35mmø) Mono Phone plug, Right angle, Jaws cable clamp*, Thermoplastic back-shell, Black finish.	Standard	TM2RBJ
			Gold Plated Contacts	TM2RBJ-AU
			Bulk Pack	TM2RBJ BULK
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Jaws cable clamp*, Thermoplastic back-shell, Satin finish.	Standard	TS3RJ
			Gold Plated Contacts	TS3RJ-AU
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Jaws cable clamp*, Thermoplastic back-shell, Black finish.	Standard	TS3RBJ
			Gold Plated Contacts	TS3RBJ-AU





*NOTE: Refer to page 122 for Jaws cable clamp specifications applicable to right angle connectors.



T SERIES (JUMBO) PLUGS

Features:
- JUMBO Cable clamping capacity
- Suits Cable OD 7.5mm (0.295") to 10.5mm (0.413")
- Mono or Stereo (TRS).
- Stylised shell design with Ergonomic grip.
- Robust diecast shell in Satin nickel or Black finish.
- Nickel or Gold contact plating.
- Keyed shell.
- Great solderability.
- Increased solder area on ground contact.
- Precision machined contacts.
- Quick and easy assembly.

Options: Gold Contacts, Bulk Pack
Specifications: Page 122


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) JUMBO Mono Phone plug, Thermoplastic back-shell, Satin finish.	Standard	JM2P
			Gold Plated Contacts	JM2P-AU
			Bulk Pack	JM2P BULK
		1/4" (6.35mmø) JUMBO Mono Phone plug, Thermoplastic back-shell, Black finish.	Standard	JM2PB
			Gold Plated Contacts	JM2PB-AU
		1/4" (6.35mmø) JUMBO Stereo Phone plug, Thermoplastic back-shell, Satin finish.	Standard	JS3P
			Gold Plated Contacts	JS3P-AU
		1/4" (6.35mmø) JUMBO Stereo Phone plug, Thermoplastic back-shell, Black finish.	Standard	JS3PB
			Gold Plated Contacts	JS3PB-AU

NOTE: Contact factory for availability of metal backshells.

PART NUMBER BREAKDOWN


T-SERIES (PRO RANGE)

E. G . **TS3PBMJ-AU BULK**
T (Series Prefix), **S3**(Stereo), **P**lug **B**lack, **M**etal Nut (Black), **J** (Large Jaws),
- **AU** (Gold Plated Contacts), **Bulk** Packaged.



SERIES PREFIX	T	=	Series Prefix
CONTACT TYPE	M1	=	Switch Plug
	M2	=	2 Pole (mono)
	S3	=	3 Pole, tip/ring/sleeve (stereo)
SHELL TYPE AND FINISH	P	=	Plug Satin Nickel
	PB	=	Plug Matt Black
	R	=	Right Angle Plug Satin Nickel
	RB	=	Right Angle Plug Matt Black
BACKSHELL TYPE	Blank	=	Plastic Nut
	M	=	Metal Nut - Black
	N	=	Metal Nut - Satin Nickel
CABLE CLAMP	Blank	=	Small Jaws
	J	=	Large Jaws
CONTACT PLATING	Blank	=	Nickel Plated Contacts (Standard)
	AU	=	Gold Plated Contacts
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

ISO VIEW OF TM2P









T-SERIES SWITCHPLUG

The Amphenol T series SwitchPlug uses a unique 360 degree precision sliding helical spring contact design to quietly and accurately switch the signal circuit safely to ground during instrument changes under load, thereby avoiding annoying thumps, pops and squeals. The sliding ring contact self-cleans every time the plug is connected preventing excessive build up of oxidization and contamination. Activation is directly off the jacks full front face assuring a positive reference point every time, and as it works instantaneously on the main circuits there is no need for the use of magnets or other elaborate switching mechanisms.

WARNING!
For use with instrument (guitar) applications only.

Part Number Breakdown: Page 117
Specifications: Page 122


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Switch Phone plug, Jaws cable clamp, Thermoplastic backshell, Satin finish	Standard	TM1P
			Gold Plated Contacts	TM1P-AU
			Large Cable Clamp	TM1PJ
		1/4" (6.35mmø) Switch Phone plug, Jaws cable clamp, Thermoplastic backshell, Black finish	Standard	TM1PB
			Gold Plated Contacts	TM1PB-AU
			Large Cable Clamp	TM1PBJ
		1/4" (6.35mmø) Switch Phone plug, Right angle, Jaws cable clamp*, Thermoplastic backshell, Satin Finish	Standard	TM1RJ*
			Gold Plated Contacts	TM1RJ-AU*
		1/4" (6.35mmø) Switch Phone plug, Right angle, Jaws cable clamp*, Thermoplastic backshell, Black Finish	Standard	TM1RBJ*
			Gold Plated Contacts	TM1RBJ-AU*


*NOTE: Refer to page Page 122 for Jaws cable clamp specifications applicable to right angle connectors.

SwitchPlug - User Instruction


CAUTION!


Use with instrument (guitar) cables only.
DO NOT connect to amplifier output.
Equipment damage may result from incorrect use.





SwitchPlug - Technology*





*US Patent No. 8,162,697



Q SERIES PLUGS

Features:
- Mono or Stereo (TRS)
- Slimline design
- Quick and Easy to assemble
- Nickel or Gold contact plating
- Chuck style cable clamp
- Nickel or Black shell finish
- Molded backshell





Options: Gold Plated Contacts, Black Shell, Bulk Pack.



Specifications: Page 122


Clamp Info:



Standard Chuck clamp (Black), Cable O.D 3mm to 7mm (0.118" to 0.275")

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Chuck cable clamp, Molded boot, Satin Finish	Standard	QM2P
		1/4" (6.35mmø) Mono Phone plug, Chuck cable clamp, Molded boot, Black Finish	Gold Plated Contacts	QM2PB-AU
		1/4" (6.35mmø) Stereo Phone plug, Chuck cable clamp, Molded boot, Satin Finish	Standard	QS3P
		1/4" (6.35mmø) Stereo Phone plug, Chuck cable clamp, Molded boot, Black Finish	Gold Plated Contacts	QS3PB-AU

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Right angle Chuck cable clamp, Molded boot, Satin Finish	Standard	QM2R
		1/4" (6.35mmø) Mono Phone plug, Right angle Chuck cable clamp, Molded boot, Black Finish	Gold Plated Contacts	QM2RB-AU
		1/4" (6.35mmø) Stereo Phone plug, Right angle Chuck cable clamp, Molded boot, Satin Finish	Standard	QS3R
		1/4" (6.35mmø) Stereo Phone plug, Right angle Chuck cable clamp, Molded boot, Black Finish	Gold Plated Contacts	QS3RB-AU



CABLE CLAMP

1/4” PHONE PLUG TECHNICAL DATA

			VALUE		
			Straight	Right Angle	Jumbo
GENERAL CHARACTERISTICS	Number of Contacts		3 Pole Tip Ring Sleeve (Stereo)		
	Termination		Solder		
	Max. Wire Gauge - Stranded Wire		2 Pole (Mono): AWG 16 - 1.5mm 3 Pole (Stereo): AWG 18 - 1mm		
	Flammability rating of insulating plastics		UL94V-0		
	Solderability, complies with		IEC 68-2-20		
	Environmental		Complies with EU RoHS 2 Directive 2011/65/EU		
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity		10A (Depends on Mating Connector and Cable)		
	Typical Contact Resistance		Depends on Mating Connector		
	Insulation Resistance (initial) After Damp Heat Test		>2GΩ ≥1GΩ		
	Dielectric Withstand Voltage		2 Pole : 1.5 kV dc 3 Pole : 1 kV dc		
CLIMATIC CHARACTERISTICS	Protection Class		IP40		
	Operating Temperature		-25°C to +75°C (-13°F to + 167°F)		
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force		≥10N - ≤30N		
	Weight[1]	Thermoplastic Backshell	28g (0.061lb)		
		Metal Backshell	35g (0.077lb)		
	Typical Cable Retenton Force		22kg to 44kg (50lb to 100lb) - Dependent on cable material and diameter.		
	Cable O.D.	Standard Jaw (T-Series)	3mm to 6mm (0.118” to 0.236”)	3mm to 5.5mm (0.118” to 0.216”)	N/A
		Large Jaw (T-Series)	6mm to 7mm (0.236” to 0.275”)	5.5mm to 6.5mm (0.216” to 0.255”)	N/A
		Standard Clamp (Q-Series)	3.5mm to 7mm (0.137” to 0.275”)	N/A	N/A
		Jumbo	NA	NA	7.5mm to 10.5mm (0.295” to 0.413”)
	Mechanical Operations		1000		
MATERIALS	Connector Shell Material		Diecast Zinc Alloy EZDA No.3		
	Shell Finish		Satin Nickel or Black Polyester		
	Insulators		UL94 V-0 PBT Resin or Modified PPE Resin - Black		
	Boot / Backshell		UL94 V-0 PBT Resin or Modified PPE Resin - Black or Metal $CuZn^{39}Pb^{3}$		
	Cable Clamp		UL94 V-0 PBT Modified PPO Resin - Black		
	Cable Bushing		Santoprene		
	Contacts / Plating		Brass /Ni or Au over 2μm Ni		

[1] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.

Rev 6 - 10/2017



MUSICIAN SERIES II PLUGS

Features:
- Mono or Stereo (TRS).
- AX Series inspired shell design.
- Large cable O.D. Entry to 8mm (0.315")
- Robust diecast shell in Satin nickel or Black finish.
- Nickel or Gold contact plating.
- Flexible grommet cable protection.
- Improved solderability.
- Precision machined contacts.
- Standard or Bulk packaging.





Clamp Info:



Cable O.D 6.5mm to 8mm (0.256" to 0.315")

Options: Black Shell, Gold contacts. Coloured grommets (ordered separately)





Specifications: Page 112

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NO.
		1/4" (6.35mmø) Mono Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPM-KN
			Gold Plated Contacts	ACPM-KN-AU
		1/4" (6.35mmø) Mono Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPM-KB
			Gold Plated Contacts	ACPM-KB-AU
		1/4" (6.35mmø) Stereo Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPS-KN
			Gold Plated Contacts	ACPS-KN-AU
		1/4" (6.35mmø) Stereo Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPS-KB
			Gold Plated Contacts	ACPS-KB-AU

*NOTE: Refer to page 103 for Jaws cable clamp specifications applicable to right angle connectors.

Plugs & Jacks

Musician Series II Plugs

PRODUCT	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NO.
		1/4" (6.35mmø) Mono Phone plug, Right angle, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPM-TN
			Gold Contacts	ACPM-TN-AU
			Bulk Pack	ACPM-TN BULK
		1/4" (6.35mmø) Mono Phone plug, Right angle, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPM-TB
			Gold Contacts	ACPM-TB-AU
			Bulk Pack	ACPM-TB BULK
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPS-TN
			Gold Contacts	ACPS-TN-AU
			Bulk Pack	ACPS-TN BULK
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPS-TB
			Gold Contacts	ACPS-TB-AU
			Bulk Pack	ACPS-TB BULK



Features:
- Mono or Stereo (TRS).
- Stylish shell design.
- Robust diecast shell in Satin nickel or Black finish.
- Nickel or Gold contact plating.
- Flexible grommet cable protection.
- Improved solderability.
- Precision machined contacts.
- Standard or Bulk packaging.
- Cable OD Entry to 6.5mm (0.256")





Options: Black Shell, Gold contacts. Coloured grommets (ordered separately)

Specifications: Page 136

Clamp Info:







Cable O.D 3mm to 6.5mm (0.118" to 0.256")

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPM-GN
			Gold Plated Contacts	ACPM-GN-AU
			Bulk Pack	ACPM-GN BULK
		1/4" (6.35mmø) Mono Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPM-GB
			Gold Plated Contacts	ACPM-GB-AU
			Bulk Pack	ACPM-GB BULK
		1/4" (6.35mmø) Stereo Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPS-GN
			Gold Plated Contacts	ACPS-GN-AU
			Bulk Pack	ACPS-GN BULK
		1/4" (6.35mmø) Stereo Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPS-GB
			Gold Plated Contacts	ACPS-GB-AU
			Bulk Pack	ACPS-GB BULK


Plugs & Jacks

Musician Series II Plugs

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	TYPE	PART NUMBER
		1/4" (6.35mmø) Mono Phone plug, Right angle, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPM-RN
			Gold contacts	ACPM-RN-AU
			Bulk Pack	ACPM-RN BULK
		1/4" (6.35mmø) Mono Phone plug, Right angle, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPM-RB
			Gold contacts	ACPM-RB-AU
			Bulk Pack	ACPM-RB BULK
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Diecast Shell, Satin finish, Flexible grommet.	Standard	ACPS-RN
			Gold contacts	ACPS-RN-AU
			Bulk Pack	ACPS-RN BULK
		1/4" (6.35mmø) Stereo Phone plug, Right angle, Diecast Shell, Black finish, Flexible grommet.	Standard	ACPS-RB
			Gold contacts	ACPS-RB-AU
			Bulk Pack	ACPS-RB BULK

PART NUMBER BREAKDOWN

M / M SERIES II (MUSICIAN RANGE)



E. G . **ACPM-GB-AU BULK**
ACP (Series Prefix), **M**ale, **G**(Shell Type), **B**lack,
- AU (Gold Plated Contacts), **Bulk** Packaged.

SERIES PREFIX	ACP	=	Series Prefix
CONTACT TYPE	M	=	2 pole (Mono)
	S	=	3 pole Tip/Ring/Sleeve (Stereo)
SHELL TYPE	G	=	M Series Straight
	K	=	M Series II Straight
	R	=	M Series Right Angle
	T	=	M Series II Right Angle
SHELL FINISH	N	=	Satin Nickel
	B	=	Matt Black
CONTACT PLATING	Blank	=	Nickel Plating
	AU	=	Gold Plated
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed



1/4” / 3.5MM PHONE JACK CONNECTORS

Amphenol phone connectors are available in 1/4” (6.35mm) and 3.5mm jack sockets or dual jack socket versions featuring combinations of both sizes. The standard heavy duty contacts provide excellent signal performance and the rugged designs excel in professional audio applications.
Our wide range of options ensures we have the connector to suit your specific requirements. Custom jacks can also be developed to suit unique applications on request.


Applications

- Audio Cables and Snakes
- Amplifiers
- Speakers
- Mixing desks
- Rack mount equipment
- Patch panel


Features / Options – OEM RANGE Phone Jack

- Mono or Stereo (TRS)
- Stackable (Piggy back) mounting
- Vertical or horizontal PCB mount
- Mono and Stereo switched contacts
- Solder contacts
- Combo Contacts
- Metal nut
- Plastic Nut
- 1/4” (6.35mm)
- 3.5mm
- Dual 1/4”(6.35mm) and 3.5mm
- EMI Shielding plates
- Metal Mounting threads
- Plastic Mounting threads
- Chassis Ground connections
- Half, Full or No threads
- Grounded or Isolated Jacks

1/4” Phone Jack Grounding/ Shielding Options



1/4” Gripper - Grounding points



1/4” Shielding Plate

Ordering Codes

We have listed the more common ordering codes in each section. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.


4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.










8) Please contact us directly if you have any further problems.



Features:









- 3.5mm and 6.35mm (1/4”) options
- Mono or Stereo (TRS)
- Single or Dual mounting
- Vertical or Horizontal PCB mount
- Mono and Stereo with switching contacts
- Solder or Combo contacts
- Various mounting option









Schematic Chart: Page 134
Panel Cutouts: Page 133
PCB Footprints: Page 135
Specifications: Page 137

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
3.5MM PHONE JACKS				
		3.5mm Jack, Horizontal PCB, Plastic housing, Metal entry bore	Mono	ACJM-NH35
			Stereo	ACJS-NH35
		3.5mm Jack, Vertical PCB mount, Needle eye contacts, Plastic housing, Metal entry bore	Refer to Schematic Chart on page 134	ACJM-NV35-2
				ACJM-NV35-2S
				ACJS-NV35-3
				ACJS-NV35-3S
				ACJS-NV35-5
		3.5mm Jack, Vertical PCB mount, Needle eye contacts, Plastic housing, Metal thread and entry bore	Refer to Schematic Chart on page 134	ACJM-MV35-2
				ACJM-MV35-2S
				ACJS-MV35-3
				ACJS-MV35-3S
				ACJS-MV35-5
		3.5mm / 1/4” (6.35mmø) Dual Phone Jack, (Piggyback), Horizontal PCB, Plastic housing, Metal nut and entry bore	Mono	ACJM-MHD985
			Stereo	ACJS-MHD985
		3.5mm / 1/4” (6.35mmØ) Dual Phone Jack, Vertical PCB mount, Needle eye contacts, Plastic housing, Metal nut and entry bore	Refer to Schematic Chart on page 134	ACJM-MVD985-2
				ACJM-MVD985-2S
				ACJS-MVD985-3
				ACJS-MVD985-3S
				ACJS-MVD985-5
1/4” PHONE JACKS HORIZONTAL				
		1/4” (6.35mmø) Phone Jack, Horizontal Snap-fit PCB, Plastic housing, Half thread, Metal entry bore. Supplied without mounting hardware.	Mono	ACJM-HHDR
			Stereo	ACJS-HHDR

Plugs & Jacks











1/4" / 3.5mm Phone Jack Connectors


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Phone Jack, Horizontal Snap-fit PCB, Plastic housing, Metal nut and entry bore	Mono	ACJM-MHDR
			Stereo	ACJS-MHDR
		1/4"(6.35mmø) Phone Jack, Horizontal Snap-fit PCB, Plastic housing, Metal thread, nut, washer and entry bore	Mono	ACJM-MHDRM
			Stereo	ACJS-MHDRM
		1/4" (6.35mmø) Offset Jack, Horizontal PCB mount, Plastic housing and entry bore with Half thread. Supplied without mounting hardware.	Refer to Schematic Chart on page 134	ACJM-HHOP
				ACJS-HHOP
		1/4" (6.35mmø) Offset Jack, Horizontal PCB mount, Plastic housing and entry bore with Half thread. Supplied without mounting hardware.	Refer to Schematic Chart on page 134	ACJM-HHOP-1
				ACJS-HHOP-1
		1/4" (6.35mmø) Offset Jack, Horizontal PCB mount, Plastic housing, thread and entry bore	Mono - Plastic Nut	ACJM-PHOP
			Mono - Metal Nut	ACJM-MHOP
			Stereo - Plastic Nut	ACJS-PHOP
			Stereo - Metal Nut	ACJS-MHOP
		1/4" (6.35mmø) Offset Jack, Horizontal PCB mount, Plastic housing, thread and entry bore. Non-switching sleeve contact with separate grounding to panel.	Refer to Schematic Chart on Page 110 PHOP - Denotes Plastic Nut MHOP - Denotes Metal Nut	ACJM-PHOP-1
				ACJM-MHOP-1
				ACJS-PHOP-1
				ACJS-MHOP-1
		1/4" (6.35mmø) Offset Jack, Horizontal PCB mount, Plastic housing, Metal thread and entry bore with Chassis ground connection	Mono - Metal Nut	ACJM-MHOM
			Stereo - Metal Nut	ACJS-MHOM
		1/4" (6.35mmø) Jack, Horizontal PCB mount, Plastic housing with metal insert	Mono - Plastic Nut	ACJM - PH
			Mono - Metal Nut	ACJM - MH

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Jack, Horizontal PCB mount, Plastic housing with metal insert	Stereo - Plastic Nut	ACJS - PH
			Stereo - Metal Nut	ACJS - MH
		1/4" (6.35mmø) Jack, Horizontal Snap-fit PCB mount, Plastic housing with metal insert	Mono - Plastic Nut	ACJM-PHR
			Mono - Metal Nut	ACJM-MHR
			Stereo - Plastic Nut	ACJS-PHR
			Stereo - Metal Nut	ACJS-MHR
		1/4" (6.35mmø) Jack, Combination Horizontal PCB and Solder lug, Plastic housing with metal insert	Mono - Plastic Nut	ACJM-PC
			Mono - Metal Nut	ACJM-MC
			Stereo - Plastic Nut	ACJS-PC
			Stereo - Metal Nut	ACJS-MC
		1/4" (6.35mmø) Jack, Solder Lug, Plastic housing with metal insert	Mono - Plastic Nut	ACJM-PHS
			Mono - Metal Nut	ACJM-MHS
			Stereo - Plastic Nut	ACJS-PHS
			Stereo - Metal Nut	ACJS-MHS
		1/4" (6.35mmø) Jack, Solder Lug, Plastic housing and Bezel with threaded Metal nut.	Mono	ACJM-IHS
			Stereo	ACJS-IHS
		1/4" (6.35mmø) Jack, Horizontal PCB mount, Plastic housing and Bezel with threaded Metal nut.	Mono	ACJM-IH
			Stereo	ACJS-IH
1/4" PHONE JACKS HORIZONTAL DUAL				
		1/4" (6.35mmø) Dual Phone Jack (Compact Piggyback), Horizontal Snap-fit PCB, Plastic housing, Metal nut and entry bore	Mono	ACJM-MHDC
			Stereo	ACJS-MHDC
		1/4"(6.35mmø) Dual Phone Jack (Compact Piggyback), Horizontal Snap-fit PCB, Plastic housing, Metal thread, nut and entry bore	Mono	ACJM-MHDCM
			Stereo	ACJS-MHDCM


Plugs & Jacks

1/4” / 3.5mm Phone Jack Connectors


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4” (6.35mmø) Dual Phone Jack (Piggyback) Horizontal Snap-fit PCB, Plastic housing, Metal nut and entry bore	Mono	ACJM-MHD
			Stereo	ACJS-MHD
		1/4”(6.35mmø) Dual Phone Jack (Pig-gyback) Shielding plate, Horizontal Snap-fit PCB, Plastic housing, Metal nut and entry bore	Mono	ACJM-MHDE
			Stereo	ACJS-MHDE
		1/4”(6.35mmø) Dual Phone Jack (Pig-gyback), Horizontal Snap-fit PCB, Plastic housing, Metal thread, nut, washer and entry bore	Mono	ACJM-MHDM
			Stereo	ACJS-MHDM
		1/4”(6.35mmø) Dual Phone Jack (Piggy-back), Shielding plate Horizontal Snap-fit PCB, Plastic housing, Metal thread, nut and entry bore	Mono	ACJM-MHDEM
			Stereo	ACJS-MHDEM
1/4” PHONE JACKS VERTICAL				
		1/4” (6.35mmØ) Jack, Vertical PCB mount, Plastic housing, nut and entry bore	Refer to Schematic Chart on page 134	ACJM-PVB-2
				ACJM-PVB-2S
				ACJS-PVB-3
				ACJS-PVB-3S
				ACJS-PVB-5
		1/4” (6.35mmø) Jack, Vertical PCB mount, Needle eye contacts, Plastic thread, Metal nut and insert	Refer to Schematic Chart on page 134	ACJM-MIV-2
				ACJM-MIV-2S
				ACJS-MIV-3
				ACJS-MIV-3S
				ACJS-MIV-5
		1/4” (6.35mmø) Jack, Vertical PCB mount, Needle eye contacts, Star washer, Metal nut and insert	Refer to Schematic Chart on page 134	ACJM-MN-2
				ACJS-MN-3
				ACJM-MN-2S
				ACJS-MN-3S
				ACJS-MN-5
		1/4” (6.35mmø) Jack, Vertical PCB mount, Metal nut and insert	Refer to Schematic Chart on page 134	ACJM-MV-2
				ACJM-MV-2S
				ACJS-MV-3
				ACJS-MV-3S
				ACJS-MV-5

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		1/4" (6.35mmø) Jack, Solder Lug, Metal nut and insert	Refer to Schematic Chart on Page 110	ACJM-MVS-2 ACJM-MVS-2S ACJS-MVS-3 ACJS-MVS-3S ACJS-MVS-5


PANEL CUTOUTS
-FRONT VIEW




ACJM-MV
ACJS-MV
ACJM-MN-2
ACJS-MN-3
ACJM-MN-2S
ACJS-MN-3S
ACJS-MN-5
ACJM-MIV
ACJS-MIV
ACJM-MVS
ACJS-MVS




ACJM/S-PH
ACJM/S-MH
ACJM/S-PC
ACJM/S-MC
ACJM/S-PHR
ACJM/S-MHR
ACJM/S-PHS
ACJM/S-MHS




ACJM-MHD
ACJS-MHD
ACJM-MHDE
ACJS-MHDE




ACJM-MHDR
ACJS-MHDR
ACJS-HHDR




ACJM-NH35
ACJS-NH35




ACJM-NV35-2
ACJM-NV35-2S
ACJS-NV-35-3
ACJS-NV-35-3S
ACJS-NV-35-5
ACJM-MV35-2
ACJM-MV35-2S
ACJS-MV-35-3
ACJS-MV-35-3S
ACJS-MV-35-5




ACJS-MHDC
ACJM-MHDC




ACJS-IH
ACJM-IH
ACJS-IHS
ACJM-IHS




ACJS-MHD985
ACJM-MHD985




ACJS-MHOM
ACJM-MHOM



ACJS-MHOP
ACJS-PHOP
ACJM-MHOP
ACJM-PHOP
ACJS-MHOP-1
ACJS-HHOP-1
ACJS-PHOP-1
ACJM-PHOP-1
ACJM-MHOP-1
ACJM-HHOP-1
ACJM-HHOP
ACJS-HHOP













ACJS-MVD985
ACJM-MVD985







ACJM-PVB-2
ACJM-PVB-2S
ACJS-PVB-3
ACJS-PVB-3S
ACJS-PVB-5


SCHEMATIC CHART

PART NO.	ACJM-MV35-2 ACJM-MN-2 ACJM-NV35-2 ACJM-PVB-2 ACJM-MV-2 ACJM-MVS-2 ACJM-MIV-2	ACJM-MV35-2S ACJM-MN-2S ACJM-NV35-2S ACJM-PVB-2S ACJM-MV-2S ACJM-MVS-2S ACJM-MIV-2S	ACJS-MV35-3 ACJS-MN-3 ACJS-NV35-3 ACJS-PVB-3 ACJS-MV-3 ACJS-MVS-3 ACJS-MIV-3	ACJS-MV35-3S ACJS-MN-3S ACJS-NV35-3S ACJS-PVB-3S ACJS-MV-3S ACJS-MVS-3S ACJS-MIV-3S	ACJS-MV35-5 ACJS-MN-5 ACJS-NV35-5 ACJS-PVB-5 ACJS-MV-5 ACJS-MVS-5 ACJS-MIV-5
GENERAL SCHEMATIC					


PART NO.	ACJM-MVD985-2	ACJM-MVD985-2S	ACJS-MVD985-3	ACJS-MVD985-3S	ACJS-MVD985-5
SCHEMATIC					

PART NO.	ACJM-HHOP-1 ACJM-PHOP-1 ACJM-MHOP-1	ACJS-HHOP-1 ACJS-PHOP-1 ACJS-MHOP-1	ACJM-HHOP ACJM-PHOP ACJM-MHOP	ACJS-HHOP ACJS-PHOP ACJS-MHOP
GENERAL SCHEMATIC				


PCB FOOTPRINT
- CONNECTOR SIDE OF PCB




ACJM-MV
ACJS-MV
ACJM-MN-2
ACJS-MN-3
ACJM-MN-2S
ACJS-MN-3S
ACJS-MN-5
ACJM-NV35-XX
ACJM-MV35-XX
ACJS-NV35-XX
ACJS-MV35-XX
ACJM-MIV-2
ACJM-MIV-2S
ACJS-MIV-3
ACJS-MIV-3S
ACJS-MIV-5




ACJM-PH
ACJM-MH
ACJS-PH
ACJS-MH
ACJM-PC
ACJM-MC
ACJS-PC
ACJS-MC




ACJM-MHD
ACJS-MHD
ACJM-MHDE
ACJS-MHDE
ACJM-MHDEM
ACJS-MHDEM
ACJM-MHDC
ACJS-MHDC
ACJM-MHDCM
ACJS-MHDCM
ACJM-MHDM
ACJS-MHDM




ACJM-MHDR
ACJS-MHDR
ACJM-PHR
ACJM-MHR
ACJS-PHR
ACJS-MHR
ACJM-HHDR
ACJS-HHDR
ACJM-MHDRM
ACJS-MHDRM




ACJS-IH
ACJM-IH




ACJS-MHD985
ACJM-MHD985




ACJS-MHOM
ACJM-MHOM




ACJS-MHOP-1
ACJS-PHOP-1
ACJS-HHOP-1
ACJM-MHOP-1
ACJM-PHOP-1
ACJM-HHOP-1




ACJS-MHOP
ACJS-PHOP
ACJM-MHOP
ACJM-PHOP
ACJM-HHOP
ACJS-HHOP



ACJS-MVD985
ACJM-MVD985



ACJS-NH35
ACJM-NH35



ACJM-PVB-2
ACJM-PVB-2S
ACJS-PVB-3
ACJS-PVB-3S
ACJS-PVB-5

1/4" PLUGS TECHNICAL DATA

		VALUE
GENERAL CHARACTERISTICS	Number of Contacts	2 Pole (Mono) 3 Pole Tip Ring Sleeve (Stereo)
	Termination	Solder
	Max. Wire Gauge - Stranded Wire	2 Pole (Mono): AWG 16˜1.5mm² 3 Pole (Stereo): AWG 18˜1mm²
	Flammability rating of insulating plastics	UL94V-0
	Solderability, complies with	IEC 68-2-20
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity	10A (Depends on Mating Connector and Cable)
	Typical Contact Resistance	Depends on Mating Connector
	Insulation resistance (initial) After Damp Heat Test	>2GΩ ≥1GΩ
	Dielectric Withstand Voltage	2 Pole : 1.5 kV dc 3 Pole : 1 kV dc
CLIMATIC CHARACTERISTICS	Protection Class	IP40
	Operating Temperature	-25ºC to +70ºC (-13ºF to 158ºF)
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force	≥10N - ≤30N
	Mating Cycles	Min. of 1000 cycles without any physical damage
	Cable O.D. - M Series - M Series II	 3mm to 6.5mm (0.118" to 0.256") 6.5mm to 8mm (0.256" to 0.315")
MATERIALS	Connector Shell Material	Diecast Zinc Alloy EZDA No.3
	Connector Shell Finish	Satin Nickel or Black Polyester
	Insulators	UL94 V-0 PBT Resin or Modified PPE Resin and fibreglass laminate
	Cable Bushing	Santoprene
	Contact Plating	Brass / Ni over Cu (Copper)

Rev 4 - 05/2014

[1)]Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.

1/4" JACKS TECHNICAL DATA

		VALUE
GENERAL CHARACTERISTICS	Number of Contacts	2 Pole (Mono) 3 Pole Tip Ring Sleeve (Stereo)
	Termination	Solder, PCB or Combo
	Flammability rating of insulating plastics	UL94V-0 or UL94-HB
	Solderability, complies with	IEC 68-2-20
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity	10A (Depends on Mating Connector and Cable)
	Typical Contact Resistance	≤10mΩ
	Insulation resistance (initial) After Damp Heat Test	>2GΩ ≥10^3 Meg Ω
	Rated Voltage Test Voltage AC RMS: Dielectric Strength	34V 500V
CLIMATIC CHARACTERISTICS	Protection Class	IP40
	Operating Temperature	-25ºC to +70ºC (-13ºF to 158ºF)
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force	≥10N - ≤30N
	Mating Cycles	Min. of 10,000 cycles
	Weight - Straight - Right Angle	 18g (0.039lb) 25g (0.055lb)
MATERIALS	Connector Housing	Nylon PA66 30% Glass Filled
	Metal Nut	Brass
	Plastic Nut	Nylon PA66 30% Glass Filled
	Washer	Fiber / Brass / Nylon PA66 30% Glass Filled
	Contact Plating	Tin - 4μm Min. over 2μm Min.Cu (Copper) Silver - 0.3μm Min. over 2μm Min.Cu (Copper) Nickel - 2μm Min. over 2μm Min.Cu (Copper) Gold Flash - 0.05μm Min. over 2μm Min.Cu (Copper)
	Contacts	Brass / Sn (Tin) over Cu (Copper)

Rev 7 - 04/2023






[1]Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.



K SERIES PLUGS (3.5MM)

Features:
- Mono or TRS (Stereo).
- AX Series inspired shell design.
- Suits Cable O.D from 2.5mm to 5mm (0.098" to 0.196")
- Robust diecast shell in Satin nickel or Black finish.
- Nickel or Gold contact plating.
- Flexible grommet cable protection.
- Improved solderability.
- Precision machined contacts.
- Standard or Bulk packaging.


Options: Black Shell, Gold contacts.

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		3.5mm, Mono Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	KM2P
			Gold Plated Contacts	KM2P-AU
			Bulk Pack	KM2P BULK
		3.5mm, Mono Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	KM2PB
			Gold Plated Contacts	KM2PB-AU
			Bulk Pack	KM2PB BULK
		3.5mm, Stereo Phone plug, Diecast Shell, Satin finish, Flexible grommet.	Standard	KS3P
			Gold Plated Contacts	KS3P-AU
			Bulk Pack	KS3P BULK
		3.5mm, Stereo Phone plug, Diecast Shell, Black finish, Flexible grommet.	Standard	KS3PB
			Gold Plated Contacts	KS3PB-AU
			Bulk Pack	KS3PB BULK
		3.5mm, Stereo Phone plug with extended shaft for mobile phones fitted with covers. Diecast Shell, Black Chrome finish, Flexible grommet	Standard	KS3PC
			Gold Plated Contacts	KS3PC-AU

PART NUMBER BREAKDOWN


K-SERIES

E. G . **KS3P-AU BULK**
K (Series Prefix), **S3**(Stereo), **P**lug,
- **AU** (Gold Plated Contacts), **Bulk** Packaged.



SERIES PREFIX	K	=	Series Prefix
CONTACT TYPE	M2	=	2 Pole (mono)
	S3	=	3 pole TRS (Stereo)
SHELL TYPE AND FINISH	P	=	Plug Satin Nickel
	PB	=	Plug Matt Black
	PC	=	Plug Black Chrome
BACKSHELL TYPE AND CABLE CLAMP	Blank	=	K Series to suit Cable O.D 2.5mm to 5mm (0.098" to 0.196")
CONTACT PLATING	Blank	=	Nickel Plated Contacts (Standard)
	AU	=	Gold Plated Contacts
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

ISO VIEW OF KS3P



3.5mm PLUG TECHNICAL DATA

		VALUE
GENERAL CHARACTERISTICS	Number of Contacts	2 Pole (Mono) 3 Pole Tip Ring Sleeve (Stereo)
	Termination	Solder
	Wire Gauge - Stranded Wire	2 Pole (Mono): AWG 16 - 1.5mm^2 3 Pole (Stereo): AWG 18 - 1mm^2
	Flammability rating of insulating plastics	UL94V-0
	Solderability, complies with	IEC 68-2-20
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity	>0.5mA (Depends on Mating Connector and Cable)
	Typical Contact Resistance	≤20mΩ (Depends on Mating Connector and Cable)
	Insulation resistance (initial) After Damp Heat Test	>200M Ω >100M Ω
	Test Voltage AC RMS: Dielectric Strength	250VAC
CLIMATIC CHARACTERISTICS	Protection Class	IP40
	Operating Temperature	-20ºC to +65ºC (-4ºF to +149ºF)
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force	<20N / >3N (depends on mating connector)
	Cable O.D.	3mm to 5mm (0.118" to 0.196")
	Mechanical Operations	1000 mating cycles
	Weight	8g (0.017lb)
MATERIALS	Connector Shell Material (Plugs)	Diecast Zinc Alloy EZDA No.3
	Connector Shell Finish	Satin Nickel or Black Polyester
	Insulators	PA66
	Cable Bushing	Santoprene
	Contacts	Brass
	Plating	Nickel or Gold Flash

[1] Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.



PLUGS AND SOCKETS

Amphenol's plugs and sockets range continually expands to meet the needs of our customers. The success of the M-Series phone plugs led to the RCA series being developed. The Miniature XLR range was a natural progression from our standard XLR series as demand for smaller interconnects increased. The latest addition to the range is a professional grade 3.5mm phone plug designed for applications that require a robust interconnect.

Applications

- Audio Cables and Snakes
- Amplifiers
- Speakers
- Mixing desks
- Rack mount equipment
- Patch panel

Features / Options – RCA Plugs and Jacks

- Red, Black, White, Yellow, Blue or Green shell colours
- Stylish shell design
- Flexible grommet cable protection
- Gold Plated Contacts

Features / Options – Miniature XLR

- 3,4,5, or 6 contacts
- Solder cup
- Printed Circuit Board
- Vertical or Horizontal mounting
- Positive locking latch
- Flexible cable clamp
- Metal cable clamp
- Locking rings
- Chassis front mount
- Chassis middle or rear mount (on request)
- Optional black finish (on request)


Features / Options – 3.5mm Plugs Phone Jack

- Mono / Stereo TRS
- Solder contacts
- Suits cable O.D 2.5mm to 5mm
- Stylised shell design
- Flexible cable grommet
- Metal cable clamp
- Nickel or Gold contact plating
- Satin Nickel or Black finish

Cable Clamp Options



RCA Cable Clamp - M-Series, Cable O.D 3mm to 6.5mm (0.118" to 0.256")



K-Series, Cable O.D 3mm to 5mm (0.118" to 0.196")

Ordering Codes

We have listed the more common ordering codes in each section. Please contact us if you need any further assistance.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use variations column to determine your choice.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.






8) Please contact us directly if you have any further problems.




RCA SERIES

Features:
- Stylish design
- Flexible grommet cable protection
- Robust diecast shell
- Gold plated contacts
- Colour coded
- Good solderability
- Quick and easy assembly
- Panel mount utilises standard 'D' type housing

Part Number Breakdown: Page 143

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		RCA Plug, Diecast Shell, Gold plated contacts, Coloured finish, Flexible coloured grommet	Red	ACPR-RED
			Black	ACPR-BLK
			Yellow	ACPR-YEL
			White	ACPR-WHT
			Blue	ACPR-BLU
			Green	ACPR-GRN
		RCA Plug, Diecast Shell, Gold plated contacts, Satin finish, Flexible coloured grommet	Satin / Red	ACPR-SRD
			Satin / Black	ACPR-SBK
			Satin / Yellow	ACPR-SYL
			Satin / White	ACPR-SWH
			Satin / Blue	ACPR-SBL
			Satin / Green	ACPR-SGR
		RCA Jack, Diecast Shell, Gold plated contacts, Coloured finish, Flexible coloured grommet	Red	ACJR-RED
			Black	ACJR-BLK
			Yellow	ACJR-YEL
			White	ACJR-WHT
			Blue	ACJR-BLU
			Green	ACJR-GRN
		RCA Jack, Diecast Shell, Gold plated contacts, Satin finish, Flexible coloured grommet	Satin / Red	ACJR-SRD
			Satin / Black	ACJR-SBK
			Satin / Yellow	ACJR-SYL
			Satin / White	ACJR-SWH
			Satin / Blue	ACJR-SBL
			Satin / Green	ACJR-SGR
		RCA Plug, Shortened Diecast Shell, Gold plated contacts, Black Chrome finish, Flexible coloured grommet	Red	ACPL-CRD
			Black	ACPL-CBK
			Yellow	ACPL-CYL
			White	ACPL-CWH
			Blue	ACPL-CBL
			Green	ACPL-CGR

NOTE: RCA Series comply with EU RoHS 2 Directive 2011/65/EU


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		RCA Jack, Diecast Shell, Gold plated contacts, Nickel finish shell, coloured insulator.	Red	ACJD-RED
			Black	ACJD-BLK
			Yellow	ACJD-YEL
			White	ACJD-WHT
			Blue	ACJD-BLU
			Green	ACJD-GRN

NOTE: RCA Series comply with EU RoHS 2 Directive 2011/65/EU

PART NUMBER BREAKDOWN

M SERIES RCA

E. G . **ACPR-RED BULK**
AC (Series Prefix), **P**lug, **R**(Shell type), **RED** (Shell and Grommet Colour),
Bulk Packaged.



SERIES PREFIX	AC	=	Series Prefix
CONTACT TYPE	J	=	RCA Female Jack
	P	=	RCA Male Plug
SHELL TYPE	R	=	Regular Shell Length
	L	=	Short Shell Length
	D	=	Chassis Jack 'D' Shell
SHELL AND GROMMET COLOUR	RED	=	Red, Red Grommet
	BLK	=	Black, Black Grommet
	YEL	=	Yellow, Yellow Grommet
	WHT	=	White, White Grommet
	BLU	=	Blue, Blue Grommet
	GRN	=	Green, Green Grommet
	SRD	=	Satin Nickel,Red Grommet
	CRD	=	Black Chrome, Red Grommet
	SBK	=	Satin Nickel, Black Grommet
	CBK	=	Black Chrome, Black Crommet
	SYL	=	Satin Nickel, Yellow Grommet
	CYL	=	Black Chrome, Yellow Grommet
	SWH	=	Satin Nickel, White Grommet
	CWH	=	Black Chrome, White Grommet
	SBL	=	Satin Nickel, Blue Grommet
	CBL	=	Black Chrome, Blue Grommet
	SGR	=	Satin Nickel, Green Grommet
	CGR	=	Black Chrome, Green Grommet
	NOTE: Denotes colour of insulator only on shell type D, Chassis Jack 'D' Shell. Shell finish is Nickel.		
PACKAGING	Blank	=	Individual Bags
	BULK	=	Bulk Packed

RCA TECHNICAL DATA

		VALUE	
GENERAL CHARACTERISTICS	Number of Contacts	2	
	Termination	Solder	
	Max. Wire Gauge - Stranded Wire	AWG 14 - 2.5mm²	
	Flammability rating of insulating plastics	UL94V-0	
	Solderability, complies with	IEC 68-2-20	
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU	
ELECTRICAL CHARACTERISTICS	Current Carrying Capacity	10A (Depends on Mating Connector)	
	Typical Contact Resistance	≤10mΩ (Depends on Mating Connector)	
	Insulation resistance (initial) After Damp Heat Test	>2GΩ ≥ 10^3 Meg Ω	
	Dielectric Strength	1500 V dc	
CLIMATIC CHARACTERISTICS	Protection Class	IP40	
	Operating Temperature	-25ºC to +75ºC (-13ºF to +167ºF)	
MECHANICAL CHARACTERISTICS	Insertion and Withdrawal Force	≥10N - ≤30N (depends on mating connector)	
	Cable O.D.	ACPL with grommet without grommet	 3mm to 6.5mm (0.118" to 0.255") 3mm to 8.5mm (0.118" to 0.334")
		ACPR with grommet without grommet	 3mm to 7mm (0.118"to 0.275") 3mm to 8.5mm (0.118" to 0.334")
	Mechanical Operations	500 mating cycles	
	Weight - Cable Mount - Panel Mount	 18g (0.039lb) 30g (0.066lb)	
MATERIALS	Connector Shell Material (Plugs)	Diecast Zinc Alloy EZDA No.3	
	Connector Shell Finish	Satin Nickel or Coloured Polyester	
	Insulators	PA66	
	Cable Bushing	Thermoplastic Polyurethane	
	Contacts	Brass Alloy	
	Plating	Gold Flash	

Rev 5 - 10/2024

[1)]Approximate weight only, does not include packaging. Please contact us for exact weight for shipping purposes.



MULTIPIN CONNECTORS

Amphenol has an extensive range of circular and rectangular multi-pin connectors ideally suited to the entertainment industry. Featuring rugged housings and precision made contacts these connectors have proven themselves in the most demanding of applications. The extensive arrangement of different connector sizes and contact numbers ensure we can offer a solution to your multi-pin wiring applications.

Applications

- Audio Cables and Snakes
- Lighting control
- Concert Touring Systems
- Outside Broadcast Systems

Features / Options - MP-41 Series

- 13 to 85 pins with Crimp / Solder bucket contacts
- 150 pins with Crimp contacts only
- 4 to 48 channel
- Gold plated contacts
- Synthetic inserts
- Environmental resistant
- Positive Bayonet locking
- PG cable gland
- 2000 mating cycles
- Bayonet wear pins
- Extended coupling ring
- Metal Housings

Features / Options - MP-62 Series

- 39 or 61 Solder bucket contacts
- Gold plated contacts
- Neoprene inserts
- Environmental resistant
- Positive Bayonet locking
- PG cable gland or NPT thread
- Metal Housings

Ordering Codes

We have listed the more common ordering codes in each section. For further options please contact us.

Simple steps to guide you in using this catalogue

1) Identify the product group listed in Contents on page 1 and go directly to that page number.

2) Each product group cover page then details information and options available.

3) Refer to the product detail pages and identify the product you require pictorially.

4) Read the product description column for the products standard features.

5) Use pins column to determine number of contacts.

6) Identify part number.

7) In the event the particular option you require is not listed please refer to the part number breakdown page at the end of each section.

8) Please contact us directly if you have any further problems.



MP-41 SERIES





Amphenol's MP-41 series of multipin connectors utilise the same design principals of the rugged Mil-C-5015 military connectors. They can withstand high shock and vibration environments and are ideal for tough on-road applications. Featuring a quick mating bayonet coupling with an audible full mating feature ensures a positive connection every time. Available from 13 to 150 pins with contacts supplied with each connector as standard.

Features:





- 13 to 85 pins with Crimp/Solder bucket contacts
- 150 pins with Crimp contacts only
- 4 to 48 channels
- Gold plated contacts
- Synthetic insert
- Protective dust caps
- Industry standard compatible
- 2000 mating cycles
- Black finish
- Positive bayonet locking
- PG cable glands
- IP67 rated
- Metal housings

Options: NPT threaded backshells.

Crimp Tooling: Page 149
Specifications: Page 150 **Part Number Breakdown: Page 149**
Wiring Information: Page 141



PRODUCT - FIGURE	Dimensions in mm (inches) DRAWING	Dimensions in mm (inches) A	B	PG	PINS	PART NUMBER	PART NUMBER With Dustcap
	Straight cable plug with socket contacts, Black finish, supplied complete with contacts.  13, 19, 25, 37 and 54 contact type  85 and 150 contact type	40.5 (1.60)	160 (6.30)	11	13	MP-4106-13S	MP-4106-13S-C
		44 (1.73)	171 (6.73)	13.5	19	MP-4106-19S	MP-4106-19S-C
		46.6 (1.83)	193 (7.60)	16	25	MP-4106-25S	MP-4106-25S-C
		54.3 (2.14)	210 (8.26)	21	37	MP-4106-37S	MP-4106-37S-C
		60.1 (2.36)	210 (8.26)	21	54	MP-4106-54S	MP-4106-54S-C
		73.3 (2.88)	137 (5.40)	29	85	MP-4106-85S	MP-4106-85S-C
		73.3 (2.88)	145 (5.70)	36	150	MP-4106-150S	MP-4106-150S-C
	Cable connecting receptacle with pin contacts, black finish, supplied complete with contacts.  13, 19, 25, 37 and 54 contact type  85 and 150 contact type	37.8 (1.49)	160 (6.30)	11	13	MP-4101-13P	MP-4101-13P-C
		41.1 (1.62)	171 (6.73)	13.5	19	MP-4101-19P	MP-4101-19P-C
		41.5 (1.63)	193 (7.60)	16	25	MP-4101-25P	MP-4101-25P-C
		51 (2.00)	210 (8.26)	21	37	MP-4101-37P	MP-4101-37P-C
		57.1 (2.25)	210 (8.26)	21	54	MP-4101-54P	MP-4101-54P-C
		70 (2.75)	137 (5.40)	29	85	MP-4101-85P	MP-4101-85P-C
		70 (2.75)	145 (5.70)	36	150	MP-4101-150P	MP-4101-150P-C



Note: NPT threaded backshells available on request. Please contact us.

PRODUCT - FIGURE	Dimensions in mm (inches) DRAWING	Dimensions in mm (inches) A	B	C	D	E	F	PINS	PART NUMBER	PART NUMBER With Dustcap
	Panel plug with socket contacts, black finish, supplied complete with contacts. 	38 (1.49)	29.4 (1.15)	3.2 (0.13)	40.5 (1.60)	38.8 (1.53)	N/A	13	MP-4164-13S	MP-4164-13S-C
		41 (1.61)	31.8 (1.25)	3.2 (0.13)	44 (1.73)	38.8 (1.53)	N/A	19	MP-4164-19S	MP-4164-19S-C
		44.5 (1.75)	34.9 (1.37)	3.73 (0.14)	48.51 (1.91)	40.6 (1.60)	N/A	25	MP-4164-25S	MP-4164-25S-C
		50.8 (1.99)	39.7 (1.56)	3.73 (0.14)	54.3 (2.14)	42 (1.65)	N/A	37	MP-4164-37S	MP-4164-37S-C
		57 (2.24)	44.5 (1.75)	4.39 (0.17)	60.8 (2.40)	45 (1.77)	N/A	54	MP-4164-54S	MP-4164-54S-C
		69.8 (2.74)	55.5 (2.18)	4.39 (0.17)	73.3 (2.88)	45 (1.77)	N/A	85	MP-4164-85S	MP-4164-85S-C
		69.8 (2.74)	55.5 (2.18)	4.39 (0.17)	73.3 (2.88)	45 (1.77)	N/A	150	MP-4164-150S	MP-4164-150S-C
	Panel receptacle with pin contacts, black finish, supplied complete with contacts. 	38 (1.49)	29.4 (1.15)	3.23 (0.13)	34.2 (1.34)	34.5 (1.35)	29 (1.14)	13	MP-4102-13P	MP-4102-13P-C
		41 (1.61)	31.8 (1.25)	3.23 (0.13)	37.4 (1.47)	34.5 (1.35)	32.2 (1.26)	19	MP-4102-19P	MP-4102-19P-C
		44.5 (1.75)	34.9 (1.37)	3.73 (0.14)	40.9 (1.61)	35.7 (1.40)	35.3 (1.38)	25	MP-4102-25P	MP-4102-25P-C
		50.8 (1.99)	39.7 (1.56)	3.73 (0.14)	46.7 (1.83)	36.5 (1.44)	41.4 (1.62)	37	MP-4102-37P	MP-4102-37P-C
		57 (2.24)	44.5 (1.75)	4.30 (0.17)	53.4 (2.10)	38.5 (1.52)	47.8 (1.88)	54	MP-4102-54P	MP-4102-54P-C
		69.8 (2.74)	55.5 (2.18)	4.30 (0.17)	65.5 (2.57)	38.5 (1.52)	59 (2.32)	85	MP-4102-85P	MP-4102-85P-C
		69.8 (2.74)	55.5 (2.18)	4.30 (0.17)	65.5 (2.57)	38.5 (1.52)	59 (2.32)	150	MP-4102-150P	MP-4102-150P-C
	Plug protective dustcap to suit MP-4164 type. 	34.16 (1.35)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	13	MP-25042-13S	-
		37.36 (1.47)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	19	MP-25042-19S	-
		40.87 (1.61)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	25	MP-25042-25S	-
		46.68 (1.84)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	37	MP-25042-37S	-
		53.36 (2.10)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	54	MP-25042-54S	-
		65.48 (2.58)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	85	MP-25042-85S	-
		65.48 (2.58)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	150	MP-25042-150S	-
	Receptacle protective dustcap to suit MP-4106 types. 	38.8 (1.53)	20.7 (0.81)	255 (8.07)	-	-	-	13	MP-25042-13L	-
		41.6 (1.64)	20.7 (0.81)	255 (8.07)	-	-	-	19	MP-25042-19L	-
		45.3 (1.78)	20.7 (0.81)	255 (8.07)	-	-	-	25	MP-25042-25L	-
		52.15 (2.05)	20.7 (0.81)	255 (8.07)	-	-	-	37	MP-25042-37L	-
		58.6 (2.30)	20.7 (0.81)	255 (8.07)	-	-	-	54	MP-25042-54L	-
		70.7 (2.78)	20.7 (0.81)	255 (8.07)	-	-	-	85	MP-25042-85L	-
		70.7 (2.78)	20.7 (0.81)	255 (8.07)	-	-	-	150	MP-25042-150L	-

Multipin Connectors

MP-41 Series

PRODUCT - FIGURE	Dimensions in mm (inches) DRAWING	Dimensions in mm (inches) A	B	C	D	E	F	PINS	PART NUMBER
	Plug protective dustcap to suit MP-4102 types. 	34.16 (1.35)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	13	MP-25043-13S
		37.36 (1.47)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	19	MP-25043-19S
		40.87 (1.61)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	25	MP-25043-25S
		46.68 (1.84)	31.5 (1.24)	110 (4.33)	4.7 (0.18)	-	-	37	MP-25043-37S
		53.36 (2.10)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	54	MP-25043-54S
		65.48 (2.58)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	85	MP-25043-85S
		65.48 (2.58)	31.5 (1.24)	110 (4.33)	5.5 (0.22)	-	-	150	MP-25043-150S
	Receptacle protective dustcap to suit MP-4101 types. 	38.8 (1.53)	20.7 (0.81)	255 (8.07)	-	-	-	13	MP-25043-13L
		41.6 (1.64)	20.7 (0.81)	255 (8.07)	-	-	-	19	MP-25043-19L
		45.3 (1.78)	20.7 (0.81)	255 (8.07)	-	-	-	25	MP-25043-25L
		52.15 (2.05)	20.7 (0.81)	255 (8.07)	-	-	-	37	MP-25043-37L
		58.6 (2.30)	20.7 (0.81)	255 (8.07)	-	-	-	54	MP-25043-54L
		70.7 (2.78)	20.7 (0.81)	255 (8.07)	-	-	-	85	MP-25043-85L
		70.7 (2.78)	20.7 (0.81)	255 (8.07)		-	-	150	MP-25043-150L

PRODUCT - FIGURE	DRAWING	DESCRIPTION	NO. OF PINS	PART NUMBER
	N/A	Crimp Tool	All	M22520/1-01
	N/A	Positioner / Turret	All	TH29-1
	N/A	Insertion tool	13-85	MP-INS-16
			150	MP-INS-18
	N/A	Extraction tool	All	MP-EXT-16/18
	N/A	Contact Pilot Pin	13-85	MP-GUIDE-16
			150	MP-GUIDE-18
	N/A	Solder/Crimp Pin Contact	13-85 (Size 16)	MP-108400
		Crimp Pin Contact (Soldering of this contact is not recommended)	150 (Size 18)	MP-108300
	N/A	Solder/Crimp Socket Contact	13-85 (Size 16)	MP-108600
		Crimp Socket Contact (Soldering of this contact is not recommended)	150 (Size 18)	MP-108500


NOTE: Complete instructions for providing reliable crimped wire to contact terminations and inserting proprietary contacts in MP-41 Series connectors are available in publication Pi523 located on our website www.amphenolaudio.com.

PART NUMBER BREAKDOWN MP-41 SERIES

MULTIPIN CIRCULAR CONNECTORS

E. G . **MP-4106-85S**
Multipin, **4106** Cable Plug, **85** Contacts, **S** Female Socket Contacts,

SERIES PREFIX	MP	=	Series Prefix
HOUSING TYPE	4101	=	Inline cable connecting receptacle
	4102	=	Panel receptacle
	4106	=	Cable plug
	4164	=	Panel plug
	25042S	=	Dustcap for panel plug
	25042L	=	Dustcap for cable plug
	25043S	=	Dustcap for panel receptacle
	25043L	=	Dustcap for cable receptacle
NO. OF CONTACTS			13, 19, 25, 37, 54, 85, 150
GENDER *Not required for dustcap part numbers	P	=	Male pin contacts
	S	=	Female socket contacts
OPTIONS	C	=	Supplied with Dustcap



STANDARD DATA MP-41 SERIES

		VALUE						
GENERAL CHARACTERISTICS	Number of contacts	13	19	25	37	54	85	150
	Number of channels	4	6	8	12	16	28	48
	Termination	Solder / Crimp “Combo”						Crimp
	Wire Gauge - Stranded Wire	16AWG - 20AWG						18AWG
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU						
ELECTRICAL CHARACTERISTICS	Operating Voltage at Sea level - DC	250V*						250V*
	Operating Voltage at Sea level - AC	200V*						200V*
	Test Voltage AC RMS	1000V						1000V
	Current Carrying Capacity	13A						7.5A
	Typical Contact Resistance	3.46mΩ						11.25mΩ
	Insulation Resistance	5000MΩ						
CLIMATIC CHARACTERISTICS	Protection Class	IP67 (when mated)						
	Operating Temperature	-55°C to +125°C (-67°F to +257°F)						
MECHANICAL CHARACTERISTICS	Cable Retention	PG Gland						
	Mechanical Operations	2000 mating cycles						
MATERIALS	Connector / Shell Finish	Aluminium Alloy / Black						
	Insert	Synthetic Insert to MIL-R-3065						
	Male pin contact / Plating	Brass / Gold plated						
	Female socket contact / Plating	Brass / Gold plated						
CLAMPING CHARACTERISTICS	PG Gland	11	13.5	16	21		29	36
	Cable Clamping range mm	4-10	5-12	9-14	13-18		14-25	19-32
	(inches)	(0.15”-0.39”)	(0.19”-0.47”)	(0.35”-0.55”)	(0.51”- 0.70”)		(0.55”-0.98”)	(0.74”-1.25”)

Rev 2 - 03/2013

*Not suitable for domestic applications above 50V







MP-62/65 SERIES

Amphenol's Multipin MP-62 series of circular connectors utilise the same design principles as the Mil-C-26482 military connectors. Featuring a three point quick mating bayonet coupling and five key polarisation ensuring a positive connection every time. Available in two contact pin layouts 39 and 61 with gold plated solder contacts fitted as standard.

Features:



- 39 or 61 pins.
- Gold plated solder contacts.
- Neoprene insert.
- Protective dust caps
- Metal housings
- Environmental resistant.
- Black finish.
- Positive bayonet locking
- PG cable glands





Specifications: Page 153 **Wiring Info: Page 141**

PRODUCT - FIGURE	Dimensions in mm (inches) DRAWING	Dimensions in mm (inches) A	B	PG	PINS	PART NUMBER	PART NUMBER With Dustcap
	Straight cable plug with pin contacts, Black finish, Gold plated solder contacts. 	38.9 (1.53)	181.5 (7.15)	16	39	MP-6216-39P	MP-6216-39P-C
		45.5 (1.80)	193 (7.60)	21	61	MP-6216-61P	MP-6216-61P-C
	Cable connecting receptacle with socket contacts, Black finish, Gold plated solder contacts. 	36.7 (1.45)	181.5 (7.15)	16	39	MP-6211-39S	MP-6211-39S-C
		43.0 (1.70)	193 (7.60)	21	61	MP-6211-61S	MP-6211-61S-C
	Straight cable plug with pin contacts, NPT 3/4" threaded backshell, Black finish, Gold plated solder contacts. 	38.9 (1.53)	90 (3.54)	NPT 3/4"	39	MP-6516-39P	MP-6516-39P-C
		45.5 (1.80)	100 (3.94)	NPT 3/4"	61	MP-6516-61P	MP-6516-61P-C
	Cable connecting receptacle with socket contacts, NPT 3/4" threaded backshell, Black finish, Gold plated solder contacts. 	36.7 (1.45)	90 (3.54)	NPT 3/4"	39	MP-6511-39S	MP-6511-39S-C
		43.0 (1.70)	100 (3.94)	NPT 3/4"	61	MP-6511-61S	MP-6511-61S-C

Multipin Connectors

MP-62/65 Series

PRODUCT - FIGURE	Dimensions in mm (inches) DRAWING	Dimensions in mm (inches) A	B	C	D	E	F	PINS	PART NUMBER	PART NUMBER With Dustcap
	Panel plug with pin contacts, Black finish, Gold plated solder contacts. 	38.86 (1.53)	29.36 (1.16)	6-32 UNC	39.0 (1.54)	32 (1.26)	-	39	MP-6256-39P	MP-6256-39P-C
		43.94 (1.73)	34.93 (1.38)	6-32 UNC	45.5 (1.80)	35 (1.38)	-	61	MP-6256-61P	MP-6256-61P-C
	Panel receptacle plug with socket contacts, Black finish, Gold plated solder contacts. 	36.7 (1.44)	29.36 (1.15)	3.05 (0.12)	31.8 (1.25)	22.3 (0.87)	30.1 (1.18)	39	MP-6212-39S	MP-6212-39S-C
		43.0 (1.69)	34.93 (1.38)	3.74 (0.15)	38.1 (1.50)	22.3 (0.87)	36.4 (1.43)	61	MP-6212-61S	MP-6212-61S-C


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	Dimensions in mm (inches) A D	B	C		PINS	PART NUMBER
		Plug protective dustcap to suit MP-6256	31.7 (1.25)	15.9 (0.62)	127 (4.99)	4.40 (0.17)	39	MP-742-39S
			38.05 (1.50)	16.70 (0.66)	127 (4.99)	4.40 (0.17)	61	MP-742-61S
		Receptacle protective dustcap to suit MP-6216	36.9 (1.45)	13.13 (0.52)	127 (4.99)	-	39	MP-742-39L
			43.14 (1.70)	14.15 (0.56)	127 (4.99)	-	61	MP-742-61L
		Plug protective dustcap to suit MP-6212	31.7 (1.25)	15.9 (0.62)	127 (4.99)	4.40 (0.17)	39	MP-738-39S
			38.05 (1.50)	16.70 (0.66)	127 (4.99)	4.40 (0.17)	61	MP-738-61S
		Receptacle protective dustcap to suit MP-6211	36.9 (1.45)	13.13 (0.52)	127 (4.99)	-	39	MP-738-39L
			43.14 (1.70)	14.15 (0.56)	127 (4.99)	-	61	MP-738-61L

STANDARD DATA MP-62 SERIES / MP - 65 SERIES

		VALUE	
GENERAL CHARACTERISTICS	Number of contacts	39	61
	Number of channels	12	20
	Termination	Solder	
	Wire Gauge - Stranded Wire	37 x 24AWG-20AWG 2 x 20AWG-16AWG	24AWG-20AWG
	Environmental	Complies with EU RoHS 2 Directive 2011/65/EU	
ELECTRICAL CHARACTERISTICS	Operating Voltage at Sea level - DC	600V*	
	Operating Voltage at Sea level - AC	600V*	
	Test Voltage AC RMS	1500V	
	Current Carrying Capacity	37 x 7.5A 2 x 13A	7.5A
	Insulation Resistance	5000MΩ	
CLIMATIC CHARACTERISTICS	Protection Class	IP67 (when mated)	
	Operating Temperature	-55°C to +125°C (-67°F to +257°F)	
MECHANICAL CHARACTERISTICS	Cable Retention	PG Gland / NPT Thread	
	Mechanical Operations	500 mating cycles (minimum)	
MATERIALS	Connector / Shell Finish	Aluminium Alloy / Black	
	Insert	Neoprene	
	Male pin contact machined - Plating	Brass / Gold plated	
	Female socket contact machined - Plating	Brass / Gold plated	
CLAMPING CHARACTERISTICS	PG Gland	16	21
	Cable Clamping range mm (inches)	9-14 (0.35”-0.55”)	13-18 (0.51”-0.70”)

Rev 3 - 03/2013

*Not suitable for domestic applications above 50V






AMPHENOL-TUCHEL C146 HEAVY|MATE CONNECTORS

Amphenol Tuchel C146 series rectangular connectors feature modular components ensuring a vast range of different features and benefits for the end user. The zinc diecast aluminum housings are finished in a durable powder coat and available in either top or side entry. Connector coupling is achieved via a positive locking lever ensuring a positive rapid connection. The C146 series is suitable for general-purpose audio and lighting applications and is completely intermateable with all competitor connectors.









FIBRE OPTIC










Amphenol has over 25 years experience in fibre optics dating back to their development of the first industry standard connector, the SMA. Today we can offer a complete range of products including Hybrid Fibre optic connectors for HDTV broadcast cameras SMPTE 304M compliant and ruggedised connectors and cable assemblies for indoor or outdoor applications.







ACCESSORIES

- Colour coded boots(backshells) and rings to assist in cable identification.
- In-line adaptors. Pre-wired for convenience.
- Termination tool for fast assembly of cable connectors.
- Mounting hardware.
- Metal boots(backshells) for rugged environments.





PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR 3 pole male to 3 pole male adapter, Pre wired, Metal Shell	Nickel Finish	AC3M3MW
			Black Finish	AC3M3MBW
		XLR 3 pole female to 3 pole female adapter, Pre wired, Metal Shell	Nickel Finish	AC3F3FW
			Black Finish	AC3F3FBW
		XLR 3 pole female to 3 pole male adapter, Pre wired, Metal Shell	Nickel Finish	AC3F3MW
			Black Finish	AC3F3MBW
		XLR 3 pole female to 5 pole male adapter, Pre wired, Metal Shell	Nickel Finish	AC3F5MW
		XLR 3 pole male to 5 pole female adapter, Pre wired, Metal Shell	Nickel Finish	AC3M5FW
		XLR 5 pole male to 5 pole male adapter, Pre wired, Metal Shell	Nickel Finish	AC5M5MW
		XLR D shell adapter, 3 pole male to 3 pole male, Pre-wired	Not Applicable	AC3M3MDW
		XLR D shell adapter, 3 pole female to 3 pole female, Pre-wired	Not Applicable	AC3F3FDW

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		XLR D shell adapter, 5 pole male to 5 pole male, Pre-wired	Not Applicable	AC5M5MDW
		XLR D shell adapter, 5 pole female to 5 pole female, Pre-wired	Not Applicable	AC5F5FDW
		SP D shell adapter, SP-2 to SP-2, Pre-wired	Not Applicable	SP2F2FDW
		SP D shell adapter, SP-4 to SP-4, Pre-wired	Not Applicable	SP4F4FDW
		D shell adapter without connectors	Not Applicable	AC-D-ADAPTER
		Termination Tool	For AC Series Cable Connectors	T2860
		Termination Tool	For AX Series cable connectors	T2890
		A Type / C Type Connector Mounting, Self-Tapping Screw	2.9 x 1.06 Tri-rondular	52500014-734
		B Type / XLRnet Connector Mounting, Self-Tapping Screw	M2.5	52500005-732

Accessories


PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		AX Series Coloured Boot	Brown	AX-BOOT-1
			Red	AX-BOOT-2
			Orange	AX-BOOT-3
			Yellow	AX-BOOT-4
			Green	AX-BOOT-5
			Blue	AX-BOOT-6
			Violet	AX-BOOT-7
			Grey	AX-BOOT-8
			White	AX-BOOT-9
			Black	AX-BOOT
		AX Series Sleeve for Custom Print Note: Custom printed numbers available (Please contact us)	Black	AX-MARK0
			Brown	AX-MARK1
			Red	AX-MARK2
			Orange	AX-MARK3
			Yellow	AX-MARK4
			Green	AX-MARK5
			Blue	AX-MARK6
			Violet	AX-MARK7
			Grey	AX-MARK8
			White	AX-MARK9
		AC Coloured Boot / Backshell Note: Number Identification optional. (Please contact us.)	Brown	AC-NUT-BRN
			Red	AC-NUT-RED
			Orange	AC-NUT-ORG
			Yellow	AC-NUT-YEL
			Green	AC-NUT-GRN
			Blue	AC-NUT-BLU
			Violet	AC-NUT-VIO
			Grey	AC-NUT-GRY
			White	AC-NUT-WHT
		Coloured Grommets to suit AC Series, T Series and Musician range	Brown	AC-GROMMET-BRN
			Red	AC-GROMMET-RED
			Orange	AC-GROMMET-ORG
			Yellow	AC-GROMMET-YEL
			Green	AC-GROMMET-GRN
			Blue	AC-GROMMET-GRN
			Violet	AC-GROMMET-VIO
			Grey	AC-GROMMET-GRY
			White	AC-GROMMET-WHT

NOTE: All accessories comply with EU RoHS 2 Directive 2011/65/EU
NOTE: Please do not refer to this printed catalogue as a colour reference. For exact colours contact your sales representative.

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
		AC Metal Boot / Backshell, Black Finish	Not Applicable	AC-NUT-METAL
		AC Thermoplastic Boot / Backshell. Suitable for use with 8.5mm (0.33") O.D. cable.	Not Applicable	AC-NUT-J-BLK
		M3 threaded metal plate to suit D-type chassis connectors	Nickel Finish	52590060-300
		M3 x 0.5mm thread Dual rear panel clip	Nickel Finish	52590074-300
		M3 Screw to suit 52590060-300 M3 x 0.5	Nickel Finish	52500016-300
			Matt Black	52500016-400

CONNECTOR WIRING INFORMATION

XLR (Microphone / Patch Cables)




The standard XLR 3 contact pin outs are as shown above for a balanced lead. In such a configuration audio "Hot" (pin 2) is the in-phase connection whilst audio "Cold" (pin 3) is the out-of-phase connection. For an unbalanced lead however, you may connect pin 1 to either pin 2 or pin 3, but not both. In such a configuration the remaining pin is used for the audio signal.


When terminating the cable shielding to pin 1 it is suggested that the shield be only grounded at one end of the cable to avoid inducing "hum". Pin 1 is a leading contact that engages at interconnection, before pin 2 or pin 3.

1/4" Phono (6.35mm) (Standard Applications)


MICROPHONE CABLE - BALANCED




MICROPHONE CABLE - UNBALANCED



INSTRUMENT / LINE CABLE (MONO)




INSTRUMENT / LINE CABLE (STEREO)



MP Series


MP-41 Series 4 Ch –13 pin

Ch	+	-	G
1	B	C	E
2	F	K	H
3	J	D	A
4	N	M	G
General Ground		L	




MP-41 Series 6 Ch – 19 pin

Ch	+	-	G
1	L	M	U
2	A	N	B
3	K	J	T
4	V	P	C
5	H	S	G
6	R	D	E
General Ground		F	




MP-41 Series 8 Ch –25 pin

Ch	+	-	G
1	A	E	F
2	G	C	B
3	D	H	J
4	M	L	K
5	Q	P	N
6	W	S	R
7	T	X	Y
8	Z	V	U
General Ground		a	




MP-41 Series 12 Ch–37 pin

Ch	+	-	G
1	E	F	A
2	B	C	G
3	H	J	D
4	S	T	K
5	L	M	U
6	V	W	N
7	P	R	X
8	a	b	g
9	c	d	j
10	e	f	m
11	n	p	h
12	r	s	k
General Ground		z	




MP-41 Series 16 Ch–54 pin

Ch	+	-	G
1	W	f	r
2	J	R	a
3	k	v	AC
4	E	M	V
5	e	q	y
6	B	H	P
7	Z	j	u
8	D	L	U
9	d	p	x
10	A	G	O
11	Y	h	t
12	C	K	T
13	c	n	w
14	F	N	X
15	g	s	AB
16	S	b	m
General Ground		AG	



MP-41 Series 28 Ch–85 pin

Ch	+	-	G
1	A	B	C
2	E	F	H
3	J	K	L
4	N	P	R
5	S	T	U
6	X	Y	Z
7	a	b	c
8	d	f	g
9	h	i	j
10	k	m	n
11	p	q	r
12	t	u	v
13	w	x	y
14	z	AA	AB
15	AC	AD	AE
16	AF	AH	AJ
17	AK	AL	AM
18	AP	AR	AS
19	AT	AU	AV
20	AW	AX	AY
21	AZ	BA	BB
22	BC	BD	BE
23	BJ	BK	BL
24	BM	BN	BP
25	BS	BT	BU
26	BV	BR	BF
27	BH	AN	s
28	W	M	D
General Ground		V	



MP-41 Series 48 Ch - 150 pin

Ch	+	-	G
1	1	2	3
2	5	6	7
3	8	9	10
4	11	12	13
5	14	15	16
6	17	18	19
7	21	22	23
8	24	25	26
9	27	28	29
10	20	30	31
11	32	33	34
12	35	36	37
13	38	39	40
14	41	42	43
15	44	45	46
16	47	48	49
17	50	51	52
18	53	54	55
19	57	58	59
20	60	61	62
21	63	64	65
22	66	67	68
23	69	70	71
24	72	73	74
25	75	76	77
26	78	79	80
27	82	83	84
28	85	86	87
29	88	89	90
30	91	92	93
31	94	95	96
32	97	98	99
33	100	101	102
34	103	104	105
35	56	81	106
36	107	108	109
37	110	111	112
38	113	114	115
39	116	117	118
40	119	120	121
41	122	123	124
42	125	126	127
43	139	128	129
44	130	131	132
45	133	134	135
46	136	137	138
47	140	141	142
48	143	144	145
General Ground		150	

MP-62 Series 12 Ch–39 pin

Ch	+	-	G
1	p	n	q
2	W	A	X
3	N	f	P
4	L	e	M
5	J	d	K
6	G	c	H
7	E	b	F
8	D	a	Z
9	C	B	Y
10	U	j	V
11	i	h	T
12	R	g	S
General Ground		N/A	



MP-62 Series 20 Ch–61 pin

Ch	+	-	G
1	JJ	HH	NN
2	MM	KK	PP
3	BB	AA	CC
4	s	FF	W
5	r	EE	V
6	e	D	x
7	f	E	y
8	q	DD	U
9	S	p	T
10	P	N	R
11	m	k	n
12	L	K	M
13	J	i	j
14	H	G	h
15	g	F	z
16	d	C	w
17	B	A	c
18	b	a	Z
19	v	u	Y
20	t	GG	X
General Ground		N/A	



INDEX

Symbols

52500005-732 155
52500014-734 155
52500016-300 157
52500016-400 157
52590060-300 157
52590074-300 157

A

AC3F 12
AC3F3FBW 154
AC3F3FDW 154
AC3F3FW 154
AC3F3MBW 154
AC3F5MW 154
AC3FAH1-AU-PRE 45
AC3FAH2-AU-PRE 45
AC3FAH-AU-PRE 45
AC3FAHL1-AU-PRE 45
AC3FAHL2-AU-PRE 45
AC3FAHL-AU-PRE 45
AC3FAV1-AU-PRE 45
AC3FAV2-AU-PRE 46
AC3FAV-AU-PRE 45
AC3FAVL1-AU-PRE 46
AC3FAVL2-AU-PRE 46
AC3FAVL-AU-PRE 46
AC3FB 12
AC3FB-AU 12
AC3FB BULK 12
AC3FBH1-AU-PRE 48
AC3FBH2-AU-PRE 48
AC3FBH3-AU-PRE 48
AC3FBH-AU-PRE 48
AC3FBHL1-AU-PRE 49
AC3FBHL2-AU-PRE 49
AC3FBHL3-AU-PRE 49
AC3FBHL-AU-PRE 48
AC3FBJ 12
AC3F BULK 12
AC3FBV1-AU-PRE 49
AC3FBV2-AU-PRE 49
AC3FBV3-AU-PRE 49
AC3FBV-AU-PRE 49
AC3FBVL1-AU-PRE 50
AC3FBVL2-AU-PRE 50
AC3FBVL3-AU-PRE 50
AC3FBVL-AU-PRE 49
AC3FCP 16
AC3FCP BULK 16
AC3FDZ 23
AC3FDZB 23
AC3FDZB-AU 23
AC3FDZ BULK 23
AC3FJ 12
AC3FPZ 26
AC3M 12
AC3M3MBW 154
AC3M3MDW 154
AC3M3MW 154
AC3M5FW 154
AC3MA-AU-PRE 45
AC3MAH1-AU-PRE 44
AC3MAH2-AU-PRE 44
AC3MAH4-SW-B 44
AC3MAH-AU-PRE 44
AC3MAV2-AU-PRE 45
AC3MAV-AU-PRE 44
AC3MB 12
AC3MB-AU 12
AC3MB BULK 12
AC3MBH1-AU-PRE 47
AC3MBH2-AU-PRE 47
AC3MBH3-AU-PRE 47
AC3MBH-AU-PRE 47
AC3MBHL-AU-PRE 47
AC3MBJ 12
AC3M BULK 12
AC3MBV1-AU-PRE 48
AC3MBV2-AU-PRE 48
AC3MBV3-AU-PRE 48
AC3MBV-AU-PRE 47
AC3MCP 16
AC3MCP BULK 16
AC3MDZ 23
AC3MDZB 23
AC3MDZB-AU 23
AC3MDZ BULK 23
AC3MJ 12
AC3MM 12
AC3MMB 12
AC3MMB-AU 12
AC3MMB BULK 12
AC3MM BULK 12
AC3MMCP 16
AC3MMCP BULK 16
AC3MMDZ 23
AC3MMDZB 23
AC3MMDZB-AU 23
AC3MMDZ BULK 23
AC3MMP 26
AC3MMPNZ 26
AC3MP 26
AC3MPNZ 26
AC4F 13
AC4FB 13
AC4FB-AU 13
AC4FB BULK 13
AC4FBJ 13
AC4F BULK 13
AC4FDZ 24
AC4FDZB 24
AC4FDZB-AU 24
AC4FDZ BULK 24
AC4FJ 13
AC4FPZ 26
AC4M 13
AC4MAH-AU-B 46
AC4MB 13
AC4MB-AU 13
AC4MB BULK 13
AC4MBJ 13
AC4M BULK 13
AC4MDZ 24
AC4MDZB 24
AC4MDZB-AU 24
AC4MJ 13
AC4MP 26
AC4MPNZ 26
AC5F 13
AC5F5FDW 155
AC5FAH-AU-B 46
AC5FAV-AU-B 46
AC5FB 13
AC5FB-AU 13
AC5FB BULK 13
AC5FBH-AU-PRE 50
AC5FBJ 13
AC5F BULK 13
AC5FBV-AU-PRE 50
AC5FDZ 24
AC5FDZB 24
AC5FDZB-AU 24
AC5FDZ BULK 24
AC5FJ 13
AC5FPZ 26
AC5M 13
AC5M5MDW 155
AC5M5MW 154
AC5MAH-AU-B 46
AC5MAV-AU-B 46
AC5MB 13
AC5MB-AU 13
AC5MB BULK 13
AC5MBH-AU-PRE 50
AC5MBJ 13
AC5M BULK 13
AC5MBV-AU-PRE 50
AC5MDZ 24
AC5MDZB 24
AC5MDZB-AU 24
AC5MDZ BULK 24
AC5MJ 13
AC5MP 26
AC5MPNZ 26
AC6AF 14
AC6AFB 14
AC6AFB-AU 14
AC6AFB BULK 14
AC6AFBJ 14
AC6AF BULK 14
AC6AFDZ 25
AC6AFDZB 25
AC6AFDZB-AU 25
AC6AFDZ BULK 25
AC6AFJ 14
AC6AFPZ 26
AC6AM 14
AC6AMB 14
AC6AMB-AU 14
AC6AMB BULK 14
AC6AMBJ 14
AC6AM BULK 14
AC6AMDZ 25
AC6AMDZB 25
AC6AMDZB-AU 25
AC6AMDZ BULK 25
AC6AMJ 14
AC6AMP 26
AC6AMPNZ 26
AC7F 14
AC7FB 14
AC7FB BULK 14
AC7FBJ 14
AC7F BULK 14
AC7FDZ 25
AC7FDZB 25
AC7FDZ BULK 25
AC7FDZV 25
AC7FDZVB 25
AC7FJ 14
AC7FPZ 26
AC7M 14
AC7MB 14
AC7MB BULK 14
AC7MBJ 14
AC7M BULK 14
AC7MDZ 25
AC7MDZB 25
AC7MDZ BULK 25
AC7MDZV 25
AC7MDZVB 25
AC7MJ 14
AC7MP 26
AC7MPNZ 26
AC-D-ADAPTER 155
AC-GROMMET-BRN 156
AC-GROMMET-GRN 156
AC-GROMMET-GRY 156
AC-GROMMET-ORG 156
AC-GROMMET-RED 156
AC-GROMMET-VIO 156
AC-GROMMET-WHT 156
AC-GROMMET-YEL 156
AC-HDMI-RR 110
AC-HDMI-RRB 110
ACJC5H BULK 60
ACJC5HL BULK 60
ACJC5S BULK 60
ACJC5SL BULK 60
ACJC5V BULK 60
ACJC5VL BULK 60
ACJC6AH BULK 58
ACJC6AHL BULK 58
ACJC6AV2 BULK 58
ACJC6AV2L BULK 58
ACJC6AV BULK 58
ACJC6AVL BULK 58
ACJC6H BULK 61
ACJC6HL BULK 61
ACJC6S BULK 61
ACJC6SL BULK 61
ACJC6V BULK 61
ACJC6VL BULK 61
ACJC9AH BULK 58
ACJC9AHL BULK 58
ACJC9AV2 BULK 59
ACJC9AV2L BULK 59
ACJC9AVL BULK 59
ACJC9H BULK 61
ACJC9HL BULK 61
ACJC9S BULK 62
ACJC9SL BULK 62
ACJC9V BULK 62
ACJC9VL BULK 62
ACJC10AH BULK 59
ACJC10AHL BULK 59
ACJC10AV2 BULK 59
ACJC10AV2L BULK 59
ACJC10AV BULK 59
ACJC10AVL BULK 59
ACJC10H BULK 62
ACJC10HL BULK 62
ACJC10S BULK 63
ACJC10SL BULK 63
ACJC10V BULK 62
ACJC10VL BULK 62
ACJD-BLK 143
ACJD-BLU 143
ACJD-GRN 143
ACJD-RED 143
ACJD-WHT 143
ACJD-YEL 143
ACJM-HHDR 129
ACJM-HHOP 130
ACJM-HHOP-1 130
ACJM-IH 131
ACJM-IHS 131
ACJM-MC 131
ACJM - MH 130
ACJM-MHD 132
ACJM-MHD985 129
ACJM-MHDC* 131
ACJM-MHDCM 131
ACJM-MHDE 132
ACJM-MHDEM 132
ACJM-MHDM 132
ACJM-MHDR 130
ACJM-MHDRM 130
ACJM-MHOM 130
ACJM-MHOP 130
ACJM-MHOP-1 130
ACJM-MHR 131
ACJM-MHS 131
ACJM-MIV-2 132
ACJM-MIV-2S 132
ACJM-MN-2 132
ACJM-MN-2S 132
ACJM-MV-2 132
ACJM-MV-2S 132
ACJM-MV35-2 129
ACJM-MV35-2S 129
ACJM-MVD985-2 129
ACJM-MVD985-2S 129
ACJM-MVS-2 133
ACJM-MVS-2S 133
ACJM-NH35 129
ACJM-NV35-2 129
ACJM-NV35-2S 129
ACJM-PC 131
ACJM - PH 130
ACJM-PHOP 130
ACJM-PHOP-1 130
ACJM-PHR 131
ACJM-PHS 131
ACJM-PVB-2 132
ACJM-PVB-2S 132
ACJR-BLK 142
ACJR-BLU 142
ACJR-GRN 142
ACJR-RED 142
ACJR-SBK 142
ACJR-SBL 142
ACJR-SGR 142
ACJR-SRD 142
ACJR-SWH 142
ACJR-SYL 142
ACJR-WHT 142
ACJR-YEL 142

Index

ACJS-HHDR 129
ACJS-HHOP 130
ACJS-HHOP-1 130
ACJS-IH 131
ACJS-IHS 131
ACJS-MC 131
ACJS - MH 131
ACJS-MHD 132
ACJS-MHD985 129
ACJS-MHDC* 131
ACJS-MHDCM 131
ACJS-MHDE 132
ACJS-MHDEM 132
ACJS-MHDM 132
ACJS-MHDR 130
ACJS-MHDRM 130
ACJS-MHOM 130
ACJS-MHOP 130
ACJS-MHOP-1 130
ACJS-MHR 131
ACJS-MHS 131
ACJS-MIV-3 132
ACJS-MIV-3S 132
ACJS-MIV-5 132
ACJS-MN-3 132
ACJS-MN-3S 132
ACJS-MN-5 132
ACJS-MV-3 132
ACJS-MV-3S 132
ACJS-MV-5 132
ACJS-MV35-3 129
ACJS-MV35-3S 129
ACJS-MV35-5 129
ACJS-MVD985-3 129
ACJS-MVD985-3S 129
ACJS-MVD985-5 129
ACJS-MVS-3 133
ACJS-MVS-3S 133
ACJS-MVS-5 133
ACJS-NH35 129
ACJS-NV35-3 129
ACJS-NV35-3S 129
ACJS-NV35-5 129
ACJS-PC 131
ACJS - PH 131
ACJS-PHOP 130
ACJS-PHOP-1 130
ACJS-PHR 131
ACJS-PHS 131
ACJS-PVB-3 132
ACJS-PVB-3S 132
ACJS-PVB-5 132
AC-NUT-BLU 156
AC-NUT-BRN 156
AC-NUT-GRN 156
AC-NUT-GRY 156
AC-NUT-J-BLK 157
AC-NUT-METAL 157
AC-NUT-ORG 156
AC-NUT-RED 156
AC-NUT-VIO 156
AC-NUT-WHT 156
AC-NUT-YEL 156
ACPL-CBK 142
ACPL-CBL 142
ACPL-CGR 142
ACPL-CRD 142
ACPL-CWH 142
ACPL-CYL 142
ACPM-GB 125
ACPM-GB-AU 125
ACPM-GB BULK 125
ACPM-GN 125
ACPM-GN-AU 125
ACPM-GN BULK 125
ACPM-KB 123
ACPM-KB-AU 123
ACPM-KN 123
ACPM-KN-AU 123
ACPM-RB 126
ACPM-RB-AU 126
ACPM-RB BULK 126
ACPM-RN 126
ACPM-RN-AU 126
ACPM-RN BULK 126
ACPM-TB 124
ACPM-TB-AU 124
ACPM-TB BULK 124
ACPM-TN 124
ACPM-TN-AU 124
ACPM-TN BULK 124
ACPR-BLK 142
ACPR-BLU 142
ACPR-GRN 142
ACPR-RED 142
ACPR-SBK 142
ACPR-SBL 142
ACPR-SGR 142
ACPR-SRD 142
ACPR-SWH 142
ACPR-SYL 142
ACPR-WHT 142
ACPR-YEL 142
ACPS-GB 125
ACPS-GB-AU 125
ACPS-GB BULK 125
ACPS-GN 125
ACPS-GN-AU 125
ACPS-GN BULK 125
ACPS-KB 123
ACPS-KB-AU 123
ACPS-KN 123
ACPS-KN-AU 123
ACPS-RB 126
ACPS-RB-AU 126
ACPS-RB BULK 126
ACPS-RN 126
ACPS-RN-AU 126
ACPS-RN BULK 126
ACPS-TB 124
ACPS-TB-AU 124
ACPS-TB BULK 124
ACPS-TN 124
ACPS-TN-AU 124
ACPS-TN BULK 124
AC-USB3-AA 110
AC-USB3-AAB 110
AG3F 66
AG3FCCH 66
AG3FCE 66
AG3FCRV 67
AG3FL 66
AG3M 66
AG3MCC 66
AG3MCCH 66
AG4F 66
AG4FCCH 66
AG4FCE 66
AG4FCRV 67
AG4FL 66
AG4M 66
AG4MCC 66
AG4MCCH 66
AG4MPCH 67
AG5F 66
AG5FCCH 66
AG5FCE 66
AG5FCRV 67
AG5FL 66
AG5M 66
AG5MCC 66
AG5MCCH 66
AG6F 66
AG6FCCH 66
AG6FCE 66
AG6FCRV 67
AG6FL 66
AG6M 66
AG6MCC 66
AG6MCCH 66
AP-4-11 82
AP-4-12 82
AP-4-21 82
AP-4-22 82
AP-5-11 82
AP-5-12 82
AP-5-21 82
AP-5-22 82
AP-6-11 82
AP-6-12 82
AP-6-21 82
AP-6-22 82
AP-8-11 82
AP-8-12 82
AP-8-21 82
AP-8-22 82
AX3FD 19
AX3FDB 19
AX3FDB-AU 19
AX3FDB-M3 19
AX3FD-M3 19
AX3M 5
AX3MB 5
AX3MB-AU 5
AX3MB BULK 5
AX3M BULK 5
AX3MD 19
AX3MDB 19
AX3MDB-AU 19
AX3MDB-M3 19
AX3MD-M3 19
AX3MDV 19
AX3MDVB 19
AX3MDVB-M3 19
AX3MDV-M3 19
AX4F 6
AX4FB 6
AX4FB-AU 6
AX4FB BULK 6
AX4F BULK 6
AX4FD 20
AX4FDB 20, 21
AX4FDB-AU 20, 21
AX4FD-M3 20
AX4FDV 20
AX4FDVB 20, 21
AX4FDV-M3 20
AX4M 6
AX4MB 6
AX4MB-AU 6
AX4MB BULK 6
AX4M BULK 6
AX4MD 20
AX4MDB 20
AX4MDB-AU 20
AX4MD-M3 20
AX4MDV 20
AX4MDVB 20
AX4MDV-M3 20
AX5F 6
AX5FB 6
AX5FB-AU 6
AX5FB BULK 6
AX5F BULK 6
AX5FD 21
AX5FD-M3 21
AX5FDV 21
AX5FDV-M3 21
AX5M 6
AX5MB 6
AX5MB-AU 6
AX5MB BULK 6
AX5M BULK 6
AX5MD 20
AX5MDB 20
AX5MDB-AU 20
AX5MD-M3 20
AX5MDV 20
AX5MDVB 20
AX5MDV-M3 20
AX6AFD 21
AX6AFDB 21
AX6AFD-M3 21
AX6AFDV 21
AX6AFDVB 21
AX6AFDV-M3 21
AX6AMD 21
AX6AMDB 21
AX6AMDB-AU 21
AX6AMD-M3 21
AX6AMDV 21
AX6AMDVB 21
AX6AMDV-M3 21
AX6FADB-AU 21
AX-BOOT 156
AX-BOOT-1 156
AX-BOOT-2 156
AX-BOOT-3 156
AX-BOOT-4 156
AX-BOOT-5 156
AX-BOOT-6 156
AX-BOOT-7 156
AX-BOOT-8 156
AX-BOOT-9 156
AX-MARK0 156
AX-MARK1 156
AX-MARK2 156
AX-MARK3 156
AX-MARK4 156
AX-MARK5 156
AX-MARK6 156
AX-MARK7 156
AX-MARK8 156
AX-MARK9 156
AXS3FP 30
AXS3FP1 30
AXS3FP1H 31
AXS3FP1V 31
AXS3FP2 30
AXS3FP2H 31
AXS3FP2V 31
AXS3FPH 31
AXS3FPV 31
AXS3MP 30
AXS3MP1 30
AXS3MP1H 30
AXS3MP1V 31
AXS3MP2 30
AXS3MP2H 30
AXS3MP2V 31
AXS3MPH 30
AXS3MPV 31
AXS4FP 31
AXS4FP1 31
AXS4FP1H 32
AXS4FP1V 32
AXS4FP2 31
AXS4FP2H 32
AXS4FP2V 32
AXS4FPH 32
AXS4FPV 32
AXS4MP 31
AXS4MP1 31
AXS4MP1H 32
AXS4MP1V 32
AXS4MP2 31
AXS4MP2H 32
AXS4MP2V 32
AXS4MPH 32
AXS4MPV 32
AXS5FP 33
AXS5FP1 33
AXS5FP1H 33
AXS5FP1V 33
AXS5FP2 33
AXS5FP2H 33
AXS5FP2V 33
AXS5FPH 33
AXS5FPV 33
AXS5MP 32
AXS5MP1 32
AXS5MP1H 33
AXS5MP1V 33
AXS5MP2 32
AXS5MP2H 33
AXS5MP2V 33
AXS5MPH 33
AXS5MPV 33
AXX3F 5
AXX3FB-AU 5
AXX3FB BULK 5
AXX3F BULK 5

E

EP-3-11P 80
EP-3-11PB 80
EP-3-12 80
EP-3-12B 80
EP-3-13P 81
EP-3-13PB 81
EP-3-14 81
EP-3-14B 81
EP-4-11P 80
EP-4-11PB 80
EP-4-12 80

Index

EP-4-12B 80
EP-4-13P 81
EP-4-13PB 81
EP-4-14 81
EP-4-14B 81
EP-5-11P 80
EP-5-11PB 80
EP-5-12 80
EP-5-12B 80
EP-5-13P 81
EP-5-13PB 81
EP-5-14 81
EP-5-14B 81
EP-6-11P 80
EP-6-11PB 80
EP-6-12 80
EP-6-12B 80
EP-6-13P 81
EP-6-13PB 81
EP-6-14 81
EP-6-14B 81
EP-8-11P 80
EP-8-11PB 80
EP-8-12 80
EP-8-12B 80
EP-8-13P 81
EP-8-13PB 81
EP-8-14 81
EP-8-14B 81

H

HP-3-F 85
HP-3-FG 85
HP-3-MD 85
HP-3-MDG 85
HP-3-MDGW 85
HP-3-MDW 85
HPT-3-CC 87
HPT-3-F 87
HPT-3-FD 87
HPT-3-FDW 87
HPT-3-FJ 87
HPT-3-M 87
HPT-3-MD 87
HPT-3-MDW 87
HPT-3-MJ 87
HPT-CAPD 88
HPT-CAPF 88
HPT-CAPM 88
HPT-CAPSD 88
HPT-CAPSF 88
HPT-CAPSM 88
HPT-RT 88

J

JM2P 116
JM2P-AU 116
JM2PB 116
JM2PB-AU 116
JM2P BULK 116
JS3P 116
JS3P-AU 116
JS3PB 116
JS3PB-AU 116

K

KM2P 138
KM2P-AU 138
KM2PB 138
KM2PB-AU 138
KM2PB BULK 138
KM2P BULK 138
KS3P 138
KS3P-AU 138
KS3PB 138
KS3PB-AU 138
KS3PB BULK 138
KS3P BULK 138
KS3PC 138
KS3PC-AU 138

M

M22520/1-01 149
MP-738-39L 152
MP-738-39S 152
MP-738-61L 152
MP-738-61S 152
MP-742-39L 152
MP-742-39S 152
MP-742-61L 152
MP-742-61S 152
MP-4101-13P 146
MP-4101-13P-C 146
MP-4101-19P 146
MP-4101-19P-C 146
MP-4101-25P 146
MP-4101-25P-C 146
MP-4101-37P 146
MP-4101-37P-C 146
MP-4101-54P 146
MP-4101-54P-C 146
MP-4101-85P 146
MP-4101-85P-C 146
MP-4101-150P 146
MP-4101-150P-C 146
MP-4102-13P 147
MP-4102-13P-C 147
MP-4102-19P 147
MP-4102-19P-C 147
MP-4102-25P 147
MP-4102-25P-C 147
MP-4102-37P 147
MP-4102-37P-C 147
MP-4102-54P 147
MP-4102-54P-C 147
MP-4102-85P 147
MP-4102-85P-C 147
MP-4102-150P 147
MP-4102-150P-C 147
MP-4106-13S 146
MP-4106-13S-C 146
MP-4106-19S 146
MP-4106-19S-C 146
MP-4106-25S 146
MP-4106-25S-C 146
MP-4106-37S 146
MP-4106-37S-C 146
MP-4106-54S 146
MP-4106-54S-C 146
MP-4106-85S 146
MP-4106-85S-C 146
MP-4106-150S 146
MP-4106-150S-C 146
MP-4164-13S 147
MP-4164-13S-C 147
MP-4164-19S 147
MP-4164-19S-C 147
MP-4164-25S 147
MP-4164-25S-C 147
MP-4164-37S 147
MP-4164-37S-C 147
MP-4164-54S 147
MP-4164-54S-C 147
MP-4164-85S 147
MP-4164-85S-C 147
MP-4164-150S 147
MP-4164-150S-C 147
MP-6211-39S 151
MP-6211-39S-C 151
MP-6211-61S 151
MP-6211-61S-C 151
MP-6212-39S 152
MP-6212-39S-C 152
MP-6212-61S 152
MP-6212-61S-C 152
MP-6216-39P 151
MP-6216-39P-C 151
MP-6216-61P 151
MP-6216-61P-C 151
MP-6256-39P 152
MP-6256-39P-C 152
MP-6256-61P 152
MP-6256-61P-C 152
MP-6511-39S 151
MP-6511-39S-C 151
MP-6511-61S 151
MP-6511-61S-C 151
MP-6516-39P 151
MP-6516-39P-C 151
MP-6516-61P 151
MP-6516-61P-C 151
MP-25042-13L 147
MP-25042-13S 147
MP-25042-19L 147
MP-25042-19S 147
MP-25042-25L 147
MP-25042-25S 147
MP-25042-37L 147
MP-25042-37S 147
MP-25042-54L 147
MP-25042-54S 147
MP-25042-85L 147
MP-25042-85S 147
MP-25042-150L 147
MP-25042-150S 147
MP-25043-13L 148
MP-25043-13S 148
MP-25043-19L 148
MP-25043-19S 148
MP-25043-25L 148
MP-25043-25S 148
MP-25043-37L 148
MP-25043-37S 148
MP-25043-54L 148
MP-25043-54S 148
MP-25043-85L 148
MP-25043-85S 148
MP-25043-150L 148
MP-25043-150S 148
MP-108300 149
MP-108400 149
MP-108500 149
MP-108600 149
MP-EXT-16/18 149
MP-GUIDE-16 149
MP-GUIDE-18 149
MP-INS-16 149
MP-INS-18 149

Q

QM2P 120
QM2PB-AU 120
QM2R 121
QM2RB-AU 121
QS3P 120
QS3PB-AU 120
QS3R 121
QS3RB-AU 121

R

RJD32A3-0050 91
RJD32U1-0050 91
RJD1112-0050 91
RJD1212-0050 91
RJD2103-0050 91
RJD2203-0050 91
RJX8FA3HB 99
RJX8FA3VB 100
RJX8FA5V2B 100
RJX8FA5VB 100
RJX8FA6HB 99
RJX8FA6V2B 100
RJX8FA6VB 100
RJX8FB3HB 99
RJX8FB3HEB 100
RJX8FB3VB 100
RJX8FB3VEB 101
RJX8FB5HB 99
RJX8FB5HEB 100
RJX8FB5HGRB 99
RJX8FB5HGREB 100
RJX8FB5HGYB 99
RJX8FB5HGYEB 100
RJX8FB5HLPB 99
RJX8FB5HLPEB 100
RJX8FB5HRGB 99
RJX8FB5HRGEB 100
RJX8FB5HRRB 99
RJX8FB5HRREB 100
RJX8FB5HRYB 99
RJX8FB5HRYEB 100
RJX8FB5HUUB 99
RJX8FB5HUUEB 100
RJX8FB5V2B 100
RJX8FB5V2EB 101
RJX8FB5V2LPB 100, 101
RJX8FB5V2LPEB 101
RJX8FB5VB 100
RJX8FB5VEB 101
RJX8FB5VGRB 101
RJX8FB5VGREB 101
RJX8FB5VGYB 101
RJX8FB5VGYEB 101
RJX8FB5VLPB 100, 101
RJX8FB5VLPEB 101
RJX8FB5VRGB 101
RJX8FB5VRGEB 101
RJX8FB5VRRB 101
RJX8FB5VRREB 101
RJX8FB5VRYB 101
RJX8FB5VRYEB 101
RJX8FB5VUUB 101
RJX8FB5VUUEB 101
RJX8FB6HB 99
RJX8FB6HEB 100
RJX8FB6HGRB 99
RJX8FB6HGREB 100
RJX8FB6HGYB 99
RJX8FB6HGYEB 100
RJX8FB6HLPB 99
RJX8FB6HLPEB 100
RJX8FB6HRGB 99
RJX8FB6HRGEB 100
RJX8FB6HRRB 99
RJX8FB6HRREB 100
RJX8FB6HRYB 99
RJX8FB6HRYEB 100
RJX8FB6HUUB 99
RJX8FB6HUUEB 100
RJX8FB6V2B 100
RJX8FB6V2EB 101
RJX8FB6V2LPB 100, 101
RJX8FB6V2LPEB 101
RJX8FB6VB 100
RJX8FB6VEB 101
RJX8FB6VGRB 101
RJX8FB6VGREB 101
RJX8FB6VGYB 101
RJX8FB6VGYEB 101
RJX8FB6VLPB 100, 101
RJX8FB6VLPEB 101
RJX8FB6VRGB 101
RJX8FB6VRGEB 101
RJX8FB6VRRB 101
RJX8FB6VRREB 101
RJX8FB6VRYB 101
RJX8FB6VRYEB 101
RJX8FB6VUUB 101
RJX8FB6VUUEB 101
RJX8FD3HB 105
RJX8FD3VB 105
RJX8FD5HB 105
RJX8FD5I 105
RJX8FD5T 105
RJX8FD5VB 105
RJX8FD6HB 105
RJX8FD6I 105
RJX8FD6VB 105
RJX8FD5110 105
RJX8FD6110 105
RJX8M 94, 96
RJX8MB 94, 96
RJX8MB BULK 94, 96
RJX8M BULK 94, 96
RJXS8FD3HB 106
RJXS8FD3VB 106
RJXS8FD5HB 106
RJXS8FD5I 106
RJXS8FD5T 106
RJXS8FD5VB 106
RJXS8FD6HB 106
RJXS8FD6I 106
RJXS8FD6VB 106
RJXS8FD5110 106
RJXS8FD6110 106
RJXS8FG3HB 106
RJXS8FG3VB 106
RJXS8FG5HB 106
RJXS8FG5I 106
RJXS8FG5T 106

Index

RJXS8FG5VB 106
RJXS8FG6HB 106
RJXS8FG6I 106
RJXS8FG6VB 106
RJXS8FG5110 106
RJXS8FG6110 106
RJXS8FP5H 36
RJXS8FP5HE 36
RJXS8FP5HP 36
RJXS8FP5HPE 36
RJXS8FP5V 37
RJXS8FP5VE 37
RJXS8FP5VP 37
RJXS8FP5VPE 37
RJXS8FP6H 36
RJXS8FP6HE 36
RJXS8FP6HP 36
RJXS8FP6HPE 36
RJXS8FP6V 37
RJXS8FP6VE 37
RJXS8FP6VP 37
RJXS8FP6VPE 37
RJXS8FP15H 36
RJXS8FP15HE 36
RJXS8FP15HP 36
RJXS8FP15HPE 36
RJXS8FP15V 37
RJXS8FP15VE 37
RJXS8FP15VP 37
RJXS8FP15VPE 37
RJXS8FP16H 36
RJXS8FP16HE 36
RJXS8FP16HP 36
RJXS8FP16HPE 36
RJXS8FP16V 37
RJXS8FP16VE 37
RJXS8FP16VP 37
RJXS8FP16VPE 37
RJXS8FP25H 36
RJXS8FP25HE 36
RJXS8FP25HP 36
RJXS8FP25HPE 36
RJXS8FP25V 37
RJXS8FP25VE 37
RJXS8FP25VP 37
RJXS8FP25VPE 37
RJXS8FP26H 36
RJXS8FP26HE 36
RJXS8FP26HP 36
RJXS8FP26HPE 36
RJXS8FP26V 37
RJXS8FP26VE 37
RJXS8FP26VP 37
RJXS8FP26VPE 37
RJXX8M 94
RJXX8MB 94
RJXX8MB BULK 94
RJXX8M BULK 94

S

SP-2-F 71
SP2F2FDW 155
SP-2-FB 71
SP-2-FBG 71
SP-2-FBGTX 71
SP-2-FBL 71
SP-2-FBLTX 71
SP-2-FBS 71
SP-2-FBSG 71
SP-2-FBSL 71
SP-2-FBTX 71
SP-2-FG 71
SP-2-FGTX 71
SP-2-FL 71
SP-2-FLTX 71
SP-2-FN 71
SP-2-FNG 71
SP-2-FNGTX 71
SP-2-FNL 71
SP-2-FNLTX 71
SP-2-FNS 71
SP-2-FNSG 71
SP-2-FNSL 71
SP-2-FNTX 71
SP-2-FS 71
SP-2-FSG 71
SP-2-FSL 71
SP-2-FTX 71
SP-2-MD 73
SP-2-MDH 73
SP-2-MDV 73
SP-4-F 72
SP4F4FDW 155
SP-4-FB 72
SP-4-FBG 72
SP-4-FBGTX 72
SP-4-FBL 72
SP-4-FBLTX 72
SP-4-FBS 72
SP-4-FBSG 72
SP-4-FBSL 72
SP-4-FBTX 72
SP-4-FG 72
SP-4-FGTX 72
SP-4-FL 72
SP-4-FLTX 72
SP-4-FN 72
SP-4-FNG 72
SP-4-FNGTX 72
SP-4-FNL 72
SP-4-FNLTX 72
SP-4-FNS 72
SP-4-FNSG 72
SP-4-FNSL 72
SP-4-FNTX 72
SP-4-FS 72
SP-4-FSG 72
SP-4-FSL 72
SP-4-FTX 72
SP-4-MC 74
SP-4-MD 73
SP-4-MD-8 73
SP-4-MDA 73
SP-4-MDAT 73
SP-4-MDH 74
SP-4-MDHT 74
SP-4-MDHT-8 74
SP-4-MDT 73, 74
SP-4-MDV 74
SP-4-MDV-2 74
SP-4-MDVT-8 74

T

T2860 155
T2890 155
TH29-1 149
TM1P 118
TM1P-AU 118
TM1PB 118
TM1PB-AU 118
TM1PBJ 118
TM1PJ 118
TM1RBJ 118
TM1RBJ-AU 118
TM1RJ 118
TM1RJ-AU 118
TM2P 114
TM2P-AU 114
TM2PB 114
TM2PB-AU 114
TM2PB BULK 114
TM2PBJ 114
TM2P BULK 114
TM2PJ 114
TM2PN 115
TM2PN-AU 115
TM2PN BULK 115
TM2PNJ 115
TM2RBJ 115
TM2RBJ-AU 115
TM2RBJ BULK 115
TM2RJ 115
TM2RJ-AU 115
TS3P 114
TS3P-AU 114
TS3PB 114
TS3PB-AU 114
TS3PB BULK 114
TS3PBJ 114
TS3P BULK 114
TS3PJ 114
TS3RBJ 115
TS3RBJ-AU 115
TS3RJ 115
TS3RJ-AU 115

PRODUCT SAFETY INFORMATION

This should be read in conjunction with Data Sheet information contained in individual product brochures. Failure to observe the advice in this information sheet and the operating conditions specified in the Data Sheets could result in hazardous situations.

1. Material Content and Physical Form

Electrical connectors do not usually contain hazardous materials. They contain conducting and non-conducting materials. Shells are manufactured in metal and plastic. Insulators can be formed in either natural rubber, synthetic rubber, plastic or glass insulating materials. Contact materials vary with the type of connector and its application. They are usually manufactured from either copper alloys, nickel, alumel, chromel or steel. In special applications, other alloys may be specified.

2. Fire Characteristics and Electric Shock Hazard

There is no fire hazard when the connector is correctly wired and used within the specified parameters. Incorrect wiring or assembly of the connector or careless use of metal tools or conductive fluids, or transit damage to any of the component parts may cause electric shock or burns. Live circuits must not be broken by separating mated connectors as this may cause arcing, ionisation and burning. Heat dissipation is greater at maximum resistance in a circuit. Hot spots may occur when resistance is raised locally by damage, e.g. cracked or deformed contacts, or broken strands of wire. Local overheating may also result from the use of the incorrect application tools or from poor quality soldering.

Overheating may occur if the ratings in the Data Sheets are exceeded and can cause breakdown of insulation and hence electric shock.

If heating is allowed to continue it intensifies by further increasing the local resistance through loss of temper or spring contact, formation of oxide film on contacts and wires, and leakage currents through carbonisation of insulation and tracking points. Fire can then result in the presence of combustible materials and this may release noxious fumes. Overheating may not be visually apparent. Burns may result from touching overheated components.

3. Handling

Care must be taken to avoid damage to any component parts of electrical connectors during installation and use. Although there are normally no sharp edges, care must be taken when handling certain components to avoid injury to fingers. Electrical connectors may be damaged in transit to customers, and damage may result in creation of hazards. Products should therefore be examined prior to installation/use and rejected if found to be damaged.

4. Disposal

Incineration of certain materials may release noxious or even toxic fumes.

5. Application

Connectors with exposed contacts should not be selected for use on the current supply side of an electrical circuit, because an electric shock could result from touching exposed contacts of an unmated connector. Voltages in excess of 30 V.A.C. or 42.5 V.D.C. are potentially hazardous and care should be taken to ensure that such voltages cannot be transmitted in any way to exposed metal parts of the connector body. The connector and wiring should be checked, before making live, to have no damage to metal parts or insulators, no solder blobs, loose strands, conducting lubricants, swarf, or any other undesired conducting particles. Circuit resistance and continuity check should be made to make certain that there are no low resistance joints or spurious conducting paths. Always use the correct application tools as specified in the Data Sheets. Do not permit untrained personnel to wire, assemble or tamper with connectors. For operation voltage please see appropriate national regulations.

Important General Information

A) Air and creepage paths / Operating voltage.

The admissible operating voltages depend on the individual applications and the valid national and other applicable safety regulations. For this reason the air and creepage path data are only reference values. Observe reduction of air and creepage paths due to PC board and/or harnessing.

B) Other important information

Amphenol Australia Pty Ltd continuously endeavours to improve its products. Therefore, products may deviate from the description, technical data and shape as shown in product brochures.

C) Assembly instructions

If applicable, special assembly instructions have been included in or on the connector packaging. See also separate instructions in product brochures.

DISTRIBUTED BY

International Headquarters

Amphenol Australia Pty Ltd

22 Industry Blvd.
Carrum Downs VIC 3201 Australia

Phone: +61 3 8796 8888
Email: info@amphenol.com.au

North America

Amphenol Audio Representative Office

44724 Morley Drive
Clinton Township, MI, USA 48036

Phone: +1 800 394 7732 or +1 586 913 8650
Email: sales@amphenolaudio.com

Europe

Amphenol Audio Representative Office

August-Haeusser – Str. 10
74080 Heilbronn Germany

Phone: +49 71 31 9 29 0
Email: industrial@amphenol.de

Asia Pacific

Amphenol Australia (China Operations)

3rd floor, Building 9 Shan Cheng Industrial Zone,
Zhou Shi Road, Shi Yan Street, Bao An District,
Shen Zhen, China 518108

Phone: (+86) 755 8173 8000
Email: apcd@amphenol.com.au

www.amphenolaudio.com.au

© 2025 Amphenol Australia Pty Ltd

Subject to all applicable laws and regulations Amphenol Australia Pty Ltd reserves the right to change specifications of any product, system or service contained in this brochure without liability.

260226

Catalogue Part Number: CAT-AUDIO-01

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View AC3MJ on WIN SOURCE
- Amphenol Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management