



# THE DATASHEET OF NC3FM-C





## NC3FM-C

World's first 3 pole unisex XLR cable connector

### Features & Benefits

- ✓ World's first unisex XLR
- ✓ 3 pole male and female cable connector in one housing
- ✓ Easy selectable gender - converted by sliding housing back and forth
- ✓ Substitute adapters, ideal as an emergency kit
- ✓ With all benefits of the XLR XX series

### Technical Information

| Product         |         |
|-----------------|---------|
| Title           | NC3FM-C |
| Connection Type | XLR     |
| Gender          | female  |

## Electrical

|                              |                                 |
|------------------------------|---------------------------------|
| Capacitance between contacts | $\leq 4 \text{ pF}$             |
| Contact resistance           | $\leq 3 \text{ m}\Omega$        |
| Dielectric strength          | 1,5 kVdc                        |
| Insulation resistance        | $> 2 \text{ G}\Omega$ (initial) |
| Rated current per contact    | 16 A                            |
| Rated voltage                | $< 50 \text{ V}$                |

## Mechanical



|                  |                         |
|------------------|-------------------------|
| Cable O.D.       | 3.5 - 8.0 mm            |
| Insertion force  | $\leq 20 \text{ N}$     |
| Withdrawal force | $\leq 20 \text{ N}$     |
| Lifetime         | $> 1000$ mating cycles  |
| Wiresize         | max. $2.5 \text{ mm}^2$ |
| Wiresize         | max. 14 AWG             |
| Wiring           | Solder contacts         |
| Locking device   | Latch lock              |

| Material        |  |
|-----------------|--|
| Boot            | Polyurethan                              |
| Contact plating | 0.2 µm Au                                |
| Contacts        | Brass (CuZn39Pb3) male                   |
| Insert          | Polyamide (PA 6.6 30 % GR)               |
| Locking element | Zinc diecast (ZnAl4Cu1) / Ck 67 (spring) |
| Shell           | Zinc diecast (ZnAl4Cu1)                  |
| Shell plating   | Nickel                                   |
| Strain relief   | Polyacetal (POM)                         |

| Environmental       |                           |
|---------------------|---------------------------|
| Flammability        | UL 94 HB                  |
| Standard compliance | IEC 61076-2-103           |
| Protection class    | IP 40                     |
| Solderability       | Complies with IEC 68-2-20 |
| Temperature range   | -30 °C to +80 °C          |

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View NC3FM-C on WIN SOURCE](#)
-  [Neutrik Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management