



**THE DATASHEET OF  
IKW15N120H3**




## High speed DuoPack: IGBT in Trench and Fieldstop technology with soft, fast recovery antiparallel diode

### Features


- $V_{CE} = 1200\text{ V}$
- $I_C = 15\text{ A}$
- Very low  $V_{CE,sat}$
- Low EMI
- Very soft, fast recovery antiparallel diode
- Maximum junction temperature  $T_{vjmax} = 175^\circ\text{C}$
- Qualified according to JEDEC for target applications
- Pb-free lead plating; RoHS compliant
- Complete product spectrum and PSpice Models: <http://www.infineon.com/igbt/>

### Potential applications

- Uninterruptible power supplies
- Welding converters
- Converters with high switching frequency



### Description



Type	Package	Marking
IKW15N120H3	PG-TO247-3	K15H1203

## Table of contents

	<b>Description</b> .....	1
	<b>Features</b> .....	1
	<b>Potential applications</b> .....	1
	<b>Table of contents</b> .....	2
<b>1</b>	<b>Package</b> .....	3
<b>2</b>	<b>IGBT</b> .....	3
<b>3</b>	<b>Diode</b> .....	5
<b>4</b>	<b>Characteristics diagrams</b> .....	7
<b>5</b>	<b>Package outlines</b> .....	14
<b>6</b>	<b>Testing conditions</b> .....	15
	<b>Revision history</b> .....	16
	<b>Disclaimer</b> .....	17

## 1 Package

**Table 1** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Internal emitter inductance measured 5 mm (0.197 in) from case	$L_E$			13.0		nH
Storage temperature	$T_{stg}$		-55		150	°C
Soldering temperature		wave soldering 1.6 mm (0.063 in.) from case for 10 s			260	°C
Mounting torque, M3 screw Maximum of mounting processes: 3	$M$				0.6	Nm
Thermal resistance, junction-ambient	$R_{th(j-a)}$				40	K/W

## 2 IGBT

**Table 2** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Collector-emitter voltage	$V_{CE}$		1200	V
DC collector current, limited by $T_{vjmax}$	$I_C$	$T_c = 25\text{ °C}$	30	A
		$T_c = 100\text{ °C}$	15	
Pulsed collector current, $t_p$ limited by $T_{vjmax}$	$I_{Cpuls}$		60	A
Turn-off safe operating area		$V_{CE} \leq 1200\text{ V}$ , $T_{vj} \leq 175\text{ °C}$	60	A
Gate-emitter voltage	$V_{GE}$		$\pm 20$	V
Short circuit withstand time	$t_{SC}$	$V_{CC} \leq 600\text{ V}$ , Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0\text{ s}$ , $T_{vj} = 175\text{ °C}$	10	$\mu\text{s}$
Power dissipation	$P_{tot}$	$T_c = 25\text{ °C}$	217	W
		$T_c = 100\text{ °C}$	105	

**Table 3** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter breakdown voltage	$V_{BRCES}$	$I_C = 0.5\text{ mA}$ , $V_{GE} = 0\text{ V}$	1200			V

**Table 3 Characteristic values (continued)**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 15.0\ A, V_{GE} = 15\ V$	$T_{vj} = 25\ ^\circ C$	2.05	2.40	V
			$T_{vj} = 125\ ^\circ C$	2.50		
			$T_{vj} = 175\ ^\circ C$	2.70		
Gate-emitter threshold voltage	$V_{GEth}$	$I_C = 0.50\ mA, V_{CE} = V_{GE}, T_{vj} = 175\ ^\circ C$	5.00	5.80	6.50	V
Zero gate voltage collector current	$I_{CES}$	$V_{CE} = 1200\ V, V_{GE} = 0\ V$	$T_{vj} = 25\ ^\circ C$		250	$\mu A$
			$T_{vj} = 175\ ^\circ C$		2500	
Gate-emitter leakage current	$I_{GES}$	$V_{CE} = 0\ V, V_{GE} = 20\ V$			600	nA
Transconductance	$g_{fs}$	$I_C = 15.0\ A, V_{CE} = 20\ V$		7.5		S
Short circuit collector current	$I_{SC}$	$V_{CC} \leq 600\ V, V_{GE} = 15\ V, t_{SC} \leq 10\ \mu s$ , Allowed number of short circuits < 1000 , Time between short circuits $\geq 1.0\ s, T_{vj} = 175\ ^\circ C$		52		A
Input capacitance	$C_{ies}$	$V_{CE} = 25\ V, V_{GE} = 0\ V, f = 1000\ kHz$		875		pF
Output capacitance	$C_{oes}$	$V_{CE} = 25\ V, V_{GE} = 0\ V, f = 1000\ kHz$		75		pF
Reverse transfer capacitance	$C_{res}$	$V_{CE} = 25\ V, V_{GE} = 0\ V, f = 1000\ kHz$		45		pF
Gate charge	$Q_G$	$I_C = 15.0\ A, V_{GE} = 15\ V, V_{CE} = 960\ V$		75		nC
Turn-on delay time	$t_{don}$	$V_{CE} = 600\ V,$ $V_{GE} = +0/+15\ V,$ $R_{Gon} = 35.0\ \Omega,$ $R_{Goff} = 35.0\ \Omega,$ $L_\sigma = 95\ nH, C_\sigma = 67\ pF$	$T_{vj} = 25\ ^\circ C,$ $I_C = 15.0\ A$	21		ns
			$T_{vj} = 175\ ^\circ C,$ $I_C = 15.0\ A$	19		
Rise time (inductive load)	$t_r$	$V_{CE} = 600\ V,$ $V_{GE} = +0/+15\ V,$ $R_{Gon} = 35.0\ \Omega,$ $R_{Goff} = 35.0\ \Omega,$ $L_\sigma = 95\ nH, C_\sigma = 67\ pF$	$T_{vj} = 25\ ^\circ C,$ $I_C = 15.0\ A$	34		ns
			$T_{vj} = 175\ ^\circ C,$ $I_C = 15.0\ A$	30		
Turn-off delay time	$t_{doff}$	$V_{CE} = 600\ V,$ $V_{GE} = +0/+15\ V,$ $R_{Gon} = 35.0\ \Omega,$ $R_{Goff} = 35.0\ \Omega,$ $L_\sigma = 95\ nH, C_\sigma = 67\ pF$	$T_{vj} = 25\ ^\circ C,$ $I_C = 15.0\ A$	260		ns
			$T_{vj} = 175\ ^\circ C,$ $I_C = 15.0\ A$	327		
Fall time (inductive load)	$t_f$	$V_{CE} = 600\ V,$ $V_{GE} = +0/+15\ V,$ $R_{Gon} = 35.0\ \Omega,$ $R_{Goff} = 35.0\ \Omega,$ $L_\sigma = 95\ nH, C_\sigma = 67\ pF$	$T_{vj} = 25\ ^\circ C,$ $I_C = 15.0\ A$	14		ns
			$T_{vj} = 175\ ^\circ C,$ $I_C = 15.0\ A$	43		

**Table 3** Characteristic values (continued)

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Turn-on energy	$E_{on}$	$V_{CE} = 600\text{ V}$ , $V_{GE} = +0/+15\text{ V}$ , $R_{Gon} = 35.0\ \Omega$ , $R_{Goff} = 35.0\ \Omega$ , $L_{\sigma} = 95\text{ nH}$ , $C_{\sigma} = 67\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	1.10		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	1.60		
Turn-off energy	$E_{off}$	$V_{CE} = 600\text{ V}$ , $V_{GE} = +0/+15\text{ V}$ , $R_{Gon} = 35.0\ \Omega$ , $R_{Goff} = 35.0\ \Omega$ , $L_{\sigma} = 95\text{ nH}$ , $C_{\sigma} = 67\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	0.45		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	0.90		
Total switching energy	$E_{ts}$	$V_{CE} = 600\text{ V}$ , $V_{GE} = +0/+15\text{ V}$ , $R_{Gon} = 35.0\ \Omega$ , $R_{Goff} = 35.0\ \Omega$ , $L_{\sigma} = 95\text{ nH}$ , $C_{\sigma} = 67\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	1.55		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$ , $I_C = 15.0\text{ A}$	2.50		
IGBT thermal resistance, junction-case	$R_{thjc}$				0.70	K/W
Operating junction temperature	$T_{vj}$		-40		175	$^{\circ}\text{C}$

Note: Electrical Characteristic, at  $T_{vj} = 25^{\circ}\text{C}$ , unless otherwise specified.

### 3 Diode

**Table 4** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	$V_{RRM}$		1200	V	
Diode forward current, limited by $T_{vjmax}$	$I_F$		$T_C = 25\text{ }^{\circ}\text{C}$	15	A
			$T_C = 100\text{ }^{\circ}\text{C}$	7.5	
Diode pulsed current, limited by $T_{vjmax}$	$I_{Fpuls}$		60	A	

**Table 5** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Diode forward voltage	$V_F$	$I_F = 7.5\text{ A}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$	1.80	2.35	V
			$T_{vj} = 175\text{ }^{\circ}\text{C}$	1.85		

**Table 5** Characteristic values (continued)

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Diode forward voltage	$V_F$	$I_F = 15.0 \text{ A}$	$T_{vj} = 25 \text{ }^\circ\text{C}$		2.40	3.05	V
					2.60		
					2.60		
Reverse leakage current	$I_R$	$V_R = 1200 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$			250	$\mu\text{A}$
						2500	
Diode reverse recovery time	$t_{rr}$	$V_R = 600 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$ , $I_F = 15.0 \text{ A}$ , $-di_F/dt = 500 \text{ A}/\mu\text{s}$		260		ns
					470		
Diode reverse recovery charge	$Q_{rr}$	$V_R = 600 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$ , $I_F = 15.0 \text{ A}$ , $-di_F/dt = 500 \text{ A}/\mu\text{s}$		0.80		$\mu\text{C}$
					1.70		
Diode peak reverse recovery current	$I_{rrm}$	$V_R = 600 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$ , $I_F = 15.0 \text{ A}$ , $-di_F/dt = 500 \text{ A}/\mu\text{s}$		7.7		A
					9.8		
Diode peak rate off fall of reverse recovery current	$di_{rr}/dt$	$V_R = 600 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$ , $I_F = 15.0 \text{ A}$ , $-di_F/dt = 500 \text{ A}/\mu\text{s}$		-110		$\text{A}/\mu\text{s}$
					-80		
Diode thermal resistance, junction-case	$R_{thjc}$					2.12	K/W
Operating junction temperature	$T_{vj}$			-40		175	$^\circ\text{C}$


**Note:** For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.

**4 Characteristics diagrams**

**Collector current as a function of switching frequency, IGBT**

$I_C = f(f)$


$D = 0.5, V_{CE} = 600\text{ V}, T_{vj} \leq 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}, R_G = 35\text{ }\Omega$



**Forward bias safe operating area, IGBT**

$I_C = f(V_{CE})$


$D = 0, T_{vj} \leq 175\text{ }^\circ\text{C}, V_{GE} = 15\text{ V}, T_c = 25\text{ }^\circ\text{C}$



**Power dissipation as a function of case temperature, IGBT**

$P_{tot} = f(T_c)$


$T_{vj} \leq 175\text{ }^\circ\text{C}$



**Collector current as a function of case temperature, IGBT**

$I_C = f(T_c)$


$T_{vj} \leq 175\text{ }^\circ\text{C}, V_{GE} \geq 15\text{ V}$



4 Characteristics diagrams


**Typical output characteristic, IGBT**

$I_C = f(V_{CE})$   
 $T_{vj} = 25\text{ }^\circ\text{C}$




**Typical output characteristic, IGBT**

$I_C = f(V_{CE})$   
 $T_{vj} = 175\text{ }^\circ\text{C}$




**Typical transfer characteristic, IGBT**

$I_C = f(V_{GE})$   
 $V_{CE} = 20\text{ V}$



**Typical collector-emitter saturation voltage as a function of junction temperature, IGBT**


$V_{CEsat} = f(T_{vj})$   
 $V_{GE} = 15\text{ V}$



**4 Characteristics diagrams**


**Gate-emitter threshold voltage as a function of junction temperature, IGBT**

$V_{GEth} = f(T_{vj})$   
 $I_C = 0.50 \text{ mA}$




**Typical switching times as a function of collector current, IGBT**

$t = f(I_C)$   
 $V_{CE} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}, R_G = 35 \text{ } \Omega$




**Typical switching times as a function of gate resistance, IGBT**

$t = f(R_G)$   
 $I_C = 15.0 \text{ A}, V_{CE} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}$



**Typical switching times as a function of junction temperature, IGBT**

$t = f(T_{vj})$   
 $I_C = 15.0 \text{ A}, V_{CE} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 35 \text{ } \Omega$




4 Characteristics diagrams

**Typical switching energy losses as a function of collector current, IGBT**

$E = f(I_C)$


$V_{CE} = 600\text{ V}, T_{vj} = 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}, R_G = 35\text{ }\Omega$



**Typical switching energy losses as a function of gate resistance, IGBT**

$E = f(R_G)$


$I_C = 15.0\text{ A}, V_{CE} = 600\text{ V}, T_{vj} = 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}$



**Typical switching energy losses as a function of junction temperature, IGBT**

$E = f(T_{vj})$


$I_C = 15.0\text{ A}, V_{CE} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_G = 35\text{ }\Omega$



**Typical switching energy losses as a function of collector emitter voltage, IGBT**

$E = f(V_{CE})$

$I_C = 15.0\text{ A}, T_{vj} = 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}, R_G = 35\text{ }\Omega$




**4 Characteristics diagrams**

**Typical gate charge, IGBT**

$V_{GE} = f(Q_{GE})$


$I_C = 15.0 \text{ A}$



**Typical capacitance as a function of collector-emitter voltage, IGBT**

$C = f(V_{CE})$


$f = 1000 \text{ kHz}, V_{GE} = 0 \text{ V}$



**Typical short circuit collector current as a function of gate-emitter voltage, IGBT**

$I_{C(SC)} = f(V_{GE})$


$V_{CE} \leq 600 \text{ V}, T_{vj, start} = 25 \text{ }^\circ\text{C}$



**Short circuit withstand time as a function of gate-emitter voltage, IGBT**

$t_{SC} = f(V_{GE})$

$V_{CE} \leq 600 \text{ V}, T_{vj} \leq 175 \text{ }^\circ\text{C}$




**4 Characteristics diagrams**

**IGBT transient thermal impedance, IGBT**

$Z_{th} = f(t_p)$


$D = t_p/T$



**Diode transient thermal impedance as a function of pulse width, Diode**


$Z_{th} = f(t_p)$

$D = t_p/T$




**Typical diode forward current as a function of forward voltage, Diode**

$I_F = f(V_F)$



**Typical diode forward voltage as a function of junction temperature, Diode**

$V_F = f(T_{vj})$




4 Characteristics diagrams

**Typical reverse recovery time as a function of diode current slope, Diode**

$t_{rr} = f(di_F/dt)$


$V_R = 600\text{ V}, I_F = 15\text{ A}$



**Typical reverse recovery charge as a function of diode current slope, Diode**

$Q_{rr} = f(di_F/dt)$


$V_R = 600\text{ V}, I_F = 15\text{ A}$



**Typical reverse recovery current as a function of diode current slope, Diode**

$I_{rr} = f(di_F/dt)$


$V_R = 600\text{ V}, I_F = 15\text{ A}$




**Typical diode peak rate of fall of reverse recovery current as a function of diode current slope, Diode**

$dI_{rr}/dt = f(di_F/dt)$

$V_R = 600\text{ V}, I_F = 15\text{ A}$




**5 Package outlines**




**Figure 6**


**6 Testing conditions**




**Figure A. Definition of switching times**




**Figure B. Definition of switching losses**



**Figure C. Definition of diode switching characteristics**



**Figure D. Thermal equivalent circuit**



**Figure E. Dynamic test circuit**  
 Parasitic inductance  $L_{\sigma}$ ,  
 parasitic capacitor  $C_{\sigma}$ ,  
 relief capacitor  $C_r$ ,  
 (only for ZVT switching)

**Figure 7**

---

**Revision history****Revision history**

<b>Document revision</b>	<b>Date of release</b>	<b>Description of changes</b>
V1.1	2009-11-27	
V1.2	2010-02-10	
V2.1	2014-12-01	Final data sheet
V2.2		Minor change figure 28
1.10	2021-09-08	Update of legend at the diagram $V_F = f(T_{vj})$

## Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2021-09-08**

**Published by**

**Infineon Technologies AG**

**81726 Munich, Germany**

**© 2021 Infineon Technologies AG**

**All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference**

**IFX-AAK484-005**

## IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.



## WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View IKW15N120H3 on WIN SOURCE](#)
-  [Infineon Technologies Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management