THE DATASHEET OF

IRF6655TRPBF

www.win-source.net 0086-755-83957316

IRF6655PbF
IRF6655TRPbF

International
IOR Rectifier

DirectFET™ Power MOSFET ②

- RoHs Compliant ①
- Lead-Free (Qualified up to 260°C Reflow)
- Application Specific MOSFETs
- Ideal for High Performance Isolated Converter Primary Switch Socket
- Ideal for Control FET sockets in 36V-75V in Synchronous Buck applications
- Low Conduction Losses
- High Cdv/dt Immunity
- Low Profile (<0.7mm)
- Dual Sided Cooling Compatible ①
- Compatible with existing Surface Mount Techniques ①

Typical values (unless otherwise specified)

V_{DSS}	V_{GS}	$R_{DS(on)}$
100V max	±20V max	53mΩ@ 10V

$Q_{g\ tot}$	Q_{gd}	Q_{gs2}	Q_{rr}	Q_{oss}	$V_{gs(th)}$
8.7nC	2.8nC	0.58nC	37nC	4.5nC	4.0V



SH

DirectFET™ ISOMETRIC

Applicable DirectFET Outline and Substrate Outline (see p.7,8 for details)①

SQ	SX	ST	**SH**	MQ	MX	MT	MN			

Description

The IRF6655PbF combines the latest HEXFET® Power MOSFET Silicon technology with the advanced DirectFET™ packaging to achieve the lowest combined on-state resistance and gate charge in a package that has a footprint similar to that of a micro-8, and only 0.7mm profile. The DirectFET package is compatible with existing layout geometries used in power applications, PCB assembly equipment and vapor phase, infra-red or convection soldering techniques, when application note AN-1035 is followed regarding the manufacturing methods and processes. The DirectFET package allows dual sided cooling to maximize thermal transfer in power systems, improving previous best thermal resistance by 80%.

The IRF6655PbF is optimized for low power primary side bridge topologies in isolated DC-DC applications, and for high side control FET sockets in non-isolated synchronous buck DC-DC applications for use in wide range universal Telecom systems (36V – 75V), and for secondary side synchronous rectification in regulated DC-DC topologies. The reduced total losses in the device coupled with the high level of thermal performance enables high efficiency and low temperatures, which are key for system reliability improvements, and makes this device ideal for high performance isolated DC-DC converters.

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{DS}	Drain-to-Source Voltage	100	V
V_{GS}	Gate-to-Source Voltage	±20	
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ 10V ③	4.2	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ 10V ③	3.4	
I_D @ T_C = 25°C	Continuous Drain Current, V_{GS} @ 10V ④	19	
I_{DM}	Pulsed Drain Current ⑤	34	
E_{AS}	Single Pulse Avalanche Energy ⑥	11	mJ
I_{AR}	Avalanche Current ⑤	5.0	A



Fig 1. Typical On-Resistance vs. Gate Voltage



Fig 2. Typical On-Resistance Vs. Gate Voltage

Notes:

① Click on this section to link to the appropriate technical paper.

② Click on this section to link to the DirectFET Website.

③ Surface mounted on 1 in. square Cu board, steady state.

④ T_C measured with thermocouple mounted to top (Drain) of part.

⑤ Repetitive rating; pulse width limited by max. junction temperature.

⑥ Starting T_J = 25°C, L = 0.89mH, R_G = 25Ω, I_{AS} = 5.0A.

08/25/06

Static @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	100	—	—	V	V_{GS} = 0V, I_D = 250μA
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	0.12	—	V/°C	Reference to 25°C, I_D = 1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	53	62	mΩ	V_{GS} = 10V, I_D = 5.0A ⑦
$V_{GS(th)}$	Gate Threshold Voltage	2.8	4.0	4.8	V	V_{DS} = V_{GS}, I_D = 25μA
$\Delta V_{GS(th)}/\Delta T_J$	Gate Threshold Voltage Coefficient	—	-11	—	mV/°C	
I_{DSS}	Drain-to-Source Leakage Current	—	—	20	μA	V_{DS} = 100V, V_{GS} = 0V
		—	—	250		V_{DS} = 80V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	V_{GS} = 20V
	Gate-to-Source Reverse Leakage	—	—	-100		V_{GS} = -20V
gfs	Forward Transconductance	6.6	—	—	S	V_{DS} = 10V, I_D = 5.0A
Q_g	Total Gate Charge	—	8.7	11.7		
Q_{gs1}	Pre-Vth Gate-to-Source Charge	—	2.1	—		V_{DS} = 50V
Q_{gs2}	Post-Vth Gate-to-Source Charge	—	0.58	—	nC	V_{GS} = 10V
Q_{gd}	Gate-to-Drain Charge	—	2.8	4.2		I_D = 5.0A
Q_{godr}	Gate Charge Overdrive	—	3.2	—		See Fig. 15
Q_{sw}	Switch Charge (Q_{gs2} + Q_{gd})	—	3.4	—		
Q_{oss}	Output Charge	—	4.5	—	nC	V_{DS} = 16V, V_{GS} = 0V
R_G	Gate Resistance	—	1.9	2.9	Ω	
$t_{d(on)}$	Turn-On Delay Time	—	7.4	—		V_{DD} = 50V, V_{GS} = 10V ⑦
t_r	Rise Time	—	2.8	—		I_D = 5.0A
$t_{d(off)}$	Turn-Off Delay Time	—	14	—	ns	R_G=6.0Ω
t_f	Fall Time	—	4.3	—		See Fig. 16 & 17
C_{iss}	Input Capacitance	—	530	—		V_{GS} = 0V
C_{oss}	Output Capacitance	—	110	—	pF	V_{DS} = 25V
C_{rss}	Reverse Transfer Capacitance	—	29	—		f = 1.0MHz
C_{oss}	Output Capacitance	—	510	—		V_{GS} = 0V, V_{DS} = 1.0V, f=1.0MHz
C_{oss}	Output Capacitance	—	67	—		V_{GS} = 0V, V_{DS} = 80V, f=1.0MHz

Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	38	A	MOSFET symbol showing the integral reverse p-n junction diode. 
I_{SM}	Pulsed Source Current (Body Diode) ⑤	—	—	34		
V_{SD}	Diode Forward Voltage	—	—	1.3	V	T_J = 25°C, I_S = 5.0A, V_{GS} = 0V ⑦
t_{rr}	Reverse Recovery Time	—	31	47	ns	T_J = 25°C, I_F = 5.0A, V_{DD} = 25V
Q_{rr}	Reverse Recovery Charge	—	37	56	nC	di/dt = 100A/μs ⑦ See Fig. 18

Notes:

⑤ Repetitive rating; pulse width limited by max. junction temperature.

⑦ Pulse width ≤ 400μs; duty cycle ≤ 2%.

Absolute Maximum Ratings

	Parameter	Max.	Units
P_D @T_A = 25°C	Power Dissipation ③	2.2	W
P_D @T_A = 70°C	Power Dissipation ③	1.4	
P_D @T_C = 25°C	Power Dissipation ④	42	
T_P	Peak Soldering Temperature	270	°C
T_J T_{STG}	Operating Junction and Storage Temperature Range	-40 to + 150	

Thermal Resistance

	Parameter	Typ.	Max.	Units
$R_{\theta JA}$	Junction-to-Ambient ③ ❶	——	58	°C/W
$R_{\theta JA}$	Junction-to-Ambient ⑨ ❶	12.5	——	
$R_{\theta JA}$	Junction-to-Ambient ⑩ ❶	20	——	
$R_{\theta JC}$	Junction-to-Case ④ ❶	——	3.0	
$R_{\theta J\text{-}PCB}$	Junction-to-PCB Mounted	1.4	——	
	Linear Derating Factor ③	0.017		W/°C



Fig 3. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Notes:

⑨ Used double sided cooling , mounting pad.

⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink.

❶ R_θ is measured at T_J of approximately 90°C.

③ Surface mounted on 1 in. square Cu (still air).



⑨ Mounted to a PCB with small clip heatsink (still air)

⑩ Mounted on minimum footprint full size board with metalized back and with small clip heatsink (still air)



Fig 4. Typical Output Characteristics



Fig 5. Typical Output Characteristics



Fig 6. Typical Transfer Characteristics



Fig 7. Normalized On-Resistance vs. Temperature



Fig 8. Typical Capacitance vs. Drain-to-Source Voltage



Fig 9. Normalized Typical On-Resistance vs. Drain Current and Gate Voltage



Fig 10. Typical Source-Drain Diode Forward Voltage



Fig11. Maximum Safe Operating Area



Fig 12. Maximum Drain Current vs. Ambient Temperature



Fig 13. Threshold Voltage vs. Temperature



Fig 14. Maximum Avalanche Energy vs. Drain Current



Fig 15a. Gate Charge Test Circuit



Fig 15b. Gate Charge Waveform



Fig 16a. Unclamped Inductive Test Circuit



Fig 16b. Unclamped Inductive Waveforms



Fig 17a. Switching Time Test Circuit



Fig 17b. Switching Time Waveforms



Fig 18. Diode Reverse Recovery Test Circuit for N-Channel HEXFET® Power MOSFETs

DirectFET™ Substrate and PCB Layout, SH Outline ③ (Small Size Can, H-Designation).

Please see DirectFET application note AN-1035 for all details regarding PCB assembly using DirectFET. This includes all recommendations for stencil and substrate designs.





DirectFET™ Outline Dimension, SH Outline (Small Size Can, H-Designation).

Please see DirectFET application note AN-1035 for all details regarding PCB assembly using DirectFET. This includes all recommendations for stencil and substrate designs.



DIMENSIONS				
	METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX
A	4.75	4.85	0.187	0.191
B	3.70	3.95	0.146	0.156
C	2.75	2.85	0.108	0.112
D	0.35	0.45	0.014	0.018
E	0.58	0.62	0.023	0.024
F	0.58	0.62	0.023	0.024
G	0.63	0.67	0.025	0.026
H	0.83	0.87	0.033	0.034
K	0.99	1.03	0.039	0.041
L	2.29	2.33	0.090	0.092
M	0.616	0.676	0.0235	0.0274
R	0.020	0.080	0.0008	0.0031
P	0.08	0.17	0.003	0.007

DirectFET™ Part Marking



DirectFET™ Tape & Reel Dimension (Showing component orientation).



NOTE: Controlling dimensions in mm
Std reel quantity is 4800 parts. (ordered as IRF6655TRPBF). For 1000 parts on 7" reel, order IRF6655TR1PBF

REEL DIMENSIONS								
STANDARD OPTION **(QTY 4800)**					TR1 OPTION **(QTY 1000)**			
	METRIC		IMPERIAL		METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
A	330.0	N.C	12.992	N.C	177.77	N.C	6.9	N.C
B	20.2	N.C	0.795	N.C	19.06	N.C	0.75	N.C
C	12.8	13.2	0.504	0.520	13.5	12.8	0.53	0.50
D	1.5	N.C	0.059	N.C	1.5	N.C	0.059	N.C
E	100.0	N.C	3.937	N.C	58.72	N.C	2.31	N.C
F	N.C	18.4	N.C	0.724	N.C	13.50	N.C	0.53
G	12.4	14.4	0.488	0.567	11.9	12.01	0.47	N.C
H	11.9	15.4	0.469	0.606	11.9	12.01	0.47	N.C

Loaded Tape Feed Direction



DIMENSIONS				
	METRIC		IMPERIAL	
CODE	MIN	MAX	MIN	MAX
A	7.90	8.10	0.311	0.319
B	3.90	4.10	0.154	0.161
C	11.90	12.30	0.469	0.484
D	5.45	5.55	0.215	0.219
E	4.00	4.20	0.158	0.165
F	5.00	5.20	0.197	0.205
G	1.50	N.C	0.059	N.C
H	1.50	1.60	0.059	0.063

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.08/06

Note: For the most current drawings please refer to the IR website at:
http://www.irf.com/package/

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View IRF6655TRPBF on WIN SOURCE
- Infineon Technologies Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management