




**THE DATASHEET OF**  
**3577**




# PC QUICK-FIT FEMALE TERMINALS



**ACCEPTS .110 (2.8) × .032 (.81) TAB**

**SMT - HORIZONTAL ENTRY**



**SPECIFICATIONS**


**Material:** .012 (.30) Brass, Tin-Nickel Plate  
**Current Rating:** 15 Amps @ 500V AC

**CAT. NO. 3569\*** (Bulk)

**CAT. NO. 3569TR\*** (Tape & Reel)

**Tape & Reel Spec's:** 24mm wide, 8mm pitch, 13 inch reel (2000 pieces per reel)


**Mounting Detail**



**ACCEPTS ALL TABS**

.110 (2.8) TO .50 (6.4) × .020 (.50) TO .032 (.80)

**SMT - VERTICAL OR HORIZONTAL ENTRY**



**SPECIFICATIONS**



**Material:** .016 (.40) Brass, Tin-Nickel Plate  
**Current Rating:** 15 Amps @ 500V AC

**CAT. NO. 3586\*** (Bulk)


**CAT. NO. 3586TR\*** (Tape & Reel)

**Tape & Reel Spec's:** 16mm wide, 12mm pitch, 13 inch reel (750 pieces per reel)

**Mounting Detail**




**Underwriters Laboratories, Inc.**  
**Recognized Component Program**  
 — UL File Number E201546



**ACCEPTS ALL TABS**

.110 (2.8) TO .50 (6.4) × .020 (.50) TO .032 (.80)

**VERTICAL OR HORIZONTAL ENTRY**




**MATERIAL:**


.016 (.41) Brass, Tin-Nickel Plate

CAT. NO.	ORIENTATION
3557	top & side entry
3577*	bottom entry

**Mounting Detail**




**Mounting Detail**



**ACCEPTS .187 (4.8), .205 (5.2), .250 (6.4) TAB**


**HORIZONTAL ENTRY**



**MATERIAL:** Brass, Tin-Nickel Plate


CAT. NO.	ACCEPTS TAB	"W"	"A"	MATL THICK
3571	.187(4.8) × .020(.51)	.222 (5.6)	.162 (4.1)	.012 (.30)
3572*	.187(4.8) × .032(.81)			
3546	.205(5.2) × .020(.51)	.240 (6.1)	.180 (4.6)	.012 (.30)
3550	.205(5.2) × .032(.81)	.291 (7.4)	.205 (5.2)	.016 (.41)
3547	.250(6.4) × .032(.81)			

**Mounting Detail**



**ACCEPTS .110 (2.8) TAB**

**HORIZONTAL ENTRY**




**MATERIAL:**

.012 (.30) Brass, Tin-Nickel Plate



CAT. NO.	ACCEPTS TAB
3545	.110 (2.8) × .020 (.51)
3549	.110 (2.8) × .032 (.81)

**Mounting Detail**



**ACCEPTS .110 (2.8) TAB**

**VERTICAL ENTRY**




**MATERIAL:**

.012 (.30) Brass, Tin-Nickel Plate



CAT. NO.	ACCEPTS TAB	W
3534	.110(2.8) × .020(.51)	.070 (1.80)
3544	.110(2.8) × .032(.81)	.075 (1.92)

**Mounting Detail**



**ACCEPTS .187 (4.8) TAB**


**VERTICAL ENTRY**



**MATERIAL:** .016 (.41) Brass, Tin-Nickel Plate



CAT. NO.	ACCEPTS TAB	"W"
3548	.187(4.8) × .020(.51)	.093 (2.36)
3578*	.187(4.8) × .020(.51)	.093 (2.36)
3551	.187(4.8) × .032(.81)	.102 (2.59)

**Mounting Detail**



**ACCEPTS .205 (5.2) TAB**

**VERTICAL ENTRY**




**MATERIAL:**

.016 (.41) Brass, Tin-Nickel Plate



CAT. NO.	ACCEPTS TAB
3525	.205 (5.2) × .020 (.51)
3575*	.205 (5.2) × .032 (.81)

**Mounting Detail**



**ACCEPTS .250 (6.4) TAB**

**VERTICAL ENTRY**




**MATERIAL:**

.016 (.41) Brass, Tin-Nickel Plate



CAT. NO.	ACCEPTS TAB
3528	.250 (6.4) × .032 (.81)

**Mounting Detail**



**ACCEPTS .312 (7.9) TAB**

**OVER SIZED**




**MATERIAL:**

.020 (.51) Copper, Tin-Nickel Plate

**CAT. NO. 3555**

**Mounting Detail**



\* Not UL Recognized

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View 3577 on WIN SOURCE](#)
- ⊖ [Adafruit Industries LLC Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management