

Qualcomm® IQ6 Series Platform

The Qualcomm IQ6 Series delivers essential, industrial-grade performance in a wide temperature operating range, offering powerful and especially efficient compute capabilities, AI workload processing capabilities, and rich peripheral support, including Wi-Fi, Ethernet, and USB, tailor-made for industrial devices in the entry and mid-tier segments.

Qualcomm IQ6 Series delivers industrial-grade performance and features for building intelligent edge computing devices, including industrial gateways, controllers, industrial machine vision, industrial HMI, and more in a cost-effective manner. It integrates a powerful image signal processor (ISP) and the Qualcomm® AI Engine, along with a heterogeneous compute architecture that includes a highly optimized CPU, GPU, and DSP for industrial-grade AI performance at the entry to mid-tier segment.

Features

- Qualcomm® Kryo™ 460 CPU with a 64-bit Octa-Core processor
- Qualcomm Spectra™ 230 ISP
- Qualcomm® Adreno™ 612 GPU
- Thermal junction (Tj) temperature range of -40°C to +105°C allows deployment in demanding industrial environments
- Adreno Video Processing Unit (VPU) 443 that features 4K60 decode and 1080p60 encode with native support for H.265/H.264, VP8, VP9 (decode)

Ordering Information

Product	Part Number
IQ-615	QCS615-0-AA

Highlights

Powerful and Efficient Computing

The Qualcomm® Kryo™ CPU delivers powerful computing with an extra emphasis on efficiency for essential, industrial-grade performance, on-device AI workload processing, and rich peripheral support.



Wide Temperature Range

The Qualcomm IQ6 Series is built to deliver essential, industrial-grade performance in a wide junction temperature operating range of -40°C to +105°C for use cases that may not need to meet the most extreme temperature demands, but still operate in far-ranging temperatures.




Peripheral Support

With a rich array of input and output interfaces, the Qualcomm IQ6 Series supports peripherals, including Wi-Fi, PCIe, Ethernet, and USB.




Developer-Friendly Design

The Qualcomm IQ6 Series is designed to be developer-friendly, with multi-OS support for Qualcomm® Linux® software stack and Ubuntu. Combined with product longevity support for 10+ years, developers can easily build, test, and deploy solutions based on this platform with confidence that their designs will be supported for years to come.



Block Diagram



Target Applications

- Industrial Gateways, Controllers
- Industrial Handheld (IHH) Devices
- Industrial HMI
- Industrial Machine Vision



Specifications

Technology		11 nm FINFET low power
Kryo CPU	Architecture	64-bit Octa-Core
	Cores	2x Kryo4 Gold @ 1.9 GHz + 6x Kryo4 Silver-lite @ 1.6 GHz
Memory	Architecture	2x 16-bit LPDDR4x 1555 MHz, up to 8 GB
GPU, Video, and Display	GPU	Adreno 612 GPU
	APIs	OpenGL ES3.2, OpenCL 2.0, DX12FL9.3, Vulkan 1.x
	Video Decode	4K 60fps 10-bit: HEVC/H.265, 8-bit VP9, VP8, and H.264
	Video Encode	1080p 60fps, 8-bit: HEVC/H.265, H.264, and VP8
	Video Decode + Encode	4K 30fps Decode + 1080p 30fps Encode
	Display Resolutions	Up to a maximum of 5 MP, e.g.: 2x 1920x1080 @ 60fps (FHD) + 1x 1280x720 @ 60fps
	Display Interfaces	1x 4-lane MIPI DSI-2 + 1x DP v1.4 (supports: SST and MST)
Camera	Camera Lanes	Up to 6 cameras over 3x 4-lane MIPI CSI-2 v1.3 (D-PHY 1.2, C-PHY 1.0)
Audio	Audio DSP (aDSP)	Hexagon QDSP6 v66K @ 1.0 GHz
	Audio Interfaces	Up to 5x I2S/PCM/TDM, 2x SLIMbus
I/O Interfaces	ETH AVB	1x RGMII / RMII with MDIO GB ETH AVB (TV8 only)
	PCIe	1-lane PCIe Gen 2 RC / EP
	USB	1x USB 3.1 Gen 1 (SS), 1x USB 2.0 (HS) OTG
	Secure Digital Interfaces	1x 4-bit SD/SDIO 3.0 (UHS-I), 1x 8-bit eMMC 5.1, 1-lane UFS2.1 Gear3 (1-lane UFS3.1 can be supported with UFS2.1 feature set), QSPI for boot
	Software-Defined Radio	2x high-speed I2S
	Multiport SPI / I2C / UART	Up to 14x 4-wire QUPv3 (UART, I2C, SPI)
	GPIOs	100+ GPIOs
Package	Balls, Dimensions	FCBGA761+HS: 23 x 23 x 2.45 mm (incl metallic heat spreader); 0.8 mm pitch, non-PoP
Power Management	PMIC	1x PMM6155AU (0.8 mm pitch)
Vector DSP	Compute DSP (cDSP)	Hexagon QDSP6 v66A @ 1.1 GHz, 2x HVX (vector extensions)
Connectivity	WLAN / Bluetooth	Optional: Wi-Fi 6E 802.11ax 2x2 Dual MAC DBS + Bluetooth 5.3. Tri-band support of 2.4GHz, 5GHz, and 6GHz
Temperature Range	Junction Temp (Tj)	-40°C to +105°C
Operating System	Multiple OS	Linux Yocto, Ubuntu
Build Design	Ball pitch	FCBGA761+HS, 23 mm x 23 mm, 0.8 mm ball pitch



The Qualcomm IQ6 Series is a part of the Product Longevity Program for Qualcomm IoT Portfolio. These products are developed and engineered with product longevity and durability in mind, helping to bring stability to our customer product designs. Product longevity dates are subject to change without notice.



To learn more visit: [qualcomm.com](https://www.qualcomm.com)



©2024 Qualcomm Technologies, Inc. and/or its affiliated companies. All Rights Reserved. Snapdragon and Qualcomm branded products are products of Qualcomm Technologies, Inc. and/or its subsidiaries. The registered trademark Linux® is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View QCA-8111-0-MSP81-TR-00-0 on WIN SOURCE](#)
-  [Qualcomm Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management