



THE DATASHEET OF MOC207M



8-pin SOIC Single-Channel Phototransistor Output Optocoupler

**MOC205M, MOC206M,
MOC207M, MOC211M,
MOC212M, MOC213M,
MOC216M, MOC217M**

Description


These devices consist of a gallium arsenide infrared emitting diode optically coupled to a monolithic silicon phototransistor detector, in a surface mountable, small outline, plastic package. They are ideally suited for high-density applications, and eliminate the need for through-the-board mounting.

Features

- Closely Matched Current Transfer Ratios Minimum BV_{CEO} of 70 V Guaranteed
 - ◆ MOC205M, MOC206M, MOC207M
- Minimum BV_{CEO} of 30 V Guaranteed
 - ◆ MOC211M, MOC212M, MOC213M, MOC216M, MOC217M
- Low LED Input Current Required for Easier Logic Interfacing
 - ◆ MOC216M, MOC217M
- Convenient Plastic SOIC-8 Surface Mountable Package Style, with 0.050" Lead Spacing
- Safety and Regulatory Approvals:
 - ◆ UL1577, 2,500 VAC_{RMS} for 1 Minute
 - ◆ DIN-EN/IEC60747-5-5, 565 V Peak Working Insulation Voltage
- These are Pb-Free Devices

Applications

- Feedback Control Circuits
- Interfacing and Coupling Systems of Different Potentials and Impedances
- General Purpose Switching Circuits
- Monitor and Detection Circuits




SOIC8
CASE 751DZ

MARKING DIAGRAM



- XXX = Specific Device Code
- V = DIN EN/IEC60747-5-5 Option (only appears on component ordered with this option)
- X = Year Code
- YY = Work Week
- S = Assembly Package Code

SCHEMATIC



ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M, MOC216M, MOC217M

SAFETY AND INSULATION RATINGS (As per DIN EN/IEC 60747-5-5, this optocoupler is suitable for “safe electrical insulation” only within the safety limit data. Compliance with the safety ratings shall be ensured by means of protective circuits.)

| Parameter | | Characteristics |
|---|-----------------------|-----------------|
| Installation Classifications per DIN VDE 0110/1.89 Table 1, For Rated Mains Voltage | <150 V _{RMS} | I-IV |
| | <300 V _{RMS} | I-III |
| Climatic Classification | | 55/100/21 |
| Pollution Degree (DIN VDE 0110/1.89) | | 2 |
| Comparative Tracking Index | | 175 |

| Symbol | Parameter | Value | Unit |
|-----------------------|--|------------------|-------------------|
| V _{PR} | Input-to-Output Test Voltage, Method A, V _{IORM} × 1.6 = V _{PR} , Type and Sample Test with t _m = 10 s, Partial Discharge < 5 pC | 904 | V _{peak} |
| | Input-to-Output Test Voltage, Method B, V _{IORM} × 1.875 = V _{PR} , 100% Production Test with t _m = 1 s, Partial Discharge < 5 pC | 1060 | V _{peak} |
| V _{IORM} | Maximum Working Insulation Voltage | 565 | V _{peak} |
| V _{IOTM} | Highest Allowable Over-Voltage | 4000 | V _{peak} |
| | External Creepage | ≥4 | mm |
| | External Clearance | ≥4 | mm |
| DTI | Distance Through Insulation (Insulation Thickness) | ≥0.4 | mm |
| T _S | Case Temperature (Note 1) | 150 | °C |
| I _{S,INPUT} | Input Current (Note 1) | 200 | mA |
| P _{S,OUTPUT} | Output Power (Note 1) | 300 | mW |
| R _{IO} | Insulation Resistance at T _S , V _{IO} = 500 V (Note 1) | >10 ⁹ | Ω |

1. Safety limit values – maximum values allowed in the event of a failure.

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

| Symbol | Rating | Value | Unit |
|--------|--------|-------|------|
|--------|--------|-------|------|

TOTAL DEVICE

| | | | |
|------------------|--|--------------------|-------|
| T _{STG} | Storage Temperature | -40 to +125 | °C |
| T _A | Ambient Operating Temperature | -40 to +100 | °C |
| T _J | Junction Temperature | -40 to +125 | °C |
| T _{SOL} | Lead Solder Temperature | 260 for 10 seconds | °C |
| P _D | Total Device Power Dissipation @ T _A = 25°C | 240 | mW |
| | Derate above 25°C | 2.94 | mW/°C |

EMITTER

| | | | |
|---------------------|---|-----|-------|
| I _F | Continuous Forward Current | 60 | mA |
| I _F (pk) | Forward Current – Peak (PW = 100 μs, 120 pps) | 1.0 | A |
| V _R | Reverse Voltage | 6.0 | V |
| P _D | LED Power Dissipation @ T _A = 25°C | 90 | mW |
| | Derate above 25°C | 0.8 | mW/°C |

DETECTOR

| | | | |
|------------------|--|------|-------|
| I _C | Continuous Collector Current | 150 | mA |
| V _{CEO} | Collector-Emitter Voltage | 30 | V |
| V _{ECO} | Emitter-Collector Voltage | 7 | V |
| P _D | Detector Power Dissipation @ T _A = 25°C | 150 | mW |
| | Derate above 25°C | 1.76 | mW/°C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M, MOC216M, MOC217M

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

| Symbol | Parameter | Test Condition | Min | Typ | Max | Unit | |
|-----------------|-------------------------|--|------------------------|-------|------|------|---|
| EMITTER | | | | | | | |
| V _F | Input Forward Voltage | MOC216M, MOC217M | I _F = 1 mA | – | 1.07 | 1.3 | V |
| | | MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M | I _F = 10 mA | – | 1.15 | 1.5 | V |
| I _R | Reverse Leakage Current | V _R = 6 V | – | 0.001 | 100 | μA | |
| C _{IN} | Input Capacitance | | – | 18 | – | pF | |

DETECTOR

| | | | | | | | |
|-------------------|-------------------------------------|---|--|----|-----|----|----|
| I _{CEO1} | Collector–Emitter Dark Current | | V _{CE} = 10 V, T _A = 25°C | – | 1.0 | 50 | nA |
| I _{CEO2} | | | V _{CE} = 10 V, T _A = 100°C | – | 1.0 | – | μA |
| BV _{CEO} | Collector–Emitter Breakdown Voltage | MOC205M, MOC206M, MOC207M | I _C = 100 μA | 70 | 100 | – | V |
| | | MOC211M, MOC212M, MOC213M, MOC216M, MOC217M | I _C = 100 μA | 30 | 100 | – | V |
| BV _{CBO} | Collector–Base Breakdown Voltage | | I _C = 10 μA | 70 | 120 | – | V |
| BV _{EBO} | Emitter–Collector Breakdown Voltage | | I _E = 100 μA | 7 | 10 | – | V |
| C _{CE} | Collector–Emitter Capacitance | | f = 1.0 MHz, V _{CE} = 0 V | – | 7 | – | pF |

COUPLED

| | | | | | | | |
|----------------------|--------------------------------------|--|---|-----|-----|-----|----|
| CTR | Collector–Output Current | MOC205M | I _F = 10 mA, V _{CE} = 10 V | 40 | – | 80 | % |
| | | MOC206M | I _F = 10 mA, V _{CE} = 10 V | 63 | – | 125 | % |
| | | MOC207M | I _F = 10 mA, V _{CE} = 10 V | 100 | – | 200 | % |
| | | MOC211M | I _F = 10 mA, V _{CE} = 10 V | 20 | – | – | % |
| | | MOC212M | I _F = 10 mA, V _{CE} = 10 V | 50 | – | – | % |
| | | MOC213M | I _F = 10 mA, V _{CE} = 10 V | 100 | – | – | % |
| | | MOC216M | I _F = 1 mA, V _{CE} = 5 V | 50 | – | – | % |
| | | MOC217M | I _F = 1 mA, V _{CE} = 5 V | 100 | – | – | % |
| V _{CE(SAT)} | Collector–Emitter Saturation Voltage | MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M | I _C = 2 mA, I _F = 10 mA | – | – | 0.4 | V |
| | | MOC216M, MOC217M | I _C = 100 μA, I _F = 1 mA | – | – | 0.4 | V |
| t _{on} | Turn–On Time | | I _C = 2 mA, V _{CC} = 10 V, R _L = 100 Ω (Figure 12) | – | 7.5 | – | μs |
| t _{off} | Turn–Off Time | | I _C = 2 mA, V _{CC} = 10 V, R _L = 100 Ω (Figure 12) | – | 5.7 | – | μs |
| t _r | Rise Time | | I _C = 2 mA, V _{CC} = 10 V, R _L = 100 Ω (Figure 12) | – | 3.2 | – | μs |
| t _f | Fall Time | | I _C = 2 mA, V _{CC} = 10 V, R _L = 100 Ω (Figure 12) | – | 4.7 | – | μs |

ISOLATION CHARACTERISTICS

| | | | | | | |
|------------------|--------------------------------|--|------------------|-----|---|--------------------|
| V _{ISO} | Input–Output Isolation Voltage | t = 1 Minute | 2500 | – | – | VAC _{RMS} |
| C _{ISO} | Isolation Capacitance | V _{I-O} = 0 V, f = 1 MHz | – | 0.2 | – | pF |
| R _{ISO} | Isolation Resistance | V _{I-O} = ±500 VDC, T _A = 25°C | 10 ¹¹ | – | – | Ω |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M, MOC216M, MOC217M

TYPICAL PERFORMANCE CURVES




Figure 1. LED Forward Voltage vs. Forward Current




Figure 2. Output Current vs. Input Current




Figure 3. Output Current vs. Ambient Temperature




Figure 4. Output Current vs. Collector-Emitter Voltage




Figure 5. Dark Current vs. Ambient Temperature




Figure 6. CTR vs. R_{BE} (Unsaturated)

MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M, MOC216M, MOC217M

TYPICAL PERFORMANCE CURVES (continued)




Figure 7. CTR vs. R_{BE} (Saturated)




Figure 8. Normalized t_{on} vs. R_{BE}




Figure 9. Normalized t_{off} vs. R_{BE}




Figure 10. Switching Time Test Circuit and Waveforms

MOC205M, MOC206M, MOC207M, MOC211M, MOC212M, MOC213M, MOC216M,
MOC217M

REFLOW PROFILE




Figure 11. Reflow Profile

Table 1.

| Profile Feature | Pb-Free Assembly Profile |
|---|--------------------------|
| Temperature Minimum (T _{smin}) | 150°C |
| Temperature Maximum (T _{smax}) | 200°C |
| Time (t _s) from (T _{smin} to T _{smax}) | 60 – 120 seconds |
| Ramp-up Rate (t _L to t _p) | 3°C/second maximum |
| Liquidous Temperature (T _L) | 217°C |
| Time (t _L) Maintained Above (T _L) | 60 – 150 seconds |
| Peak Body Package Temperature | 260°C +0°C / -5°C |
| Time (t _p) within 5°C of 260°C | 30 seconds |
| Ramp-down Rate (T _P to T _L) | 6°C/second maximum |
| Time 25°C to Peak Temperature | 8 minutes maximum |

ORDERING INFORMATION (Note 2)

| Part Number | Package | Shipping [†] |
|-------------|---|-----------------------|
| MOC205M | Small Outline 8-Pin | 50 Units / Tube |
| MOC205R2M | Small Outline 8-Pin | 2500 / Tape & Reel |
| MOC205VM | Small Outline 8-Pin, DIN EN/IEC60747-5-5 Option | 50 Units / Tube |
| MOC205R2VM | Small Outline 8-Pin, DIN EN/IEC60747-5-5 Option | 2500 / Tape & Reel |

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

2. The product orderable part number system listed in this table also applies to the MOC20XM and MOC21XM products.

MECHANICAL CASE OUTLINE





PACKAGE DIMENSIONS

ON Semiconductor®




SOIC8
CASE 751DZ
ISSUE O

DATE 30 SEP 2016



NOTES:

- A) NO STANDARD APPLIES TO THIS PACKAGE
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
- D) LANDPATTERN STANDARD: SOIC127P600X175-8M.



| | | |
|-------------------------|--------------------|--|
| DOCUMENT NUMBER: | 98AON13733G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | SOIC8 | PAGE 1 OF 1 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View MOC207M on WIN SOURCE](#)
- ⊖ [Fairchild/ON Semiconductor Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management