



**THE DATASHEET OF
NDD05N50ZT4G**



NDF05N50Z, NDD05N50Z

N-Channel Power MOSFET 500 V, 1.5 Ω

Features

- Low ON Resistance
- Low Gate Charge
- ESD Diode–Protected Gate
- 100% Avalanche Tested
- 100% Rg Tested
- These Devices are Pb–Free, Halogen Free/BFR Free and are RoHS Compliant

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

| Rating | Symbol | NDF | NDD | Unit |
|---|-----------------------------------|-----------------|-----|------|
| Drain–to–Source Voltage | V _{DSS} | 500 | | V |
| Continuous Drain Current R _{θJC} | I _D | 5.5 (Note 1) | 4.7 | A |
| Continuous Drain Current R _{θJC} , T _A = 100°C | I _D | 3.5 (Note 1) | 3 | A |
| Pulsed Drain Current, V _{GS} @ 10 V | I _{DM} | 20 | 19 | A |
| Power Dissipation R _{θJC} | P _D | 30 | 83 | W |
| Gate–to–Source Voltage | V _{GS} | ±30 | | V |
| Single Pulse Avalanche Energy, I _D = 5.0 A | E _{AS} | 130 | | mJ |
| ESD (HBM) (JESD22–A114) | V _{esd} | 3000 | | V |
| RMS Isolation Voltage (t = 0.3 sec., R.H. ≤ 30%, T _A = 25°C) (Figure 17) | V _{ISO} | 4500 | | V |
| Peak Diode Recovery (Note 2) | dV/dt | 4.5 | | V/ns |
| MOSFET dV/dt | dV/dt | 60 | | V/ns |
| Continuous Source Current (Body Diode) | I _S | 5 | | A |
| Maximum Temperature for Soldering Leads | T _L | 260 | | °C |
| Operating Junction and Storage Temperature Range | T _J , T _{stg} | –55 to 150 | | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



1. Limited by maximum junction temperature
2. I_S = 4.4 A, di/dt ≤ 100 A/μs, V_{DD} ≤ BV_{DSS}, T_J = +150°C




ON Semiconductor®

www.onsemi.com


| V _{DSS} | R _{DS(on)} (MAX) @ 2.2 A |
|------------------|-----------------------------------|
| 500 V | 1.5 Ω |



NDF05N50ZG,
NDF05N50ZH
TO–220FP
CASE 221AH



NDD05N50Z–1G
IPAK
CASE 369D



NDD05N50ZT4G
DPAK
CASE 369AA

ORDERING AND MARKING INFORMATION

See detailed ordering, marking and shipping information on page 7 of this data sheet.

NDF05N50Z, NDD05N50Z

THERMAL RESISTANCE

| Parameter | Symbol | Value | Unit |
|----------------------------------|------------------|----------------------|------|
| Junction-to-Case (Drain) | R _{θJC} | NDF05N50Z | 4.2 |
| | | NDD05N50Z | 1.5 |
| Junction-to-Ambient Steady State | R _{θJA} | (Note 3) NDF05N50Z | 50 |
| | | (Note 4) NDD05N50Z | 38 |
| | | (Note 3) NDD05N50Z-1 | 80 |

3. Insertion mounted

4. Surface mounted on FR4 board using 1" sq. pad size, (Cu area = 1.127 in sq [2 oz] including traces).

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

| Characteristic | Symbol | Test Conditions | Min | Typ | Max | Unit |
|----------------|--------|-----------------|-----|-----|-----|------|
|----------------|--------|-----------------|-----|-----|-----|------|

OFF CHARACTERISTICS

| | | | | | | |
|--|-------------------------------------|--|-------|-----|-----|------|
| Drain-to-Source Breakdown Voltage | BV _{DSS} | V _{GS} = 0 V, I _D = 1 mA | 500 | | | V |
| Breakdown Voltage Temperature Co-efficient | ΔBV _{DSS} /ΔT _J | Reference to 25°C, I _D = 1 mA | | 0.6 | | V/°C |
| Drain-to-Source Leakage Current | I _{DSS} | V _{DS} = 500 V, V _{GS} = 0 V | 25°C | | 1 | μA |
| | | | 150°C | | 50 | |
| Gate-to-Source Forward Leakage | I _{GSS} | V _{GS} = ±20 V | | | ±10 | μA |

ON CHARACTERISTICS (Note 5)

| | | | | | | |
|--------------------------------------|---------------------|--|-----|------|-----|---|
| Static Drain-to-Source On-Resistance | R _{DS(on)} | V _{GS} = 10 V, I _D = 2.2 A | | 1.25 | 1.5 | Ω |
| Gate Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 50 μA | 3.0 | 3.9 | 4.5 | V |
| Forward Transconductance | g _{FS} | V _{DS} = 15 V, I _D = 2.5 A | | 3.5 | | S |

DYNAMIC CHARACTERISTICS

| | | | | | | |
|--|------------------|---|-----|------|-----|----|
| Input Capacitance (Note 6) | C _{iss} | V _{DS} = 25 V, V _{GS} = 0 V, f = 1.0 MHz | 421 | 530 | 632 | pF |
| Output Capacitance (Note 6) | C _{oss} | | 50 | 68 | 80 | |
| Reverse Transfer Capacitance (Note 6) | C _{rss} | | 8 | 15 | 25 | |
| Total Gate Charge (Note 6) | Q _g | V _{DD} = 250 V, I _D = 5 A, V _{GS} = 10 V | 9 | 18.5 | 28 | nC |
| Gate-to-Source Charge (Note 6) | Q _{gs} | | 2 | 4 | 6 | |
| Gate-to-Drain ("Miller") Charge (Note 6) | Q _{gd} | | 5 | 10 | 15 | |
| Plateau Voltage | V _{GP} | | | 6.5 | | V |
| Gate Resistance | R _g | | 1.5 | 4.5 | 8 | Ω |

RESISTIVE SWITCHING CHARACTERISTICS

| | | | | | | |
|---------------------|---------------------|---|--|----|--|----|
| Turn-On Delay Time | t _{d(on)} | V _{DD} = 250 V, I _D = 5 A, V _{GS} = 10 V, R _G = 5 Ω | | 11 | | ns |
| Rise Time | t _r | | | 15 | | |
| Turn-Off Delay Time | t _{d(off)} | | | 24 | | |
| Fall Time | t _f | | | 14 | | |

SOURCE-DRAIN DIODE CHARACTERISTICS (T_C = 25°C unless otherwise noted)

| | | | | | | |
|-------------------------|-----------------|---|--|------|-----|----|
| Diode Forward Voltage | V _{SD} | I _S = 5 A, V _{GS} = 0 V | | | 1.6 | V |
| Reverse Recovery Time | t _{rr} | V _{GS} = 0 V, V _{DD} = 30 V, I _S = 5 A, di/dt = 100 A/μs | | 255 | | ns |
| Reverse Recovery Charge | Q _{rr} | | | 1.25 | | μC |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Pulse Width ≤ 380 μs, Duty Cycle ≤ 2%.

6. Guaranteed by design.

NDF05N50Z, NDD05N50Z

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Region versus Gate-to-Source Voltage




Figure 4. On-Resistance versus Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. BV_{DSS} Variation with Temperature

NDF05N50Z, NDD05N50Z

TYPICAL CHARACTERISTICS




Figure 7. Drain-to-Source Leakage Current versus Voltage




Figure 8. Capacitance Variation




Figure 9. Gate-to-Source Voltage and Drain-to-Source Voltage versus Total Charge




Figure 10. Resistive Switching Time Variation versus Gate Resistance




Figure 11. Diode Forward Voltage versus Current

NDF05N50Z, NDD05N50Z

TYPICAL CHARACTERISTICS




Figure 12. Maximum Rated Forward Biased Safe Operating Area NDF05N50Z




Figure 13. Maximum Rated Forward Biased Safe Operating Area NDD05N50Z




Figure 14. Thermal Impedance (Junction-to-Case) for NDF05N50Z




Figure 15. Thermal Impedance (Junction-to-Case) for NDD05N50Z

NDF05N50Z, NDD05N50Z

TYPICAL CHARACTERISTICS




Figure 16. Thermal Impedance (Junction-to-Ambient) for NDD05N50Z




Figure 17. Isolation Test Diagram

Measurement made between leads and heatsink with all leads shorted together.

*For additional mounting information, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


NDF05N50Z, NDD05N50Z

ORDERING INFORMATION

| Order Number | Package | Shipping† |
|--------------|-------------------------------------|----------------------|
| NDF05N50ZG | TO-220FP (Pb-Free, Halogen-Free) | 50 Units / Rail |
| NDF05N50ZH | TO-220FP (Pb-Free, Halogen-Free) | 50 Units / Rail |
| NDD05N50Z-1G | IPAK (Pb-Free, Halogen-Free) | 75 Units / Rail |
| NDD05N50ZT4G | DPAK (Pb-Free, Halogen-Free) | 2500 / Tape and Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

MARKING DIAGRAMS




A = Location Code
 Y = Year
 WW = Work Week
 G, H = Pb-Free, Halogen-Free Package

NDF05N50Z, NDD05N50Z

PACKAGE DIMENSIONS



TO-220 FULLPACK, 3-LEAD
CASE 221AH
ISSUE F



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR UNCONTROLLED IN THIS AREA.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH AND GATE PROTRUSIONS. MOLD FLASH AND GATE PROTRUSIONS NOT TO EXCEED 0.13 PER SIDE. THESE DIMENSIONS ARE TO BE MEASURED AT OUTERMOST EXTREME OF THE PLASTIC BODY.
5. DIMENSION b2 DOES NOT INCLUDE DAMBAR PROTRUSION. LEAD WIDTH INCLUDING PROTRUSION SHALL NOT EXCEED 2.00.
6. CONTOURS AND FEATURES OF THE MOLDED PACKAGE BODY MAY VARY WITHIN THE ENVELOPE DEFINED BY DIMENSIONS A1 AND H1 FOR MANUFACTURING PURPOSES.

| MILLIMETERS | | |
|-------------|----------|-------|
| DIM | MIN | MAX |
| A | 4.30 | 4.70 |
| A1 | 2.50 | 2.90 |
| A2 | 2.50 | 2.90 |
| b | 0.54 | 0.84 |
| b2 | 1.10 | 1.40 |
| c | 0.49 | 0.79 |
| D | 14.70 | 15.30 |
| E | 9.70 | 10.30 |
| e | 2.54 BSC | |
| H1 | 6.60 | 7.10 |
| L | 12.50 | 14.73 |
| L1 | --- | 2.80 |
| P | 3.00 | 3.40 |
| Q | 2.80 | 3.20 |




ALTERNATE CONSTRUCTION

NDF05N50Z, NDD05N50Z

PACKAGE DIMENSIONS

IPAK
CASE 369D
ISSUE C



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.235 | 0.245 | 5.97 | 6.35 |
| B | 0.250 | 0.265 | 6.35 | 6.73 |
| C | 0.086 | 0.094 | 2.19 | 2.38 |
| D | 0.027 | 0.035 | 0.69 | 0.88 |
| E | 0.018 | 0.023 | 0.46 | 0.58 |
| F | 0.037 | 0.045 | 0.94 | 1.14 |
| G | 0.090 BSC | | 2.29 BSC | |
| H | 0.034 | 0.040 | 0.87 | 1.01 |
| J | 0.018 | 0.023 | 0.46 | 0.58 |
| K | 0.350 | 0.380 | 8.89 | 9.65 |
| R | 0.180 | 0.215 | 4.45 | 5.45 |
| S | 0.025 | 0.040 | 0.63 | 1.01 |
| V | 0.035 | 0.050 | 0.89 | 1.27 |
| Z | 0.155 | --- | 3.93 | --- |


STYLE 2:

- PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

NDF05N50Z, NDD05N50Z

PACKAGE DIMENSIONS

DPAK (SINGLE GAUGE) CASE 369AA ISSUE B




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.086 | 0.094 | 2.18 | 2.38 |
| A1 | 0.000 | 0.005 | 0.00 | 0.13 |
| b | 0.025 | 0.035 | 0.63 | 0.89 |
| b2 | 0.030 | 0.045 | 0.76 | 1.14 |
| b3 | 0.180 | 0.215 | 4.57 | 5.46 |
| c | 0.018 | 0.024 | 0.46 | 0.61 |
| c2 | 0.018 | 0.024 | 0.46 | 0.61 |
| D | 0.235 | 0.245 | 5.97 | 6.22 |
| E | 0.250 | 0.265 | 6.35 | 6.73 |
| e | 0.090 BSC | | 2.29 BSC | |
| H | 0.370 | 0.410 | 9.40 | 10.41 |
| L | 0.055 | 0.070 | 1.40 | 1.78 |
| L1 | 0.108 REF | | 2.74 REF | |
| L2 | 0.020 BSC | | 0.51 BSC | |
| L3 | 0.035 | 0.050 | 0.89 | 1.27 |
| L4 | --- | 0.040 | --- | 1.01 |
| Z | 0.155 | --- | 3.93 | --- |

SOLDERING FOOTPRINT*




SCALE 3:1 $\left(\frac{\text{mm}}{\text{inches}}\right)$

STYLE 2:

- PIN 1. GATE
- DRAIN
- SOURCE
- DRAIN

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and the  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marketing.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View NDD05N50ZT4G on WIN SOURCE](#)

 [ON Semiconductor](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management