



**THE DATASHEET OF
NL322522T-1R0J**



Inductors

For General Applications
SMD

NL Series NL3225 Type

FEATURES

- The NL series are available in 5 form factors ranging from 2016 to 5650.
- Utilizing a miniaturized winding structure, these products provide high Q characteristics.
- Inductance tolerance is ± 5 percent.

APPLICATIONS

Personal computers, hard disk drives, and other electronic equipment.

SPECIFICATIONS

| | |
|-----------------------------|---------------------------------|
| Operating temperature range | -20 to +85°C |
| Storage temperature range | -40 to +85°C [Unit of products] |

RECOMMENDED SOLDERING CONDITIONS

REFLOW SOLDERING



FLOW SOLDERING



IRON SOLDERING

Perform soldering at 250°C on 30W max. within 5 seconds.

VAPOR-PHASING



FLUX AND CLEANING

Rosin-based flux is recommended.

Cleaning Conditions

| | |
|---------|---|
| Solvent | Chlorine-based solvent (Do not use acid or alkali solvents.) |
| Time | 2min max. |

PRODUCT IDENTIFICATION

| | | | | |
|-----|--------|-----|-----|-----|
| NL | 201614 | T | 2R2 | J |
| (1) | (2) | (3) | (4) | (5) |

(1) Series name

(2) Dimensions L×W×T

| | |
|--------|---------------|
| 201614 | 2.1×1.6×1.4mm |
| 252018 | 2.5×2.0×1.8mm |
| 322522 | 3.2×2.5×2.2mm |
| 453232 | 4.5×3.2×3.2mm |
| 565050 | 5.6×5.0×5.0mm |

(3) Packaging style

| | |
|---|---------------|
| T | Taping (reel) |
|---|---------------|

(4) Inductance value

| | |
|-----|------|
| 1R0 | 1μH |
| 330 | 33μH |

(5) Inductance tolerance

| | |
|---|------------|
| J | $\pm 5\%$ |
| K | $\pm 10\%$ |

PACKAGING STYLE AND QUANTITIES

| Packaging style | Type | Quantity |
|-----------------|-----------|------------------|
| Taping | NL201614T | 2000 pieces/reel |
| | NL252018T | 2000 pieces/reel |
| | NL322522T | 2000 pieces/reel |
| | NL453232T | 500 pieces/reel |
| | NL565050T | 400 pieces/reel |

Inductors

For General Applications
SMD

NL Series NL3225 Type

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN



ELECTRICAL CHARACTERISTICS

| Inductance (μH) | Inductance tolerance | Q min. | Test frequency L, Q (MHz) | Self-resonant frequency (MHz)min. | DC resistance (Ω)max. | Rated current (mA)max. | Part No. |
|-----------------|----------------------|--------|---------------------------|-----------------------------------|-----------------------|------------------------|-----------------|
| 0.01 | ±10, ±5% | 15 | 100 | 2500 | 0.13 | 450 | NL322522T-010X* |
| 0.012 | ±10, ±5% | 17 | 100 | 2300 | 0.14 | 450 | NL322522T-012X |
| 0.015 | ±10, ±5% | 19 | 100 | 2100 | 0.16 | 450 | NL322522T-015X |
| 0.018 | ±10, ±5% | 21 | 100 | 1900 | 0.18 | 450 | NL322522T-018X |
| 0.022 | ±10, ±5% | 23 | 100 | 1700 | 0.2 | 450 | NL322522T-022X |
| 0.027 | ±10, ±5% | 23 | 100 | 1500 | 0.22 | 450 | NL322522T-027X |
| 0.033 | ±10, ±5% | 25 | 100 | 1400 | 0.24 | 450 | NL322522T-033X |
| 0.039 | ±10, ±5% | 25 | 100 | 1300 | 0.27 | 450 | NL322522T-039X |
| 0.047 | ±10, ±5% | 26 | 100 | 1200 | 0.3 | 450 | NL322522T-047X |
| 0.056 | ±10, ±5% | 26 | 100 | 1100 | 0.33 | 450 | NL322522T-056X |
| 0.068 | ±10, ±5% | 27 | 100 | 1000 | 0.36 | 450 | NL322522T-068X |
| 0.082 | ±10, ±5% | 27 | 100 | 900 | 0.4 | 450 | NL322522T-082X |
| 0.1 | ±10, ±5% | 28 | 100 | 700 | 0.44 | 450 | NL322522T-R10X |
| 0.12 | ±10, ±5% | 30 | 25.2 | 500 | 0.22 | 450 | NL322522T-R12X |
| 0.15 | ±10, ±5% | 30 | 25.2 | 450 | 0.25 | 450 | NL322522T-R15X |
| 0.18 | ±10, ±5% | 30 | 25.2 | 400 | 0.28 | 450 | NL322522T-R18X |
| 0.22 | ±10, ±5% | 30 | 25.2 | 350 | 0.32 | 450 | NL322522T-R22X |
| 0.27 | ±10, ±5% | 30 | 25.2 | 320 | 0.36 | 450 | NL322522T-R27X |
| 0.33 | ±10, ±5% | 30 | 25.2 | 300 | 0.4 | 450 | NL322522T-R33X |
| 0.39 | ±10, ±5% | 30 | 25.2 | 250 | 0.45 | 450 | NL322522T-R39X |
| 0.47 | ±10, ±5% | 30 | 25.2 | 220 | 0.5 | 450 | NL322522T-R47X |
| 0.56 | ±10, ±5% | 30 | 25.2 | 180 | 0.55 | 450 | NL322522T-R56X |
| 0.68 | ±10, ±5% | 30 | 25.2 | 160 | 0.6 | 450 | NL322522T-R68X |
| 0.82 | ±10, ±5% | 30 | 25.2 | 140 | 0.65 | 450 | NL322522T-R82X |
| 1 | ±5% | 30 | 7.96 | 120 | 0.7 | 400 | NL322522T-1R0J |
| 1.2 | ±5% | 30 | 7.96 | 100 | 0.75 | 390 | NL322522T-1R2J |
| 1.5 | ±5% | 30 | 7.96 | 85 | 0.85 | 370 | NL322522T-1R5J |
| 1.8 | ±5% | 30 | 7.96 | 80 | 0.9 | 350 | NL322522T-1R8J |
| 2.2 | ±5% | 30 | 7.96 | 75 | 1 | 320 | NL322522T-2R2J |
| 2.7 | ±5% | 30 | 7.96 | 70 | 1.1 | 290 | NL322522T-2R7J |
| 3.3 | ±5% | 30 | 7.96 | 60 | 1.2 | 260 | NL322522T-3R3J |
| 3.9 | ±5% | 30 | 7.96 | 55 | 1.3 | 250 | NL322522T-3R9J |
| 4.7 | ±5% | 30 | 7.96 | 50 | 1.5 | 220 | NL322522T-4R7J |
| 5.6 | ±5% | 30 | 7.96 | 45 | 1.6 | 200 | NL322522T-5R6J |
| 6.8 | ±5% | 30 | 7.96 | 40 | 1.8 | 180 | NL322522T-6R8J |
| 8.2 | ±5% | 30 | 7.96 | 35 | 2 | 170 | NL322522T-8R2J |
| 10 | ±5% | 30 | 2.52 | 30 | 2.1 | 150 | NL322522T-100J |
| 12 | ±5% | 30 | 2.52 | 20 | 2.5 | 140 | NL322522T-120J |

* X: Please specify the inductance tolerance, K(±10%) or J(±5%)

• Inductance tolerance is only standard.

• Test equipment L, Q: YHP4194A IMPEDANCE ANALYZER (16085A+16093B+TDK TF-1) [$L \geq 0.12\mu\text{H}$]

SRF: HP8753C NETWORK ANALYZER

Rdc: MATSUSHITA VP-2941A DIGITAL MILLIOHM METER

Inductors

For General Applications
SMD

NL Series NL3225 Type

ELECTRICAL CHARACTERISTICS

| Inductance (μH) | Inductance tolerance | Q min. | Test frequency L, Q (MHz) | Self-resonant frequency (MHz)min. | DC resistance (Ω)max. | Rated current (mA)max. | Part No. |
|-----------------|----------------------|--------|---------------------------|-----------------------------------|-----------------------|------------------------|----------------|
| 15 | ±5% | 30 | 2.52 | 20 | 2.8 | 130 | NL322522T-150J |
| 18 | ±5% | 30 | 2.52 | 20 | 3.3 | 120 | NL322522T-180J |
| 22 | ±5% | 30 | 2.52 | 20 | 3.7 | 110 | NL322522T-220J |
| 27 | ±5% | 30 | 2.52 | 20 | 5 | 80 | NL322522T-270J |
| 33 | ±5% | 30 | 2.52 | 17 | 5.6 | 70 | NL322522T-330J |
| 39 | ±5% | 30 | 2.52 | 16 | 6.4 | 65 | NL322522T-390J |
| 47 | ±5% | 30 | 2.52 | 15 | 7 | 60 | NL322522T-470J |
| 56 | ±5% | 30 | 2.52 | 13 | 8 | 55 | NL322522T-560J |
| 68 | ±5% | 30 | 2.52 | 12 | 9 | 50 | NL322522T-680J |
| 82 | ±5% | 30 | 2.52 | 11 | 10 | 45 | NL322522T-820J |
| 100 | ±5% | 20 | 0.796 | 10 | 10 | 40 | NL322522T-101J |
| 120 | ±5% | 20 | 0.796 | 10 | 11 | 70 | NL322522T-121J |
| 150 | ±5% | 20 | 0.796 | 8 | 15 | 65 | NL322522T-151J |
| 180 | ±5% | 20 | 0.796 | 7 | 17 | 60 | NL322522T-181J |
| 220 | ±5% | 20 | 0.796 | 7 | 21 | 50 | NL322522T-221J |
| 270 | ±5% | 20 | 0.796 | 6 | 28 | 45 | NL322522T-271J |
| 330 | ±5% | 20 | 0.796 | 5 | 34 | 40 | NL322522T-331J |
| 390 | ±5% | 20 | 0.796 | 5 | 42 | 35 | NL322522T-391J |
| 470 | ±5% | 20 | 0.796 | 4 | 40 | 25 | NL322522T-471J |

- Inductance tolerance is only standard.
- Test equipment L, Q: YHP4194A IMPEDANCE ANALYZER (16085A+16093B+TDK TF-1) [$L \geq 0.12\mu\text{H}$]
SRF: HP8753C NETWORK ANALYZER
Rdc: MATSUSHITA VP-2941A DIGITAL MILLIOHM METER

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE vs. FREQUENCY CHARACTERISTICS



INDUCTANCE CHANGE vs. DC

SUPERPOSITION CHARACTERISTICS



Inductors

For General Applications
SMD

NL Series NL3225 Type

TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS



INDUCTANCE CHANGE vs. TEMPERATURE CHARACTERISTICS





Q vs. FREQUENCY CHARACTERISTICS



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View NL322522T-1R0J on WIN SOURCE](#)
-  [TDK Corporation Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management