



**THE DATASHEET OF
NTB25P06T4G**



NTB25P06, NVB25P06

MOSFET – P-Channel, D²PAK -60 V, -27.5 A

Designed for low voltage, high speed switching applications and to withstand high energy in the avalanche and commutation modes.

Features

- AEC Q101 Qualified – NVB25P06
- These Devices are Pb-Free and are RoHS Compliant

Typical Applications

- PWM Motor Controls
- Power Supplies
- Converters
- Bridge Circuits

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	-60	V
Gate-to-Source Voltage	V _{GS}	± 15	V
– Continuous	V _{GS}	± 15	V
– Non-Repetitive (t _p ≤ 10 μs)	V _{GSM}	± 20	Vpk
Drain Current	I _D	27.5	A
– Continuous @ T _A = 25°C	I _{DM}	80	Apk
– Single Pulse (t _p ≤ 10 μs)			
Total Power Dissipation @ T _A = 25°C	P _D	120	W
Operating and Storage Temperature Range	T _J , T _{stg}	-55 to +175	°C
Single Pulse Drain-to-Source Avalanche Energy – Starting T _J = 25°C (V _{DD} = 25 V, V _{GS} = 10 V, I _{L(pk)} = 20 A, L = 3 mH, R _G = 25 Ω)	E _{AS}	600	mJ
Thermal Resistance			°C/W
– Junction-to-Case	R _{θJC}	1.25	
– Junction-to-Ambient (Note 1)	R _{θJA}	46.8	
– Junction-to-Ambient (Note 2)	R _{θJA}	63.2	
Maximum Lead Temperature for Soldering Purposes, (1/8" from case for 10 s)	T _L	260	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. When surface mounted to an FR4 board using 1" pad size (Cu Area 1.127 in²).
2. When surface mounted to an FR4 board using the minimum recommended pad size (Cu Area 0.412 in²).




ON Semiconductor®

<http://onsemi.com>

V _{(BR)DSS}	R _{DS(on)} TYP	I _D MAX
-60 V	65 mΩ @ -10 V	-27.5 A



MARKING DIAGRAM & PIN ASSIGNMENT



ORDERING INFORMATION

Device	Package	Shipping†
NTB25P06T4G	D ² PAK (Pb-Free)	800 / Tape & Reel
NVB25P06T4G	D ² PAK (Pb-Free)	800 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NTB25P06, NVB25P06

ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Drain-to-Source Breakdown Voltage (Note 3) ($V_{GS} = 0\text{ V}$, $I_D = -250\ \mu\text{A}$) (Positive Temperature Coefficient)	$V_{(BR)DSS}$	-60 -	- 64	- -	V mV/°C
Zero Gate Voltage Drain Current ($V_{GS} = 0\text{ V}$, $V_{DS} = -60\text{ V}$, $T_J = 25^\circ\text{C}$) ($V_{GS} = 0\text{ V}$, $V_{DS} = -60\text{ V}$, $T_J = 150^\circ\text{C}$)	I_{DSS}	- -	- -	-10 -100	μA
Gate-Body Leakage Current ($V_{GS} = \pm 15\text{ V}$, $V_{DS} = 0\text{ V}$)	I_{GSS}	-	-	± 100	nA

ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage ($V_{DS} = V_{GS}$, $I_D = -250\ \mu\text{A}$) (Negative Threshold Temperature Coefficient)	$V_{GS(th)}$	-2.0 -	-2.8 6.2	-4.0 -	V mV/°C
Static Drain-Source On-State Resistance ($V_{GS} = -10\text{ V}$, $I_D = -12.5\text{ A}$) ($V_{GS} = -10\text{ V}$, $I_D = -25\text{ A}$)	$R_{DS(on)}$	- -	0.065 0.070	0.075 0.082	Ω
Forward Transconductance ($V_{DS} = -10\text{ V}$, $I_D = -12.5\text{ A}$)	gFS	-	13	-	Mhos

DYNAMIC CHARACTERISTICS

Input Capacitance	$(V_{DS} = -25\text{ V}$, $V_{GS} = 0\text{ V}$, $F = 1.0\text{ MHz}$)	C_{iss}	-	1200	1680	pF
Output Capacitance		C_{oss}	-	345	480	
Reverse Transfer Capacitance		C_{rss}	-	90	180	

SWITCHING CHARACTERISTICS (Notes 3 & 4)

Turn-On Delay Time	$(V_{DD} = -30\text{ V}$, $I_D = -25\text{ A}$, $V_{GS} = -10\text{ V}$, $R_G = 9.1\ \Omega$)	$t_{d(on)}$	-	14	24	ns
Rise Time		t_r	-	72	118	ns
Turn-Off Delay Time		$t_{d(off)}$	-	43	68	ns
Fall Time		t_f	-	190	320	ns
Gate Charge	$(V_{DS} = -48\text{ V}$, $I_D = -25\text{ A}$, $V_{GS} = -10\text{ V}$)	Q_T	-	33	50	nC
		Q_1	-	6.5	-	
		Q_2	-	15	-	

BODY-DRAIN DIODE RATINGS (Note 3)

Diode Forward On-Voltage $(I_S = -25\text{ A}$, $V_{GS} = 0\text{ V}$) $(I_S = -25\text{ A}$, $V_{GS} = 0\text{ V}$, $T_J = 150^\circ\text{C}$)	V_{SD}	- -	-1.8 -1.4	-2.5 -	V	
Reverse Recovery Time	$(I_S = -25\text{ A}$, $V_{GS} = 0\text{ V}$, $di_S/dt = 100\text{ A}/\mu\text{s}$)	t_{rr}	-	70	-	ns
		t_a	-	50	-	
		t_b	-	20	-	
Reverse Recovery Stored Charge	Q_{RR}	-	0.2	-	μC	

3. Indicates Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2\%$.

4. Switching characteristics are independent of operating junction temperatures.

NTB25P06, NVB25P06




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Temperature




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

NTB25P06, NVB25P06




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area





Figure 12. Maximum Avalanche Energy vs. Starting Junction Temperature

NTB25P06, NVB25P06


PACKAGE DIMENSIONS

D²PAK 3 CASE 418B-04 ISSUE K




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. 418B-01 THRU 418B-03 OBSOLETE, NEW STANDARD 418B-04.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.035	0.51	0.89
E	0.045	0.055	1.14	1.40
F	0.310	0.350	7.87	8.89
G	0.100 BSC		2.54 BSC	
H	0.080	0.110	2.03	2.79
J	0.018	0.025	0.46	0.64
K	0.090	0.110	2.29	2.79
L	0.052	0.072	1.32	1.83
M	0.280	0.320	7.11	8.13
N	0.197 REF		5.00 REF	
P	0.079 REF		2.00 REF	
R	0.039 REF		0.99 REF	
S	0.575	0.625	14.60	15.88
V	0.045	0.055	1.14	1.40




SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NTB25P06, NVB25P06

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local
Sales Representative

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View NTB25P06T4G](#) on WIN SOURCE

 [ON Semiconductor](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management