



**THE DATASHEET OF  
NTHS4166NT1G**



# NTHS4166N

## MOSFET – Power, Single, N-Channel, ChipFET Package

**30 V, 8.2 A**

### Features

- Trench Technology
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Leadless ChipFET Package has 40% Smaller Footprint than TSOP-6
- Excellent Thermal Capabilities

This is a Pb-Free Device

### Applications

- Load Switching
- DC-DC Converters
- Low Side Switching

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter   | Symbol               | Value  | Unit             |   |
|---|----------------------|--|------------------|---|
| Drain-to-Source Voltage   | $V_{DSS}$            | 30   | V                |   |
| Gate-to-Source Voltage  | $V_{GS}$             | $\pm 20$   | V                |   |
| Continuous Drain Current $R_{\theta JA}$ (Note 1)   | $I_D$                | $T_A = 25^\circ\text{C}$                             | 6.6              | A |
|   |                      | $T_A = 85^\circ\text{C}$                             | 4.8              |   |
| Power Dissipation $R_{\theta JA}$ (Note 1)  | $P_D$                | $T_A = 25^\circ\text{C}$                             | 1.5              | W |
|   |                      | $T_A = 85^\circ\text{C}$                             |                  |   |
| Continuous Drain Current $R_{\theta JA}$ (Note 2)   | $I_D$                | $T_A = 25^\circ\text{C}$                             | 4.9              | A |
|   |                      | $T_A = 85^\circ\text{C}$                             | 3.6              |   |
| Power Dissipation $R_{\theta JA}$ (Note 2)  | $P_D$                | $T_A = 25^\circ\text{C}$                             | 0.8              | W |
|   |                      | $T_A = 85^\circ\text{C}$                             |                  |   |
| Continuous Drain Current $R_{\theta JA}$ , $t \leq 5$ s (Note 1)  | $I_D$                | $T_A = 25^\circ\text{C}$                             | 8.2              | A |
|   |                      | $T_A = 85^\circ\text{C}$                             | 5.9              |   |
| Power Dissipation $R_{\theta JA}$ (Note 1)  | $P_D$                | 2.2  | W                |   |
| Pulsed Drain Current  | $I_{DM}$             | 32   | A                |   |
|   |                      | $T_A = 25^\circ\text{C}$ ,<br>$t_p = 10 \mu\text{s}$ |                  |   |
| Operating Junction and Storage Temperature  | $T_J$ ,<br>$T_{STG}$ | -55 to 150   | $^\circ\text{C}$ |   |
| Source Current (Body Diode) $R_{\theta JF}$   | $I_S$                | 2.6  | A                |   |
| Single Pulse Drain-to-Source Avalanche Energy $T_J = 25^\circ\text{C}$ , $V_{DD} = 50$ V, $V_{GS} = 10$ V, $I_L = 20$ A <sub>pk</sub> , $L = 0.1$ mH, $R_G = 25 \Omega$ | EAS                  | 20   | mJ               |   |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s)   | $T_L$                | 260  | $^\circ\text{C}$ |   |


Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.




ON Semiconductor®

<http://onsemi.com>

| $V_{(BR)DSS}$ | $R_{DS(on)}$ Max      | $I_D$ Max |
|---------------|-----------------------|-----------|
| 30 V          | 22 m $\Omega$ @ 10 V  | 8.2 A     |
|               | 27 m $\Omega$ @ 4.5 V |           |




N-Channel MOSFET



ChipFET  
CASE 1206A  
STYLE 1

### MARKING DIAGRAM AND PIN ASSIGNMENT



- 466 = Specific Device Code
- M = Month Code
- = Pb-Free Package

### ORDERING INFORMATION

| Device       | Package           | Shipping†        |
|--------------|-------------------|------------------|
| NTHS4166NT1G | ChipFET (Pb-Free) | 3000/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NTHS4166N

1. Surface Mounted on FR4 Board using 1 in sq. pad, 1 oz Cu.
2. Surface Mounted on FR4 Board using the minimum recommended pad size.

## THERMAL RESISTANCE RATINGS

| Parameter                                      | Symbol          | Max | Unit |
|--|-----------------|-----|------|
| Junction-to-Ambient – Steady State (Note 3)    | $R_{\theta JA}$ | 86  | °C/W |
| Junction-to-Ambient – $t \leq 5$ s (Note 3)    | $R_{\theta JA}$ | 57  |      |
| Junction-to-Ambient – $t \leq 5$ s (Note 4)    | $R_{\theta JA}$ | 155 |      |
| Junction-to-Foot (Drain) Steady State (Note 3) | $R_{\theta JF}$ | 20  |      |

3. Surface Mounted on FR4 Board using 1 in sq. pad, 1 oz Cu.
4. Surface Mounted on FR4 Board using the minimum recommended pad size.

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Units |
|-----------|--------|-----------------|-----|-----|-----|-------|
|-----------|--------|-----------------|-----|-----|-----|-------|

### OFF CHARACTERISTICS

|   |                   |   |                           |      |           |               |
|---|-------------------|---|---------------------------|------|-----------|---------------|
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$   | 30                        |      |           | V             |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ |   |                           | 18.3 |           | mV/°C         |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0\text{ V}, V_{DS} = 30\text{ V}$     | $T_J = 25^\circ\text{C}$  |      | 1.0       | $\mu\text{A}$ |
|   |                   |   | $T_J = 125^\circ\text{C}$ |      | 10        |               |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$ |                           |      | $\pm 100$ | nA            |

### ON CHARACTERISTICS (Note 5)

|  |                  |   |     |     |     |            |
|--|------------------|---|-----|-----|-----|------------|
| Gate Threshold Voltage                     | $V_{GS(TH)}$     | $V_{GS} = V_{DS}, I_D = 250\ \mu\text{A}$   | 1.1 |     | 2.3 | V          |
| Negative Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ |   |     | 5.5 |     | mV/°C      |
| Drain-to-Source On-Resistance              | $R_{DS(on)}$     | $V_{GS} = 10\text{ V}, I_D = 4.9\text{ A}$  |     | 18  | 22  | m $\Omega$ |
|  |                  | $V_{GS} = 4.5\text{ V}, I_D = 3.7\text{ A}$ |     | 23  | 27  |            |
| Forward Transconductance                   | $g_{FS}$         | $V_{DS} = 5\text{ V}, I_D = 4.9\text{ A}$   |     | 9.0 |     | S          |

### CHARGES AND CAPACITANCES

|                              |              |   |  |      |  |    |
|------------------------------|--------------|---|--|------|--|----|
| Input Capacitance            | $C_{ISS}$    | $V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}, V_{DS} = 15\text{ V}$   |  | 900  |  | pF |
| Output Capacitance           | $C_{OSS}$    |   |  | 210  |  |    |
| Reverse Transfer Capacitance | $C_{RSS}$    |   |  | 140  |  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 4.5\text{ V}, V_{DS} = 15\text{ V}, I_D = 4.9\text{ A}$ |  | 9.2  |  | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  |   |  | 0.85 |  |    |
| Gate-to-Source Charge        | $Q_{GS}$     |   |  | 2.86 |  |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |   |  | 3.84 |  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 10\text{ V}, V_{DS} = 15\text{ V}, I_D = 4.9\text{ A}$  |  | 18   |  | nC |
| Gate Resistance              | $R_G$        |   |  | 1.6  |  |    |

### SWITCHING CHARACTERISTICS (Note 6)

|                     |              |  |  |     |  |    |
|---------------------|--------------|--|--|-----|--|----|
| Turn-On Delay Time  | $t_{d(on)}$  | $V_{GS} = 4.5\text{ V}, V_{DS} = 15\text{ V}, I_D = 4.9\text{ A}, R_G = 3.0\ \Omega$ |  | 12  |  | ns |
| Rise Time           | $t_r$        |  |  | 13  |  |    |
| Turn-Off Delay Time | $t_{d(off)}$ |  |  | 16  |  |    |
| Fall Time           | $t_f$        |  |  | 5.0 |  |    |
| Turn-On Delay Time  | $t_{d(on)}$  | $V_{GS} = 10\text{ V}, V_{DS} = 15\text{ V}, I_D = 4.9\text{ A}, R_G = 3.0\ \Omega$  |  | 8.0 |  | ns |
| Rise Time           | $t_r$        |  |  | 11  |  |    |
| Turn-Off Delay Time | $t_{d(off)}$ |  |  | 20  |  |    |
| Fall Time           | $t_f$        |  |  | 4.0 |  |    |

5. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .
6. Switching characteristics are independent of operating junction temperatures.

# NTHS4166N

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25°C unless otherwise noted)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Units |
|-----------|--------|-----------------|-----|-----|-----|-------|
|-----------|--------|-----------------|-----|-----|-----|-------|

### DRAIN-SOURCE DIODE CHARACTERISTICS

|                         |                 |  |                        |      |     |    |
|-------------------------|-----------------|--|------------------------|------|-----|----|
| Forward Diode Voltage   | V <sub>SD</sub> | V <sub>GS</sub> = 0 V, I <sub>S</sub> = 5.2 A                                    | T <sub>J</sub> = 25°C  | 0.83 | 1.0 | V  |
|                         |                 |  | T <sub>J</sub> = 125°C | 0.7  |     |    |
| Reverse Recovery Time   | t <sub>RR</sub> | V <sub>GS</sub> = 0 V, I <sub>S</sub> = 5.2 A,<br>dI <sub>S</sub> /dt = 100 A/μs |                        | 16   |     | ns |
| Charge Time             | t <sub>a</sub>  |  |                        | 7.5  |     |    |
| Discharge Time          | t <sub>b</sub>  |  |                        | 8.5  |     |    |
| Reverse Recovery Charge | Q <sub>RR</sub> |  |                        | 6.0  |     |    |

5. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
6. Switching characteristics are independent of operating junction temperatures.

TYPICAL PERFORMANCE CURVES




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Drain Voltage

TYPICAL PERFORMANCE CURVES




Figure 7. Capacitance Variation




Figure 8. Gate-To-Source and Drain-To-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area





Figure 12. Maximum Avalanche Energy vs. Starting Junction Temperature

# NTHS4166N

## PACKAGE DIMENSIONS

### ChipFET™ CASE 1206A-03 ISSUE H




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MOLD GATE BURRS SHALL NOT EXCEED 0.13 MM PER SIDE.
4. LEADFRAME TO MOLDED BODY OFFSET IN HORIZONTAL AND VERTICAL SHALL NOT EXCEED 0.08 MM.
5. DIMENSIONS A AND B EXCLUSIVE OF MOLD BURRS.
6. NO MOLD FLASH ALLOWED ON THE TOP AND BOTTOM LEAD SURFACE.

| DIM   | MILLIMETERS |      |      | INCHES    |       |       |
|-------|-------------|------|------|-----------|-------|-------|
|       | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A     | 1.00        | 1.05 | 1.10 | 0.039     | 0.041 | 0.043 |
| b     | 0.25        | 0.30 | 0.35 | 0.010     | 0.012 | 0.014 |
| c     | 0.10        | 0.15 | 0.20 | 0.004     | 0.006 | 0.008 |
| D     | 2.95        | 3.05 | 3.10 | 0.116     | 0.120 | 0.122 |
| E     | 1.55        | 1.65 | 1.70 | 0.061     | 0.065 | 0.067 |
| e     | 0.65 BSC    |      |      | 0.025 BSC |       |       |
| e1    | 0.55 BSC    |      |      | 0.022 BSC |       |       |
| L     | 0.28        | 0.35 | 0.42 | 0.011     | 0.014 | 0.017 |
| HE    | 1.80        | 1.90 | 2.00 | 0.071     | 0.075 | 0.079 |
| theta | 5° NOM      |      |      | 5° NOM    |       |       |

### SOLDERING FOOTPRINTS\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ChipFET is a trademark of Vishay Siliconix

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION



**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View NTHS4166NT1G on WIN SOURCE](#)
-  [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management