THE DATASHEET OF

ZXMN6A11DN8TC

Product Summary

BV_{DSS}	$R_{DS(ON)}$ Max	I_D MAX T_A = +25°C
60V	120mΩ @ V_{GS} = 10V	3.2A
	180mΩ @ V_{GS} = 4.5V	2.6A

Features and Benefits

- Low On-Resistance
- Fast Switching Speed
- Low Threshold
- Low Gate Drive
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Description and Applications

This new generation MOSFET is designed to minimize the on-state resistance ($R_{DS(ON)}$) and yet maintain superior switching performance, making it ideal for high efficiency power management applications.

- DC-DC Converters
- Power Management Functions
- Motor Control

Mechanical Data

- Case: SO-8
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram
- Terminals: Finish – Tin Finish Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.074 grams (Approximate)



Top View



Top View
Pin Configuration



Equivalent Circuit

Ordering Information (Note 4)

Part Number	Case	Packaging
ZXMN6A11DN8TA	SO-8	2,500/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



= Manufacturer's Marking
ZXMN6A11D = Product Type Marking Code
YYWW = Date Code Marking
YY = Year (ex: 19 = 2019)
WW = Week (01 to 53)

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	60	V
Gate-Source Voltage			V_{GSS}	±20	V
Continuous Drain Current (V_{GS} = 10V)	Steady State t<10s	T_A = +25°C (Note 6) T_A = +70°C (Note 6) T_A = +25°C (Note 5)	I_D	3.2 2.6 2.5	A
Maximum Body Diode Forward Current (Note 6)			I_S	3.1	A
Pulsed Drain Current (Note 7)			I_{DM}	13.7	A
Pulsed Body Diode Forward Current ((Note 7)			I_{SM}	13.7	A

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Total Power Dissipation (Note 5 & Note 8)	P_D	1.25	W
Thermal Resistance, Junction to Ambient (Note 5 & Note 8)	$R_{\theta JA}$	100	°C/W
Total Power Dissipation(Note 5 & Note 9)	P_D	1.8	W
Thermal Resistance, Junction to Ambient (Note 5 & Note 9)	$R_{\theta JA}$	70	°C/W
Total Power Dissipation (Note 6 & Note 8)	P_D	2.1	W
Thermal Resistance, Junction to Ambient (Note 6 & Note 8)	$R_{\theta JA}$	60	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 10)						
Drain-Source Breakdown Voltage	BV_{DSS}	60	—	—	V	V_{GS} = 0V, I_D = 250µA
Zero Gate Voltage Drain Current	I_{DSS}	—	—	1	µA	V_{DS} = 60V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS (Note 10)						
Gate Threshold Voltage	$V_{GS(TH)}$	1	—	—	V	V_{DS} = V_{GS}, I_D = 250µA
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	—	120	mΩ	V_{GS} = 10V, I_D = 2.5A
		—	—	180		V_{GS} = 4.5V, I_D = 2A
Forward Transconductance	gfs	—	4.9	—	S	V_{DS} = 15V, I_D = 2.5A
Diode Forward Voltage	V_{SD}	—	0.85	0.95	V	T_J = +25°C, V_{GS} = 0V, I_S = 2.8A
DYNAMIC CHARACTERISTICS (Note 11)						
Input Capacitance	C_{iss}	—	330	—	pF	V_{DS} = 40V, V_{GS} = 0V f = 1.0MHz
Output Capacitance	C_{oss}	—	35.2	—		
Reverse Transfer Capacitance	C_{rss}	—	17.1	—		
Total Gate Charge (V_{GS} = 10V)	Q_g	—	5.7	—	nC	V_{DS} = 15V, I_D = 2.5A
Total Gate Charge (V_{GS} = 5V)	Q_g	—	3	—		
Gate-Source Charge	Q_{gs}	—	1.25	—		
Gate-Drain Charge	Q_{gd}	—	0.86	—		
Turn-On Delay Time	$t_{D(ON)}$	—	1.95	—	ns	V_{GS} = 10V, V_{DD} = 30V, R_g = 6Ω, I_D = 2.5A
Turn-On Rise Time	t_R	—	3.5	—		
Turn-Off Delay Time	$t_{D(OFF)}$	—	8.2	—		
Turn-Off Fall Time	t_F	—	4.6	—		
Body Diode Reverse Recovery Time	t_{RR}	—	21.5	—	ns	T_J = +25°C, I_S = 2.5A, di/dt = 100A/µs
Body Diode Reverse Recovery Charge	Q_{RR}	—	20.5	—	nC	T_J = +25°C, I_S = 2.5A, di/dt = 100A/µs

Notes:
5. For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.
6. For a device surface mounted on FR4 PCB.
7. Repetitive rating - 25mm x 25mm FR4 PCB, D=0.02, pulse width 300µs - pulse width limited by maximum junction temperature.
8. For a dual device with one active die.
9. For a device with two active dice running at equal power.
10. Short duration pulse test used to minimize self-heating effect.
11. Guaranteed by design. Not subject to product testing.

© Diodes Incorporated



Typical Transfer Characteristics



Normalised Curves v Temperature



Output Characteristics



Output Characteristics



On-Resistance v Drain Current



Source-Drain Diode Forward Voltage

© Diodes Incorporated



Capacitance v Drain-Source Voltage



Gate-Source Voltage v Gate Charge



Basic gate charge waveform



Gate charge test circuit



Switching time waveforms



Switching time test circuit

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SO-8



SO-8			
Dim	**Min**	**Max**	**Typ**
A	1.40	1.50	1.45
A1	0.10	0.20	0.15
b	0.30	0.50	0.40
c	0.15	0.25	0.20
D	4.85	4.95	4.90
E	5.90	6.10	6.00
E1	3.80	3.90	3.85
E0	3.85	3.95	3.90
e	--	--	1.27
h	--	--	0.35
L	0.62	0.82	0.72
Q	0.60	0.70	0.65
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SO-8



Dimensions	Value (in mm)
C	1.27
X	0.802
X1	4.612
Y	1.505
Y1	6.50

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2019, Diodes Incorporated

www.diodes.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View ZXMN6A11DN8TC on WIN SOURCE
- Diodes Incorporated Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management