





# THE DATASHEET OF 5KP30A



### 5KP Series



#### Agency Approvals

| AGENCY  | AGENCY FILE NUMBER |
|---|--------------------|
|  | E230531            |


#### Maximum Ratings and Thermal Characteristics (T<sub>A</sub>=25°C unless otherwise noted)

| Parameter  | Symbol                            | Value      | Unit |
|--|-----------------------------------|------------|------|
| Peak Pulse Power Dissipation by 10/1000µs Test Waveform (Fig.2) (Note 1)             | P <sub>PPM</sub>                  | 5          | kW   |
| Steady State Power Dissipation on Infinite Heat Sink at T <sub>L</sub> =75°C         | P <sub>D</sub>                    | 8.0        | W    |
| Peak Forward Surge Current, 8.3ms Single Half Sine Wave Unidirectional Only (Note 2) | I <sub>FSM</sub>                  | 400        | A    |
| Maximum Instantaneous Forward Voltage at 100A for Unidirectional Only (Note 3)       | V <sub>F</sub>                    | 3.5/5.0    | V    |
| Operating Junction and Storage Temperature Range                                     | T <sub>J</sub> , T <sub>STG</sub> | -55 to 175 | °C   |
| Typical Thermal Resistance Junction to Lead  | R <sub>θJL</sub>                  | 8.0        | °C/W |
| Typical Thermal Resistance Junction to Ambient                                       | R <sub>θJA</sub>                  | 40         | °C/W |

#### Notes:

1. Non-repetitive current pulse, per Fig. 4 and derated above T<sub>J</sub> (initial) =25°C per Fig. 3.
2. Measured on 8.3ms single half sine wave or equivalent square wave, duty cycle=4 per minute maximum.
3. V<sub>F</sub> < 3.5V for single die parts and V<sub>F</sub> < 5.0V for stacked-die parts.

#### Functional Diagram



#### Description

The 5KP Series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

#### Features

- 5 kW peak pulse capability at 10/1000µs waveform, repetition rate (duty cycles):0.01 %
- Glass passivated chip junction in P600 package
- Fast response time: typically less than 1.0ps from 0 Volts to BV min
- Excellent clamping capability
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC 61000-4-2 ESD 30kV(Air), 30kV (Contact)
- EFT protection of data lines in accordance with IEC 61000-4-4
- Low incremental surge resistance
- Typical I<sub>R</sub> less than 2µA when V<sub>BR</sub> min>12V
- High temperature to reflow soldering guaranteed: 260°C/40sec / 0.375"; (9.5mm) lead length, 5 lbs., (2.3kg) tension
- V<sub>BR</sub> @ T<sub>J</sub> = V<sub>BR</sub> @ 25°C × (1 + α × (T<sub>J</sub> - 25)) (α T: Temperature Coefficient, typical value is 0.1 %)
- UL Recognized compound meeting flammability rating V-0
- Matte tin lead-free plated
- Halogen free and RoHS compliant
- Pb-free E3 indicates that 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)

#### Applications

TVS components are ideal for the protection of I/O interfaces, V<sub>CC</sub> bus and other vulnerable circuits used in telecom, computer, industrial and consumer electronic applications.

#### Additional Information



Datasheet



Resources





Samples

### Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise noted)

| Part Number (Uni) | Part Number (Bi) | Reverse Stand off Voltage V <sub>R</sub> (Volts) | Breakdown Voltage V <sub>BR</sub> (Volts) @ I <sub>T</sub> |        | Test Current I <sub>T</sub> (mA) | Maximum Clamping Voltage V <sub>C</sub> @ I <sub>PP</sub> (V) | Maximum Peak Pulse Current I <sub>PP</sub> (A) | Maximum Reverse Leakage I <sub>R</sub> @ V <sub>R</sub> (µA) | Agency Recognition  |
|-------------------|------------------|--|--|--------|----------------------------------|---|--|--|--|
|                   |                  |  | MIN  | MAX    |                                  |   |  |  |  |
| 5KP5.0A           | 5KP5.0CA         | 5.0  | 6.40   | 7.00   | 50                               | 9.2   | 554.3  | 5000   | X  |
| 5KP6.0A           | 5KP6.0CA         | 6.0  | 6.67   | 7.37   | 50                               | 10.3  | 495.1  | 5000   | X  |
| 5KP6.5A           | 5KP6.5CA         | 6.5  | 7.22   | 7.98   | 50                               | 11.2  | 455.4  | 2000   | X  |
| 5KP7.0A           | 5KP7.0CA         | 7.0  | 7.78   | 8.60   | 50                               | 12.0  | 425.0  | 1000   | X  |
| 5KP7.5A           | 5KP7.5CA         | 7.5  | 8.33   | 9.21   | 5                                | 12.9  | 395.3  | 250  | X  |
| 5KP8.0A           | 5KP8.0CA         | 8.0  | 8.89   | 9.83   | 5                                | 13.6  | 375.0  | 150  | X  |
| 5KP8.5A           | 5KP8.5CA         | 8.5  | 9.44   | 10.40  | 5                                | 14.4  | 354.2  | 50   | X  |
| 5KP9.0A           | 5KP9.0CA         | 9.0  | 10.00  | 11.10  | 5                                | 15.4  | 331.2  | 20   | X  |
| 5KP10A            | 5KP10CA          | 10.0   | 11.10  | 12.30  | 5                                | 17.0  | 300.0  | 15   | X  |
| 5KP11A            | 5KP11CA          | 11.0   | 12.20  | 13.50  | 5                                | 18.2  | 280.2  | 2  | X  |
| 5KP12A            | 5KP12CA          | 12.0   | 13.30  | 14.70  | 5                                | 19.9  | 256.3  | 2  | X  |
| 5KP13A            | 5KP13CA          | 13.0   | 14.40  | 15.90  | 5                                | 21.5  | 237.2  | 2  | X  |
| 5KP14A            | 5KP14CA          | 14.0   | 15.60  | 17.20  | 5                                | 23.2  | 219.8  | 2  | X  |
| 5KP15A            | 5KP15CA          | 15.0   | 16.70  | 18.50  | 5                                | 24.4  | 209.0  | 2  | X  |
| 5KP16A            | 5KP16CA          | 16.0   | 17.80  | 19.70  | 5                                | 26.0  | 196.2  | 2  | X  |
| 5KP17A            | 5KP17CA          | 17.0   | 18.90  | 20.90  | 5                                | 27.6  | 184.8  | 2  | X  |
| 5KP18A            | 5KP18CA          | 18.0   | 20.00  | 22.10  | 5                                | 29.2  | 174.7  | 2  | X  |
| 5KP20A            | 5KP20CA          | 20.0   | 22.20  | 24.50  | 5                                | 32.4  | 157.4  | 2  | X  |
| 5KP22A            | 5KP22CA          | 22.0   | 24.00  | 26.90  | 5                                | 35.5  | 143.7  | 2  | X  |
| 5KP24A            | 5KP24CA          | 24.0   | 26.70  | 29.50  | 5                                | 38.9  | 131.1  | 2  | X  |
| 5KP26A            | 5KP26CA          | 26.0   | 28.90  | 31.90  | 5                                | 42.1  | 121.1  | 2  | X  |
| 5KP28A            | 5KP28CA          | 28.0   | 31.10  | 34.40  | 5                                | 45.4  | 112.3  | 2  | X  |
| 5KP30A            | 5KP30CA          | 30.0   | 33.30  | 36.80  | 5                                | 48.4  | 105.4  | 2  | X  |
| 5KP33A            | 5KP33CA          | 33.0   | 36.70  | 40.60  | 5                                | 53.3  | 95.7   | 2  | X  |
| 5KP36A            | 5KP36CA          | 36.0   | 40.00  | 44.20  | 5                                | 58.1  | 87.8   | 2  | X  |
| 5KP40A            | 5KP40CA          | 40.0   | 44.40  | 49.10  | 5                                | 64.5  | 79.1   | 2  | X  |
| 5KP43A            | 5KP43CA          | 43.0   | 47.80  | 52.80  | 5                                | 69.4  | 73.5   | 2  | X  |
| 5KP45A            | 5KP45CA          | 45.0   | 50.00  | 55.30  | 5                                | 72.7  | 70.2   | 2  | X  |
| 5KP48A            | 5KP48CA          | 48.0   | 53.30  | 58.90  | 5                                | 77.4  | 65.9   | 2  | X  |
| 5KP51A            | 5KP51CA          | 51.0   | 56.70  | 62.70  | 5                                | 82.4  | 61.9   | 2  | X  |
| 5KP54A            | 5KP54CA          | 54.0   | 60.00  | 66.30  | 5                                | 87.1  | 58.6   | 2  | X  |
| 5KP58A            | 5KP58CA          | 58.0   | 64.40  | 71.20  | 5                                | 93.6  | 54.5   | 2  | X  |
| 5KP60A            | 5KP60CA          | 60.0   | 66.70  | 73.70  | 5                                | 96.8  | 52.7   | 2  | X  |
| 5KP64A            | 5KP64CA          | 64.0   | 71.10  | 78.60  | 5                                | 103.0   | 49.5   | 2  | X  |
| 5KP70A            | 5KP70CA          | 70.0   | 77.80  | 86.00  | 5                                | 113.0   | 45.1   | 2  | X  |
| 5KP75A            | 5KP75CA          | 75.0   | 83.30  | 92.10  | 5                                | 121.0   | 42.1   | 2  | X  |
| 5KP78A            | 5KP78CA          | 78.0   | 86.70  | 95.80  | 5                                | 126.0   | 40.5   | 2  | X  |
| 5KP85A            | 5KP85CA          | 85.0   | 94.40  | 104.00 | 5                                | 137.0   | 37.2   | 2  | X  |
| 5KP90A            | 5KP90CA          | 90.0   | 100.00   | 111.00 | 5                                | 146.0   | 34.9   | 2  | X  |
| 5KP100A           | 5KP100CA         | 100.0  | 110.00   | 123.00 | 5                                | 162.0   | 31.5   | 2  | X  |
| 5KP110A           | 5KP110CA         | 110.0  | 122.00   | 135.00 | 5                                | 177.0   | 28.8   | 2  | X  |
| 5KP120A           | 5KP120CA         | 120.0  | 133.00   | 147.00 | 5                                | 193.0   | 26.4   | 2  | X  |
| 5KP130A           | 5KP130CA         | 130.0  | 144.00   | 159.00 | 5                                | 209.0   | 24.4   | 2  | X  |
| 5KP150A           | 5KP150CA         | 150.0  | 167.00   | 185.00 | 5                                | 243.0   | 21.0   | 2  | X  |
| 5KP160A           | 5KP160CA         | 160.0  | 178.00   | 197.00 | 5                                | 259.0   | 19.7   | 2  | X  |
| 5KP170A           | 5KP170CA         | 170.0  | 189.00   | 209.00 | 5                                | 275.0   | 18.5   | 2  | X  |
| 5KP180A           | 5KP180CA         | 180.0  | 200.00   | 221.00 | 5                                | 292.0   | 17.5   | 2  | X  |
| 5KP190A           | 5KP190CA         | 190.0  | 211.00   | 233.00 | 5                                | 310.0   | 16.5   | 2  | -  |
| 5KP200A           | 5KP200CA         | 200.0  | 222.00   | 246.00 | 5                                | 329.2   | 15.5   | 2  | X  |
| 5KP210A           | 5KP210CA         | 210.0  | 233.00   | 258.00 | 5                                | 349.5   | 14.6   | 2  | -  |
| 5KP220A           | 5KP220CA         | 220.0  | 244.00   | 270.00 | 5                                | 371.1   | 13.7   | 2  | X  |
| 5KP250A           | 5KP250CA         | 250.0  | 277.00   | 306.00 | 5                                | 425.0   | 12.0   | 2  | X  |

For bidirectional type having V<sub>R</sub> of 10 volts and less, the I<sub>R</sub> limit is double.  
 For parts without A, the V<sub>BR</sub> is ± 10% and V<sub>C</sub> is 5% higher than with A parts

## I-V Curve Characteristics



- $P_{PPM}$  Peak Pulse Power Dissipation** – Max power dissipation
- $V_r$  Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- $V_{BR}$  Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current ( $I_t$ )
- $V_c$  Clamping Voltage** – Peak voltage measured across the TVS at a specified  $I_{ppm}$  (peak impulse current)
- $I_r$  Reverse Leakage Current** – Current measured at  $V_r$
- $V_f$  Forward Voltage Drop for Uni-directional**

## Ratings and Characteristic Curves ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Figure 1 - TVS Transients Clamping Waveform






Figure 2 - Peak Pulse Power Rating Curve




continues on next page.

### Ratings and Characteristic Curves ( $T_A=25^\circ\text{C}$ unless otherwise noted) (Continued)


**Figure 3 - Peak Pulse Power Derating Curve**




**Figure 4 - Pulse Waveform**




**Figure 5 - Typical Junction Capacitance**




**Figure 6 - Typical Transient Thermal Impedance**



**Figure 7 - Maximum Non-Repetitive Peak Forward Surge Current Uni-Directional Only**




**Figure 8 - Peak Forward Voltage Drop vs Peak Forward Current (Typical Values)**



### Soldering Parameters

|  |                                    |                         |
|--|------------------------------------|-------------------------|
| Reflow Condition                                       |                                    | Lead-free assembly      |
| Pre Heat   | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|  | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|  | - Time (min to max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus Temp ( $T_A$ ) to peak) |                                    | 3°C/second max          |
| $T_{s(max)}$ to $T_A$ - Ramp-up Rate                   |                                    | 3°C/second max          |
| Reflow   | - Temperature ( $T_A$ ) (Liquidus) | 217°C                   |
|  | - Time (min to max) ( $t_s$ )      | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds         |
| Ramp-down Rate   |                                    | 6°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes Max.          |
| Do not exceed  |                                    | 260°C                   |



### Flow/Wave Soldering (Solder Dipping)

|                           |            |
|---------------------------|------------|
| <b>Peak Temperature :</b> | 265°C      |
| <b>Dipping Time :</b>     | 10 seconds |
| <b>Soldering :</b>        | 1 time     |


### Physical Specifications

|                 |  |
|-----------------|--|
| <b>Weight</b>   | 0.07oz., 2.1g                                      |
| <b>Case</b>     | P600 molded plastic body over passivated junction. |
| <b>Polarity</b> | Color band denotes the cathode except Bipolar.     |
| <b>Terminal</b> | Matte Tin axial leads, solderable per JESD22-B102. |

### Environmental Specifications

|                            |             |
|----------------------------|-------------|
| <b>High Temp. Storage</b>  | JESD22-A103 |
| <b>HTRB</b>                | JESD22-A108 |
| <b>Temperature Cycling</b> | JESD22-A104 |
| <b>H3TRB</b>               | JESD22-A101 |
| <b>RSH</b>                 | JESD22-B106 |

### Dimensions




| Dimensions | Inches |       | Millimeters |      |
|------------|--------|-------|-------------|------|
|            | Min    | Max   | Min         | Max  |
| A          | 1.000  | -     | 25.40       | -    |
| B          | 0.340  | 0.360 | 8.60        | 9.10 |
| C          | 0.048  | 0.054 | 1.22        | 1.36 |
| D          | 0.340  | 0.360 | 8.60        | 9.10 |

### Part Numbering System

**5KPxxxXXX**




### Part Marking System



### Packing Options

| Part Number | Component Package | Quantity | Packaging Option | Packaging Specification |
|-------------|-------------------|----------|------------------|-------------------------|
| 5KPxxxXX    | P600              | 800      | Tape & Reel      | EIA STD RS-296          |
| 5KPxxxXX-B  | P600              | 100      | BULK             | Littelfuse Spec.        |

### Tape and Reel Specification



**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 5KP30A on WIN SOURCE](#)

 [Littelfuse Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management