



**THE DATASHEET OF
2N7002F,215**



Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of <http://www.nxp.com>, <http://www.philips.com/> or <http://www.semiconductors.philips.com/>, use <http://www.nexperia.com>

Instead of sales.addresses@www.nxp.com or sales.addresses@www.semiconductors.philips.com, use salesaddresses@nexperia.com (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:

- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved

Should be replaced with:

- © **Nexperia B.V. (year). All rights reserved.**

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via salesaddresses@nexperia.com). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia



2N7002F

N-channel TrenchMOS FET

Rev. 03 — 28 April 2006

Product data sheet

1. Product profile

1.1 General description

N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology.

1.2 Features

- Logic level threshold compatible
- Surface-mounted package
- Very fast switching
- TrenchMOS technology

1.3 Applications

- Logic level translator
- High-speed line driver

1.4 Quick reference data

- $V_{DS} \leq 60 \text{ V}$
- $R_{DSon} \leq 2 \Omega$
- $I_D \leq 475 \text{ mA}$
- $P_{tot} \leq 0.83 \text{ W}$

2. Pinning information

Table 1: Pinning

| Pin | Description | Simplified outline | Symbol |
|-----|-------------|--------------------|---------------|
| 1 | gate (G) | <p>SOT23</p> | <p>mbb076</p> |
| 2 | source (S) | | |
| 3 | drain (D) | | |

PHILIPS

3. Ordering information

Table 2: Ordering information


| Type number | Package | | |
|-------------|----------|--|---------|
| | Name | Description | Version |
| 2N7002F | TO-236AB | plastic surface-mounted package; 3 leads | SOT23 |

4. Limiting values

Table 3: Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|---------------------------|--------------------------|---|-----|----------|------|
| V_{DS} | drain-source voltage | $25\text{ °C} \leq T_j \leq 150\text{ °C}$ | - | 60 | V |
| V_{DGR} | drain-gate voltage (DC) | $25\text{ °C} \leq T_j \leq 150\text{ °C}$; $R_{GS} = 20\text{ k}\Omega$ | - | 60 | V |
| V_{GS} | gate-source voltage | | - | ± 30 | V |
| V_{GSM} | peak gate-source voltage | $t_p \leq 50\text{ }\mu\text{s}$; pulsed; duty cycle = 25 % | - | ± 40 | V |
| I_D | drain current | $T_{sp} = 25\text{ °C}$; $V_{GS} = 10\text{ V}$; see Figure 2 and 3 | - | 475 | mA |
| | | $T_{sp} = 100\text{ °C}$; $V_{GS} = 10\text{ V}$; see Figure 2 | - | 300 | mA |
| I_{DM} | peak drain current | $T_{sp} = 25\text{ °C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$; see Figure 3 | - | 1.9 | A |
| P_{tot} | total power dissipation | $T_{sp} = 25\text{ °C}$; see Figure 1 | - | 0.83 | W |
| T_{stg} | storage temperature | | -65 | +150 | °C |
| T_j | junction temperature | | -65 | +150 | °C |
| Source-drain diode | | | | | |
| I_S | source current | $T_{sp} = 25\text{ °C}$ | - | 475 | mA |
| I_{SM} | peak source current | $T_{sp} = 25\text{ °C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$ | - | 1.9 | A |




$$P_{der} = \frac{P_{tot}}{P_{tot(25^\circ C)}} \times 100\%$$

Fig 1. Normalized total power dissipation as a function of solder point temperature



$$I_{der} = \frac{I_D}{I_{D(25^\circ C)}} \times 100\%$$

Fig 2. Normalized continuous drain current as a function of solder point temperature



T_{sp} = 25 °C; I_{DM} is single pulse

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

5. Thermal characteristics

Table 4: Thermal characteristics

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|----------------|--|------------------------------|-----|-----|-----|------|
| $R_{th(j-sp)}$ | thermal resistance from junction to solder point | see Figure 4 | - | - | 150 | K/W |
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | | [1] | - | 350 | K/W |

[1] Mounted on a printed-circuit board; minimum footprint; vertical in still air





Fig 4. Transient thermal impedance from junction to solder point as a function of pulse duration

6. Characteristics


Table 5: Characteristics
T_j = 25 °C unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|--------------------------------|----------------------------------|---|-----|------|------|------|
| Static characteristics | | | | | | |
| V _{(BR)DSS} | drain-source breakdown voltage | I _D = 10 μA; V _{GS} = 0 V T _j = 25 °C | 60 | - | - | V |
| | | T _j = -55 °C | 55 | - | - | V |
| V _{GS(th)} | gate-source threshold voltage | I _D = 0.25 mA; V _{DS} = V _{GS} ; see Figure 9 and 10 T _j = 25 °C | 1 | 2 | 2.5 | V |
| | | T _j = 150 °C | 0.6 | - | - | V |
| | | T _j = -55 °C | - | - | 2.75 | V |
| I _{DSS} | drain leakage current | V _{DS} = 48 V; V _{GS} = 0 V T _j = 25 °C | - | 0.01 | 1 | μA |
| | | T _j = 150 °C | - | - | 10 | μA |
| I _{GSS} | gate leakage current | V _{GS} = ±15 V; V _{DS} = 0 V | - | 10 | 100 | nA |
| R _{DS(on)} | drain-source on-state resistance | V _{GS} = 10 V; I _D = 500 mA; see Figure 6 and 8 T _j = 25 °C | - | 0.78 | 2 | Ω |
| | | T _j = 150 °C | - | 1.45 | 3.7 | Ω |
| | | V _{GS} = 4.5 V; I _D = 75 mA; see Figure 6 and 8 | - | 1.2 | 4 | Ω |
| Dynamic characteristics | | | | | | |
| Q _{G(tot)} | total gate charge | I _D = 300 mA; V _{DS} = 30 V; V _{GS} = 10 V; see Figure 11 and 12 | - | 0.69 | - | nC |
| Q _{GS} | gate-source charge | | - | 0.1 | - | nC |
| Q _{GD} | gate-drain charge | | - | 0.27 | - | nC |
| C _{iss} | input capacitance | V _{GS} = 0 V; V _{DS} = 10 V; f = 1 MHz; see Figure 14 | - | 31 | 50 | pF |
| C _{oss} | output capacitance | | - | 6.8 | 30 | pF |
| C _{rss} | reverse transfer capacitance | | - | 3.5 | 10 | pF |
| t _{on} | turn-on time | V _{DS} = 50 V; R _L = 250 Ω; V _{GS} = 10 V; | - | 2.5 | 10 | ns |
| t _{off} | turn-off time | R _G = 50 Ω; R _{GS} = 50 Ω | - | 11 | 15 | ns |
| Source-drain diode | | | | | | |
| V _{SD} | source-drain voltage | I _S = 300 mA; V _{GS} = 0 V; see Figure 13 | - | 0.85 | 1.5 | V |
| t _{rr} | reverse recovery time | I _S = 300 mA; dI _S /dt = -100 A/μs; V _{GS} = 0 V | - | 30 | - | ns |
| Q _r | recovered charge | | - | 30 | - | nC |




$T_j = 25\text{ }^\circ\text{C}$

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values




$T_j = 25\text{ }^\circ\text{C}$

Fig 6. Drain-source on-state resistance as a function of drain current; typical values




$T_j = 25\text{ }^\circ\text{C}$ and $150\text{ }^\circ\text{C}$; $V_{DS} > I_D \times R_{DSon}$

Fig 7. Transfer characteristics: drain current as a function of gate-source voltage; typical values




$$a = \frac{R_{DSon}}{R_{DSon(25\text{ }^\circ\text{C})}}$$

Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature




$I_D = 0.25 \text{ mA}; V_{DS} = V_{GS}$

Fig 9. Gate-source threshold voltage as a function of junction temperature



$T_j = 25 \text{ }^\circ\text{C}; V_{DS} = 5 \text{ V}$

Fig 10. Sub-threshold drain current as a function of gate-source voltage



$I_D = 300 \text{ mA}; V_{DS} = 30 \text{ V}$

Fig 11. Gate-source voltage as a function of gate charge; typical values






Fig 12. Gate charge waveform definitions



$T_j = 25\text{ }^\circ\text{C}$ and $150\text{ }^\circ\text{C}$; $V_{GS} = 0\text{ V}$

Fig 13. Source current as a function of source-drain voltage; typical values



$V_{GS} = 0\text{ V}$; $f = 1\text{ MHz}$

Fig 14. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values

7. Package outline

Plastic surface-mounted package; 3 leads

SOT23




Fig 15. Package outline SOT23

8. Revision history

Table 6: Revision history

| Document ID | Release date | Data sheet status | Change notice | Doc. number | Supersedes |
|----------------|--|--------------------|---------------|----------------|------------|
| 2N7002F_3 | 20060428 | Product data sheet | - | - | 2N7002F_2 |
| Modifications: | <ul style="list-style-type: none"> • Table 5 “Characteristics”: $V_{GS(th)}$ I_D condition modified • Table 5 “Characteristics”: $V_{GS(th)}$ maximum limits modified • Table 5 “Characteristics”: $R_{DS(on)}$ typical values modified • Table 5 “Characteristics”: g_{fs} removed • Table 5 “Characteristics”: Addition of $Q_{G(tot)}$, Q_{GS} and Q_{GD} • Table 5 “Characteristics”: C_{iss}, C_{oss} and C_{rss} values modified • Table 5 “Characteristics”: t_{on} and t_{off} typical values modified • Figure 3, 4, 5, 6, 7, 9, 10, 13 and 14: modified • Figure 11: added | | | | |
| 2N7002F_2 | 20050509 | Product data sheet | - | 9397 750 14945 | 2N7002F-01 |
| 2N7002F-01 | 20020211 | Product data | - | 9397 750 09096 | - |

9. Data sheet status

| Level | Data sheet status ^[1] | Product status ^[2] ^[3] | Definition |
|-------|----------------------------------|--|--|
| I | Objective data | Development | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice. |
| II | Preliminary data | Qualification | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product. |
| III | Product data | Production | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

13. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: sales.addresses@www.semiconductors.philips.com

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

Notice — All referenced brands, product names, service names and trademarks are the property of their respective owners.

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

14. Contents

| | | |
|-----------|--------------------------------------|-----------|
| 1 | Product profile | 1 |
| 1.1 | General description | 1 |
| 1.2 | Features | 1 |
| 1.3 | Applications | 1 |
| 1.4 | Quick reference data | 1 |
| 2 | Pinning information | 1 |
| 3 | Ordering information | 2 |
| 4 | Limiting values | 2 |
| 5 | Thermal characteristics | 4 |
| 6 | Characteristics | 5 |
| 7 | Package outline | 9 |
| 8 | Revision history | 10 |
| 9 | Data sheet status | 11 |
| 10 | Definitions | 11 |
| 11 | Disclaimers | 11 |
| 12 | Trademarks | 11 |
| 13 | Contact information | 11 |



© Koninklijke Philips Electronics N.V. 2006



All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 28 April 2006
Document number: 2N7002F_3

Published in The Netherlands

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 2N7002F,215 on WIN SOURCE](#)
-  [Nexperia USA Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management