



**THE DATASHEET OF
BSL308CH6327XTSA1**





OptiMOS™ P3 + Optimos™ 2 Small Signal Transistor
Features

- Complementary P + N channel
- Enhancement mode
- Logic level (4.5V rated)
- Avalanche rated
- Qualified according to AEC Q101
- 100% Lead-free; RoHS compliant
- Halogen free according to IEC61249-2-21

Product Summary

		P	N	
V_{DS}		-30	30	V
$R_{DS(on),max}$	$V_{GS}=\pm 10\text{ V}$	80	57	mΩ
	$V_{GS}=\pm 4.5\text{ V}$	130	93	
I_D		-2.0	2.3	A


PG-TSOP-6


Type	Package	Tape and Reel Information	Marking	Lead Free	Packing
BSL308C	PG-TSOP6	H6327: 3000 pcs / reel	sPS	Yes	Non dry

Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified ¹⁾

Parameter	Symbol	Conditions	Value		Unit
			P	N	
Continuous drain current	I_D	$T_A=25\text{ °C}$	-2.0	2.3	A
		$T_A=70\text{ °C}$	-1.6	1.8	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ °C}$	-8.0	9	
Avalanche energy, single pulse	E_{AS}	P: $I_D=-2.0\text{ A}$, N: $I_D=2.3\text{ A}$, $R_{GS}=25\text{ }\Omega$	10.7	10.8	mJ
Gate source voltage	V_{GS}		± 20		V
Power dissipation ²⁾	P_{tot}	$T_A=25\text{ °C}$	0.5		W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150		°C
ESD class		JESD22-A114-HBM	class 0 (<250V)		
Soldering temperature	T_{solder}		260		°C
IEC climatic category; DIN IEC 68-1			55/150/56		

¹⁾ Remark: only one of both transistors active

Parameter		Symbol	Conditions	Values			Unit
				min.	typ.	max.	

Thermal characteristics

Thermal resistance, junction - ambient ¹⁾	P	R_{thJA}	minimal footprint ²⁾	-	-	250	K/W
	N						

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified
Static characteristics

Drain-source breakdown voltage	P	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=-250\text{ }\mu\text{A}$	-	-	-30	V
	N		$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	30	-	-	
Gate threshold voltage	P	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-11\text{ }\mu\text{A}$	-2	-1.5	-1	
	N		$V_{DS}=V_{GS}, I_D=11\text{ }\mu\text{A}$	1.2	1.6	2	
Zero gate voltage drain current	P	I_{DSS}	$V_{DS}=-30\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	-1	μA
	N		$V_{DS}=30\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	1	
	P		$V_{DS}=-30\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ °C}$	-	-	-100	
	N		$V_{DS}=30\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ °C}$	-	-	100	
Gate-source leakage current	P	I_{GSS}	$V_{GS}=\pm 20\text{ V}, V_{DS}=0\text{ V}$	-	-	± 100	nA
	N						
Drain-source on-state resistance	P	$R_{DS(on)}$	$V_{GS}=-4.5\text{ V}, I_D=-1.7\text{ A}$	-	88	130	m Ω
	N		$V_{GS}=4.5\text{ V}, I_D=1.85\text{ A}$	-	67	93	
	P		$V_{GS}=-10\text{ V}, I_D=-2.0\text{ A}$	-	62	80	
	N		$V_{GS}=10\text{ V}, I_D=2.3\text{ A}$	-	44	57	
Transconductance	P	g_{fs}	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=-1.6\text{ A}$	-	4.6	-	S
	N		$ V_{DS} >2 I_D R_{DS(on)max}, I_D=1.8\text{ A}$	-	5	-	

²⁾ Performed on 40mm² FR4 PCB. The traces are 1mm wide, 70 μm thick and 20mm long; they are present on both sides of the PCB

Parameter		Symbol	Conditions	Values			Unit
				min.	typ.	max.	

Dynamic characteristics

Input capacitance	P	C_{iss}	$V_{GS}=0\text{ V}$, P: $V_{DS}=-15\text{ V}$, N: $V_{DS}=15\text{ V}$, $f=1\text{ MHz}$	-	376	500	pF			
	N			-	207	275				
Output capacitance	P	C_{oss}		$V_{GS}=0\text{ V}$, P: $V_{DS}=-15\text{ V}$, N: $V_{DS}=15\text{ V}$, $f=1\text{ MHz}$	-	196	261	pF		
	N				-	75	100			
Reverse transfer capacitance	P	C_{rss}			$V_{GS}=0\text{ V}$, P: $V_{DS}=-15\text{ V}$, N: $V_{DS}=15\text{ V}$, $f=1\text{ MHz}$	-	12	18	pF	
	N					-	12	17		
Turn-on delay time	P	$t_{d(on)}$				P: $V_{DD}=-15\text{ V}$, $V_{GS}=-10\text{ V}$, $R_G=6\ \Omega$, $I_D=-2\text{ A}$	-	5.6	-	ns
	N						-	4.4	-	
Rise time	P	t_r	P: $V_{DD}=-15\text{ V}$, $V_{GS}=-10\text{ V}$, $R_G=6\ \Omega$, $I_D=-2\text{ A}$				-	7.7	-	ns
	N						-	2.3	-	
Turn-off delay time	P	$t_{d(off)}$		N: $V_{DD}=15\text{ V}$, $V_{GS}=10\text{ V}$, $R_G=6\ \Omega$, $I_D=2.3\text{ A}$			-	15.3	-	ns
	N						-	8.3	-	
Fall time	P	t_f			N: $V_{DD}=15\text{ V}$, $V_{GS}=10\text{ V}$, $R_G=6\ \Omega$, $I_D=2.3\text{ A}$		-	2.8	-	ns
	N						-	1.4	-	

Gate Charge Characteristics

Gate to source charge	P	Q_{gs}	$V_{DD}=-15\text{ V}$, $I_D=-2\text{ A}$, $V_{GS}=0\text{ to }-10\text{ V}$	-	-1.2	-	nC
Gate to drain charge		Q_{gd}		-	-0.6	-	
Switching charge		Q_g		-	-5.0	-	
Gate plateau voltage		$V_{plateau}$		-	-3.1	-	
Gate to source charge	N	Q_{gs}	$V_{DD}=15\text{ V}$, $I_D=2.3\text{ A}$, $V_{GS}=0\text{ to }10\text{ V}$	-	0.65	-	nC
Gate to drain charge		Q_{gd}		-	0.45	-	
Switching charge		Q_g		-	1.5	-	
Gate plateau voltage		$V_{plateau}$		-	3.1	-	


Parameter		Symbol	Conditions	Values			Unit
				min.	typ.	max.	

Reverse Diode

Diode continuous forward current	P	I_S	$T_C=25\text{ °C}$	-	-	-0.4	A
	N			-	-	0.5	
Diode pulse current	P	$I_{S,pulse}$		-	-	-8.4	
	N			-	-	9	
Diode forward voltage	P	V_{SD}	$V_{GS}=0\text{ V}, I_F=-2\text{ A},$ $T_j=25\text{ °C}$	-	-0.8	-1.1	V
	N		$V_{GS}=0\text{ V}, I_F=2.3\text{ A},$ $T_j=25\text{ °C}$	-	0.83	1.1	
Reverse recovery time	P	t_{rr}	$V_R=-15\text{ V}, I_F=-2\text{ A},$ $di_F/dt=-100\text{ A}/\mu\text{s}$	-	14	-	ns
		Q_{rr}		-	-5.9	-	nC
Reverse recovery charge	N	t_{rr}	$V_R=15\text{ V}, I_F=2.3\text{ A}$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	14.4	-	ns
		Q_{rr}		-	2.9	-	nC


1 Power dissipation (P)

$P_{tot}=f(T_A)$



2 Power dissipation (N)


$P_{tot}=f(T_A)$



3 Drain current (P)

$I_D=f(T_A)$


parameter: $V_{GS} \leq -10$ V



4 Drain current (N)

$I_D=f(T_A)$


parameter: $V_{GS} \geq 10$ V



5 Safe operating area (P)

$I_D=f(V_{DS}); T_A=25\text{ }^\circ\text{C}; D=0$


parameter: t_p



6 Safe operating area (N)

$I_D=f(V_{DS}); T_A=25\text{ }^\circ\text{C}; D=0$


parameter: t_p



7 Max. transient thermal impedance (P)

$Z_{thJA}=f(t_p)$


parameter: $D=t_p/T$



8 Max. transient thermal impedance (N)

$Z_{thJA}=f(t_p)$


parameter: $D=t_p/T$



9 Typ. output characteristics (P)

$I_D=f(V_{DS}); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS}



10 Typ. output characteristics (N)

$I_D=f(V_{DS}); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS}



11 Typ. drain-source on resistance (P)

$R_{DS(on)}=f(I_D); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS}



12 Typ. drain-source on resistance (N)

$R_{DS(on)}=f(I_D); T_j=25\text{ }^\circ\text{C}$


parameter: V_{GS}



13 Typ. transfer characteristics (P)

$$I_D = f(V_{GS}); |V_{DS}| > 2 |I_D| R_{DS(on)max}$$


parameter: T_j



14 Typ. transfer characteristics (N)


$$I_D = f(V_{GS}); |V_{DS}| > 2 |I_D| R_{DS(on)max}$$

parameter: T_j




15 Drain-source on-state resistance (P)

$$R_{DS(on)} = f(T_j); I_D = -2.0 \text{ A}; V_{GS} = -10 \text{ V}$$




16 Drain-source on-state resistance (N)

$$R_{DS(on)} = f(T_j); I_D = 2.3 \text{ A}; V_{GS} = 10 \text{ V}$$




17 Typ. gate threshold voltage (P)

$V_{GS(th)}=f(T_j)$; $V_{GS}=V_{DS}$; $I_D=-11 \mu A$




18 Typ. gate threshold voltage (N)

$V_{GS(th)}=f(T_j)$; $V_{GS}=V_{DS}$; $I_D=11 \mu A$




19 Typ. capacitances (P)

$C=f(V_{DS})$; $V_{GS}=0 V$; $f=1 MHz$



20 Typ. capacitances (N)


$C=f(V_{DS})$; $V_{GS}=0 V$; $f=1 MHz$



21 Forward characteristics of reverse diode (P)

$I_F=f(V_{SD})$


parameter: T_j



22 Forward characteristics of reverse diode (N)

$I_F=f(V_{SD})$


parameter: T_j



23 Avalanche characteristics (P)

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter: $T_{j(start)}$



24 Avalanche characteristics (N)

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter: $T_{j(start)}$



25 Typ. gate charge (P)

$V_{GS}=f(Q_{gate}); I_D=-2.0$ A pulsed


parameter: V_{DD}



26 Typ. gate charge (N)


$V_{GS}=f(Q_{gate}); I_D=2.3$ A pulsed

parameter: V_{DD}




27 Drain-source breakdown voltage (P)

$V_{BR(DSS)}=f(T_j); I_D=-250$ μ A




28 Drain-source breakdown voltage (N)

$V_{BR(DSS)}=f(T_j); I_D=250$ μ A




TSOP-6

Package Outline:




Footprint:



Remark: Wave soldering possible dep. on customers process conditions

HLG09283

Packaging:



Dimensions in mm

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).



Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View BSL308CH6327XTSA1 on WIN SOURCE](#)
-  [Infineon Technologies Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management