



FW344A

Power MOSFET

30V, 4.5A, 64mΩ, -30V, -3.5A, 102mΩ, Complementary Dual SOIC8

ON Semiconductor®

<http://onsemi.com>

Features

- ON-resistance Nch : $R_{DS(on)1}=49m\Omega$ (typ.)
Pch : $R_{DS(on)1}=78m\Omega$ (typ.)
- 4V drive
- Halogen free compliance
- Nch+Pch MOSFET

Specifications

Absolute Maximum Ratings at $T_a=25^\circ C$

Parameter	Symbol	Conditions	N-channel	P-channel	Unit
Drain-to-Source Voltage	V_{DSS}		30	-30	V
Gate-to-Source Voltage	V_{GSS}		± 20	± 20	V
Drain Current (DC)	I_D		4.5	-3.5	A
Drain Current ($PW \leq 10\mu s$)	I_{DP}	Duty cycle $\leq 1\%$	5	-4	A
Drain Current ($PW \leq 10\mu s$)	I_{DP}	Duty cycle $\leq 1\%$	18	-14	A
Allowable Power Dissipation	P_D	When mounted on ceramic substrate (2000mm ² x0.8mm) 1unit	1.4		W
Total Dissipation	P_T	When mounted on ceramic substrate (2000mm ² x0.8mm)	1.7		W
Channel Temperature	T_{ch}		150		$^\circ C$
Storage Temperature	T_{stg}		-55 to +150		$^\circ C$

This product is designed to "ESD immunity < 200V**", so please take care when handling.


* Machine Model

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ)


7072-001




Product & Package Information

- Package : SOIC8
- JEITA, JEDEC : SC-87, SOT-96
- Minimum Packing Quantity : 2,500 pcs./reel


Packing Type : TL



Marking



Electrical Connection




FW344A

Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
[N-channel]						
Drain-to-Source Breakdown Voltage	V(BR)DSS	ID=1mA, VGS=0V	30			V
Zero-Gate Voltage Drain Current	IDSS	VDS=30V, VGS=0V			1	μA
Gate-to-Source Leakage Current	IGSS	VGS=±16V, VDS=0V			±10	μA
Cutoff Voltage	VGS(off)	VDS=10V, ID=1mA	1.2		2.6	V
Forward Transfer Admittance	yfs	VDS=10V, ID=4.5A		2.6		S
Static Drain-to-Source On-State Resistance	RDS(on)1	ID=4.5A, VGS=10V		49	64	mΩ
	RDS(on)2	ID=2A, VGS=4.5V		80	112	mΩ
	RDS(on)3	ID=2A, VGS=4V		100	140	mΩ
Input Capacitance	Ciss	VDS=10V, f=1MHz		280		pF
Output Capacitance	Coss			60		pF
Reverse Transfer Capacitance	Crss			30		pF
Turn-ON Delay Time	t _{d(on)}		See specified Test Circuit.		6	
Rise Time	t _r			21		ns
Turn-OFF Delay Time	t _{d(off)}			20		ns
Fall Time	t _f			10		ns
Total Gate Charge	Qg	VDS=10V, VGS=10V, ID=4.5A			5.6	
Gate-to-Source Charge	Qgs			1.2		nC
Gate-to-Drain "Miller" Charge	Qgd			0.8		nC
Diode Forward Voltage	VSD		IS=4.5A, VGS=0V		0.85	1.2
[P-channel]						
Drain-to-Source Breakdown Voltage	V(BR)DSS	ID=-1mA, VGS=0V	-30			V
Zero-Gate Voltage Drain Current	IDSS	VDS=-30V, VGS=0V			-1	μA
Gate-to-Source Leakage Current	IGSS	VGS=±16V, VDS=0V			±10	μA
Cutoff Voltage	VGS(off)	VDS=-10V, ID=-1mA	-1.2		-2.3	V
Forward Transfer Admittance	yfs	VDS=-10V, ID=-3.5A		3.9		S
Static Drain-to-Source On-State Resistance	RDS(on)1	ID=-3.5A, VGS=-10V		78	102	mΩ
	RDS(on)2	ID=-2A, VGS=-4.5V		125	175	mΩ
	RDS(on)3	ID=-2A, VGS=-4V		145	205	mΩ
Input Capacitance	Ciss	VDS=-10V, f=1MHz		250		pF
Output Capacitance	Coss			65		pF
Reverse Transfer Capacitance	Crss			46		pF
Turn-ON Delay Time	t _{d(on)}		See specified Test Circuit.		5.4	
Rise Time	t _r			34		ns
Turn-OFF Delay Time	t _{d(off)}			28		ns
Fall Time	t _f			24		ns
Total Gate Charge	Qg	VDS=-10V, VGS=-10V, ID=-3.5A			5	
Gate-to-Source Charge	Qgs			1		nC
Gate-to-Drain "Miller" Charge	Qgd			1.2		nC
Diode Forward Voltage	VSD		IS=-3.5A, VGS=0V		-0.88	-1.5

Switching Time Test Circuit

[N-channel]















[P-channel]











Ordering Information



Device	Package	Shipping	memo
FW344A-TL-2W	SOIC8	2,500pcs./reel	Pb Free and Halogen Free





FW344A





Taping Specification
FW344A-TL-2W

1. Packing Format


Package Name	Carrier Tape Type	Maximum Number of devices contained (pcs)			Packing format	
		Reel	Inner box	Outer box	Inner BOX W206-112	Outer BOX W207-124
SOIC8	B202-101	2,500	12,500	25,000	5 reels contained Dimensions :mm(external) 340×95×340	2 inner boxes contained Dimensions :mm(external) 360×210×375

Packing method

Reel label, Inner box label
(unit: mm)

Outer box label


It is a label at the time of factory shipments.
The form of a label may change in physical distribution process.




Label	JEITA Phase
LEAD FREE 4	JEITA Phase 3

2. Taping configuration


2-1. Carrier tape size (unit: mm)



2-2. Device placement direction




2-3. Leader portion and trailer portion (unit: mm)




FW344A

Outline Drawing FW344A-TL-2W



Land Pattern Example



Note on usage : Since the FW344A is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View FW344A-TL-2W](#) on WIN SOURCE
- ⊖ [ON Semiconductor](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management