



**THE DATASHEET OF  
SMV1265-040LF**



DATA SHEET


# SMV1265-040LF: Hyperabrupt Junction Tuning Varactor

## Applications

- Wideband RF and microwave VCOs
- Analog phase shifters
- Digital TV tuners

## Features

- High tuning ratio
- Low series resistance
- Designed for high-volume, low-cost applications
- Small footprint package (MSL1, 260 °C per JEDEC J-STD-020)




Skyworks Green™ products are compliant with all applicable legislation and are halogen-free. For additional information, refer to *Skyworks Definition of Green™*, document number SQ04-0074.

## Description

The SMV1265-040LF hyperabrupt junction tuning varactors is designed for very high capacitance tuning ratios with low series resistance, which makes this device especially attractive for wideband voltage controlled oscillator (VCO) applications.

The packaging and marking information is shown in Table 1. The absolute maximum ratings of the SMV1265-040LF are provided in Table 2. Electrical specifications are specified in Table 3. Figure 1 shows the typical performance of capacitance versus voltage. The SPICE model for the SMV1265-040LF is shown in Figure 2 and the associated model parameters are provided in Table 4. The relationship between voltage and capacitance for the SMV1265-040LF is shown in Table 5.

**Table 1. Packaging and Marking**

|   |
|---|
|  |
| Single  |
| SOD-882<br>Green™   |
| <b>SMV1265-040LF</b><br>Marking: HD1  |
| Ls = 0.45 nH  |



The Pb-free symbol or "LF" in the part number denotes a lead-free, RoHS-compliant package unless otherwise noted as Green™. Tin/lead (Sn/Pb) packaging is not recommended for new designs.

**Table 2. SMV1265-040LF Absolute Maximum Ratings (Note 1)**

| Parameter             | Symbol           | Minimum | Typical | Maximum | Units |
|-----------------------|------------------|---------|---------|---------|-------|
| Power dissipation     | P <sub>DIS</sub> |         |         | 250     | mW    |
| Forward current       | I <sub>F</sub>   |         |         | 20      | mA    |
| Operating temperature | T <sub>OP</sub>  | -55     |         | +125    | °C    |
| Storage temperature   | T <sub>STG</sub> | -55     |         | +150    | °C    |

**Note 1:** Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

**CAUTION:** Although this device is designed to be as robust as possible, electrostatic discharge (ESD) can damage this device. These devices must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times.

**Table 3. SMV1265-040LF Electrical Specifications (Note 1)**  
(T<sub>OP</sub> = 25 °C, Unless Otherwise Noted)

| Parameter                 | Symbol                            | Test Condition                             | Min  | Typical | Max  | Units |
|---------------------------|-----------------------------------|--|------|---------|------|-------|
| Reverse leakage current   | I <sub>R</sub>                    | V <sub>R</sub> = 26 V                      |      |         | 20   | nA    |
| Reverse breakdown voltage | V <sub>BR</sub>                   | I <sub>R</sub> = 10 μA                     | 28   |         |      | V     |
| Capacitance               | C <sub>T1</sub>                   | V <sub>R</sub> = 1 V, f = 1 MHz            | 12.5 | 13.8    | 14.7 | pF    |
|                           | C <sub>T26</sub>                  | V <sub>R</sub> = 26 V, f = 1 MHz           | 0.58 | 0.70    | 0.83 | pF    |
| Capacitance ratio         | C <sub>T1</sub> /C <sub>T26</sub> | C <sub>T</sub> (1 V)/C <sub>T</sub> (26 V) | 17.7 | 19.5    |      | –     |
| Series resistance         | R <sub>S</sub>                    | V <sub>R</sub> = 1 V, f = 470 MHz          |      | 2.4     |      | Ω     |

**Note 1:** Performance is guaranteed only under the conditions listed in this table.

### Typical Performance Characteristics




Figure 1. Capacitance vs Voltage @ 25 °C




Figure 2. SPICE Model

Table 4. SPICE Model Parameters

| Part Number   | CJO (pF) | VJ (V) | M  | CP (pF) | RS (Ω) | LS (nH) |
|---------------|----------|--------|----|---------|--------|---------|
| SMV1265-040LF | 22.5     | 30     | 13 | 0.71    | 2.4    | 0.45    |

**Table 5. SMV1265-040LF Voltage vs Capacitance**

| Voltage (V <sub>R</sub> )<br>(V) | Typical Capacitance (C <sub>T</sub> )<br>(pF) |
|----------------------------------|---|
| 0                                | 22.47   |
| 0.5                              | 17.41   |
| 1.0                              | 14.26   |
| 2.0                              | 10.23   |
| 3.0                              | 7.40  |
| 4.0                              | 5.15  |
| 5.0                              | 3.38  |
| 6.0                              | 2.37  |
| 7.0                              | 1.86  |
| 8.0                              | 1.61  |
| 9.0                              | 1.45  |
| 10                               | 1.30  |
| 12                               | 1.12  |
| 14                               | 1.05  |
| 16                               | 0.97  |
| 18                               | 0.91  |
| 20                               | 0.83  |
| 22                               | 0.78  |
| 24                               | 0.75  |
| 26                               | 0.73  |
| 28                               | 0.73  |
| 30                               | 0.71  |

**Package and Handling Information**


The package dimensions and tape and reel dimensions are shown in Figure 3 and 4, respectively.

Instructions on the shipping container label regarding exposure to moisture after the container seal is broken must be followed. Otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly.

The SMV1265-040LF is rated to Moisture Sensitivity Level 1 (MSL1) at 260 °C. They can be used for lead or lead-free

soldering. For additional information, refer to the Skyworks Application Note, *Solder Reflow Information*, document number 200164.


Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. Production quantities of this product are shipped in a standard tape and reel format.



- NOTES:
1. All measurements are in millimeters.
  2. Dimensions and tolerances according to ASME Y14.5M-1994.
  3. These packages are used principally for discrete devices.
  4. This dimension includes stand-off height and package body thickness, but does not include attached features, e.g., external heatsink or chip capacitors. An integral heatslug is not considered an attached feature.
  5. This dimension is primarily terminal plating, but does not include small metal protrusion.

Y1410

Figure 3. SOD-882 Package Dimensions



- Notes:
1. Carrier tape: black conductive polycarbonate.
  2. Cover tape: transparent conductive material.
  3. Cover tape size: 5.4 mm width.
  4. ESD surface resistivity is  $\geq 1 \times 10^4 \sim \leq 1 \times 10^8$  Ohms/square.
  5. All dimensions are in millimeters.

S1922

Figure 4. SOD-882 Tape and Reel Dimensions

**DATA SHEET • SMV1265-040LF: HYPERABRUPT JUNCTION TUNING VARACTOR**

Copyright © 2002-2007, 2009-2011, 2014-2015 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.



Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks and the Skyworks symbol are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at [www.skyworksinc.com](http://www.skyworksinc.com), are incorporated by reference.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SMV1265-040LF on WIN SOURCE](#)
-  [Skyworks Solutions Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management