THE DATASHEET OF

IPP70N10SL16AKSA1

www.win-source.net 0086-755-83957316

SIPMOS® Power-Transistor

Feature

- N-Channel
- Enhancement mode
- Logic Level
- 175°C operating temperature
- Avalanche rated
- d*v*/d*t* rated

- Green Package (lead free)

Product Summary

V_{DS}	100	V
$R_{DS(on)}$	16	mΩ
I_D	70	A

P-TO262-3-1 P-TO263-3-2 P-TO220-3-1





Type	Package	Ordering Code	Marking
IPP70N10SL-16	PG-TO220-3-1	SP0002-25708	N10L16
IPB70N10SL-16	PG-TO263-3-2	SP0002-25700	N10L16
IPI70N10SL-16	PG-TO262-3-1	SP000225705	N10L-16

Maximum Ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current T_C=25°C TC=100°C	I_D	 70 50	A
Pulsed drain current T_C=25°C	$I_{D\ puls}$	280	
Avalanche energy, single pulse I_D=70 A , V_{DD}=25V, R_{GS}=25Ω	E_{AS}	700	mJ
Avalanche energy, periodic limited by T_{jmax}	E_{AR}	25	
Reverse diode d*v*/d*t* I_S=70A, V_{DS}=0V, d*i*/d*t*=200A/µs	d*v*/d*t*	6	kV/µs
Gate source voltage	V_{GS}	±20	V
Power dissipation T_C=25°C	P_{tot}	250	W
Operating and storage temperature	T_j , T_{stg}	-55... +175	°C
IEC climatic category; DIN IEC 68-1		55/175/56	

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Thermal resistance, junction - case	R_{thJC}	-	-	0.6	K/W
Thermal resistance, junction - ambient, leaded	R_{thJA}	-	-	62.5	
SMD version, device on PCB:	R_{thJA}				
@ min. footprint		-	-	62	
@ 6 cm^2 cooling area [1)]		-	-	40	

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Drain-source breakdown voltage V_{GS}=0V, I_D=2mA	$V_{(BR)DSS}$	100	-	-	V
Gate threshold voltage, V_{GS} = V_{DS} I_D = 2 mA	$V_{GS(th)}$	1.2	1.6	2	
Zero gate voltage drain current	I_{DSS}				µA
V_{DS}=100V, V_{GS}=0V, T_j=25°C		-	0.1	1	
V_{DS}=100V, V_{GS}=0V, T_j=150°C		-	-	100	
Gate-source leakage current V_{GS}=20V, V_{DS}=0V	I_{GSS}	-	10	100	nA
Drain-source on-state resistance V_{GS}=4.5V, I_D=50A	$R_{DS(on)}$	-	14	25	mΩ
Drain-source on-state resistance V_{GS}=10V, I_D=50A	$R_{DS(on)}$	-	10	16	

[1]Device on 40mm*40mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 µm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic Characteristics						
Transconductance	g_{fs}	V_{DS}≥2*I_D*$R_{DS(on)max}$, I_D=50A	30	65	-	S
Input capacitance	C_{iss}	V_{GS}=0V, V_{DS}=25V, f=1MHz	-	3630	4540	pF
Output capacitance	C_{oss}		-	640	800	
Reverse transfer capacitance	C_{rss}		-	345	430	
Turn-on delay time	$t_{d(on)}$	V_{DD}=50V, V_{GS}=4.5V, I_D=70A, R_G=1.3Ω	-	70	105	ns
Rise time	t_r		-	250	375	
Turn-off delay time	$t_{d(off)}$		-	250	375	
Fall time	t_f		-	95	145	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=80V, I_D=70A	-	10	15	nC
Gate to drain charge	Q_{gd}		-	34	51	
Gate charge total	Q_g	V_{DD}=80V, I_D=70A, V_{GS}=0 to 10V	-	160	240	
Gate plateau voltage	$V_{(plateau)}$	V_{DD}=80V, I_D=70A	-	3.22	-	V
Reverse Diode						
Inverse diode continuous forward current	I_S	T_C=25°C	-	-	70	A
Inv. diode direct current, pulsed	I_{SM}		-	-	280	
Inverse diode forward voltage	V_{SD}	V_{GS}=0V, I_F=140A	-	1.2	1.8	V
Reverse recovery time	t_{rr}	V_R=50V, I_F=I_S, di_F/dt=100A/µs	-	100	150	ns
Reverse recovery charge	Q_{rr}		-	600	900	nC

1 Power dissipation

$P_{tot} = f(T_C)$



2 Drain current

$I_D = f(T_C)$

parameter: $V_{GS} \geq 10$ V



3 Safe operating area

$I_D = f(V_{DS})$

parameter : $D = 0$, $T_C = 25$ °C



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$

parameter : $D = t_p/T$



5 Typ. output characteristic

$I_D = f(V_{DS})$; T_j=25°C

parameter: t_p = 80 µs



6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D)$

parameter: V_{GS}



7 Typ. transfer characteristics

$I_D = f(V_{GS})$; $V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$

parameter: t_p = 80 µs



8 Typ. forward transconductance

$g_{fs} = f(I_D)$; T_j=25°C

parameter: g_{fs}



9 Drain-source on-state resistance

$R_{DS(on)} = f(T_j)$

parameter : I_D = 50 A, V_{GS} = 4.5 V



10 Typ. gate threshold voltage

$V_{GS(th)} = f(T_j)$

parameter: $V_{GS} = V_{DS}$, I_D = 2 mA



11 Typ. capacitances

$C = f(V_{DS})$

parameter: V_{GS}=0V, f=1 MHz



12 Forward character. of reverse diode

$I_F = f(V_{SD})$

parameter: T_j , tp = 80 µs



13 Typ. avalanche energy

$E_{AS} = f(T_j)$

par.: I_D = 70 A , V_{DD} = 25 V, R_{GS} = 25 Ω



14 Typ. gate charge

$V_{GS} = f(Q_{Gate})$

parameter: I_D = 70 A pulsed



15 Drain-source breakdown voltage

$V_{(BR)DSS} = f(T_j)$



Published by
Infineon Technologies AG,
Bereichs Kommunikation
St.-Martin-Strasse 53,
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!
The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Reprensatives worldwide (see address list).

Warnings
Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system Life support devices or systems are intended to be implanted in the human body, or to support

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View IPP70N10SL16AKSA1 on WIN SOURCE
- Infineon Technologies Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management