



**THE DATASHEET OF
IRF7807VD1**



IRF7807VD1


FETKY™ MOSFET / SCHOTTKY DIODE

- Co-Pack N-channel HEXFET® Power MOSFET and Schottky Diode
- Ideal for Synchronous Rectifiers in DC-DC Converters Up to 5A Output
- Low Conduction Losses
- Low Switching Losses
- Low Vf Schottky Rectifier
- 100% R_c Tested

Description

The FETKY™ family of Co-Pack HEXFET® MOSFETs and Schottky diodes offers the designer an innovative, board space saving solution for switching regulator and power management applications. HEXFET power MOSFETs utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. Combining this technology with International Rectifier's low forward drop Schottky rectifiers results in an extremely efficient device suitable for use in a wide variety of portable electronics applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics. The SO-8 package is designed for vapor phase, infrared or wave soldering techniques.



DEVICE CHARACTERISTICS^⑤

| IRF7807VD1 | |
|---------------------|-------|
| R _{DS(on)} | 17mΩ |
| Q _G | 9.5nC |
| Q _{sw} | 3.4nC |
| Q _{oss} | 12nC |

Absolute Maximum Ratings

| Parameter | Symbol | Max | Units |
|---|-----------------------------------|------------|-------|
| Drain-to-Source Voltage | V _{DS} | 30 | V |
| Gate-to-Source Voltage | V _{GS} | ±20 | |
| Continuous Output Current (V _{GS} ≥ 4.5V) | I _D | 25°C | 8.3 |
| | | 70°C | 6.6 |
| Pulsed Drain Current ^① | I _{DM} | 66 | A |
| Power Dissipation ^③ | P _D | 25°C | 2.5 |
| | | 70°C | 1.6 |
| Schottky and Body Diode | I _F (AV) | 25°C | 3.5 |
| Average Forward Current ^④ | | 70°C | 2.2 |
| Junction & Storage Temperature Range | T _J , T _{STG} | -55 to 150 | °C |

Thermal Resistance

| Parameter | Symbol | Typ | Max | Units |
|---|------------------|-----|-----|-------|
| Maximum Junction-to-Ambient ^③ ^⑥ | R _{θJA} | — | 50 | °C/W |
| Maximum Junction-to-Lead ^⑥ | R _{θJL} | — | 20 | |

Electrical Characteristics

| Parameter | Symbol | Min | Typ | Max | Units | Conditions |
|---|--------------|-----|-----|-----------|------------|--|
| Drain-Source Breakdown Voltage | BV_{DSS} | 30 | — | — | V | $V_{GS} = 0V, I_D = 250\mu A$ |
| Static Drain-Source On-Resistance | $R_{DS(on)}$ | — | 17 | 25 | m Ω | $V_{GS} = 4.5V, I_D = 7.0A$ ② |
| Gate Threshold Voltage | $V_{GS(th)}$ | 1.0 | — | 3.0 | V | $V_{DS} = V_{GS}, I_D = 250\mu A$ |
| Drain-Source Leakage Current | I_{DSS} | — | — | 100 | μA | $V_{DS} = 30V, V_{GS} = 0V$ |
| | | — | — | 20 | μA | $V_{DS} = 24V, V_{GS} = 0V$ |
| | | — | — | 2.0 | mA | $V_{DS} = 24V, V_{GS} = 0V, T_J = 100^\circ C$ |
| Gate-Source Leakage Current | I_{GSS} | — | — | ± 100 | nA | $V_{GS} = \pm 20V$ |
| Total Gate Charge* | Q_G | — | 9.5 | 14 | nC | $V_{DS} = 4.5V$ $I_D = 7.0A$ $V_{DS} = 16V$ |
| Pre-V _{th} Gate-Source Charge | Q_{GS1} | — | 2.3 | — | | |
| Post-V _{th} Gate-Source Charge | Q_{GS2} | — | 1.0 | — | | |
| Gate-to-Drain Charge | Q_{GD} | — | 2.4 | — | | |
| Switch Charge ($Q_{gs2} + Q_{gd}$) | Q_{SW} | — | 3.4 | 5.2 | | |
| Output Charge* | Q_{OSS} | — | 12 | 16.8 | | |
| Gate Resistance | R_G | 0.9 | — | 2.8 | Ω | |
| Turn-On Delay Time | $t_{d(on)}$ | — | 6.3 | — | ns | $V_{DD} = 16V, I_D = 7.0V$ $V_{GS} = 5V, R_G = 2\Omega$ Resistive Load |
| Rise Time | t_r | — | 1.2 | — | | |
| Turn-Off Delay Time | $t_{d(off)}$ | — | 11 | — | | |
| Fall Time | t_f | — | 2.2 | — | | |

Diode Characteristics

| Parameter | Symbol | Min | Typ | Max | Units | Conditions |
|---------------------------|----------|-----|-----|------|-------|--|
| Diode Forward Voltage | V_{SD} | — | — | 0.5 | V | $T_J = 25^\circ C, I_S = 1.0A, V_{GS} = 0V$ ② |
| | | — | — | 0.39 | | $T = 125^\circ C, I_S = 1.0A, V_{GS} = 0V$ ② |
| Reverse Recovery Time ④ | t_{rr} | — | 51 | — | ns | $di/dt = 700A/\mu s$ $V_{DD} = 16V, V_{GS} = 0V, I_D = 15A$ |
| Reverse Recovery Charge ④ | Q_{rr} | — | 51 | — | nC | $T_J = 25^\circ C, I_S = 7.0A, V_{DS} = 16V$ $di/dt = 100A/\mu s$ |

- Notes:**
- ① Repetitive rating; pulse width limited by max. junction temperature.
 - ② Pulse width $\leq 400 \mu s$; duty cycle $\leq 2\%$.
 - ③ When mounted on 1 inch square copper board
 - ④ 50% Duty Cycle, Rectangular
 - ⑤ Typical values of $R_{DS(on)}$ measured at $V_{GS} = 4.5V$, Q_G , Q_{SW} and Q_{OSS} measured at $V_{GS} = 5.0V, I_F = 7.0A$.
 - ⑥ R_{θ} is measured at T_J approximately $90^\circ C$
 - * Device are 100% tested to these parameters.

Power MOSFET Selection for DC/DC Converters

Control FET

Special attention has been given to the power losses in the switching elements of the circuit - Q1 and Q2. Power losses in the high side switch Q1, also called the Control FET, are impacted by the $R_{ds(on)}$ of the MOSFET, but these conduction losses are only about one half of the total losses.

Power losses in the control switch Q1 are given by;

$$P_{loss} = P_{conduction} + P_{switching} + P_{drive} + P_{output}$$

This can be expanded and approximated by;

$$P_{loss} = (I_{rms}^2 \times R_{ds(on)}) + \left(I \times \frac{Q_{gd}}{i_g} \times V_{in} \times f \right) + \left(I \times \frac{Q_{gs2}}{i_g} \times V_{in} \times f \right) + (Q_g \times V_g \times f) + \left(\frac{Q_{oss}}{2} \times V_{in} \times f \right)$$

This simplified loss equation includes the terms Q_{gs2} and Q_{oss} which are new to Power MOSFET data sheets. Q_{gs2} is a sub element of traditional gate-source charge that is included in all MOSFET data sheets. The importance of splitting this gate-source charge into two sub elements, Q_{gs1} and Q_{gs2} , can be seen from Fig 1.

Q_{gs2} indicates the charge that must be supplied by the gate driver between the time that the threshold voltage has been reached (t1) and the time the drain current rises to I_{dmax} (t2) at which time the drain voltage begins to change. Minimizing Q_{gs2} is a critical factor in reducing switching losses in Q1.

Q_{oss} is the charge that must be supplied to the output capacitance of the MOSFET during every switching cycle. Figure 2 shows how Q_{oss} is formed by the parallel combination of the voltage dependant (non-linear) capacitance's C_{ds} and C_{dg} when multiplied by the power supply input buss voltage.




Figure 1: Typical MOSFET switching waveform

Synchronous FET

The power loss equation for Q2 is approximated by;

$$P_{loss} = P_{conduction} + P_{drive} + P_{output}^* \\ P_{loss} = (I_{rms}^2 \times R_{ds(on)}) + (Q_g \times V_g \times f) + \left(\frac{Q_{oss}}{2} \times V_{in} \times f \right) + (Q_{rr} \times V_{in} \times f)$$

*dissipated primarily in Q1.

IRF7807VD1

International
IR Rectifier

For the synchronous MOSFET Q2, $R_{ds(on)}$ is an important characteristic; however, once again the importance of gate charge must not be overlooked since it impacts three critical areas. Under light load the MOSFET must still be turned on and off by the control IC so the gate drive losses become much more significant. Secondly, the output charge Q_{oss} and reverse recovery charge Q_{rr} both generate losses that are transferred to Q1 and increase the dissipation in that device. Thirdly, gate charge will impact the MOSFETs' susceptibility to Cdv/dt turn on.

The drain of Q2 is connected to the switching node of the converter and therefore sees transitions between ground and V_{in} . As Q1 turns on and off there is a rate of change of drain voltage dV/dt which is capacitively coupled to the gate of Q2 and can induce a voltage spike on the gate that is sufficient to turn

the MOSFET on, resulting in shoot-through current. The ratio of Q_{gd}/Q_{gs1} must be minimized to reduce the potential for Cdv/dt turn on.

Spice model for IRF7807V can be downloaded in machine readable format at www.irf.com.




Figure 2: Q_{oss} Characteristic

Typical Mobile PC Application

The performance of these new devices has been tested in circuit and correlates well with performance predictions generated by the system models. An advantage of this new technology platform is that the MOSFETs it produces are suitable for both control FET and synchronous FET applications. This has been demonstrated with the 3.3V and 5V converters. (Fig 3 and Fig 4). In these applications the same MOSFET IRF7807V was used for both the control FET (Q1) and the synchronous FET (Q2). This provides a highly effective cost/performance solution.




Figure 3




Figure 4




Fig 5. Normalized On-Resistance Vs. Temperature




Fig 7. On-Resistance Vs. Gate Voltage




Fig 7. Typical Reverse Output Characteristics




Fig 8. Typical Reverse Output Characteristics




Figure 9. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




Fig 10. Typical Gate Charge Vs. Gate-to-Source Voltage

MOSFET , Body Diode & Schottky Diode Characteristics




Fig. 11 - Typical Forward Voltage Drop Characteristics





Fig. 12 - Typical Values of Reverse Current Vs. Reverse Voltage


IRF7807VD1

SO-8 Package Details



| DIM | INCHES | | MILLIMETERS | |
|----------|------------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | .0532 | .0688 | 1.35 | 1.75 |
| A1 | .0040 | .0098 | 0.10 | 0.25 |
| B | .014 | .018 | 0.36 | 0.46 |
| C | .0075 | .0098 | 0.19 | 0.25 |
| D | .189 | .196 | 4.80 | 4.98 |
| E | .150 | .157 | 3.81 | 3.99 |
| e | .050 BASIC | | 1.27 BASIC | |
| e1 | .025 BASIC | | 0.635 BASIC | |
| H | .2284 | .2440 | 5.80 | 6.20 |
| K | .011 | .019 | 0.28 | 0.48 |
| L | 0.16 | .050 | 0.41 | 1.27 |
| θ | 0° | 8° | 0° | 8° |

RECOMMENDED FOOTPRINT




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
2. CONTROLLING DIMENSION : INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
- ⑤ DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS
MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.006).
- ⑥ DIMENSIONS IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE..


SO-8 Part Marking

SO-8 (MS-012AA)


EXAMPLE: THIS IS AN IRF7807D1 (FETKY)



SO-8 Tape and Reel



- NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
 2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
 3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



- NOTES :
1. CONTROLLING DIMENSION : MILLIMETER.
 2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

This product has been designed and qualified for the commercial market.
 Qualification Standards can be found on IR's Web site.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View IRF7807VD1 on WIN SOURCE](#)

 [Infineon Technologies](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management