





**THE DATASHEET OF
SUD50N024-09P-E3**





N-Channel 22-V (D-S) 175°C MOSFET

| PRODUCT SUMMARY | | |
|---------------------|---------------------------------|---------------------------------|
| V _{DS} (V) | r _{DS(on)} (Ω) | I _D (A) ^d |
| 24 ^c | 0.0095 @ V _{GS} = 10 V | 49 |
| | 0.017 @ V _{GS} = 4.5 V | 36 |



FEATURES

- TrenchFET® Power MOSFET
- 175°C Junction Temperature
- PWM Optimized for High Efficiency

APPLICATIONS

- High-Side Synchronous Buck DC/DC Conversion
 - Desktop
 - Server

Ordering Information: SUD50N024-09P
SUD50N024-09P—E3 (Lead Free)

| ABSOLUTE MAXIMUM RATINGS (T _A = 25°C UNLESS OTHERWISE NOTED) | | | | |
|---|------------------------|-----------------------------------|------------------|------|
| Parameter | | Symbol | Limit | Unit |
| Drain-Source Pulse Voltage | | V _{DS(pulse)} | 24 ^c | V |
| Drain-Source Voltage | | V _{DS} | 22 | |
| Gate-Source Voltage | | V _{GS} | ±20 | |
| Continuous Drain Current ^a | T _C = 25°C | I _D | 49 ^d | A |
| | T _C = 100°C | | 34 ^d | |
| Pulsed Drain Current | | I _{DM} | 100 | |
| Continuous Source Current (Diode Conduction) ^a | | I _S | 4.3 | |
| Avalanche Current, Single Pulse | L = 0.1 mH | I _{AS} | 29 | |
| Avalanche Energy, Single Pulse | | E _{AS} | 42 | mJ |
| Maximum Power Dissipation | T _A = 25°C | P _D | 6.5 ^a | W |
| | T _C = 25°C | | 39.5 | |
| Operating Junction and Storage Temperature Range | | T _J , T _{stg} | -55 to 175 | °C |

| THERMAL RESISTANCE RATINGS | | | | | |
|--|--------------|-------------------|---------|---------|------|
| Parameter | | Symbol | Typical | Maximum | Unit |
| Maximum Junction-to-Ambient ^a | t ≤ 10 sec | R _{thJA} | 19 | 23 | °C/W |
| | Steady State | | 40 | 50 | |
| Maximum Junction-to-Case | | R _{thJC} | 3.1 | 3.8 | |

Notes

- Surface Mounted on FR4 Board, t ≤ 10 sec.
- Limited by package
- Pulse condition: T_A = 105°C, 50 ns, 300 kHz operation
- Calculation based on maximum allowable Junction Temperature. Package limitation current is 25 A.





SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)

| Parameter | Symbol | Test Condition | Min | Typ ^a | Max | Unit |
|---|----------------------|--|-----|------------------|--------|------|
| Static | | | | | | |
| Drain-Source Breakdown Voltage | V _{(BR)DSS} | V _{GS} = 0 V, I _D = 250 μA | 22 | | | V |
| Gate Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 250 μA | 0.8 | | 3.0 | |
| Gate-Body Leakage | I _{GSS} | V _{DS} = 0 V, V _{GS} = ±20 V | | | ±100 | nA |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} = 20 V, V _{GS} = 0 V | | | 1 | μA |
| | | V _{DS} = 20 V, V _{GS} = 0 V, T _J = 125°C | | | 50 | |
| On-State Drain Current ^b | I _{D(on)} | V _{DS} = 5 V, V _{GS} = 10 V | 50 | | | A |
| Drain-Source On-State Resistance ^b | r _{DS(on)} | V _{GS} = 10 V, I _D = 20 A | | 0.008 | 0.0095 | Ω |
| | | V _{GS} = 10 V, I _D = 20 A, T _J = 125°C | | | 0.014 | |
| | | V _{GS} = 4.5 V, I _D = 20 A | | 0.0135 | 0.017 | |
| Forward Transconductance ^b | g _{fs} | V _{DS} = 15 V, I _D = 20 A | 15 | | | S |
| Dynamic^a | | | | | | |
| Input Capacitance | C _{iss} | V _{GS} = 0 V, V _{DS} = 10 V, f = 1 MHz | | 1300 | | pF |
| Output Capacitance | C _{oss} | | | 470 | | |
| Reverse Transfer Capacitance | C _{rss} | | | 275 | | |
| Gate Resistance | R _g | | 1.6 | 4.0 | 6 | Ω |
| Total Gate Charge ^c | Q _g | V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 50 A | | 10.5 | 16 | nC |
| Gate-Source Charge ^c | Q _{gs} | | | 4.2 | | |
| Gate-Drain Charge ^c | Q _{gd} | | | 4.0 | | |
| Turn-On Delay Time ^c | t _{d(on)} | V _{DD} = 10 V, R _L = 0.2 Ω I _D ≅ 50 A, V _{GEN} = 10 V, R _g = 2.5 Ω | | 8 | 12 | ns |
| Rise Time ^c | t _r | | | 10 | 15 | |
| Turn-Off Delay Time ^c | t _{d(off)} | | | 25 | 40 | |
| Fall Time ^c | t _f | | | 12 | 20 | |
| Source-Drain Diode Ratings and Characteristic (T_C = 25°C) | | | | | | |
| Pulsed Current | I _{SM} | | | | 100 | A |
| Diode Forward Voltage ^b | V _{SD} | I _F = 50 A, V _{GS} = 0 V | | 1.2 | 1.5 | V |
| Source-Drain Reverse Recovery Time | t _{rr} | I _F = 50 A, di/dt = 100 A/μs | | 35 | 70 | ns |

Notes







- Guaranteed by design, not subject to production testing.
- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Independent of operating temperature.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)




THERMAL RATINGS


Maximum Drain Current vs. Ambient Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Ambient





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SUD50N024-09P-E3 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management