



**THE DATASHEET OF
SUD25N04-25-E3**






N-Channel 40-V (D-S) 175°C MOSFET


PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
40	0.025 @ $V_{GS} = 10$ V	25
	0.040 @ $V_{GS} = 4.5$ V	20

175°C Rated
Maximum Junction Temperature
TrenchFET®
Power MOSFETS



Order Number:
SUD25N04-25

Drain Connected to Tab



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	40	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$) ^b	$T_C = 25^\circ\text{C}$	I_D	25	A
	$T_C = 125^\circ\text{C}$		15	
Pulsed Drain Current		I_{DM}	50	
Continuous Source Current (Diode Conduction) ^b		I_S	50	
Avalanche Current		I_{AR}	25	mJ
Repetitive Avalanche Energy (Duty Cycle $\leq 1\%$)	$L = 0.1$ mH	E_{AR}	31	
Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	33 ^b	W
	$T_A = 25^\circ\text{C}$		3 ^b	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Junction-to-Ambient ^b	$t \leq 10$ sec	R_{thJA}	20	25	$^\circ\text{C}/\text{W}$
	Steady State		40	50	
Junction-to-Case		R_{thJC}	3.7	4.5	

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. See SOA curve for voltage derating.




SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ ^a	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 μA	40			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	1.0	2.0	3.0	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 40 V, V _{GS} = 0 V			1	μA
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 175 °C			150	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	50			A
Drain-Source On-State Resistance ^b	r _{DS(on)}	V _{GS} = 10 V, I _D = 25 A		0.02	0.025	Ω
		V _{GS} = 10 V, I _D = 25 A, T _J = 125 °C			0.040	
		V _{GS} = 10 V, I _D = 25 A, T _J = 175 °C			0.053	
		V _{GS} = 4.5 V, I _D = 10 A		0.031	0.040	
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 25 A		15		S
Dynamic^a						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, F = 1 MHz		510		pF
Output Capacitance	C _{oss}			125		
Reverse Transfer Capacitance	C _{rss}			65		
Total Gate Charge ^c	Q _g	V _{DS} = 20 V, V _{GS} = 10 V, I _D = 25 A		13	20	nC
Gate-Source Charge ^c	Q _{gs}			2.5		
Gate-Drain Charge ^c	Q _{gd}			3		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 20 V, R _L = 0.8 Ω I _D = 25 A, V _{GEN} = 10 V, R _G = 2.5 Ω		5	10	ns
Rise Time ^c	t _r			47	70	
Turn-Off Delay Time ^c	t _{d(off)}			15	30	
Fall Time ^c	t _f			5	10	
Source-Drain Diode Ratings and Characteristic (T_C = 25 °C)						
Pulsed Current	I _{SM}				50	A
Diode Forward Voltage ^b	V _{SD}	I _F = 25 A, V _{GS} = 0 V		1.1	1.3	V
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 25 A, di/dt = 100 A/μs		17	30	ns

Notes


- a. Guaranteed by design, not subject to production testing.
- b. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- c. Independent of operating temperature.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




Transconductance




On-Resistance vs. Drain Current





Capacitance





Gate Charge



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



THERMAL RATINGS





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SUD25N04-25-E3 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management