

# UNR221x Series (UN221x Series)

## Silicon NPN epitaxial planar type

For digital circuits

### ■ Features


- Costs can be reduced through downsizing of the equipment and reduction of the number of parts.
- Mini type package allowing easy automatic insertion through tape packing and magazine packing

### ■ Resistance by Part Number


|                    |    | Marking Symbol (R <sub>1</sub> ) | (R <sub>2</sub> ) |
|--------------------|----|----------------------------------|-------------------|
| • UNR2210 (UN2210) | 8L | 47 kΩ                            | —                 |
| • UNR2211 (UN2211) | 8A | 10 kΩ                            | 10 kΩ             |
| • UNR2212 (UN2212) | 8B | 22 kΩ                            | 22 kΩ             |
| • UNR2213 (UN2213) | 8C | 47 kΩ                            | 47 kΩ             |
| • UNR2214 (UN2214) | 8D | 10 kΩ                            | 47 kΩ             |
| • UNR2215 (UN2215) | 8E | 10 kΩ                            | —                 |
| • UNR2216 (UN2216) | 8F | 4.7 kΩ                           | —                 |
| • UNR2217 (UN2217) | 8H | 22 kΩ                            | —                 |
| • UNR2218 (UN2218) | 8I | 0.51 kΩ                          | 5.1 kΩ            |
| • UNR2219 (UN2219) | 8K | 1 kΩ                             | 10 kΩ             |
| • UNR221D (UN221D) | 8M | 47 kΩ                            | 10 kΩ             |
| • UNR221E (UN221E) | 8N | 47 kΩ                            | 22 kΩ             |
| • UNR221F (UN221F) | 8O | 4.7 kΩ                           | 10 kΩ             |
| • UNR221K (UN221K) | 8P | 10 kΩ                            | 4.7 kΩ            |
| • UNR221L (UN221L) | 8Q | 4.7 kΩ                           | 4.7 kΩ            |
| • UNR221M (UN221M) | EL | 2.2 kΩ                           | 47 kΩ             |
| • UNR221N (UN221N) | EX | 4.7 kΩ                           | 47 kΩ             |
| • UNR221T (UN221T) | EZ | 22 kΩ                            | 47 kΩ             |
| • UNR221V (UN221V) | FD | 2.2 kΩ                           | 2.2 kΩ            |
| • UNR221Z (UN221Z) | FF | 4.7 kΩ                           | 22 kΩ             |

### ■ Absolute Maximum Ratings T<sub>a</sub> = 25°C

| Parameter                             | Symbol           | Rating      | Unit |
|---------------------------------------|------------------|-------------|------|
| Collector-base voltage (Emitter open) | V <sub>CBO</sub> | 50          | V    |
| Collector-emitter voltage (Base open) | V <sub>CEO</sub> | 50          | V    |
| Collector current                     | I <sub>C</sub>   | 100         | mA   |
| Total power dissipation               | P <sub>T</sub>   | 200         | mW   |
| Junction temperature                  | T <sub>j</sub>   | 150         | °C   |
| Storage temperature                   | T <sub>stg</sub> | -55 to +150 | °C   |



### Internal Connection



Note) The part numbers in the parenthesis show conventional part number.

■ Electrical Characteristics  $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$ 

| Parameter                                          |                                           | Symbol               | Conditions                                                                                          | Min  | Typ  | Max  | Unit          |
|----------------------------------------------------|-------------------------------------------|----------------------|-----------------------------------------------------------------------------------------------------|------|------|------|---------------|
| Collector-base voltage (Emitter open)              |                                           | $V_{\text{CBO}}$     | $I_{\text{C}} = 10\ \mu\text{A}$ , $I_{\text{E}} = 0$                                               | 50   |      |      | V             |
| Collector-emitter voltage (Base open)              |                                           | $V_{\text{CEO}}$     | $I_{\text{C}} = 2\ \text{mA}$ , $I_{\text{B}} = 0$                                                  | 50   |      |      | V             |
| Collector-base cutoff current (Emitter open)       |                                           | $I_{\text{CBO}}$     | $V_{\text{CB}} = 50\ \text{V}$ , $I_{\text{E}} = 0$                                                 |      |      | 0.1  | $\mu\text{A}$ |
| Collector-emitter cutoff current (Base open)       |                                           | $I_{\text{CEO}}$     | $V_{\text{CE}} = 50\ \text{V}$ , $I_{\text{B}} = 0$                                                 |      |      | 0.5  | $\mu\text{A}$ |
| Emitter-base<br>cutoff current<br>(Collector open) | UNR2210/2215/2216/2217                    | $I_{\text{EBO}}$     | $V_{\text{EB}} = -6\ \text{V}$ , $I_{\text{C}} = 0$                                                 |      |      | 0.01 | mA            |
|                                                    | UNR2213                                   |                      |                                                                                                     |      |      | 0.1  |               |
|                                                    | UNR2212/2214/221D/<br>221E/221M/221N/221T |                      |                                                                                                     |      |      | 0.2  |               |
|                                                    | UNR221Z                                   |                      |                                                                                                     |      |      | 0.4  |               |
|                                                    | UNR2211                                   |                      |                                                                                                     |      |      | 0.5  |               |
|                                                    | UNR221F/221K                              |                      |                                                                                                     |      |      | 1.0  |               |
|                                                    | UNR2219                                   |                      |                                                                                                     |      |      | 1.5  |               |
|                                                    | UNR2218/221L/221V                         |                      |                                                                                                     |      |      | 2.0  |               |
| Forward current<br>transfer ratio                  | UNR221V                                   | $h_{\text{FE}}$      | $V_{\text{CE}} = 10\ \text{V}$ , $I_{\text{C}} = 5\ \text{mA}$                                      | 6    |      | 20   | —             |
|                                                    | UNR2218/221K/221L                         |                      |                                                                                                     | 20   |      |      |               |
|                                                    | UNR2219/221D/221F                         |                      |                                                                                                     | 30   |      |      |               |
|                                                    | UNR2211                                   |                      |                                                                                                     | 35   |      |      |               |
|                                                    | UNR2212/221E                              |                      |                                                                                                     | 60   |      |      |               |
|                                                    | UNR221Z                                   |                      |                                                                                                     | 60   |      | 200  |               |
|                                                    | UNR2213/2214/221M                         |                      |                                                                                                     | 80   |      |      |               |
|                                                    | UNR221N/221T                              |                      |                                                                                                     | 80   |      | 400  |               |
|                                                    | UNR2210*/2215*/2216*/2217*                |                      |                                                                                                     | 160  |      | 460  |               |
| Collector-emitter saturation voltage               |                                           | $V_{\text{CE(sat)}}$ | $I_{\text{C}} = 10\ \text{mA}$ , $I_{\text{B}} = 0.3\ \text{mA}$                                    |      |      | 0.25 | V             |
| UNR221V                                            |                                           |                      | $I_{\text{C}} = 10\ \text{mA}$ , $I_{\text{B}} = 1.5\ \text{mA}$                                    |      |      |      |               |
| Output voltage high-level                          |                                           | $V_{\text{OH}}$      | $V_{\text{CC}} = 5\ \text{V}$ , $V_{\text{B}} = 0.5\ \text{V}$ , $R_{\text{L}} = 1\ \text{k}\Omega$ | 4.9  |      |      | V             |
| Output voltage low-level                           |                                           | $V_{\text{OL}}$      | $V_{\text{CC}} = 5\ \text{V}$ , $V_{\text{B}} = 2.5\ \text{V}$ , $R_{\text{L}} = 1\ \text{k}\Omega$ |      |      | 0.2  | V             |
| UNR2213/221K                                       |                                           |                      | $V_{\text{CC}} = 5\ \text{V}$ , $V_{\text{B}} = 3.5\ \text{V}$ , $R_{\text{L}} = 1\ \text{k}\Omega$ |      |      |      |               |
| UNR221D                                            |                                           |                      | $V_{\text{CC}} = 5\ \text{V}$ , $V_{\text{B}} = 10\ \text{V}$ , $R_{\text{L}} = 1\ \text{k}\Omega$  |      |      |      |               |
| UNR221E                                            |                                           |                      | $V_{\text{CC}} = 5\ \text{V}$ , $V_{\text{B}} = 6\ \text{V}$ , $R_{\text{L}} = 1\ \text{k}\Omega$   |      |      |      |               |
| Transition frequency                               |                                           | $f_{\text{T}}$       | $V_{\text{CB}} = 10\ \text{V}$ , $I_{\text{E}} = -2\ \text{mA}$ , $f = 200\ \text{MHz}$             |      | 150  |      | MHz           |
| Input resistance                                   | UNR2218                                   | $R_{\text{I}}$       |                                                                                                     | -30% | 0.51 | +30% | k $\Omega$    |
|                                                    | UNR2219                                   |                      |                                                                                                     |      | 1.0  |      |               |
|                                                    | UNR221M/211V                              |                      |                                                                                                     |      | 2.2  |      |               |
|                                                    | UNR2216/221F/221L/<br>221N/221Z           |                      |                                                                                                     |      | 4.7  |      |               |
|                                                    | UNR2211/2214/2215/221K                    |                      |                                                                                                     |      | 10   |      |               |
|                                                    | UNR2212/2217/221T                         |                      |                                                                                                     |      | 22   |      |               |
|                                                    | UNR2210/2213/221D/221E                    |                      |                                                                                                     |      | 47   |      |               |

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

2. \*: Rank classification


| Rank            | Q          | R          | S          | No-rank    |
|-----------------|------------|------------|------------|------------|
| $h_{\text{FE}}$ | 160 to 260 | 210 to 340 | 290 to 460 | 160 to 460 |

■ Electrical Characteristics (continued)  $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$ 




| Parameter        | Symbol                 | Conditions | Min  | Typ   | Max  | Unit |
|------------------|------------------------|------------|------|-------|------|------|
| Resistance ratio | UNR221M                | $R_1/R_2$  |      | 0.047 |      | —    |
|                  | UNR221N                |            |      | 0.1   |      |      |
|                  | UNR2218/2219           |            | 0.08 | 0.10  | 0.12 |      |
|                  | UNR221Z                |            |      | 0.21  |      |      |
|                  | UNR2214                |            | 0.17 | 0.21  | 0.25 |      |
|                  | UNR221T                |            |      | 0.47  |      |      |
|                  | UNR221F                |            | 0.37 | 0.47  | 0.57 |      |
|                  | UNR221V                |            |      | 1.0   |      |      |
|                  | UNR2211/2212/2213/221L |            | 0.8  | 1.0   | 1.2  |      |
|                  | UNR221K                |            | 1.70 | 2.13  | 2.60 |      |
|                  | UNR221E                |            | 1.70 | 2.14  | 2.60 |      |
|                  | UNR221D                |            | 3.7  | 4.7   | 5.7  |      |




Note) Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

Common characteristics chart









Characteristics charts of UNR2210







## Characteristics charts of UNR2211






Characteristics charts of UNR2212









Characteristics charts of UNR2213







## Characteristics charts of UNR2214






Characteristics charts of UNR2215











Characteristics charts of UNR2216














Characteristics charts of UNR2217




**Characteristics charts of UNR2218****Characteristics charts of UNR2219**




Characteristics charts of UNR221D






Characteristics charts of UNR221E










Characteristics charts of UNR221F














Characteristics charts of UNR221K




**Characteristics charts of UNR221L****Characteristics charts of UNR221M**




Characteristics charts of UNR221N






Characteristics charts of UNR221T









Characteristics charts of UNR221V





Characteristics charts of UNR221Z



## utions in using the technical information and scribed in this book

s book is to be exported or provided to non-residents, the laws and  
rd to security export control, must be observed.

ly to show the main characteristics and application circuit examples  
l property right or other right owned by our company or any other  
any as to the infringement upon any such right owned by any other  
rmation described in this book.

standard applications or general electronic equipment (such as office  
and household appliances).

ng applications:

biles, traffic control equipment, combustion equipment, life support  
reliability are required, or if the failure or malfunction of the prod-

k are subject to change without notice for modification and/or im-  
use of the products, therefore, ask for the most up-to-date Product  
atisfy your requirements.

bsolute maximum rating and the guaranteed operating conditions  
(.). Especially, please be careful not to exceed the range of absolute  
er-off and mode-switching. Otherwise, we will not be liable for any

take into the consideration of incidence of break down and failure  
n the systems such as redundant design, arresting the spread of fire  
al injury, fire, social damages, for example, by using the products.

own and characteristics change due to external factors (ESD, EOS,  
mounting or at customer's process. When using products for which  
shelf life and the elapsed time since first opening the packages.

ly or partially, without the prior written permission of Matsushita

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 View [UNR221200L](#) on WIN SOURCE

 [Panasonic](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management