




# TrenchT2™ Power MOSFET


# IXTA260N055T2 IXTP260N055T2

N-Channel Enhancement Mode  
Avalanche Rated




$V_{DSS} = 55V$   
 $I_{D25} = 260A$   
 $R_{DS(on)} \leq 3.3m\Omega$

TO-263 (IXTA)



TO-220 (IXTP)



G = Gate      D = Drain  
 S = Source    Tab = Drain

| Symbol       | Test Conditions   | Maximum Ratings    |            |
|--------------|---|--------------------|------------|
| $V_{DSS}$    | $T_J = 25^\circ C$ to $175^\circ C$                       | 55                 | V          |
| $V_{DGR}$    | $T_J = 25^\circ C$ to $175^\circ C$ , $R_{GS} = 1M\Omega$ | 55                 | V          |
| $V_{GSM}$    | Transient   | $\pm 20$           | V          |
| $I_{D25}$    | $T_C = 25^\circ C$  | 260                | A          |
| $I_{L(RMS)}$ | External Lead Current Limit                               | 120                | A          |
| $I_{DM}$     | $T_C = 25^\circ C$ , Pulse Width Limited by $T_{JM}$      | 780                | A          |
| $I_A$        | $T_C = 25^\circ C$  | 100                | A          |
| $E_{AS}$     | $T_C = 25^\circ C$  | 600                | mJ         |
| $P_D$        | $T_C = 25^\circ C$  | 480                | W          |
| $T_J$        |   | -55 ... +175       | $^\circ C$ |
| $T_{JM}$     |   | 175                | $^\circ C$ |
| $T_{stg}$    |   | -55 ... +175       | $^\circ C$ |
| $T_L$        | Maximum Lead Temperature for Soldering                    | 300                | $^\circ C$ |
| $T_{SOLD}$   | 1.6 mm (0.062in.) from Case for 10s                       | 260                | $^\circ C$ |
| $F_C$        | Mounting Force (TO-263)                                   | 10..65 / 2.2..14.6 | N/lb       |
| $M_d$        | Mounting Torque (TO-220)                                  | 1.13 / 10          | Nm/lb.in   |
| Weight       | TO-263  | 2.5                | g          |
|              | TO-220  | 3.0                | g          |

## Features

- International Standard Packages
- Avalanche Rated
- Low Package Inductance
- Fast Intrinsic Rectifier
- 175°C Operating Temperature
- High Current Handling Capability
- ROHS Compliant
- High Performance Trench Technology for extremely low  $R_{DS(on)}$

## Advantages

- High Power Density
- Easy to Mount
- Space Savings

## Applications

- Automotive Engine Control
- Synchronous Buck Converter (for Notebook SystemPower & General Purpose Point & Load)
- DC/DC Converters
- High Current Switching Applications
- Power Train Management
- Distributed Power Architecture

| Symbol       | Test Conditions<br>( $T_J = 25^\circ C$ Unless Otherwise Specified) | Characteristic Values |      |                          |
|--------------|---|-----------------------|------|--------------------------|
|              |   | Min.                  | Typ. | Max.                     |
| $BV_{DSS}$   | $V_{GS} = 0V$ , $I_D = 250\mu A$                                    | 55                    |      | V                        |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = 250\mu A$                                | 2.0                   |      | V                        |
| $I_{GSS}$    | $V_{GS} = \pm 20V$ , $V_{DS} = 0V$                                  |                       |      | $\pm 200$ nA             |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$ , $V_{GS} = 0V$<br>$T_J = 150^\circ C$           |                       |      | 5 $\mu A$<br>150 $\mu A$ |
| $R_{DS(on)}$ | $V_{GS} = 10V$ , $I_D = 50A$ , Notes 1 & 2                          |                       |      | 3.3 m $\Omega$           |


| Symbol       | Test Conditions  | Characteristic Values |      |           |
|--------------|--|-----------------------|------|-----------|
|              |  | Min.                  | Typ. | Max.      |
| $g_{fs}$     | $V_{DS} = 10V, I_D = 60A$ , Note 1   | 55                    | 94   | S         |
| $C_{iss}$    | $V_{GS} = 0V, V_{DS} = 25V, f = 1MHz$  |                       | 10.8 | nF        |
| $C_{oss}$    |  |                       | 1460 | pF        |
| $C_{rss}$    |  |                       | 215  | pF        |
| $t_{d(on)}$  | <b>Resistive Switching Times</b><br>$V_{GS} = 10V, V_{DS} = 28V, I_D = 100A$<br>$R_G = 2\Omega$ (External) |                       | 20   | ns        |
| $t_r$        |  |                       | 27   | ns        |
| $t_{d(off)}$ |  |                       | 36   | ns        |
| $t_f$        |  |                       | 24   | ns        |
| $Q_{g(on)}$  | $V_{GS} = 10V, V_{DS} = 0.5 \cdot V_{DSS}, I_D = 0.5 \cdot I_{DSS}$  |                       | 140  | nC        |
| $Q_{gs}$     |  |                       | 52   | nC        |
| $Q_{gd}$     |  |                       | 32   | nC        |
| $R_{thJC}$   | TO-220   |                       |      | 0.31 °C/W |
| $R_{thCS}$   |  | 0.50                  |      | °C/W      |

**Source-Drain Diode**

| Symbol   | Test Conditions  | Characteristic Values |      |        |
|----------|--|-----------------------|------|--------|
|          |  | Min.                  | Typ. | Max.   |
| $I_s$    | $V_{GS} = 0V$  |                       |      | 260 A  |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$                    |                       |      | 1000 A |
| $V_{SD}$ | $I_F = 100A, V_{GS} = 0V$ , Note 1                             |                       |      | 1.3 V  |
| $t_{rr}$ | $I_F = 130A, V_{GS} = 0V,$<br>$-di/dt = 100A/\mu s, V_R = 27V$ |                       | 60   | ns     |
| $I_{RM}$ |  |                       | 3.4  | A      |
| $Q_{RM}$ |  |                       | 102  | nC     |


- Notes: 1. Pulse test,  $t \leq 300\mu s$ ; duty cycle,  $d \leq 2\%$ .  
2. On through-hole packages,  $R_{DS(on)}$  Kelvin test contact location must be 5mm or less from the package body.

**TO-263 Outline**



| SYM  | INCHES   |      | MILLIMETER |       |
|------|----------|------|------------|-------|
|      | MIN      | MAX  | MIN        | MAX   |
| A    | .170     | .185 | 4.30       | 4.70  |
| A1   | .000     | .008 | 0.00       | 0.20  |
| A2   | .091     | .098 | 2.30       | 2.50  |
| b    | .028     | .035 | 0.70       | 0.90  |
| b2   | .046     | .060 | 1.18       | 1.52  |
| C    | .018     | .024 | 0.45       | 0.60  |
| C2   | .049     | .060 | 1.25       | 1.52  |
| D    | .340     | .370 | 8.63       | 9.40  |
| D1   | .300     | .327 | 7.62       | 8.30  |
| E    | .380     | .410 | 9.65       | 10.41 |
| E1   | .270     | .330 | 6.86       | 8.38  |
| (E)  | .100 BSC |      | 2.54 BSC   |       |
| H    | .580     | .620 | 14.73      | 15.75 |
| L    | .075     | .105 | 1.91       | 2.67  |
| L1   | .039     | .060 | 1.00       | 1.52  |
| L2   | —        | .070 | —          | 1.77  |
| (L3) | .010 BSC |      | 0.254 BSC  |       |

**TO-220 Outline**



| SYM  | INCHES   |      | MILLIMETERS |       |
|------|----------|------|-------------|-------|
|      | MIN      | MAX  | MIN         | MAX   |
| A    | .169     | .185 | 4.30        | 4.70  |
| A1   | .047     | .055 | 1.20        | 1.40  |
| A2   | .079     | .106 | 2.00        | 2.70  |
| b    | .024     | .039 | 0.60        | 1.00  |
| b2   | .045     | .057 | 1.15        | 1.45  |
| c    | .014     | .026 | 0.35        | 0.65  |
| D    | .587     | .626 | 14.90       | 15.90 |
| D1   | .335     | .370 | 8.50        | 9.40  |
| (D2) | .500     | .531 | 12.70       | 13.50 |
| E    | .382     | .406 | 9.70        | 10.30 |
| (E1) | .283     | .323 | 7.20        | 8.20  |
| e    | .100 BSC |      | 2.54 BSC    |       |
| e1   | .200 BSC |      | 5.08 BSC    |       |
| H1   | .244     | .268 | 6.20        | 6.80  |
| L    | .492     | .547 | 12.50       | 13.90 |
| L1   | .110     | .154 | 2.80        | 3.90  |
| ØP   | .134     | .150 | 3.40        | 3.80  |
| Q    | .106     | .126 | 2.70        | 3.20  |

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

|  |           |           |           |           |             |             |             |             |             |             |
|--|-----------|-----------|-----------|-----------|-------------|-------------|-------------|-------------|-------------|-------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665   | 6,404,065B1 | 6,683,344   | 6,727,585   | 7,005,734B2 | 7,157,338B2 |
|  | 4,860,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123B1 | 6,534,343   | 6,710,405B2 | 6,759,692   | 7,063,975B2 |             |
|  | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728B1 | 6,583,505   | 6,710,463   | 6,771,478B2 | 7,071,537   |             |

Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$




Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$




Fig. 3. Output Characteristics @  $T_J = 150^\circ\text{C}$




Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 130\text{A}$  Value vs. Junction Temperature




Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 130\text{A}$  Value vs. Drain Current




Fig. 6. Drain Current vs. Case Temperature




Fig. 7. Input Admittance




Fig. 8. Transconductance




Fig. 9. Forward Voltage Drop of Intrinsic Diode




Fig. 10. Gate Charge




Fig. 11. Capacitance







Fig. 12. Forward-Bias Safe Operating Area




**Fig. 13. Resistive Turn-on**  
Rise Time vs. Junction Temperature




**Fig. 14. Resistive Turn-on**  
Rise Time vs. Drain Current




**Fig. 15. Resistive Turn-on**  
Switching Times vs. Gate Resistance




**Fig. 16. Resistive Turn-off**  
Switching Times vs. Junction Temperature




**Fig. 17. Resistive Turn-off**  
Switching Times vs. Drain Current



**Fig. 18. Resistive Turn-off**  
Switching Times vs. Gate Resistance



**Fig. 19. Maximum Transient Thermal Impedance**





---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View IXTP260N055T2 on WIN SOURCE](#)

 [IXYS Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management