THE DATASHEET OF

PJE8406_R1_00001

win-source.net 0086-755-83957316

PJE8406

20V N-Channel Enhancement Mode MOSFET – ESD Protected

Voltage	20 V	Current	800 mA



Features

- $R_{DS(ON)}$, V_{GS}@4.5V,I_{DS}@500mA=0.4Ω
- $R_{DS(ON)}$, V_{GS}@2.5V,I_{DS}@300mA=0.7Ω
- $R_{DS(ON)}$, V_{GS}@1.8V,I_{DS}@100mA=1.2Ω(typ)
- Advanced Trench Process Technology
- Specially Designed for Load Switch or PWM application.
- ESD Protected
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOT-523 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.002 grams
- Marking : E06

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current		I_D	800	mA
Pulsed Drain Current		I_{DM}	3000	mA
Power Dissipation	T_A=25°C	P_D	350	mW
	Derate above 25°C		2.8	mW/°C
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~150	°C
Typical Thermal Resistance - Junction to Ambient(Note 3)		$R_{\theta JA}$	357	°C/W

PJE8406

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V,I_D=250uA	20	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250uA	0.4	0.63	1.0	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=4.5V,I_D=500mA	-	0.35	0.4	Ω
		V_{GS}=2.5V,I_D=300mA	-	0.6	0.7	
		V_{GS}=1.8V,I_D=100mA	-	1.2	-	
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=16V,V_{GS}=0V	-	0.02	1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±4.5V,V_{DS}=0V	-	±0.05	±1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±10V,V_{DS}=0V	-	±2	±10	uA
Dynamic						
Total Gate Charge	Q_g	V_{DS}=10V, I_D=500mA, V_{GS}=4.5V(Note 1,2)	-	0.92	-	nC
Gate-Source Charge	Q_{gs}		-	0.31	-	
Gate-Drain Charge	Q_{gd}		-	0.08	-	
Input Capacitance	Ciss	V_{DS}=10V, V_{GS}=0V, f=1.0MHZ	-	50	-	pF
Output Capacitance	Coss		-	10	-	
Reverse Transfer Capacitance	Crss		-	8.5	-	
Switching						
Turn-On Delay Time	$td_{(on)}$	V_{DD}=10V, I_D=500mA, V_{GS}=4.5V, R_G=6Ω(Note 1,2)	-	4	-	ns
Turn-On Rise Time	tr		-	20	-	
Turn-Off Delay Time	$td_{(off)}$		-	12	-	
Turn-Off Fall Time	tf		-	25	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	500	mA
Diode Forward Voltage	V_{SD}	I_S=500mA, V_{GS}=0V	-	0.91	1.3	V

NOTES :

1. Pulse width≤300us, Duty cycle≤2%
2. Essentially independent of operating temperature typical characteristics.
3. $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. mounted on a 1 inch square pad of copper

PJE8406

TYPICAL CHARACTERISTIC CURVES



Fig.1 On-Region Characteristics



Fig.2 Transfer Characteristics



Fig.3 On-Resistance vs. Drain Current



Fig.4 On-Resistance vs. Junction temperature



Fig.5 On-Resistance Variation with VGS.



Fig.6 Body Diode Characteristics

TYPICAL CHARACTERISTIC CURVES



Fig.7 Gate-Charge Characteristics



Fig.8 Breakdown Voltage Variation vs. Temperature



Fig.9 Threshold Voltage Variation with Temperature.

PART NO. PACKING CODE VERSION

Part No. Packing Code	Package Type	Packing Type	Marking	Version
PJE8406_R1_00001	SOT-523	4K pcs / 7” reel	E06	Halogen free RoHS compliant

MOUNTING PAD LAYOUT

SOT-523 Unit : inch(mm)



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View PJE8406_R1_00001 on WIN SOURCE
- Panjit Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management